6/20/00

COMPUTED BY: MJ DuVAL DATE: 06/10/02
CHECKED BY: JRH DATE: 11/12/03

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-0513BA	3-D

LIST OF PIPES, ENDWALLS, ETC. (FOR PIPES 1200 mm & UNDER)

STATION	LOCATION (LT, RT, OR CL)	STRUCTURE NO. FROM	STRUCTURE NO. TO	TOP ELEVATION	INVERT ELEVATION	INVERT ELEVATION	SLOPE CRITICAL	CLASS III R.C. PIPE (UNLESS NOTED OTHERWISE) SIZE 300	375	450	600	750	900	1050	1200	BITUMINOUS COATED C.S. PIPE TYPE B (UNLESS NOTED OTHERWISE) SIZE 300	400	450	600	800	900	1000	1200	375mm SIDE DRAIN PIPE	450mm SIDE DRAIN PIPE	600mm SIDE DRAIN PIPE	ENDWALLS STD. 838.01 OR STD. 838.11 (UNLESS NOTED OTHERWISE) CU. METERS R.C.P.	C.S.P.	QUANTITIES: STRUCTURES PER EACH (0 THRU 1.50)	FOR DRAINAGE "TOTAL (N.H.L.) QUANTITY" (W.H.L. "A" + (1.5 X COL. "B") METERS 1.50 THRU 3.00	3.00 AND ABOVE	C.B. STD. 840.01 OR 840.02	FRAME, GRATES, AND HOOD STD. 840.03 TYPE OF GRATE E	F	G	D.I. STD 840.14 OR STD. 840.15	D.I. FRAME & GRATE STD. 840.16	M.D.I. TYPE "D" STD. 840.19 OR 840.28	M.D.I. TYPE "B" STD. 840.18 OR 840.27	M.D.I. TYPE "A" STD. 840.17 OR 840.26	M.D.I. FRAME W/TWO GRATES STD. 840.22	M.D.I. FRAME WITH GRATE STD. 840.22	M.D.I (N.S.) FRAME W/ 2 GRATES STD. 840.24	M.D.I (N.S.) FRAME W/ 2 GRATES STD. 840.29	M.D.I FRAME WITH TWO GRATES STD. 840.20	T.B.D.I. STD. 840.35	T.B.D.I. FRAME WITH TWO GRATE STD. 840.37	M.H. FRAME & COVER STD. 840.54	J.B. STD 840.31 OR 840.32	T.B.J.B. STD 840.34	ADJUST 2 GI	375mm PARALLEL PIPE END SECTION	450mm PARALLEL PIPE END SECTION	CORR. STEEL ELBOW NO. & SIZE	PREFORMED SCOUR HOLE	CONC. COLLARS, CL. B STD. 840.72	CONC. & BRICK PIPE PLUG m3 STD. 840.71	PIPE REMOVAL	REMARKS
15+95	CL.	94	95		45.883	44.72				25.2																																										
–SR1–																																																				
16+60	CL.	96			45.79	45.72					24.0																																									
–L–																																																			
120+30	LT.	97		47.499																										1																						
120+30	CL.	97	98		46.661	46.496			34.8																																										
120+30	CL.	98		48.52																										1																						
120+30	CL.	98	99		46.421	45.89				38.4																																									
120+30	RT.	99		46.807																										1																						
–SR2–																																																			
15+76	CL.	99	100		45.74	44.47					26.4																																									
–L–																																																			
124+40	LT.	101		47.453																										1																						
124+40	CL.	101	102		46.539	46.132				33.6																																									
124+40	CL.	102		48.523																										1	0.9																				
124+40	CL.	102	103		46.102	45.671				36.0																																									
124+40	RT.	103		46.63																										1																						
–SR2–																																																			
19+86	CL.	103	104		45.563	45.327					24.0																																									
–L–																																																			
126+00	LT.	105		46.858																										1																						
126+00	CL.	105	106		46.02	45.823			33.6																																									
126+00	CL.	106		48.041																										1	0.8																				
126+00	CL.	106	107		45.748	45.514				34.8																																									
127+60	LT.	108		46.377																										1																						
127+60	LT.	108	109		45.539	45.246			33.6																																									
127+60	CL.	109		47.559																										1	0.9																				
127+60	CL.	109	110		45.171	44.821				37.2																																									
129+20	LT.	112		46.055																										1																						
129+20	CL.	112	113		45.141	45.104				34.2																																									
129+20	CL.	113		47.077																										1	0.6																				
129+20	CL.	113	114		44.954	44.913					37.2																																									
130+66	LT.	115		46.191																										1																						
130+66	LT.	115	116		45.531	45.50				30.0																																									
130+66	CL.	116		46.677																										1																						
130+66	CL.	116	117		45.386	45.352					34.8																																									
131+60	CL.	118		47.183																										1																						
131+60	CL.	118	119		46.345	45.188			34.8																																									
132+50	RT.	120		49.37																										1																				1		
132+42	RT.	120	121		48.532	48.152			18.0																																									
132+33	RT.	121		49.041																										1																				1		
132+33	RT.	121	122		48.127	44.863											14.0																																		
SHEET TOTAL									154.8	269.4	146.4						14.0													18	3.2													1	16		15			2			

ABBREVIATIONS

C.B.	CATCH BASIN
N.D.I.	NARROW DROP INLET
D.I.	DROP INLET
M.D.I.	MEDIAN DROP INLET
M.D.I. (N.S.)	MEDIAN DROP INLET (NARROW SLOT)
J.B.	JUNCTION BOX
M.H.	MANHOLE
T.B.D.I.	TRAFFIC BEARING DROP INLET
T.B.J.B.	TRAFFIC BEARING JUCTION BOX

14-JUL-2004 16:16
WCRoach
R0513bsum
R0513bc
R0513bs
R0513bd
R0513bl
R0513bm
R0513bt
R0513bp
R0513bx
R0513bf
R0513bg
R0513bh
R0513bi
R0513bj
R0513bk
R0513bn
R0513bo
R0513bq
R0513br
R0513bu
R0513bv
R0513bw
R0513by
R0513bz
R0513ba
R0513be
R0513bb