

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL UNIT

ID	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
R-0513BA	6.469002T	2	11

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION	GRADATION	TERMS AND DEFINITIONS	ABBREVIATIONS																																																																											
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS ACCORDING TO STANDARD PENETRATION TEST (ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION AND OTHER PERTINENT FACTORS, SUCH AS, MINERALOGICAL COMPOSITION, ANGULARITY STRUCTURE, PLASTICITY, ETC. EXAMPLE: <i>VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p> <p style="text-align: center;">SOIL LEGEND AND AASHTO CLASSIFICATION</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GENERAL CLASS.</th> <th colspan="2">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="2">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="2">ORGANIC MATERIALS</th> </tr> <tr> <td>GROUP CLASS.</td> <td>A-1</td> <td>A-2</td> <td>A-3</td> <td>A-4</td> <td>A-5</td> <td>A-6</td> </tr> <tr> <td>SYMBOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>% PASSING</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> <td>10 40 200</td> </tr> <tr> <td>LIQUID LIMIT</td> <td>6</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> </tr> <tr> <td>PLASTIC INDEX</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>GROUP INDEX</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td>STONE FRAGS, GRAVEL AND SAND</td> <td>FINE SAND</td> <td>SILTY OR CLAYEY GRAVEL AND SAND</td> <td>SILTY SOILS</td> <td>CLAYEY SOILS</td> <td>MUCK, PEAT</td> </tr> <tr> <td>GEN. RATING AS A SUBGRADE</td> <td colspan="2">EXCELLENT TO GOOD</td> <td colspan="2">FAIR TO POOR</td> <td>POOR</td> <td>UNSATURABLE</td> </tr> </table> <p style="text-align: center;">P.I. OF A-7-5 ≤ L.L. - 30 ; P.I. OF A-7-6 > L.L. - 30</p>	GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)		SILT-CLAY MATERIALS (> 35% PASSING #200)		ORGANIC MATERIALS		GROUP CLASS.	A-1	A-2	A-3	A-4	A-5	A-6	SYMBOL							% PASSING	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	LIQUID LIMIT	6	10	10	10	10	10	PLASTIC INDEX	0	0	0	0	0	0	GROUP INDEX	0	0	0	0	0	0	USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS	MUCK, PEAT	GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD		FAIR TO POOR		POOR	UNSATURABLE	<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED)</p> <p>GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p style="text-align: center;">ANGULARITY OF GRAINS</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p> <p style="text-align: center;">MINERALOGICAL COMPOSITION</p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p> <p style="text-align: center;">COMPRESSIBILITY</p> <p>SLIGHTLY COMPRESSIBLE LIQUID LIMIT LESS THAN 30 MODERATELY COMPRESSIBLE LIQUID LIMIT 31-50 HIGHLY COMPRESSIBLE LIQUID LIMIT GREATER THAN 50</p> <p style="text-align: center;">ROCK DESCRIPTION</p> <p>IN THE BROADEST MEANING, HARD ROCK IS CONSIDERED THAT MATERIAL WHICH CANNOT BE SAMPLED BY CONVENTIONAL SOIL SAMPLING TOOLS OR TECHNIQUES. THE BOUNDARY BETWEEN SOIL AND ROCK IS ARBITRARY. TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF "WEATHERED ROCK". FOR THE PURPOSE OF THIS INVESTIGATION, THESE MATERIALS ARE DIVIDED AS FOLLOWS:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;"></td> <td style="width: 25%;">SOFT WEATHERED ROCK</td> <td style="width: 25%;">HARD WEATHERED ROCK</td> <td style="width: 25%;">MATERIAL THAT CAN BE PENETRATED WITH SOME DIFFICULTY USING POWER AUGERS AND YIELDS SPT VALUES > 100 BLOWS BUT < SPT REFUSAL</td> </tr> <tr> <td></td> <td>INFERRED ROCK LINE</td> <td></td> <td>MATERIAL THAT CAN BE PENETRATED WITH GREAT DIFFICULTY USING POWER AUGERS AND YIELDS SPT REFUSAL.</td> </tr> <tr> <td></td> <td></td> <td></td> <td>MATERIAL THAT CANNOT BE PENETRATED BY POWER AUGERS, EXCEPT IN THIN LEDGES, AND REQUIRES ROCK CORING TOOLS FOR OBTAINING A SAMPLE.</td> </tr> </table>		SOFT WEATHERED ROCK	HARD WEATHERED ROCK	MATERIAL THAT CAN BE PENETRATED WITH SOME DIFFICULTY USING POWER AUGERS AND YIELDS SPT VALUES > 100 BLOWS BUT < SPT REFUSAL		INFERRED ROCK LINE		MATERIAL THAT CAN BE PENETRATED WITH GREAT DIFFICULTY USING POWER AUGERS AND YIELDS SPT REFUSAL.				MATERIAL THAT CANNOT BE PENETRATED BY POWER AUGERS, EXCEPT IN THIN LEDGES, AND REQUIRES ROCK CORING TOOLS FOR OBTAINING A SAMPLE.	<p>ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER.</p> <p>APPARENT DIP - THE DIP OF ROCK STRATA NOT PERPENDICULAR TO STRIKE.</p> <p>AQUIFER - A WATER BEARING FORMATION OR STRATA.</p> <p>AUGER REFUSAL (A.R.) - POINT AT WHICH POWER AUGERS WILL NOT PENETRATE.</p> <p>BEDDED - SOIL OR ROCK LYING IN A POSITION ESSENTIALLY PARALLEL.</p> <p>BEDROCK - ROCK OF RELATIVELY GREAT THICKNESS AND EXTENT IN ITS ORIGINAL LOCATION.</p> <p>CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.</p> <p>COHESIVE SOIL - A SOIL THAT WHEN UNCONFINED HAS CONSIDERABLE DRY STRENGTH AND SIGNIFICANT COHESION WHEN SUBMERGED.</p> <p>COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.</p> <p>CORE RECOVERY (% REC.) - TOTAL LENGTH OF ALL ROCK DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>COQUINA - A ROCK TYPE COMPOSED ESSENTIALLY OF MARINE SHELLS CEMENTED BY CALCIUM CARBONATE.</p> <p>DIKE - IGNEOUS ROCK INTRUSION WHICH IS NARROW COMPARED WITH ITS OTHER DIMENSIONS.</p> <p>DIP - THE ANGLE BETWEEN A BEDDING PLANE, JOINT PLANE OR FAULT PLANE AND THE HORIZONTAL, MEASURED PERPENDICULAR TO THE STRIKE.</p> <p>DUMPS - UNCOVERED DEPOSITS OF WASTE MATERIAL SUCH AS WOOD, MASONRY DEBRIS OR GARBAGE.</p> <p>FAULT - A BREAK IN THE CONTINUITY OF A BODY OF ROCK, ATTENDED BY A MOVEMENT ON EITHER OR BOTH SIDES OF THE BREAK.</p> <p>FINES - PORTIONS OF A SOIL FINER THAN NO. 200 U.S. STANDARD SIEVE.</p> <p>FISSILE OR FISSILE - A PROPERTY OF SPLITTING EASILY ALONG CLOSELY SPACED PARALLEL PLANES.</p> <p>FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL.</p> <p>FLOODPLAIN - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.</p> <p>FORMATION - A MAPPABLE UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.</p> <p>FRACTURE - A CRACK LARGE ENOUGH TO BE VISIBLE TO THE UNAIDED EYE.</p> <p>FRIABLE - EASY TO BREAK OR CRUMBLE.</p> <p>GRANULAR MATERIAL - SOIL THAT WHEN UNCONFINED HAS LITTLE OR NO DRY STRENGTH AND HAS LITTLE OR NO COHESION WHEN SUBMERGED.</p> <p>GROUNDWATER (G.W.) - WATER THAT IS FREE TO MOVE THROUGH SOIL MASS UNDER THE INFLUENCE OF GRAVITY.</p> <p>GROUNDWATER LEVEL - LEVEL OF WATER WITH RESPECT TO EXISTING GROUND SURFACE.</p> <p>HARDPAN - A GENERAL TERM USED TO DESCRIBE A HARD CEMENTED SOIL LAYER WHICH DOES NOT SOFTEN WHEN WET.</p> <p>INDURATED - EARTH MATERIAL HARDENED BY HEAT, PRESSURE OR CEMENTATION.</p> <p>INTERBEDDED - ALTERNATING LENSES OR LAYERS OF SOIL AND/OR ROCK MATERIALS.</p> <p>JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.</p> <p>LAMINATED - VERY THIN ALTERNATING LAYERS LESS THAN 1cm.</p> <p>LAYER - SUBJECT MATERIAL GREATER THAN 1cm IN THICKNESS.</p> <p>LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.</p> <p>LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.</p> <p>MARL - A NON-INDURATED, CALCAREOUS DEPOSIT OF CLAYS, SILTS AND SANDS, OFTEN CONTAINING SHELLS.</p> <p>MICACEOUS SOIL (MIC.) - A SOIL OR ROCK TYPE CONTAINING AN APPRECIABLE AMOUNT OF MICA.</p> <p>MUCK (MK.) - A HIGHLY ORGANIC SOIL OF VERY SOFT CONSISTENCY, GENERALLY FOUND ON TIDAL FLATS, LAKE OR STREAM FLOODPLAINS.</p> <p>PEAT (PI) - A FIBROUS MASS OF ORGANIC MATTER IN VARIOUS STAGES OF DECOMPOSITION.</p> <p>PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.</p> <p>RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.</p> <p>ROCK - SEE LEGEND</p> <p>ROCK QUALITY DESIGNATION (R.O.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 0.1m DIVIDED BY THE TOTAL LENGTH OF CORE RUN EXPRESSED AS A PERCENTAGE.</p> <p>SANITARY LANDFILLS - COMPACTED AND/OR COVERED LAYERS OF SOIL AND WASTE PRODUCTS.</p> <p>SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.</p> <p>SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLAIN.</p> <p>SILL - AN IGNEOUS SHEET OF INTRUSIVE ROCK WHOSE THICKNESS IS SLIGHT COMPARED TO ITS LATERAL EXTENT.</p> <p>SOME - PRESENCE OF 5% TO 30% OF SUBJECT MATERIAL.</p> <p>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N) OF A 63.5 kg HAMMER FALLING 0.76 METERS REQUIRED TO PRODUCE A PENETRATION OF 30 cm INTO SOIL WITH A 5 cm OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION RESISTANCE OF LESS THAN 2.5 cm WITH 50 BLOWS.</p> <p>STRIKE - THE DIRECTION OR BEARING OF A HORIZONTAL LINE IN THE PLANE OF AN INCLINED STRATUM, JOINT, FAULT OR OTHER STRUCTURAL PLANE.</p> <p>SUBGRADE - THE SOIL PREPARED TO SUPPORT A STRUCTURE OR A PAVEMENT SYSTEM.</p> <p>TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p> <p>TRACE - PRESENCE OF LESS THAN 5% OF SUBJECT MATERIAL.</p>	<p>BLDR. - BOULDER</p> <p>CL. - CLAY</p> <p>COB. - COBBLE</p> <p>CSE. - COARSE</p> <p>EST. - ESTIMATED</p> <p>F. - FINE</p> <p>FOSS. - FOSSILIFEROUS</p> <p>FRAC. - FRACTURED</p> <p>GR. - GRAVEL</p> <p>LL - LIQUID LIMIT</p> <p>MED. - MEDIUM</p> <p>MO. - MOTTLED</p> <p>OM - OPTIMUM MOISTURE</p> <p>ORG. - ORGANIC</p> <p>PL - PLASTIC LIMIT</p> <p>PI - PLASTICITY INDEX</p> <p>n - POROSITY</p> <p>SD. - SAND</p> <p>SAT. - SATURATED</p> <p>SL. - SILT, SILTY</p> <p>SLI. - SLIGHTLY</p> <p>G_s - SPECIFIC GRAVITY</p> <p>qu - UNCONFINED COMPRESSIVE STRENGTH</p> <p>γ - UNIT WEIGHT (WET UNIT WEIGHT)</p> <p>γ_d - DRY UNIT WEIGHT</p> <p>γ_{SAT} - SATURATED UNIT WEIGHT</p> <p>e - VOID RATIO</p> <p>v. - VERY</p>
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)		SILT-CLAY MATERIALS (> 35% PASSING #200)		ORGANIC MATERIALS																																																																									
GROUP CLASS.	A-1	A-2	A-3	A-4	A-5	A-6																																																																								
SYMBOL																																																																														
% PASSING	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200	10 40 200																																																																								
LIQUID LIMIT	6	10	10	10	10	10																																																																								
PLASTIC INDEX	0	0	0	0	0	0																																																																								
GROUP INDEX	0	0	0	0	0	0																																																																								
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS	CLAYEY SOILS	MUCK, PEAT																																																																								
GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD		FAIR TO POOR		POOR	UNSATURABLE																																																																								
	SOFT WEATHERED ROCK	HARD WEATHERED ROCK	MATERIAL THAT CAN BE PENETRATED WITH SOME DIFFICULTY USING POWER AUGERS AND YIELDS SPT VALUES > 100 BLOWS BUT < SPT REFUSAL																																																																											
	INFERRED ROCK LINE		MATERIAL THAT CAN BE PENETRATED WITH GREAT DIFFICULTY USING POWER AUGERS AND YIELDS SPT REFUSAL.																																																																											
			MATERIAL THAT CANNOT BE PENETRATED BY POWER AUGERS, EXCEPT IN THIN LEDGES, AND REQUIRES ROCK CORING TOOLS FOR OBTAINING A SAMPLE.																																																																											
<p style="text-align: center;">CONSISTENCY OR DENSITY</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (BLOWS)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (KN/m²)</th> </tr> <tr> <td rowspan="4">GENERALLY GRANULAR MATERIAL</td> <td>VERY LOOSE</td> <td>< 4</td> <td rowspan="4">N/A</td> </tr> <tr> <td>LOOSE</td> <td>4 TO 10</td> </tr> <tr> <td>MEDIUM DENSE</td> <td>10 TO 30</td> </tr> <tr> <td>DENSE</td> <td>30 TO 50</td> </tr> <tr> <td rowspan="4">GENERALLY SILT-CLAY MATERIAL</td> <td>VERY SOFT</td> <td>< 2</td> <td>< 25</td> </tr> <tr> <td>SOFT</td> <td>2 TO 4</td> <td>25 TO 50</td> </tr> <tr> <td>MEDIUM STIFF</td> <td>4 TO 8</td> <td>50 TO 100</td> </tr> <tr> <td>STIFF</td> <td>8 TO 15</td> <td>100 TO 200</td> </tr> <tr> <td rowspan="2">VERY STIFF</td> <td></td> <td>15 TO 30</td> <td>200 TO 400</td> </tr> <tr> <td>HARD</td> <td>> 30</td> <td>> 400</td> </tr> </table>	PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (BLOWS)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (KN/m ²)	GENERALLY GRANULAR MATERIAL	VERY LOOSE	< 4	N/A	LOOSE	4 TO 10	MEDIUM DENSE	10 TO 30	DENSE	30 TO 50	GENERALLY SILT-CLAY MATERIAL	VERY SOFT	< 2	< 25	SOFT	2 TO 4	25 TO 50	MEDIUM STIFF	4 TO 8	50 TO 100	STIFF	8 TO 15	100 TO 200	VERY STIFF		15 TO 30	200 TO 400	HARD	> 30	> 400	<p style="text-align: center;">GROUND WATER</p> <p> WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING.</p> <p> STATIC WATER LEVEL AFTER _____ HOURS.</p> <p> PERCHED WATER, SATURATED ZONE OR WATER BEARING STRATA</p> <p> SPRING OR SEEPAGE</p>	<p style="text-align: center;">MISCELLANEOUS SYMBOLS AND ABBREVIATIONS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td></td> <td>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</td> <td></td> <td>SPT TEST BORING</td> <td></td> <td>SAMPLE DESIGNATIONS</td> </tr> <tr> <td></td> <td>SOIL SYMBOL</td> <td></td> <td>AUGER BORING</td> <td></td> <td>S- BULK SAMPLE</td> </tr> <tr> <td></td> <td>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</td> <td></td> <td>CORE BORING</td> <td></td> <td>SS- SPLIT SPOON SAMPLE</td> </tr> <tr> <td></td> <td>INFERRED SOIL BOUNDARIES</td> <td></td> <td>MONITORING WELL</td> <td></td> <td>ST- SHELBY TUBE SAMPLE</td> </tr> <tr> <td></td> <td>ALLUVIAL/RESIDUAL BOUNDARIES</td> <td></td> <td>PIEZOMETER INSTALLATION</td> <td></td> <td>RS- ROCK SAMPLE</td> </tr> <tr> <td></td> <td>25° DIP DIRECTION AND DIP OF STRUCTURES</td> <td></td> <td>SLOPE INDICATOR INSTALLATION</td> <td></td> <td>● - SOUNDING ROD</td> </tr> <tr> <td></td> <td>APPARENT DIP (NORMAL TO _____)</td> <td></td> <td>SPT N-COUNT</td> <td></td> <td></td> </tr> </table>		ROADWAY EMBANKMENT WITH SOIL DESCRIPTION		SPT TEST BORING		SAMPLE DESIGNATIONS		SOIL SYMBOL		AUGER BORING		S- BULK SAMPLE		ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS		CORE BORING		SS- SPLIT SPOON SAMPLE		INFERRED SOIL BOUNDARIES		MONITORING WELL		ST- SHELBY TUBE SAMPLE		ALLUVIAL/RESIDUAL BOUNDARIES		PIEZOMETER INSTALLATION		RS- ROCK SAMPLE		25° DIP DIRECTION AND DIP OF STRUCTURES		SLOPE INDICATOR INSTALLATION		● - SOUNDING ROD		APPARENT DIP (NORMAL TO _____)		SPT N-COUNT		
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (BLOWS)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (KN/m ²)																																																																											
GENERALLY GRANULAR MATERIAL	VERY LOOSE	< 4	N/A																																																																											
	LOOSE	4 TO 10																																																																												
	MEDIUM DENSE	10 TO 30																																																																												
	DENSE	30 TO 50																																																																												
GENERALLY SILT-CLAY MATERIAL	VERY SOFT	< 2	< 25																																																																											
	SOFT	2 TO 4	25 TO 50																																																																											
	MEDIUM STIFF	4 TO 8	50 TO 100																																																																											
	STIFF	8 TO 15	100 TO 200																																																																											
VERY STIFF		15 TO 30	200 TO 400																																																																											
	HARD	> 30	> 400																																																																											
	ROADWAY EMBANKMENT WITH SOIL DESCRIPTION		SPT TEST BORING		SAMPLE DESIGNATIONS																																																																									
	SOIL SYMBOL		AUGER BORING		S- BULK SAMPLE																																																																									
	ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS		CORE BORING		SS- SPLIT SPOON SAMPLE																																																																									
	INFERRED SOIL BOUNDARIES		MONITORING WELL		ST- SHELBY TUBE SAMPLE																																																																									
	ALLUVIAL/RESIDUAL BOUNDARIES		PIEZOMETER INSTALLATION		RS- ROCK SAMPLE																																																																									
	25° DIP DIRECTION AND DIP OF STRUCTURES		SLOPE INDICATOR INSTALLATION		● - SOUNDING ROD																																																																									
	APPARENT DIP (NORMAL TO _____)		SPT N-COUNT																																																																											
<p style="text-align: center;">TEXTURE OR GRAIN SIZE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.0</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table>	U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.0	0.42	0.25	0.075	0.053	<p style="text-align: center;">EQUIPMENT USED ON SUBJECT PROJECT</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td><input type="checkbox"/> MOBILE B</td> <td><input type="checkbox"/> 6" (152 mm) CONTINUOUS FLIGHT</td> <td><input checked="" type="checkbox"/> AUTOMATIC</td> <td><input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input type="checkbox"/> 8" (203 mm) HOLLOW AUGERS</td> <td><input type="checkbox"/> -AX</td> <td><input type="checkbox"/> -BX</td> </tr> <tr> <td><input type="checkbox"/> CME-45</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -NX</td> <td></td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-550</td> <td><input type="checkbox"/> TUNG. - CARBIDE INSERTS</td> <td></td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/> OTHER _____</td> <td></td> <td><input type="checkbox"/> HAND AUGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/> OTHER _____</td> <td></td> <td><input type="checkbox"/> SOUNDING ROD</td> <td></td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td></td> </tr> </table>	<input type="checkbox"/> MOBILE B	<input type="checkbox"/> 6" (152 mm) CONTINUOUS FLIGHT	<input checked="" type="checkbox"/> AUTOMATIC	<input type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input type="checkbox"/> 8" (203 mm) HOLLOW AUGERS	<input type="checkbox"/> -AX	<input type="checkbox"/> -BX	<input type="checkbox"/> CME-45	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -NX		<input checked="" type="checkbox"/> CME-550	<input type="checkbox"/> TUNG. - CARBIDE INSERTS			<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> POST HOLE DIGGER		<input type="checkbox"/> OTHER _____		<input type="checkbox"/> HAND AUGER		<input type="checkbox"/> OTHER _____		<input type="checkbox"/> SOUNDING ROD				<input type="checkbox"/> VANE SHEAR TEST		<p style="text-align: center;">SOIL MOISTURE - CORRELATION OF TERMS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PLASTIC RANGE (PI)</td> <td>- WET - (W)</td> <td>SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>	SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PLASTIC RANGE (PI)	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE															
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																								
	4.76	2.0	0.42	0.25	0.075	0.053																																																																								
<input type="checkbox"/> MOBILE B	<input type="checkbox"/> 6" (152 mm) CONTINUOUS FLIGHT	<input checked="" type="checkbox"/> AUTOMATIC	<input type="checkbox"/> MANUAL																																																																											
<input type="checkbox"/> BK-51	<input type="checkbox"/> 8" (203 mm) HOLLOW AUGERS	<input type="checkbox"/> -AX	<input type="checkbox"/> -BX																																																																											
<input type="checkbox"/> CME-45	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -NX																																																																												
<input checked="" type="checkbox"/> CME-550	<input type="checkbox"/> TUNG. - CARBIDE INSERTS																																																																													
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> POST HOLE DIGGER																																																																												
<input type="checkbox"/> OTHER _____		<input type="checkbox"/> HAND AUGER																																																																												
<input type="checkbox"/> OTHER _____		<input type="checkbox"/> SOUNDING ROD																																																																												
		<input type="checkbox"/> VANE SHEAR TEST																																																																												
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																												
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																												
PLASTIC RANGE (PI)	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																												
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																												
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																												
<p style="text-align: center;">PLASTICITY</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>	NONPLASTIC	PLASTICITY INDEX	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p style="text-align: center;">COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, MOTTLED, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>	<p style="text-align: center;">CAUTION NOTICE :</p> <p>THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WAS MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. SOME DATA OBTAINED MAY BE OMITTED FROM THIS RELEASE.</p> <p>ADDITIONAL INFORMATION MAY BE AVAILABLE, INCLUDING, BUT NOT LIMITED TO THE FOLLOWING:</p> <p style="text-align: center;">FIELD BORING LOGS ROCK CORES SOIL & ROCK TEST DATA SUBSURFACE REPORT</p> <p>THIS INFORMATION MAY BE VIEWED BY APPOINTMENT BY CONTACTING THE N.C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL UNIT @ (919) 250-4088. NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOGS, ROCK CORES, OR SOIL TEST DATA IS PART OF THE CONTRACT.</p> <p>GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.</p> <p>THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE OR OPINIONS OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.</p> <p>NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N.C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IS IT CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THIS PROJECT.</p> <p>NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.</p>																																																													
NONPLASTIC	PLASTICITY INDEX	DRY STRENGTH																																																																												
LOW PLASTICITY	0-5	VERY LOW																																																																												
MED. PLASTICITY	6-15	SLIGHT																																																																												
HIGH PLASTICITY	16-25	MEDIUM																																																																												
	26 OR MORE	HIGH																																																																												
<p style="text-align: center;">PLASTICITY</p> <p>PLASTICITY INDEX</p> <p>DRY STRENGTH</p>	<p style="text-align: center;">EQUIPMENT USED ON SUBJECT PROJECT</p> <p>DRILL UNITS:</p> <p><input type="checkbox"/> MOBILE B</p> <p><input type="checkbox"/> BK-51</p> <p><input type="checkbox"/> CME-45</p> <p><input checked="" type="checkbox"/> CME-550</p> <p><input type="checkbox"/> PORTABLE HOIST</p> <p><input type="checkbox"/> OTHER _____</p> <p><input type="checkbox"/> OTHER _____</p>	<p style="text-align: center;">EQUIPMENT USED ON SUBJECT PROJECT</p> <p>AUGER TOOLS:</p> <p><input type="checkbox"/> 6" (152 mm) CONTINUOUS FLIGHT</p> <p><input type="checkbox"/> 8" (203 mm) HOLLOW AUGERS</p> <p><input type="checkbox"/> HARD FACED FINGER BITS</p> <p><input type="checkbox"/> TUNG. - CARBIDE INSERTS</p> <p><input type="checkbox"/> CLAY BITS</p> <p>OTHER:</p> <p><input type="checkbox"/> DRAG BIT, AW RODS</p>	<p>NOTES:</p> <p>BENCH MARK: STA. 138+05.900 -L-, CENTERLINE</p> <p>ELEVATION: 46.30 METERS</p>																																																																											