



PROJECT REFERENCE NO. R2562D	SHEET NO. EC-17/CONST.17
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
CONST.REV.	
R/W REV.	

NOTE: PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE-B AND TEMPORARY ROCK SILT CHECKS TYPE-A AT DRAINAGE OUTLETS.

-L6- STA.16+20.000 MATCH TO SHEET NO.16

MATCH TO SHEET NO.18

NC 87 5385 9100	NC 41/87 12954 21000
119 200	7688 13100
2004 ADT	7807 13300
2025 ADT	

Pls Sta. 49+17.604 Os = 5° 55' 37.7" Ls = 60.000 LT = 40.022 ST = 20.020	Pls Sta. 49+87.207 Δ = 7° 44' 35.0" (LT) L = 39.191 T = 19.625 R = 290.000 SE = 0.05	Pls Sta. 50+26.793 Os = 5° 55' 37.7" Ls = 60.000 LT = 40.022 ST = 20.020	Pls Sta. 51+20.299 Os = 2° 38' 39.9" Ls = 60.000 LT = 40.004 ST = 20.004	Pls Sta. 52+13.086 Δ = 12° 46' 46.2" (LT) L = 144.979 T = 72.791 R = 650.000 SE = 0.07	Pls Sta. 53+05.278 Os = 2° 38' 39.9" Ls = 60.000 LT = 40.004 ST = 20.004
Pls Sta. 48+63.587 Os = 2° 50' 51.7" Ls = 60.000 LT = 40.005 ST = 20.005	Pls Sta. 49+94.064 Δ = 20° 44' 42.4" (LT) L = 218.546 T = 110.483 R = 603.600 SE = 0.06	Pls Sta. 51+28.154 Os = 1° 13' 27.6" Ls = 60.000 LT = 33.998 ST = 26.026	Pls Sta. 52+63.547 Δ = 8° 15' 56.4" (LT) L = 202.488 T = 101.420 R = 1,403.600 SE = 0.04	Pls Sta. 53+92.951 Os = 1° 44' 05.6" Ls = 85.000 LT = 56.669 ST = 28.336	

NOTE: ALL Y LINE RADII ARE 10m UNLESS OTHERWISE NOTED
 NOTE: ALL DRIVES ARE 3.6m WITH 3m RADII UNLESS OTHERWISE NOTED
 NOTE: ALL DRIVES IN C&G ARE 6m UNLESS OTHERWISE NOTED
 SEE SHEET 32 FOR -LIREV- PROFILE
 SEE SHEET 34 FOR -L2REV- PROFILE
 SEE SHEET 43 FOR -L6- PROFILE