

DATUM DESCRIPTION
 THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCOOT FOR MONUMENT "R2823-P16" WITH NAD 1983/95 STATE PLANE GRID COORDINATES OF NORTHING: 826864.432(11) EASTING: 2364491.501(11) THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.99995903 THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "R2823-P16" TO -LREV- STATION 6+15.00 IS S 02° 41' 06.9" W 25.45925' ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES VERTICAL DATUM USED IS NAD 88

PI Sta 12+29.69
 $\Delta = 13^{\circ} 06' 42.0"$ (RT)
 $D = 2^{\circ} 52' 00.4"$
 $L = 457.37'$
 $T = 229.69'$
 $R = 1,998.61'$
 $SE = 0.25(RC)$

STOKES ST.	3900	4400
16700	2800	1400
25400	2800	1400
US 64 BUS	400	200
400	400	
STOKES ST.	800	1000
		2004
		2025

PROJECT REFERENCE NO.	U-3328	SHEET NO.	4
R/W SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	

