



NO.	DESCRIPTION
150	
149	DATUM DESCRIPTION
148	THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NGD83 FOR MONUMENT "R2231-10"
147	WITH MAD 83 STATE PLANE GRID COORDINATES OF NORTHING 14735.107(m) EASTING 542189.156(m)
146	THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999861638
145	THE NC LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "R2231-10" TO "STATION" (supplied by roadway) IS
144	ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
143	VERTICAL DATUM USED IS NGVD 29
142	
141	
140	
139	
138	
137	
136	
135	
134	
133	
132	
131	
130	
129	
128	

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	LL	PL	% BY WEIGHT				% PASSING SIEVES			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-143	10 RT	9+60	1.20-1.65	A-2-6(0)	32	17	61.9	13.9	6.1	18.1	65	43	32	-	-
SS-144	10 RT	9+60	2.75-3.17	A-4(6)	29	6	1.0	5.8	67.0	36.2	100	100	96	-	-
SS-140	10 RT	10+20	1.21-1.66	A-2-7(3)	46	23	48.6	11.3	3.9	36.2	86	56	35	-	-
SS-141	10 RT	10+20	2.75-3.18	A-2-7(3)	47	27	58.9	9.0	3.9	28.1	93	49	32	-	-
SS-142	10 RT	10+20	4.25-4.71	A-2-4(0)	29	8	50.3	23.9	7.7	18.1	100	77	27	-	-
SS-137	10 LT	11+20	0.00-0.45	A-2-4(0)	16	NP	59.1	21.7	7.1	12.1	98	54	22	-	-
SS-138	10 LT	11+20	1.38-1.83	A-7-6(5)	52	30	46.8	10.9	8.1	34.2	85	55	37	-	-
SS-139	10 LT	11+20	2.88-3.33	A-2-4(0)	29	7	66.5	12.7	6.7	14.1	86	45	19	-	-
SS-134	10 RT	11+40	0.15-0.45	A-2-7(1)	41	16	59.9	12.3	9.7	18.1	96	66	27	-	-
SS-135	10 RT	11+40	1.25-1.70	A-2-4(0)	34	10	62.9	10.3	7.7	12.1	78	37	17	-	-
SS-136	10 RT	11+40	2.77-3.22	A-7-8(20)	61	15	0.8	1.8	63.2	44.2	100	99	98	-	-

