

B-3348
Bridge #52 on US 264 over Wallace Canal

| HOLE # | SAMPLE # | PASS 10 | PASS 40 | PASS 200 | CSESAND | FINESAND | SI | CL | LL | PI | CLASS | DEPTH | MOIST. | ORG. |
|--------|----------|---------|---------|----------|---------|----------|------|------|----|----|-----------|---------------|--------|------|
| EB1-A | SS-1 | 100 | 100 | 41 | 0.4 | 71.6 | 13.9 | 14.0 | 20 | NP | A-4(0) | 8.50-10.00 | | |
| | SS-2 | 100 | 99 | 17 | 7.6 | 79.2 | 7.1 | 6.0 | 19 | NP | A-2-4(0) | 23.50-25.00 | | |
| | SS-3 | 100 | 99 | 80 | 1.6 | 36.5 | 29.8 | 32.1 | 26 | 10 | A-4(6) | 28.50-30.00 | | |
| | SS-4 | 100 | 68 | 9 | 42.1 | 50.4 | 1.5 | 6.0 | 21 | NP | A-3(0) | 33.50-35.00 | | |
| | SS-5 | 77 | 75 | 11 | 3.6 | 85.7 | 2.7 | 8.0 | 25 | NP | A-2-4(0) | 48.50-50.00 | | |
| | SS-6 | 98 | 74 | 15 | 35.1 | 52.6 | 6.3 | 6.0 | 21 | NP | A-2-4(0) | 53.50-55.00 | | |
| | SS-7 | 83 | 82 | 53 | 1.4 | 52.0 | 28.6 | 18.1 | 30 | 9 | A-4(2) | 68.50-70.00 | | |
| | SS-8 | 100 | 99 | 49 | 1.2 | 76.2 | 16.5 | 6.0 | 24 | NP | A-4(0) | 83.10-84.60 | | |
| | SS-9 | 100 | 99 | 94 | 0.8 | 10.6 | 48.4 | 40.1 | 34 | 15 | A-6(14) | 103.10-104.60 | | |
| EB2-A | SS-10 | 100 | 100 | 83 | 0.6 | 27.1 | 34.2 | 38.1 | 33 | 16 | A-6(12) | 6.20-7.70 | | |
| | SS-11 | 100 | 62 | 20 | 52.2 | 30.5 | 7.3 | 10.0 | 24 | 6 | A-2-4(0) | 58.10-59.60 | | |
| | SS-12 | 100 | 48 | 16 | 41.3 | 39.1 | 9.5 | 10.0 | 20 | 3 | A-1-b(0) | 79.10-80.60 | | |
| EB1-B | SS-13 | 100 | 100 | 26 | 0.8 | 78.4 | 10.8 | 10.0 | 21 | NP | A-2-4(0) | 13.30-14.80 | | |
| | SS-14 | 100 | 100 | 86 | 1.2 | 26.7 | 36.1 | 36.1 | 32 | 17 | A-6(13) | 28.30-29.80 | | |
| | SS-15 | 91 | 54 | 6 | 53.1 | 41.1 | 1.8 | 4.0 | 21 | NP | A-3(0) | 33.30-34.80 | | |
| | SS-16 | 100 | 99 | 17 | 3.0 | 84.6 | 2.4 | 10.0 | 23 | NP | A-2-4(0) | 48.30-49.80 | | |
| | SS-17 | 100 | 99 | 58 | 1.8 | 56.7 | 21.4 | 20.0 | 31 | 9 | A-4(3) | 68.30-69.80 | | |
| | SS-18 | 100 | 99 | 46 | 0.8 | 74.7 | 14.4 | 10.0 | 22 | NP | A-4(0) | 83.30-84.80 | | |
| | SS-19 | 100 | 99 | 94 | 0.8 | 15.4 | 47.7 | 36.1 | 35 | 16 | A-6(15) | 99.00-99.80 | | |
| EB2-B | SS-51 | 100 | 100 | 20 | 4.1 | 85.0 | 6.8 | 4.0 | 20 | NP | A-2-4(0) | 22.60-24.10 | | |
| | SS-52 | 100 | 100 | 91 | 1.2 | 22.0 | 40.6 | 36.3 | 36 | 20 | A-6(18) | 27.60-29.10 | | |
| | SS-55 | 98 | 93 | 26 | 6.1 | 71.7 | 10.1 | 12.1 | 22 | NP | A-2-4(0) | 62.60-64.10 | | |
| | SS-57 | 100 | 99 | 30 | 0.8 | 78.2 | 18.9 | 2.0 | 28 | NP | A-2-4(0) | 82.60-84.10 | | |
| | SS-58 | 100 | 100 | 66 | 0.6 | 68.1 | 27.3 | 4.0 | 28 | NP | A-4(0) | 92.60-94.10 | | |
| | SS-59 | 100 | 100 | 95 | 0.4 | 13.9 | 53.5 | 32.2 | 44 | 26 | A-7-6(26) | 102.60-104.10 | | |