



NOTES:

1. ALL CABLE ATTACHMENT POINTS SHALL BE 40 INCHES BELOW POWER, FRONT SIDE (FS) OF POLE UNLESS OTHERWISE NOTED.
2. ATTACH FIBER OPTIC CABLE TO METAL SIGNAL POLES 12 INCHES ABOVE SIGNAL CABLE, FRONT SIDE (FS) OF POLE UNLESS OTHERWISE NOTED.
3. BOND MESSENGER CABLE TO POLE GROUND.
4. BOND TRACER WIRE TO EQUIPMENT GROUND BUSS BAR.
5. BOND RISER TO POLE GROUND.

***** SYSTEMS *****
 ***** DESIGN *****
 ***** DRAWING *****

ARCADIS
 G & M of North Carolina, Inc.
 WWW.ARCADIS-US.COM
 801 Corporate Center Drive, Suite 300
 Raleigh, NC 27607-5073
 Tel: 919/854-1282 Fax: 919/854-5448

Prepared in the Offices of: 122 N. McDowell St., Raleigh, NC 27603	COMMUNICATIONS CABLE AND CONDUIT ROUTING PLANS		SEAL SEAL 21080 ENGINEER T. A. GRIMES								
	DIVISION 12 IREDELL COUNTY E. OF STATESVILLE PLAN DATE: AUGUST 2002 REVIEWED BY: K. MILAM PREPARED BY: X. FAN REVIEWED BY:										
SCALE 1:500		REVISIONS <table border="1"> <thead> <tr> <th>NO.</th> <th>DESCRIPTION</th> <th>INIT.</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>		NO.	DESCRIPTION	INIT.	DATE				
NO.	DESCRIPTION	INIT.	DATE								
SEAL NOT VALID UNLESS SIGNED AND DATED SIGNATURE: DATE: 1-27-02 CADD FILENAME:											