



NOTES:

1. ALL CABLE ATTACHMENT POINTS SHALL BE 40 INCHES BELOW POWER, FRONT SIDE (FS) OF POLE UNLESS OTHERWISE NOTED.
2. ATTACH FIBER OPTIC CABLE TO METAL SIGNAL POLES 12 INCHES ABOVE SIGNAL CABLE, FRONT SIDE (FS) OF POLE UNLESS OTHERWISE NOTED.
3. BOND MESSENGER CABLE TO POLE GROUND.

ARCADIS
 G & M of North Carolina, Inc.
 WWW.ARCADIS-US.COM
 801 Corporate Center Drive, Suite 300
 Raleigh, NC 27607-5073
 Tel: 919/854-1282 Fax: 919/854-5448

	COMMUNICATIONS CABLE AND CONDUIT ROUTING PLANS								
	DIVISION 12 IREDELL COUNTY E. OF STATESVILLE PLAN DATE: AUGUST 2002 REVIEWED BY: K. MILAM PREPARED BY: X. FAN REVIEWED BY:			SEAL 21080 ENGINEER TYSON A. GRAVES SIGNATURE DATE					
SCALE 1:500		REVISIONS <table border="1"> <thead> <tr> <th>NO.</th> <th>DATE</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>		NO.	DATE	DESCRIPTION			
NO.	DATE	DESCRIPTION							

*****SYTIME*****
 *****REVISIONS*****
 *****DATE*****