


-BL-	-Y16-	-L-
PI Sta 162+10.371	PI Sta 10+66.925	PI Sta 87+10.370
D = 3° 06' 53.4" (RT)	Δ = 8° 33' 14.3" (LT)	Δ = 3° 06' 53.4" (RT)
L = 190.456	L = 29.859	L = 190.456
T = 95.252	T = 14.957	T = 95.252
R = 3,503.352	R = 200.000	R = 3,503.352
	SE = 0.033	SE = 02
	RUNOFF = 15m	RUNOFF = 18

**CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 27**



PROJECT REFERENCE NO.	SHEET NO.
R-2610 B	EC-26/CONST.27
ROADWAY DESIGN ENGINEER	
HYDRAULICS ENGINEER	

NOTE:
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE-B
AND TEMPORARY ROCK SILT CHECKS TYPE-A AT
DRAINAGE OUTLETS.



CONST. REV.
R/W REV.

SEE SHEET 50 & 51 FOR -L- PROFILE
SEE SHEET 61 FOR -Y16- PROFILE
SEE SHEET 2-1 FOR -Y16- DETAILS
SEE SHEET 2-H FOR -L- & -Y15-
INTERSECTION DETAILS

MATCHLINE -L- 87 + 70 SEE SHEET 26

MATCHLINE -L- 91 + 20 SEE SHEET 28

