



KCI Associates
of North Carolina, P.A.
RALEIGH OFFICE
ENGINEERS PLANNERS • ECOLOGISTS

SUITE 220, LANDMARK CENTER II 460I SIX FORKS RD. RALEIGH, N.C. 27609-5210 (919) 783-9214

PROJECT REFERENCE NO.		SHEET NO.
B−345I		2-A
RW SHEET NO.		
ROADWAY DESIGN ENGINEER WAS SEAL 22701 10 10 10 10 10 10 10 10 10 10 10 10 1	Harring Assessment of the Control of	SEAL 22896 NGINEER NGINEER

PAVEMENT SCHEDULE

CODE	DESCRIPTION
\bigcirc	PROP. APPROX. 1 ¹ /4" ASPHALT CONC. SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 140 LBS PER SQ. YARD
C 2	PROP. APPROX. 2½" ASPHALT CONC. SURFACE COURSE, Type S9.5B, at an average rate of 140 lbs per sq. yard In each of two layers.
© 3	PROP. VAR. DEPTH ASPHALT CONC. SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 112 LBS PER SQ. YARD PER 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 11/2" IN DEPTH.
	PROP. APPROX. 3½" ASPHALT CONC. INTERMEDIATE COURSE, TYPE 119.0B, AT AN AVERAGE RATE OF 399 LBS PER SQ. YARD.
D 2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE II9.0B, AT AN AVERAGE RATE OF II4 LBS. PER SQ. YD. PER I"DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 21/4" IN DEPTH OR GREATER THAN 4" IN DEPTH.
EI	PROP. APPROX. 5" ASPHALT CONC. BASE COURSE, TYPE B25.OB, AT AN AVERAGE RATE OF 570 LBS PER SQ. YARD.
E2	PROP. VAR. DEPTH ASPHALT CONC. BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 114 LBS PER SQ. YARD PER 1" DEPTH. TO BE PLACED IN LAYERS NOT GREATER THAN 51/2" IN DEPTH OR LESS THAN 3" IN DEPTH.
Ţ	EARTH MATERIAL.
	EXISTING PAVEMENT MATERIAL.
W	VAR. DEPTH ASPHALT PAVEMENT. (SEE WEDGING DETAIL)

USE I: PAVEMENT EDGE SLOPES UNLESS OTHERWISE NOTED