STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH STANDARD DRAWING FOR
DRUMS

SHEET 1 OF 1
1130D01

STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH STANDARD DRAWING FOR
DRUMS

SHEET 1 OF 1
1130D01

TOP
18" MIN. TO 24" MAX.
DIAMETER

NOT TO EXCEED
BASE DIAMETER

ORANGE, OR FLUORESCENT RED-ORANGE
ULTRA VIOLET STABILIZED
IMPACT RESISTANT PLASTIC

6" TO 8" STRIPES
TYPICAL

36"
MINIMUM

CIRCUMFERENTIAL
ALTERNATE WHITE & ORANGE
RETROREFLECTIVE STRIPES,
3 ORANGE & 2 WHITE MINIMUM
COVERING ENTIRE OUTSIDE

2" MAX. TYPICAL
BETWEEN STRIPES

21" MIN. TO 24" MAX. DIAMETER

GENERAL NOTES

-BALLASTING SHALL BE ACHIEVED BY THE SAND BAG, TIRE-SIDEWALL BALLAST, OR PREFORMED WEIGHTED BASE BALLASTING
METHODS. DO NOT PLACE BALLAST ON TOP OF THE DRUM.

-IF NECESSARY PLACE THE NAME OF THE AGENCY, CONTRACTOR, OR SUPPLIER ON NON-RETROREFLECTIVE DRUM SURFACES.
SHOW THE LETTERS AND NUMBERS USING A NON-RETROREFLECTIVE COLOR AND NOT OVER 2" IN HEIGHT.

APPROVED:_____ DATE:_____

SEAL

REPLACEMENT DETAIL FOR
RSD 1130.01

SCALE:	NONE		REVISIONS
DATE:	4/02		11/02
DWG. BY:	MMM		
DESIGN BY:	MMM		
REVIEWED BY:	MMM		
		CADD FILE	

23-DEC-2004 II:50
\\ets-ccfs0\TCU\TCU\2Group-MM\Resurfacing\Divi3\wbsI3CRI08II2etc\I3CRI08II2etcDrums_englishII2304.dgn
pseymore   AT TETC206427