DIVISION OF HIGHWAYS

GEOTECHNICAL UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

TRACE - PRESENCE OF LESS THAN 5% OF SUBJECT MATERIAL.

	SOIL D	ESCRIPTION		GRADATION TERMS AND DEFINITIONS	
SOIL IS CONSIDERED TO BE THE	UNCONSOLIDATED, SEMI-CONS	SOLIDATED OR WEATHERED EARTH MA	ATERIALS WHICH CAN BE PENETRATED	WELL GRADED- INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM- INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER.	BLDR.
WITH A CONTINUOUS FLIGHT POW	VER AUGER, AND WHICH YIELDS	S LESS THAN 100 BLOWS ACCORDIN	NG TO STANDARD PENETRATION	UNIFORM- INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER. POORLY GRADED) APPARENT DIP - THE DIP OF ROCK STRATA NOT PERPENDICULAR TO STRIKE.	CL (
TEST (ASTM D-1586). SOIL CLAS	ASSIFICATION IS BASED ON THE	E AASHTO SYSTEM AND BASIC DESCR	RIPTIONS GENERALLY SHALL INCLUDE:	GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.	COB
CONSISTENCY, COLOR, TEXTUR	RE, MOISTURE, AASHTO CLASS	SIFICATION AND OTHER PERTINENT	FACTORS, SUCH AS, MINERALOGICAL	ANGULARITY OF GRAINS	CSE
	RUCTURE, PLASTICITY, ETC.	EXAMPLE: VERY STIFF, GRAY SILTY	CLAY, MOIST WITH INTERBEDDED FINE SAND	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS; ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED. AUGER REFUSAL (A.R.) - POINT AT WHICH POWER AUGERS WILL NOT PENETRATE. BEDDED - SOIL OR ROCK LYING IN A POSITION ESSENTIALLY PARALLEL.	EST
LAYERS, HIGHLY PLASTIC, A-7-6.				DEDDOCK DOCK OF DELATIVELY CREAT THICKNECS AND EVTENT IN ITS ORIGINAL LOCATION	E F.
SOIL	L LEGEND AND	AASHTO CLASSIF	FICATION	MINERALOGICAL COMPOSITION CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.	FOSS.
	JLAR MATERIALS	SILT-CLAY MATERIALS	I IRIANII MATERIALS	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN	
	(PASSING #200)	(> 35% PASSING #200)	SIGNIFICANT COHESION WHEN SUBMERGED.	FRAC.
0,,00,	1-3 A-2		7 A-1, A-2 A-4, A-5 5 A-3 A-6, A-7	COMPRESSIBILITY COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT SLIGHTLY COMPRESSIBLE LIQUID LIMIT LESS THAN 30 ROTTOM OF SLOPE.	GR (
CLASS. A-1-AA-1-B	A-2-4A-2-5A-2-6A-	7 V V V V V V V V V V V V V V V V V V V	6		LL - L]
SYMBOL 00000000000000000000000000000000000		P 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		CONE NECOVENT (% NEC.) - TOTAL LENGTH OF ALL NOON DIVIDED DI TOTAL LENGTH OF CONL	MED
% PASSING			GRANIII AR SILT-	ROCK DESCRIPTION COQUINA - A ROCK TYPE COMPOSED ESSENTIALLY OF MARINE SHELLS CEMENTED BY CALCIUM CARBONATE.	W - MO]
# 10 50 MX # 40 30 MX50 MX51	MNI		GRANULAR SILI- MUCK, SOILS CLAY PEAT	IN THE BROADEST MEANING, HARD ROCK IS CONSIDERED THAT MATERIAL WHICH CANNOT BE DIKE - IGNEOUS ROCK INTRUSION WHICH IS NARROW COMPARED WITH ITS OTHER DIMENSIONS.	MOT
		5 MX36 MN 36 MN 36 MN 36 M	l corre l'-'''	SAMPLED BY CONVENTIONAL SOIL SAMPLING TOOLS OR TECHNIQUES. THE BOUNDARY BETWEEN DIP - THE ANGLE BETWEEN A BEDDING PLANE, JOINT PLANE OR FAULT PLANE AND THE	OM - OF
				SOIL AND ROCK IS ARBITRARY. TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED HORIZONTAL, MEASURED PERPENDICULAR TO THE STRIKE.	ORG
LIQUID LIMIT PLASTIC INDEX 6 MX N.		. MN 40 MX 41 MN 40 MX 41 M . MN 10 MX 10 MX 11 MN 11 M	ANI SUILS WITH	BY A ZONE OF "WEATHERED ROCK". FOR THE PURPOSE OF THIS INVESTIGATION, THESE MATERIALS ARE DIVIDED AS FOLLOWS: DUMPS - UNCOVERED DEPOSITS OF WASTE MATERIAL SUCH AS WOOD, MASONRY DEBRIS OR GARBAGE.	
			- HIGHLY	FAULT - A BREAK IN THE CONTINUITY OF A BODY OF ROCK, ATTENDED BY A MOVEMENT ON	
GROUP INDEX Ø	Ø Ø 4 MX	(8 MX 12 MX 16 MX NO M	MUDERATE ORGANIC AMOUNTS OF SOILS	SOFT MATERIAL THAT CAN BE PENETRATED WITH SOME EITHER OR BOTH SIDES OF THE BREAK. WEATHERED WEATHERED DIFFICULTY USING POWER AUGERS AND YIELDS FINES - PORTIONS OF A SOIL FINER THAN NO. 200 U.S. STANDARD SIEVE.	AUT
USUAL TYPES STONE FRAGS. FI	INE SILTY OR CLAYE	1	ORGANIC	ROCK SPT VALUES > 100 BLOWS BUT < SPT REFUSAL STORY OF SPECIAL	
MATERIALS SAND SA	AND GRAVEL AND SAN	ND SOILS SOILS	MATTER	(SWR) HARD MATERIAL THAT CAN BE PENETRATED WITH GREAT PLANES	IE SUBSURFA)R THE PURP
GEN. RATING			FAIR TO BOOK	WEATHERED DIFFICULTY USING POWER AUGERS AND YIELDS FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED SOL	OME DATA OF
!	LENT TO GOOD	FAIR TO POOR	POOR POOR UNSUITABLE	HARD CORED ROCK INFERRED ROCK MATERIAL THAT CANNOT BE PENETRATED BY POWER INCORPULATION OF SERVICE DEPOSITED BY THE STREAM ADD	DITIONAL INFO
SUBGRADE P. T. OE		 80 : P.I. OF A-7-5 >	> 1 1 - 20	ROCK STATE THE CHING BE FENERAL THAT CHING BE FENERAL THAT CHING BE TOWER FLOUDPLAIN - LAND BURDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.	DITIONAL IN C
rala Ur		ICY OR DENSENES		(HR) SSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS	
	COMPACTNESS OR	RANGE OF STANDARD	RANGE OF UNCONFINED	*SPT REFUSAL ≤2.5cm OF PENETRATION PER 50 BLOWS. FRACTURE - A CRACK LARGE ENOUGH TO BE VISIBLE TO THE UNAIDED EYE.	
PRIMARY SOIL TYPE	CONSISTENCY	PENETRATION RESISTENCE		** AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH AUGERS COULD NO LONGER FRIABLE - EASY TO BREAK OR CRUMBLE.	
		(BLOWS)	(kN/m ²)	PENETRATE. THE HARD ROCK SYMBOL IS SHOWN WHEN ROCK IS CORED AND ONLY TO THAT DEPTH CORED. A DESCRIPTION OF ROCK IS GIVEN INCLUDING: GRANULAR MATERIAL - SOIL THAT WHEN UNCONFINED HAS LITTLE OR NO DRY STRENGTH AND HAS TH	HIS INFORMAT
GENERALLY	VERY LOOSE LOOSE	< 4 4 TO 10		LITTLE OR NO COHESION WHEN SUBMERGED.	RANSPORTATI
GRANULAR	MEDIUM DENSE	4 TO 1Ø 1Ø TO 3Ø	N/A	CORE RECOVERY (REC.)- TOTAL LENGTH OF ROCK RECOVERED IN THE CORE BARREL DIVIDED GROUNDWATER (G.W.) - WATER THAT IS FREE TO MOVE THROUGH SOIL MASS UNDER THE INFLUENCE NO BY THE TOTAL LENGTH OF THE CORE RUN TIMES 100%.	OR THE FIELD
MATERIAL	DENSE	3Ø TO 5Ø		or outviri.	ENERAL SOIL
	VERY DENSE	>50		THE STATE OF THE S	EOTECHNICAL
	VERY SOFT SOFT	<2	<25	BY THE TOTAL LENGTH OF THE CORE RUN TIMES 100%. NOT SOFTEN WHEN WET.	EFLECT THE
GENERALLY	MEDIUM STIFF	2 TO 4 4 TO 8	25 TO 50 50 TO 100	I INDIDALD - EADIU MALDIAL DA DESCRIPE DE CEMENTATION	ITHIN THE BO ELIED ON ONI
SILT-CLAY MATERIAL	STIFF	8 TO 15	100 TO 200		HE OBSERVED
MHILIVIHL	VERY STIFF HARD	15 TO 3Ø >3Ø	200 TO 400 >400	I A CIVIL MVIED LEVEL VEIED ΔV HUIDG	VESTIGATIONS
				LAMINATED - VERY THIN ALTERNATING LAYERS LESS THAN TINCH.	OISTURE CON EMPERATURES
	TEXTURE	OR GRAIN SIZE		LAYER - SUBJECT MATERIAL GREATER THAN LINCH IN THICKNESS.	
U.S. STD. SIEVE SIZE 4 10 40 60 200 270				() SPRING OR SEEPAGE LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED OR PROJECTION OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED OR PROJECTION OR P	HE BIDDER OF RE PRELIMINA
OPENING (MM)	4.76 2.	0 0.42 0.25 0.0	75 0.053	TO TIS LATERAL EXTENT.	ND CONSTRUC
		COARSE FINE	F		FORMATION (
BOULDER COBB	BLE GRAVEL	SAND SANI		TEST BORING DECICAL INDURATIONS DEPOSIT OF CLAYS, SILIS AND SANDS, OFTEN	R ACCURACY EPARTMENT /
				COMPANIO SHELLS.	ONTRACTOR I
GRAIN MM 305 SIZE IN. 12"	75 2.	Ø Ø.25	0.05 0.005		ECESSARY TO
				SS- SPLIT SPOON MUCK (MK.) - A HIGHLY ORGANIC SOIL OF VERY SOFT CONSISTENCY, GENERALLY FOUND ON	ONTRACTOR : NY REASON F
		- CORRELATION (OF TERMS	ROADWAY EMBANKMENTS — CORE BORING SAMPLE TIDAL FLATS, LAKE OR STREAM FLOODPLAINS.	HOSE INDICAT
SOIL MOISTURE SC (ATTERBERG LIMIT	l l	MOISTURE GUIDE FOR	FIELD MOISTURE DESCRIPTION	ST- SHELBY TUBE PEAT (PT) - A FIBROUS MASS OF ORGANIC MATTER IN VARIOUS STAGES OF DECOMPOSITION. SAMPLE PERCUED WATER MAINTAINED ABOVE THE NORMAL CROWND WATER LEVEL BY THE RESERVE.	
VIII TERBERO ETITI	107 BEGGIN			THE POLICE OF THE POLICE TO MUNITURING WELL PERCHED WHICH INCIDENCE I THE POLICE OF TH	OTE – THE IN F TRANSPORT
			LIQUID; VERY WET, USUALLY	of the intervention in civilous states on	PECIFICATION:
LL LIQUID L		AT.) FROM BEL	LOW THE GROUND WATER TABLE	INSTALLATION DOCK OFF LEGEND	
PLASTIC T		CEMICOLI	ID: REQUIRES DRYING TO		OTE – BY HAI OR INCREASE
RANGE <	- WET	_ (\4)	DPTIMUM MOISTURE	() OLGI E TINDIGITION TO GOOTH THE TINDIGET TO THE TINDIGET T	ONDITIONS IN
PLL PLASTIC	LIMIT			LENGTH OF CORE RUN EXPRESSED AS A PERCENTAGE.	
ODT IMUM N	MOTOTUDE - MOTO	ST - (M) SOLID; A	AT OR NEAR OPTIMUM MOISTURE	(NORMAL TO) SPIN-COUNT SANITARY LANDFILLS - COMPACTED AND/OR COVERED LAYERS OF SOIL AND WASTE PRODUCTS.	NOTES:
OM _ OPTIMUM N SL _ SHRINKAGI	HOTOTORE			SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF NEW THE PARENT ROCK.	VOILJ.
JE — SIINTINKHOI	remain term de l'1 de l'	טרטונטרנ	S ADDITIONAL WATER TO	DRILL UNITS: AUGER TOOLS: HAMMER TYPE: SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A	
	- DRY	()	S AUDITIUNAL WATER TU SPTIMUM MOISTURE	FAULT OR SLIP PLAIN.	
				MOBILE B-47 6" (152 mm) CONTINUOUS FLIGHT MAIL SILL - AN IGNEOUS SHEET OF INTRUSIVE ROCK WHOSE THICKNESS IS SLIGHT COMPARED TO	
		ASTICITY Ticity index	DRY STRENGTH	BK-51 8" (203 mm) HOLLOW AUGERS CORE BORING TOOLS: COME PRECENCE OF 5% TO 20% OF SUBJECT MATERIAL	
	rlas I	ICIII INDEX		SOME - PRESENCE OF 5% TO 30% OF SUBJECT MATERIAL.	
NONPLASTIC		J-5	VERY LOW	CME-45B HARD FACED FINGER BITS -AX -BX STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR B.P.F.) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH	
LOW PLASTICITY MED. PLASTICITY		S-15 S-25	SLIGHT MEDIUM	CME-550 TUNG CARBIDE INSERTS HAND TOOLS: A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL PENETRATION RESISTANCE OF LESS	
HIGH PLASTICITY		OR MORE	HIGH	THAN TINCH WITH 50 BLOWS.	
		COLOR		PORTABLE HOIST CLAY BITS SIRIKE - THE DIRECTION OR BEARING OF A HORIZONTAL LINE IN THE PLANE OF AN	
DECORIDITIONS				OTHER OTHER: HAND AUGER SUBGRADE - THE SOIL PREPARED TO SUPPORT A STRUCTURE OR A PAVEMENT SYSTEM.	
			RED, YEL-BRN, BLUE-GRAY)	SOUNDING ROD TORROST OF THE SO	
LWODILIEU2 2004 82 FI	UNI, DHKK, MUIILEU,	SINEHNEU, EIL. AKE L	USED TO DESCRIBE APPEARANCE.	OTHER VANE SHEAR TEST TRACE - PRESENCE OF LESS THAN 5% OF SUBJECT MATERIAL.	

BOULDER PL - PLASTIC LIMIT CLAY PI - PLASTICITY INDEX COBBLE n - POROSITY COARSE SD. - SAND ESTIMATED SAT. - SATURATED SL. - SILT, SILTY FOSSILIFEROUS SLI. - SLIGHTLY FRACTURED G_S - SPECIFIC GRAVITY GRAVEL qu - UNCONFINED COMPRESSIVE STRENGTH IQUID LIMIT - UNIT WEIGHT (WET UNIT WEIGHT) MEDIUM 7d - DRY UNIT WEIGHT ISTURE CONTENT SAT - SATURATED UNIT WEIGHT MOTTLED e - VOID RATIO PTIMUM MOISTURE ORGANIC V. - VERY

ABBREVIATIONS

STATE PROJECT NO. | SHEET NO. | TOTAL SHEETS

220

ION NOTICE:

ID

ACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WAS MADE POSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. BTAINED MAY BE OMITTED FROM THIS RELEASE.

FORMATION MAY BE AVAILABLE, INCLUDING, BUT NOT LIMITED TO THE FOLLOWING:

FIELD BORING LOGS ROCK CORES SOIL & ROCK TEST DATA SUBSURFACE REPORT


TION MAY BE VIEWED BY APPOINTMENT BY CONTACTING THE N. C. DEPARTMENT OF TION, GEOTECHNICAL UNIT @ (919)250-4088. NEITHER THE SUBSURFACE PLANS AND REPORTS, D BORING LOGS, ROCK CORES, OR SOIL TEST DATA IS PART OF THE CONTRACT.

AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA OREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE NLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE IS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL NDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING ES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING JCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE OR OPINIONS OF THE AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT. THE SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM TED IN THE SUBSURFACE INFORMATION.

NFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT TATION AS BEING ACCURATE NOR IS IT CONSIDERED TO BE PART OF THE PLANS, NS, OR CONTRACT FOR THE PROJECT.

AVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS ED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE NDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.



REVISED AUGUST 10, 1998