6/20/00

COMPUTED BY: D.M.W. DATE: 9/2004
CHECKED BY: W.C.B. DATE: 12/2004

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

METRIC

PROJECT REFERENCE NO.	SHEET NO.
R-2552C	3-D

LIST OF PIPES, ENDWALLS, ETC. (FOR PIPES 1200 mm & UNDER)

| STATION | LOCATION (LT, RT, OR CL) | STRUCTURE NO. FROM | STRUCTURE NO. TO | TOP ELEVATION | INVERT ELEVATION | INVERT ELEVATION | SLOPE CRITICAL | CLASS III R.C. PIPE (UNLESS NOTED OTHERWISE) SIZE | 300 | 375 | 450 | 600 | 750 | 900 | 1050 | 1200 | BITUMINOUS COATED C.S. PIPE TYPE B (UNLESS NOTED OTHERWISE) SIZE | 300 | 400 | 450 | 600 | 800 | 900 | 1000 | 1200 | C.S. PLAIN PIPE SIZE | 400 | 450 | BITUMINOUS COATED C.S. PIPE TYPE A SIZE | 400 | 450 | 600 | 800 | 900 | 375mm SIDE DRAIN PIPE | 450mm SIDE DRAIN PIPE | 600mm SIDE DRAIN PIPE | ENDWALLS STD. 838.01, STD. 838.11 OR STD. 838.80 (UNLESS NOTED OTHERWISE) (UNLESS NOTED OTHERWISE) R.C.P. (CM) | ENDWALLS STD. 838.01, STD. 838.11 OR STD. 838.80 (UNLESS NOTED OTHERWISE) (UNLESS NOTED OTHERWISE) C.S.P. (CM) | QUANTITIES: STRUCTURES FOR DRAINAGE "TOTAL M FOR PAY QUANTITY" (USE COL. 'A' + (1.3 X COL. 'B') METERS A | QUANTITIES: STRUCTURES FOR DRAINAGE "TOTAL M FOR PAY QUANTITY" (USE COL. 'A' + (1.3 X COL. 'B') METERS B | FRAME, GRATES, AND HOOD STD. 840.03 TYPE OF GRATE E | F | G | D.I. STD. 840.14 OR STD. 840.15 | D.I. FRAME & GRATE STD. 840.16 | B.A.D.I. (SEE SHEET 2-P) | T.B.D.I. STD. 840.36 | T.B.D.I. FRAME WITH STEEL GRATE STD. 840.37 | M.D.I. TYPE "A" STD. 840.17 OR 840.26 | M.D.I. TYPE "B" STD. 840.18 OR 840.27 | M.D.I. TYPE "D" STD. 840.19 OR 840.28 | M.D.I. FRAME WITH TWO FLAT GRATES STD. 840.20 | M.D.I. FRAME WITH SAG GRATE STD. 840.22 | M.D.I. FRAME WITH TWO SAG GRATES STD. 840.22 | M.D.I. (N.S.) FRAME WITH TWO SAG GRATE STD. 840.24 | M.D.I. (N.S.) FRAME WITH TWO SAG GRATES STD. 840.24 | J.B. STD. 840.31 OR 840.32 | C.B. STD. 840.01 OR 840.02 | O.T.C.B. STD. 840.04 OR 840.05 | M.H. STD. 840.51, 840.52 OR 840.53 | M.H. FRAME AND COVER STD. 840.54 | T.B.J.B. STD. 840.34 | 800 x 800 x 800mm PERF. C.S.P. TEE RISER 2.01mm THICK | CONVERT EXISTING D.I. OR C.B. TO J.B. (SEE SHEET 2-AC) | 375mm BORE AND JACK SPIRAL WELDED STEEL (7mm THICK) | 450mm BORE AND JACK SPIRAL WELDED STEEL (8mm THICK) | 600mm BORE AND JACK SPIRAL WELDED STEEL (13mm THICK) | ADJUST EXISTING 2GI | MODIFIED CONCRETE FLUME (SEE SHEET 2-AA) | PREFORMED SCOUR HOLE (SEE REMARKS) | C.S. ELBOWS NO. | C.S. ELBOWS SIZE | CONC. COLLARS CL. "B" M3 STD. 840.72 | CONC. & BRICK PIPE PLUG, M3 STD. 840.71 | PIPE REMOVAL (METERS) | REMARKS |
|---|---|---