




CONST. REV.  
R/W REV.

PROJECT REFERENCE NO. R-2552C	SHEET NO. 2
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	STATE PAVEMENT DESIGN ENGINEER
	

## PAVEMENT SCHEDULE

C1	PROP. APPROX. 40 MM ASPH. CONC. SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 96 KG. PER SQ. METER.	E6	PROP. VAR. DEPTH ASPH. CONC. BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 2.45 KG PER SQ. METER PER 1 MM DEPTH. TO BE PLACED IN LAYERS NOT GREATER THAN 140 MM IN DEPTH OR LESS THAN 75 MM IN DEPTH.
C2	PROP. APPROX. 80 MM ASPH. CONC. SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 96 KG PER SQ. METER IN EACH OF TWO LAYERS.	E7	PROP. VAR. DEPTH ASPH. CONC. BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 2.45 KG PER SQ. METER PER 1 MM DEPTH. TO BE PLACED IN LAYERS NOT GREATER THAN 140 MM IN DEPTH OR LESS THAN 75 MM IN DEPTH.
C3	PROP. APPROX. 100 MM ASPH. CONC. SURFACE COURSE, TYPE S12.5C, AT AN AVERAGE RATE OF 120 KG PER SQ. METER IN EACH OF TWO LAYERS.	E8	PROP. APPROX. 170 MM ASPH. CONC. BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 208.25 KG PER SQ. METER IN EACH OF TWO LAYERS.
C4	PROP. APPROX. 60 MM ASPH. CONC. SURFACE COURSE, TYPE SF9.5A, AT AN AVERAGE RATE OF 70.5 KG. PER SQ. METER IN EACH OF TWO LAYERS.	J1	PROP. 150 MM AGGREGATE BASE COURSE.
C5	PROP. VAR. DEPTH ASPH. CONC. SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 2.4 KG PER SQ. METER PER 1 MM DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 40 MM OR GREATER THAN 50 MM IN DEPTH.	J2	PROP. 200 MM AGGREGATE BASE COURSE.
C6	PROP. VAR. DEPTH ASPH. CONC. SURFACE COURSE, TYPE S12.5C, AT AN AVERAGE RATE OF 2.4 KG PER SQ. METER PER 1 MM DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 50 MM OR GREATER THAN 100 MM IN DEPTH.	J3	PROP. 250 MM AGGREGATE BASE COURSE.
C7	PROP. VAR. DEPTH ASPH. CONC. SURFACE COURSE, TYPE SF9.5A, AT AN AVERAGE RATE OF 2.35 KG PER SQ. METER PER 1 MM DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 25 MM OR GREATER THAN 50 MM IN DEPTH.	J4	PROP. 150 MM INCIDENTAL STONE BASE.
D1	PROP. APPROX. 65 MM ASPH. CONC. INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 159.25 KG PER SQ. METER.	K	SUBBASE TO BE TREATED WITH LIME TO A DEPTH OF 200 MM, AT A RATE OF 11 KG PER SQ. METER AS DIRECTED BY THE ENGINEER.
D2	PROP. APPROX. 80 MM ASPH. CONC. INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 196 KG PER SQ. METER.		SUBBASE TO BE TREATED WITH CEMENT TO A DEPTH OF 180 MM, AT A RATE OF 30 KG PER SQ. METER AS DIRECTED BY THE ENGINEER.
D3	PROP. APPROX. 100 MM ASPH. CONC. INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 245 KG PER SQ. METER.	P1	PRIME COAT AT THE RATE OF 1.6 L PER SQ. METER.
D4	PROP. VAR. DEPTH ASPH. CONC. INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 2.45 KG PER SQ. METER PER 1 MM DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 65 MM OR GREATER THAN 110 MM IN DEPTH.	R1	750 MM CONCRETE CURB AND GUTTER.
E1	PROP. APPROX. 75 MM ASPH. CONC. BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 183.75 KG PER SQ. METER.	R2	SHOULDER BERM GUTTER.
E2	PROP. APPROX. 80 MM ASPH. CONC. BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 196 KG PER SQ. METER.	R3	175 MM MONOLITHIC CONCRETE ISLAND (FUTURE).
E3	PROP. APPROX. 100 MM ASPH. CONC. BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 245 KG PER SQ. METER.	T	EARTH MATERIAL.
E4	PROP. APPROX. 140 MM ASPH. CONC. BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 343 KG PER SQ. METER.	U	EXISTING PAVEMENT.
E5	PROP. APPROX. 200 MM ASPH. CONC. BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 245 KG PER SQ. METER IN EACH OF TWO LAYERS.	W	VARIABLE DEPTH ASPHALT PAVEMENT. (SEE STANDARD WEDGING DETAILS ON SHEET 2-F).

NOTE: ON WIDENING AREAS WHERE ABC IS USED, USE BLACK BASE AS RECOMMENDED BY PAVEMENT DESIGN FROM 0 TO 2.4m

NOTE: PROPOSED PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.

24 MAR 2006 10:32 AM C:\P2552C\RDY\_TYP.DGN

**LOCHNER**  
H. W. LOCHNER, INC.  
2840 PLAZA PLACE, SUITE 202  
RALEIGH, NC 27612