

NOTES

STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR ANCHOR BOLTS.

FOR PILE SPLICE DETAILS, SEE SHEET 3 OF 3

BACKWALL SHALL BE PLACED BEFORE APPLYING THE EPOXY PROTECTIVE COATING.


FOR EPOXY PROTECTIVE COATING, SEE SPECIAL PROVISIONS

THE TOP SURFACE AREAS OF THE END BENT CAP SHALL BE CURED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS EXCEPT THAT THE MEMBRANE CURING COMPOUND METHOD SHALL NOT BE USED.

THE TOP SURFACE OF THE CAP EXCEPT THE BRIDGE SEAT BUILDUPS SHALL BE SLOPED TRANSVERSELY FROM THE FILL FACE TO THE BACK FACE AT THE RATE OF 2%.


FOR TEMPORARY DRAINAGE AT END BENT, SEE SHEET 3 OF 3.

▲ DENOTES BATTER PILES 250:1000 IN DIRECTION OF ARROW



PLAN

BAR	MIN. SPLICE
*13B2	740



ELEVATION

SEE SECTION A-A ON SHEET 3 OF 3 FOR ELEVATION LOCATIONS

WING WALLS OMITTED FOR CLARITY

PROJECT NO. R-2552B

JOHNSTON COUNTY


STATION: 65+51.880 -L-
14+25.318 -Y7-

SHEET 1 of 3


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

END BENT #2
SUBSTRUCTURE

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-22
1			3			TOTAL SHEETS
2			4			431



1-13-04



1616 E. MILLBROOK RD., SUITE 310
RALEIGH, NORTH CAROLINA 27609
PHONE (919) 876-6888
FAX (919) 876-6848

DRAWN BY: SD DATE: 7/03
CHECKED BY: JL DATE: 8/03