

PROJECT NOTES

PHASING

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

ADAPT THE TRAFFIC CONTROL PLANS, WHEN DIRECTED BY THE ENGINEER, TO MEET FIELD CONDITIONS TO PROVIDE SAFE AND EFFICIENT TRAFFIC MOVEMENT. CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS AND ROADWAY DETAILS ARE NOT ATTAINABLE OR RESULT IN DUPLICATE OR UNDESIRED OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING OR REMOVAL OF DEVICES.

TRAFFIC PATTERN ALTERATIONS

- A) NOTIFY THE ENGINEER 21 CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

SIGNING

- B) PROVIDE PERMANENT SIGNING WITHIN THE PROJECT LIMITS.
- C) PROVIDE DETOUR SIGNING WITHIN AND OFF THE PROJECT LIMITS.
- D) COVER OR REMOVE ALL DETOUR SIGNS WITHIN AND OFF THE PROJECT LIMITS WHEN A DETOUR IS NOT IN OPERATION.
- E) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.

TRAFFIC CONTROL DEVICES

- F) PLACE TYPE III BARRICADES, WITH "ROAD CLOSED" SIGN R11-2 ATTACHED, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY. STAGGER OR OVERLAP BARRICADES TO ALLOW FOR INGRESS OR EGRESS.

PAVEMENT MARKINGS AND MARKERS

- G) INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE AS FOLLOWS:

ROAD NAME	MARKING	MARKER
1. 13 BRIDGES ROAD (SR 1003)	THERMOPLASTIC	PERMANENT RAISED

- H) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.

STEP 1: USING SHEETS TCP-3 AND TCP-4, INSTALL DETOUR SIGNS AND PLACE BARRICADES TO CLOSE SR 1003 (13 BRIDGES ROAD) TO THRU TRAFFIC. DETOUR TRAFFIC ONTO PROPOSED DETOUR.

STEP 2: AWAY FROM TRAFFIC, REMOVE EXISTING STRUCTURES NO. 40 AND NO. 45 AND CONSTRUCT BOTH PROPOSED STRUCTURES.



- CONSTRUCT PROPOSED ROADWAY FROM -L- STA. 16+00 TO -L- STA. 35+46.97 UP TO AND INCLUDING FINAL SURFACE COURSE.

- PLACE PERMANENT PAVEMENT MARKINGS (THERMO) AND PERMANENT RAISED MARKERS ON -L- AND TIE INTO EXISTING MARKINGS AND MARKERS AT -L- STA. 16+00 AND -L- STA. 35+46.97.

STEP 3: REMOVE ALL TRAFFIC CONTROL DEVICES AND REMOVE ALL DETOUR SIGNING.

- OPEN SR 1003 (13 BRIDGES ROAD) TO ALL TRAFFIC.

FINAL PAVEMENT MARKING SCHEDULE			
TIP PROJECT # B-3467			
SYMBOL	DESCRIPTION	PAY ITEM QUANTITY BREAKDOWN	TOTAL QUANTITY
PAVEMENT MARKINGS			
	THERMOPLASTIC (4", 90 MILS)		
TA	WHITE EDGELINE	3900 LF	
	THERMOPLASTIC (4", 120 MILS)		
TI	YELLOW DOUBLE CENTER	3900 LF	
		TOTAL	7800 LF
MARKERS			
	PERMANENT RAISED PAVEMENT MARKERS		
MA	YELLOW & YELLOW	180 EA	
		TOTAL	180 EA

APPROVED: <i>Joseph Isham</i> DATE: 5/13/04	PROJECT NOTES, PHASING AND FINAL PAVEMENT MARKING SCHEDULE	
SEAL		
SCALE: NONE	DATE: 3/28/04	REVISIONS
DWG. BY: JLF	DESIGN BY: JLF	
REVIEWED BY: BW		