

151091

SURFACING SCHEDULE

| ITEM NO | DESCRIPTION |
|---------|---|
| C1 | ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. (1 1/2") |
| C2 | PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF9.5A, AT AN AVERAGE RATE OF 70 LBS. PER SQ. YD. (LEVELING COURSE) |
| C3 | PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF9.5A, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. (LEVELING COURSE) |
| C4 | PROPOSED VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF9.5A, (LEVELING SUNKEN AREAS IN FILL SECTIONS AS MARKED BY THE PROJECT ENGINEER) |
| D | ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD.(3") |
| V | MILLING ASPHALT PAVEMENT 3" IN DEPTH & 4 FT. OR GREATER IN WIDTH IN DISTRESSED AREAS AS DIRECTED BY THE PROJECT ENGINEER. |
| T | SHOULDER RECONSTRUCTION WITH ABCM - SEE SPECIAL PROVISIONS. |
| W1 | ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 684 LBS. PER SQ. YD (6"). (WIDENING - SEE SPECIAL PROVISIONS) |
| W2 | ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 912 LBS. PER SQ. YD (8"). (REMOVAL OF EXISTING PAVED SHOULDERS & WIDENING - SEE SPECIAL PROVISIONS). |

| PROJECT REFERENCE NO. | | SHEET NO. |
|-----------------------|------------------|-------------|
| 14CR10201.2 | | 10 OF 10 |
| STATE PROJECT | F.A. PROJECT NO. | DESCRIPTION |
| 14CR10201.2 | | |
| 14CR203813 | | |
| 14CR10871.1 | | |
| 14CR20871.3 | | |