

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL UNIT


ID	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
	MA5018B	2	26

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

<p>SOIL DESCRIPTION</p> <p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:</p> <p style="text-align: center;"><i>VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGH PLASTIC, A-7-6</i></p>		<p>GRADATION</p> <p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE UNIFORM. INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED)</p> <p>GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>		<p>ROCK DESCRIPTION</p> <p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK.</p> <p>ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>		<p>TERMS AND DEFINITIONS</p> <p>ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER.</p> <p>AQUIFER - A WATER BEARING FORMATION OR STRATA.</p> <p>ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC.</p> <p>ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.</p> <p>CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.</p> <p>COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.</p> <p>CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.</p> <p>DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.</p> <p>DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.</p> <p>FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.</p> <p>FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.</p> <p>FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL.</p> <p>FLOOD PLAIN (F.P.) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.</p> <p>FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.</p> <p>JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.</p> <p>LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.</p> <p>LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.</p> <p>MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.</p> <p>PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.</p> <p>RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.</p> <p>ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.</p> <p>SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDER ROCKS.</p> <p>SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.</p> <p>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS IN OR B.P.F. OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS LESS THAN 0.1 FOOT PENETRATION WITH 60 BLOWS.</p> <p>STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.</p> <p>STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.</p> <p>TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																																												
<p>SOIL LEGEND AND AASHTO CLASSIFICATION</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th rowspan="2">GENERAL CLASS.</th> <th colspan="7">GRANULAR MATERIALS (75% PASSING #200)</th> <th colspan="7">SILT-CLAY MATERIALS (75% PASSING #200)</th> <th colspan="3">ORGANIC MATERIALS</th> </tr> <tr> <th>A-1</th> <th>A-3</th> <th colspan="2">A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th>A-7-5</th> <th>A-7-6</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> </tr> <tr> <td>GROUP CLASS.</td> <td>A-1-a</td> <td>A-1-b</td> <td>A-2-a</td> <td>A-2-b</td> <td>A-2-c</td> <td>A-2-d</td> <td>A-2-e</td> <td>A-2-f</td> <td>A-2-g</td> <td>A-2-h</td> <td>A-2-i</td> <td>A-2-j</td> <td>A-2-k</td> <td>A-2-l</td> <td>A-2-m</td> <td>A-2-n</td> <td>A-2-o</td> <td>A-2-p</td> </tr> <tr> <td>SYMBOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>% PASSING</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> </tr> <tr> <td>LIQUID LIMIT</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> </tr> <tr> <td>PLASTIC INDEX</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> <td>6</td> </tr> <tr> <td>GROUP INDEX</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td>STONE FRAGS. GRAVEL AND SAND</td> <td>FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="3">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="3">HIGHLY ORGANIC SOILS</td> </tr> <tr> <td>GEN. RATING AS A SUBGRADE</td> <td colspan="7">EXCELLENT TO GOOD</td> <td colspan="7">FAIR TO POOR</td> <td colspan="3">POOR</td> <td>UNSATURABLE</td> </tr> </table> <p style="text-align: center;">P.I. OF A-7-5 ≤ LL - 30 ; P.I. OF A-7-6 > LL - 30</p>		GENERAL CLASS.	GRANULAR MATERIALS (75% PASSING #200)							SILT-CLAY MATERIALS (75% PASSING #200)							ORGANIC MATERIALS			A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	A-7-5	A-7-6	A-1, A-2	A-3	A-4, A-5	A-6, A-7	GROUP CLASS.	A-1-a	A-1-b	A-2-a	A-2-b	A-2-c	A-2-d	A-2-e	A-2-f	A-2-g	A-2-h	A-2-i	A-2-j	A-2-k	A-2-l	A-2-m	A-2-n	A-2-o	A-2-p	SYMBOL																			% PASSING	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	LIQUID LIMIT	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	PLASTIC INDEX	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	GROUP INDEX	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER			HIGHLY ORGANIC SOILS			GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD							FAIR TO POOR							POOR			UNSATURABLE	<p>MINERALOGICAL COMPOSITION</p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p>		<p>COMPRESSIONIBILITY</p> <p>SLIGHTLY COMPRESSIBLE LIQUID LIMIT LESS THAN 30</p> <p>MODERATELY COMPRESSIBLE LIQUID LIMIT 31-50</p> <p>HIGHLY COMPRESSIBLE LIQUID LIMIT GREATER THAN 50</p>		<p>WEATHERED ROCK (WR)</p> <p>NON-COASTAL PLAIN MATERIAL THAT YIELDS SPT N VALUES > 100 BLOWS PER FOOT.</p> <p>CRYSTALLINE ROCK (CR)</p> <p>FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p> <p>NON-CRYSTALLINE ROCK (NCR)</p> <p>FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.</p> <p>COASTAL PLAIN SEDIMENTARY ROCK (CP)</p> <p>COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.</p>	
GENERAL CLASS.	GRANULAR MATERIALS (75% PASSING #200)							SILT-CLAY MATERIALS (75% PASSING #200)							ORGANIC MATERIALS																																																																																																																																																																																			
	A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	A-7-5	A-7-6	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																																
GROUP CLASS.	A-1-a	A-1-b	A-2-a	A-2-b	A-2-c	A-2-d	A-2-e	A-2-f	A-2-g	A-2-h	A-2-i	A-2-j	A-2-k	A-2-l	A-2-m	A-2-n	A-2-o	A-2-p																																																																																																																																																																																
SYMBOL																																																																																																																																																																																																		
% PASSING	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10																																																																																																																																																																																
LIQUID LIMIT	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6																																																																																																																																																																															
PLASTIC INDEX	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6																																																																																																																																																																															
GROUP INDEX	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																																																																																															
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER			HIGHLY ORGANIC SOILS																																																																																																																																																																																						
GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD							FAIR TO POOR							POOR			UNSATURABLE																																																																																																																																																																																
<p>CONSISTENCY OR DENSENESS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th rowspan="2">PRIMARY SOIL TYPE</th> <th rowspan="2">COMPACTNESS OR CONSISTENCY</th> <th colspan="2">RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th rowspan="2">RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <th><4</th> <th>4 TO 10</th> </tr> <tr> <td rowspan="3">GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE</td> <td>4</td> <td>10</td> <td rowspan="3">N/A</td> </tr> <tr> <td>LOOSE</td> <td>10</td> <td>30</td> </tr> <tr> <td>MEDIUM DENSE</td> <td>30</td> <td>50</td> </tr> <tr> <td rowspan="4">GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT</td> <td><2</td> <td><0.25</td> <td rowspan="4">0.25 TO 0.5</td> </tr> <tr> <td>SOFT</td> <td>2 TO 4</td> <td>0.5 TO 1</td> </tr> <tr> <td>MEDIUM STIFF</td> <td>4 TO 8</td> <td>1 TO 2</td> </tr> <tr> <td>STIFF</td> <td>8 TO 15</td> <td>2 TO 4</td> </tr> <tr> <td rowspan="2"></td> <td>VERY STIFF</td> <td>15 TO 30</td> <td>>4</td> <td></td> </tr> <tr> <td>HARD</td> <td>>30</td> <td>>4</td> <td></td> </tr> </table>		PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)		RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	<4	4 TO 10	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	4	10	N/A	LOOSE	10	30	MEDIUM DENSE	30	50	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	<2	<0.25	0.25 TO 0.5	SOFT	2 TO 4	0.5 TO 1	MEDIUM STIFF	4 TO 8	1 TO 2	STIFF	8 TO 15	2 TO 4		VERY STIFF	15 TO 30	>4		HARD	>30	>4		<p>MISCELLANEOUS SYMBOLS</p> <table border="0" style="width: 100%;"> <tr> <td></td> <td>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</td> <td></td> <td>SPT DMT YST TEST BORING</td> <td></td> <td>SAMPLE DESIGNATIONS</td> </tr> <tr> <td></td> <td>SOIL SYMBOL</td> <td></td> <td>AUGER BORING</td> <td></td> <td>S-BULK SAMPLE</td> </tr> <tr> <td></td> <td>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</td> <td></td> <td>CORE BORING</td> <td></td> <td>SS-SPLIT SPOON SAMPLE</td> </tr> <tr> <td></td> <td>INFERRED SOIL BOUNDARIES</td> <td></td> <td>ST-SHELBY TUBE SAMPLE</td> <td></td> <td>RS-ROCK SAMPLE</td> </tr> <tr> <td></td> <td>INFERRED ROCK LINE</td> <td></td> <td>MONITORING WELL</td> <td></td> <td>RT-RECOMPACTED TRIAXIAL SAMPLE</td> </tr> <tr> <td></td> <td>ALLUVIAL SOIL BOUNDARY</td> <td></td> <td>PIEZOMETER INSTALLATION</td> <td></td> <td>CBR - CBR SAMPLE</td> </tr> <tr> <td></td> <td>DIP/DIP DIRECTION OF ROCK STRUCTURES</td> <td></td> <td>SLOPE INDICATOR INSTALLATION</td> <td></td> <td>SOUNDING ROD</td> </tr> <tr> <td></td> <td>SOUNDING ROD</td> <td></td> <td>SPT N-VALUE</td> <td></td> <td>SPT REFUSAL</td> </tr> </table>			ROADWAY EMBANKMENT WITH SOIL DESCRIPTION		SPT DMT YST TEST BORING		SAMPLE DESIGNATIONS		SOIL SYMBOL		AUGER BORING		S-BULK SAMPLE		ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS		CORE BORING		SS-SPLIT SPOON SAMPLE		INFERRED SOIL BOUNDARIES		ST-SHELBY TUBE SAMPLE		RS-ROCK SAMPLE		INFERRED ROCK LINE		MONITORING WELL		RT-RECOMPACTED TRIAXIAL SAMPLE		ALLUVIAL SOIL BOUNDARY		PIEZOMETER INSTALLATION		CBR - CBR SAMPLE		DIP/DIP DIRECTION OF ROCK STRUCTURES		SLOPE INDICATOR INSTALLATION		SOUNDING ROD		SOUNDING ROD		SPT N-VALUE		SPT REFUSAL	<p>GROUND WATER</p> <p></p> <p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING.</p> <p></p> <p>STATIC WATER LEVEL AFTER 24 HOURS.</p> <p></p> <p>PERCHED WATER, SATURATED ZONE OR WATER BEARING STRATA</p> <p></p> <p>SPRING OR SEEPAGE</p>		<p>ROCK HARDNESS</p> <p>VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</p> <p>HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p> <p>MODERATELY HARD CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p> <p>MEDIUM HARD CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p> <p>SOFT CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p> <p>VERY SOFT CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</p>																																																																																																			
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY			RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)			RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																																											
		<4	4 TO 10																																																																																																																																																																																															
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	4	10	N/A																																																																																																																																																																																														
	LOOSE	10	30																																																																																																																																																																																															
	MEDIUM DENSE	30	50																																																																																																																																																																																															
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	<2	<0.25	0.25 TO 0.5																																																																																																																																																																																														
	SOFT	2 TO 4	0.5 TO 1																																																																																																																																																																																															
	MEDIUM STIFF	4 TO 8	1 TO 2																																																																																																																																																																																															
	STIFF	8 TO 15	2 TO 4																																																																																																																																																																																															
	VERY STIFF	15 TO 30	>4																																																																																																																																																																																															
	HARD	>30	>4																																																																																																																																																																																															
	ROADWAY EMBANKMENT WITH SOIL DESCRIPTION		SPT DMT YST TEST BORING		SAMPLE DESIGNATIONS																																																																																																																																																																																													
	SOIL SYMBOL		AUGER BORING		S-BULK SAMPLE																																																																																																																																																																																													
	ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS		CORE BORING		SS-SPLIT SPOON SAMPLE																																																																																																																																																																																													
	INFERRED SOIL BOUNDARIES		ST-SHELBY TUBE SAMPLE		RS-ROCK SAMPLE																																																																																																																																																																																													
	INFERRED ROCK LINE		MONITORING WELL		RT-RECOMPACTED TRIAXIAL SAMPLE																																																																																																																																																																																													
	ALLUVIAL SOIL BOUNDARY		PIEZOMETER INSTALLATION		CBR - CBR SAMPLE																																																																																																																																																																																													
	DIP/DIP DIRECTION OF ROCK STRUCTURES		SLOPE INDICATOR INSTALLATION		SOUNDING ROD																																																																																																																																																																																													
	SOUNDING ROD		SPT N-VALUE		SPT REFUSAL																																																																																																																																																																																													
<p>TEXTURE OR GRAIN SIZE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE (OPENING MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.0</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F. SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td>GRAIN SIZE MM</td> <td>305</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> <tr> <td>IN.</td> <td>12"</td> <td>3"</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>		U.S. STD. SIEVE SIZE (OPENING MM)	4	10	40	60	200	270		4.76	2.0	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE MM	305	75	2.0	0.25	0.05	0.005	IN.	12"	3"					<p>ABBREVIATIONS</p> <table border="0" style="width: 100%;"> <tr> <td>AR - AUGER REFUSAL</td> <td>PMT - PRESSUREMETER TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>REF. - SPT REFUSAL</td> </tr> <tr> <td>CL - CLAY</td> <td>SD. - SAND, SANDY</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>SL. - SILT, SILTY</td> </tr> <tr> <td>CSE. - COARSE</td> <td>SL. - SLIGHTLY</td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>TCR - TRICONE REFUSAL</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>U - UNIT WEIGHT</td> </tr> <tr> <td>e - VOID RATIO</td> <td>U_d - DRY UNIT WEIGHT</td> </tr> <tr> <td>F. - FINE</td> <td>W - MOISTURE CONTENT</td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td>V. - VERY</td> </tr> <tr> <td>FRAC. - FRACTURED</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td></td> </tr> <tr> <td>MED. - MEDIUM</td> <td></td> </tr> </table>		AR - AUGER REFUSAL	PMT - PRESSUREMETER TEST	BT - BORING TERMINATED	REF. - SPT REFUSAL	CL - CLAY	SD. - SAND, SANDY	CPT - CONE PENETRATION TEST	SL. - SILT, SILTY	CSE. - COARSE	SL. - SLIGHTLY	DMT - DILATOMETER TEST	TCR - TRICONE REFUSAL	DPT - DYNAMIC PENETRATION TEST	U - UNIT WEIGHT	e - VOID RATIO	U _d - DRY UNIT WEIGHT	F. - FINE	W - MOISTURE CONTENT	FOSS. - FOSSILIFEROUS	V. - VERY	FRAC. - FRACTURED	VST - VANE SHEAR TEST	FRAGS. - FRAGMENTS		MED. - MEDIUM		<p>EQUIPMENT USED ON SUBJECT PROJECT</p> <table border="0" style="width: 100%;"> <tr> <td><input type="checkbox"/> MOBILE B-</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC</td> <td><input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td colspan="2">CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-45</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> -B</td> <td></td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -N</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td><input checked="" type="checkbox"/> -H0</td> <td></td> </tr> <tr> <td><input checked="" type="checkbox"/> OTHER D-50</td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td colspan="2">HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/> OTHER</td> <td><input checked="" type="checkbox"/> TRICONE 3" STEEL TEETH</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE TUNG-CARB.</td> <td><input type="checkbox"/> HAND AUGER</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> SOUNDING ROD</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> OTHER</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td></td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> OTHER</td> <td></td> </tr> </table>		<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC	<input type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:		<input type="checkbox"/> CME-45	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B		<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input checked="" type="checkbox"/> -H0		<input checked="" type="checkbox"/> OTHER D-50	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	HAND TOOLS:		<input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRICONE 3" STEEL TEETH	<input type="checkbox"/> POST HOLE DIGGER			<input type="checkbox"/> TRICONE TUNG-CARB.	<input type="checkbox"/> HAND AUGER			<input type="checkbox"/> CORE BIT	<input type="checkbox"/> SOUNDING ROD			<input type="checkbox"/> OTHER	<input type="checkbox"/> VANE SHEAR TEST				<input type="checkbox"/> OTHER		<p>FRACATURE SPACING</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table> <p>BEDDING</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>> 4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>		TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FEET	VERY CLOSE	LESS THAN 0.16 FEET	TERM	THICKNESS	VERY THICKLY BEDDED	> 4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET																																																								
U.S. STD. SIEVE SIZE (OPENING MM)	4	10	40	60	200	270																																																																																																																																																																																												
	4.76	2.0	0.42	0.25	0.075	0.053																																																																																																																																																																																												
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																												
GRAIN SIZE MM	305	75	2.0	0.25	0.05	0.005																																																																																																																																																																																												
IN.	12"	3"																																																																																																																																																																																																
AR - AUGER REFUSAL	PMT - PRESSUREMETER TEST																																																																																																																																																																																																	
BT - BORING TERMINATED	REF. - SPT REFUSAL																																																																																																																																																																																																	
CL - CLAY	SD. - SAND, SANDY																																																																																																																																																																																																	
CPT - CONE PENETRATION TEST	SL. - SILT, SILTY																																																																																																																																																																																																	
CSE. - COARSE	SL. - SLIGHTLY																																																																																																																																																																																																	
DMT - DILATOMETER TEST	TCR - TRICONE REFUSAL																																																																																																																																																																																																	
DPT - DYNAMIC PENETRATION TEST	U - UNIT WEIGHT																																																																																																																																																																																																	
e - VOID RATIO	U _d - DRY UNIT WEIGHT																																																																																																																																																																																																	
F. - FINE	W - MOISTURE CONTENT																																																																																																																																																																																																	
FOSS. - FOSSILIFEROUS	V. - VERY																																																																																																																																																																																																	
FRAC. - FRACTURED	VST - VANE SHEAR TEST																																																																																																																																																																																																	
FRAGS. - FRAGMENTS																																																																																																																																																																																																		
MED. - MEDIUM																																																																																																																																																																																																		
<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC	<input type="checkbox"/> MANUAL																																																																																																																																																																																															
<input type="checkbox"/> BK-51	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																																																																																																																																																																
<input type="checkbox"/> CME-45	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B																																																																																																																																																																																																
<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N																																																																																																																																																																																																
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input checked="" type="checkbox"/> -H0																																																																																																																																																																																																
<input checked="" type="checkbox"/> OTHER D-50	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	HAND TOOLS:																																																																																																																																																																																																
<input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRICONE 3" STEEL TEETH	<input type="checkbox"/> POST HOLE DIGGER																																																																																																																																																																																																
	<input type="checkbox"/> TRICONE TUNG-CARB.	<input type="checkbox"/> HAND AUGER																																																																																																																																																																																																
	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> SOUNDING ROD																																																																																																																																																																																																
	<input type="checkbox"/> OTHER	<input type="checkbox"/> VANE SHEAR TEST																																																																																																																																																																																																
		<input type="checkbox"/> OTHER																																																																																																																																																																																																
TERM	SPACING																																																																																																																																																																																																	
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																																																																	
WIDE	3 TO 10 FEET																																																																																																																																																																																																	
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																																																																	
CLOSE	0.16 TO 1 FEET																																																																																																																																																																																																	
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																																																																	
TERM	THICKNESS																																																																																																																																																																																																	
VERY THICKLY BEDDED	> 4 FEET																																																																																																																																																																																																	
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																	
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																	
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																	
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																	
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																	
<p>PLASTICITY</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>		NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p>INDURATION</p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>																																																																																																																																																																																	
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																																
LOW PLASTICITY	0-5	VERY LOW																																																																																																																																																																																																
MED. PLASTICITY	6-15	SLIGHT																																																																																																																																																																																																
HIGH PLASTICITY	16-25	MEDIUM																																																																																																																																																																																																
	26 OR MORE	HIGH																																																																																																																																																																																																
<p>COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>		<p>NOTES:</p> <p style="text-align: right;">ELEVATION: 204.36'</p>																																																																																																																																																																																																

8+00 9+00 10+00 11+00 12+00 13+00 14+00 15+00




NOTES:

BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RT., ELEVATION 204.36'

PLANS ADOPTED FROM HYDRAULIC SURVEY FILES
RECEIVED FROM SUNGATE, DATED 9-28-04

STATIONING ON LOCATION PLAN, CROSS-SECTIONS, PROFILE AND
BORING LOGS BASED UPON HYDRO REPORT DATED 9-28-04




BORING LOCATION PLAN

NCDOT PROJECT #: MA5018B
FRANKLIN CO., NC
BRIDGE #42 ON SR 1235 (DYKING RD.)
OVER LYNCH CREEK




TIERRA
GEOTECHNICAL • MATERIALS
ENGINEERING

TIERRA, INC.
2736 ROWLAND RD.
RALEIGH, NC 27615
PHONE (919) 871-0800
FAX (919) 871-0803



BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'




PROFILE 15' LEFT OF -L-

NCDOT PROJECT #: MA5018B
FRANKLIN CO., NC
BRIDGE #42 ON SR 1235 (DYKING RD.)
OVER LYNCH CREEK

TIERRA, INC.
2736 HOWLAND RD.
RALEIGH, NC 27605
PHONE: 919-877-0330
FAX: 919-877-0332


ELEV. (FT.)

ELEV. (FT.)




BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE




HORIZONTAL SCALE



CROSS SECTION END BENT 1


NCDOT PROJECT #: MA5018B
FRANKLIN CO., NC
BRIDGE #42 ON SR 1235 (DYKING RD.)
OVER LYNCH CREEK






BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE




HORIZONTAL SCALE



CROSS SECTION END BENT 2

NCDOT PROJECT #: MA5018B
FRANKLIN CO., NC
BRIDGE #42 ON SR 1235 (DYKING RD.)
OVER LYNCH CREEK





2736 ROWLAND ROAD
 RALEIGH, NORTH CAROLINA 27615
 Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
 BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-064		ID. MA5018B		COUNTY FRANKLIN		GEOLOGIST J. HOWARD							
SITE DESCRIPTION BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK						GROUND WATER (ft)							
BORING NO. EB1A		BORING LOCATION 9+94		OFFSET 16.0' LT.		ALIGNMENT -L-							
COLLAR ELEV. 211.5 ft		NORTHING		EASTING		0 HR. 14.0 24 HR. 10.8							
TOTAL DEPTH 26.5 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO							
DATE STARTED 3-15-05		COMPLETED 3-15-05		SURFACE WATER DEPTH N/A									
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
211.5													EXISTING GROUND
210	0.0	1	WOH	1									211.5 ROOTMAT RDWY EMB: TAN AND ORANGE, V. SOFT TO SOFT, CLAYEY SANDY SILT (A-4)
	3.5	1	1	1									211.3
205	6.0	1	WOH	1									205.5 ALLUV: TAN, V. LOOSE, SILTY SAND (A-2-4)
	8.5	1	1	1									6.0
200	13.5	12	20	60									199.0 RES: TAN AND ORANGE, V. DENSE, SILTY SAND (A-2-4)
	18.5	8	8	60/4									196.5 WR: TAN, ORANGE AND BLACK, GRANITE
190	20.5	60/0											191.0 CR: TAN, ORANGE AND GRAY, MOD. WEATHERED TO FRESH, HARD, MOD. CLOSELY FRACTURED, GRANITE
185													185.0 CORING TERMINATED AT ELEV. 185.0' IN CR: TAN, ORANGE AND GRAY, GRANITE

NCDOT_BORE_VARIABLE DEPTH 04-064 BR 42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05

CORE BORING REPORT

DATE: 3-15-05

PROJECT: MA5018B I.D. NO.: BORING NO: EB1A GEOLOGIST: J. HOWARD

DESCRIPTION: BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK

COUNTY: FRANKLIN COLLAR ELEV.: 211.5 FT TOTAL DEPTH: 26.5 FT

ELEV. (FT)	DEPTH (FT)	DRILL RATE MIN/FT	RUN (FT)	REC FT %	RQD FT %	SAMP #	FIELD CLASSIFICATION AND REMARKS
191.0	20.5	3:00	1.0	1.0/1.0	1.0/1.0		20.5-26.5 CR: TAN, ORANGE AND GRAY, MOD. WEATHERED TO FRESH, HARD, MOD. CLOSELY FRACTURED, GRANITE
190.0	21.5			100%	100%		
190.0	21.5	3:30	5.0	4.25/5.0	4.25/5.0		STRATA REC = 88% STRATA RQD = 88%
		3:00					
		1:15					
185.0	26.5	2:15		85%	85%		
		3:00					

CORING TERMINATED AT 26.5 FT
 ELEVATION 185.0 FT

DRILLER: F. COX CORE SIZE: HQ EQUIPMENT: D-50




2736 ROWLAND ROAD
 RALEIGH, NORTH CAROLINA 27615
 Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
 BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-064	ID. MA5018B	COUNTY FRANKLIN	GEOLOGIST J. HOWARD
SITE DESCRIPTION BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK			
BORING NO. EB1B	BORING LOCATION 9+88	OFFSET 17.0' RT.	ALIGNMENT -L-
COLLAR ELEV. 211.3 ft	NORTHING	EASTING	GROUND WATER (ft)
TOTAL DEPTH 23.8 ft	DRILL MACHINE D-50	DRILL METHOD MUD ROTARY	HAMMER TYPE AUTO
DATE STARTED 3-15-05	COMPLETED 3-15-05	SURFACE WATER DEPTH N/A	



NCDOT_BORE_VARIABLE_DEPTH_04-064_BR_42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05




2736 ROWLAND ROAD
 RALEIGH, NORTH CAROLINA 27615
 Phone (919) 871-0800 Fax (919) 871-0803


BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-064	ID. MA5018B	COUNTY FRANKLIN	GEOLOGIST J. HOWARD
SITE DESCRIPTION BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK			GROUND WATER (ft)
BORING NO. B1A	BORING LOCATION 10+26	OFFSET 19.0' LT.	ALIGNMENT -L-
COLLAR ELEV. 204.3 ft	NORTHING	EASTING	0 HR. 0.0 24 HR. 5.0
TOTAL DEPTH 54.1 ft	DRILL MACHINE D-50	DRILL METHOD MUD ROTARY	HAMMER TYPE AUTO
DATE STARTED 3-14-05	COMPLETED 3-14-05	SURFACE WATER DEPTH N/A	



NCDOT_BORE_VARIABLE_DEPTH_04-064_BR_42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05



2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-064		ID. MA5018B		COUNTY FRANKLIN		GEOLOGIST J. HOWARD						
SITE DESCRIPTION BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK												
BORING NO. EB2A		BORING LOCATION 11+22		OFFSET 14.0' LT.		ALIGNMENT -L-						
COLLAR ELEV. 211.0 ft		NORTHING		EASTING		GROUND WATER (ft)						
TOTAL DEPTH 53.7 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO						
DATE STARTED 3-17-05		COMPLETED 3-17-05		SURFACE WATER DEPTH N/A								
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
211.0	0.0	3	2	1	EXISTING GROUND							
210	3.5	1	1	1	ROOTMAT RDWY EMB: TAN AND ORANGE, V. LOOSE TO LOOSE, CLAYEY SAND (A-2-B)							
205	6.0	1	1	2								
	8.5	1	1	3								
200	13.5	3	2	2	ALLUV: GRAY, SOFT TO MED. STIFF, SANDY SILT (A-4)					SS-5	33.9%	
195	18.5	3	2	4								
190	23.5	7	11	8	ALLUV: GRAY, MED. DENSE, SAND (A-1-b)					SS-6		
185	28.5	4	5	7	RES: ORANGE, TAN AND BLACK, MED. DENSE, SILTY SAND (A-2-4)							
180	33.5	5	7	10								
175	38.5	7	6	6								
170	43.5	9	9	18								
165	48.5	60/4			WR: ORANGE AND BLACK, GRANITE, MICACEOUS							
160	53.5	60/2			BORING TERMINATED AT ELEV. 157.3' ON CR: ORANGE AND BLACK, GRANITE							

NCDOT_BORE_VARIABLE_DEPTH_04-064_BR_42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05



2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-064		ID. MA5018B		COUNTY FRANKLIN		GEOLOGIST C. BRUINSMA						
SITE DESCRIPTION BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK												
BORING NO. EB2B		BORING LOCATION 11+21		OFFSET 14.0' RT.		ALIGNMENT -L-						
COLLAR ELEV. 211.1 ft		NORTHING		EASTING		GROUND WATER (ft)						
TOTAL DEPTH 52.8 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO						
DATE STARTED 3-21-05		COMPLETED 3-21-05		SURFACE WATER DEPTH N/A								
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
211.1	0.1	3	5	4	EXISTING GROUND							
210	2.8	2	2	1	ROOTMAT RDWY EMB: ORANGE AND BROWN, LOOSE TO V. LOOSE, CLAYEY SILTY SAND (A-2-4)							
205	5.8	2	1	2								
	7.8	2	3	4								
200	12.7	4	1	1	ALLUV: BROWN, LOOSE, CLAYEY SILTY SAND (A-2-4)					SS-8		
195	17.7	4	3	3								
190	22.7	4	4	9	ALLUV: DARK GRAY, SOFT, SILTY SANDY CLAY (A-6)					SS-9	26.4%	
185	27.7	4	3	3	ALLUV: GRAY, LOOSE TO MED. DENSE, SAND (A-1-b) WITH GRAVEL							
180	32.7	28	27	24								
175	37.7	31	27	20								
170	42.7	10	20	30								
165	47.7	60/2			RES: BROWN AND TAN, LOOSE TO V. DENSE, SILTY SAND (A-2-4) SAPROLITIC, V. MICACEOUS					SS-10		
160	52.7	60/1			WR: BROWN, TAN AND BLACK, GRANITE, V. MICACEOUS							
					BORING TERMINATED AT ELEV. 158.3' IN WR: BROWN, TAN AND BLACK, GRANITE							

NCDOT_BORE_VARIABLE_DEPTH_04-064_BR_42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS

GEOTECHNICAL UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

ID	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
	MA5017B	2	20

SOIL DESCRIPTION		GRADATION		ROCK DESCRIPTION		TERMS AND DEFINITIONS																																																																																																																																																																												
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (ASHTO T208, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:</p> <p>VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HARDY PLASTIC, A-7-6</p>		<p>WELL GRADED: INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE UNIFORM: INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (A-5, A-6, A-7) POORLY GRADED</p> <p>GAP-GRADED: INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>		<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS, IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK.</p> <p>ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>		<p>ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER.</p> <p>AQUIFER - A WATER BEARING FORMATION OR STRATA.</p> <p>ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.</p> <p>ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC.</p> <p>ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.</p> <p>CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.</p> <p>COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.</p> <p>CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.</p> <p>DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.</p> <p>DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.</p> <p>FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.</p> <p>FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.</p> <p>FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOOSED FROM PARENT MATERIAL.</p> <p>FLOOD PLAIN (F.P.) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.</p> <p>FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.</p> <p>JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.</p> <p>LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.</p> <p>LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.</p> <p>MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLED IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.</p> <p>PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERWEAVING IMPERVIOUS STRATUM.</p> <p>RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.</p> <p>ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.</p> <p>SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRODUCED ROCKS.</p> <p>SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.</p> <p>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS IN OR B.P.F. OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS LESS THAN 0.1 FOOT PENETRATION WITH 60 BLOWS.</p> <p>STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.</p> <p>STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.</p> <p>TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																												
<p>SOIL LEGEND AND AASHTO CLASSIFICATION</p> <table border="1"> <tr> <th>GENERAL CLASS.</th> <th colspan="7">GRANULAR MATERIALS (>55% PASSING #200)</th> <th colspan="7">SILT-CLAY MATERIALS (>85% PASSING #200)</th> <th colspan="3">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th><th>A-3</th><th>A-2</th><th>A-4</th><th>A-5</th><th>A-6</th><th>A-7</th> <th>A-1, A-2</th><th>A-3</th><th>A-4, A-5</th><th>A-6, A-7</th> <th>A-1, A-2</th><th>A-3</th><th>A-4, A-5</th><th>A-6, A-7</th> <th>A-1, A-2</th><th>A-3</th><th>A-4, A-5</th> </tr> <tr> <th>SYMBOL</th> <td></td><td></td><td></td><td></td><td></td><td></td><td></td> <td></td><td></td><td></td><td></td> <td></td><td></td><td></td><td></td> <td></td><td></td><td></td> </tr> <tr> <th>% PASSING</th> <td>10</td><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td> <td>10</td><td>10</td><td>10</td><td>10</td> <td>10</td><td>10</td><td>10</td><td>10</td> <td>10</td><td>10</td><td>10</td> </tr> <tr> <th>LIQUID LIMIT</th> <td>50</td><td>50</td><td>50</td><td>50</td><td>50</td><td>50</td><td>50</td> <td>50</td><td>50</td><td>50</td><td>50</td> <td>50</td><td>50</td><td>50</td><td>50</td> <td>50</td><td>50</td><td>50</td> </tr> <tr> <th>PLASTIC INDEX</th> <td>6</td><td>6</td><td>6</td><td>6</td><td>6</td><td>6</td><td>6</td> <td>6</td><td>6</td><td>6</td><td>6</td> <td>6</td><td>6</td><td>6</td><td>6</td> <td>6</td><td>6</td><td>6</td> </tr> <tr> <th>GROUP INDEX</th> <td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td> <td>0</td><td>0</td><td>0</td><td>0</td> <td>0</td><td>0</td><td>0</td><td>0</td> <td>0</td><td>0</td><td>0</td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td>STONE FRAGS, GRAVEL AND SAND</td><td>FINE SAND</td><td>SILTY OR CLAYEY GRAVEL AND SAND</td><td>SILTY SAND</td><td>CLAYEY SAND</td><td>SILTY SILT</td><td>CLAYEY SILT</td> <td>SILT</td><td>CLAY</td><td>SILT</td><td>CLAY</td> <td>SILT</td><td>CLAY</td><td>SILT</td><td>CLAY</td> <td>SILT</td><td>CLAY</td><td>SILT</td> </tr> <tr> <th>GENERATING AS A SUBGRADE</th> <td colspan="7">EXCELLENT TO GOOD</td> <td colspan="7">FAIR TO POOR</td> <td>FAIR TO POOR</td><td>POOR</td><td>UNSATISFACTORY</td> </tr> </table> <p>P.I. OF A-7-5 ≤ L.L. - 30 + P.I. OF A-7-6 > L.L. - 30</p>		GENERAL CLASS.	GRANULAR MATERIALS (>55% PASSING #200)							SILT-CLAY MATERIALS (>85% PASSING #200)							ORGANIC MATERIALS			GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	A-1, A-2	A-3	A-4, A-5	SYMBOL																			% PASSING	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	LIQUID LIMIT	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	PLASTIC INDEX	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	GROUP INDEX	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SAND	CLAYEY SAND	SILTY SILT	CLAYEY SILT	SILT	CLAY	SILT	CLAY	SILT	CLAY	SILT	CLAY	SILT	CLAY	SILT	GENERATING AS A SUBGRADE	EXCELLENT TO GOOD							FAIR TO POOR							FAIR TO POOR	POOR	UNSATISFACTORY	<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p>		<p>WEATHERED ROCK (WR)</p> <p>CRYSTALLINE ROCK (CR)</p> <p>NON-CRYSTALLINE ROCK (NCR)</p> <p>COASTAL PLAIN SEDIMENTARY ROCK (CP)</p>		<p>MINERALOGICAL COMPOSITION</p> <p>COMPRESSIBILITY</p> <p>PERCENTAGE OF MATERIAL</p> <p>GROUND WATER</p> <p>MISCELLANEOUS SYMBOLS</p> <p>ABBREVIATIONS</p> <p>EQUIPMENT USED ON SUBJECT PROJECT</p>		<p>WEATHERING</p> <p>ROCK HARDNESS</p> <p>FRACTURE SPACING</p> <p>BEDDING</p> <p>INDURATION</p>	
GENERAL CLASS.	GRANULAR MATERIALS (>55% PASSING #200)							SILT-CLAY MATERIALS (>85% PASSING #200)							ORGANIC MATERIALS																																																																																																																																																																			
GROUP CLASS.	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7	A-1, A-2	A-3	A-4, A-5																																																																																																																																																																
SYMBOL																																																																																																																																																																																		
% PASSING	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10																																																																																																																																																																
LIQUID LIMIT	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50																																																																																																																																																																
PLASTIC INDEX	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6																																																																																																																																																																
GROUP INDEX	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																																																																																
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND	SILTY SAND	CLAYEY SAND	SILTY SILT	CLAYEY SILT	SILT	CLAY	SILT	CLAY	SILT	CLAY	SILT	CLAY	SILT	CLAY	SILT																																																																																																																																																																
GENERATING AS A SUBGRADE	EXCELLENT TO GOOD							FAIR TO POOR							FAIR TO POOR	POOR	UNSATISFACTORY																																																																																																																																																																	
<p>CONSISTENCY OR DENSENESS</p> <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>4 4 TO 10 10 TO 30 30 TO 50 >50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30</td> <td><0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 >4</td> </tr> </table>		PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	4 4 TO 10 10 TO 30 30 TO 50 >50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30	<0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 >4	<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>		<p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p>																																																																																
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																															
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	4 4 TO 10 10 TO 30 30 TO 50 >50	N/A																																																																																																																																																																															
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	2 TO 4 4 TO 8 8 TO 15 15 TO 30 >30	<0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 >4																																																																																																																																																																															

8+00

9+00

10+00


11+00

12+00

13+00

14+00

15+00




NOTES:

BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RT., ELEVATION 204.36'

PLANS ADOPTED FROM HYDRAULIC SURVEY FILES
RECEIVED FROM SUNGATE, DATED 9-28-04

STATIONING ON LOCATION PLAN, CROSS-SECTIONS, PROFILE AND
BORING LOGS BASED UPON HYDRO REPORT DATED 9-28-04




BORING LOCATION PLAN


NCDOT PROJECT #: MA5017B
FRANKLIN CO., NC
BRIDGE #41 ON SR 1235 (DYKING RD.)
OVER TOOLES CREEK



TIERRA, INC.
2735 ROWLAND RD.
RALEIGH, NC 27615
PHONE (919) 871-0800
FAX (919) 871-0803




ELEV. (FT.)




ELEV. (FT.)

BENCH MARK: BM #2, -BL- STA. 12+59.47, 52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE



HORIZONTAL SCALE




CROSS SECTION END BENT 1

NCDOT PROJECT #: MA5017B
FRANKLIN CO., NC
BRIDGE #41 ON SR 1235 (DYKING RD.)
OVER TOOLE'S CREEK




ELEV. (FT.)

ELEV. (FT.)




BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE



HORIZONTAL SCALE



CROSS SECTION END BENT 2

NCDOT PROJECT #: MA5017B
FRANKLIN CO., NC
BRIDGE #41 ON SR 1235 (DYKING RD.)
OVER TOOLE'S CREEK





2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-063		ID: MA5017B		COUNTY FRANKLIN		GEOLOGIST J. HOWARD							
SITE DESCRIPTION BRIDGE #41 ON SR 1235 (DYKING RD.) OVER TOOLES CREEK						GROUND WATER (ft)							
BORING NO. EB1A		BORING LOCATION 12+90		OFFSET 17.0' LT.		ALIGNMENT -L-							
COLLAR ELEV. 211.0 ft		NORTHING		EASTING		0 HR. 3.5							
TOTAL DEPTH 34.0 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO							
DATE STARTED 3-17-05		COMPLETED 3-17-05		SURFACE WATER DEPTH N/A									
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
211.0													EXISTING GROUND
210	0.0	2	3	3									211.0 ROOTMAT
	3.5	1	1	2									210.9 RDWY EMB: ORANGE, MED. STIFF TO SOFT, SANDY CLAY (A-7-6)
205	6.0	1	WOH	2									
	8.5	2	1	1									
200	13.5	2	1	2									201.2 ALLUV: TAN, V. LOOSE, SILTY SAND (A-2-4)
	18.5	2	1	2									197.5 ALLUV: GRAY, SOFT, SANDY CLAY (A-6)
195	23.5	4	5	9									192.5 ALLUV: GRAY, MED. DENSE, SILTY SAND (A-2-4)
190	28.5	10	15	20									187.5 RES: GRAY, DENSE TO V. DENSE, SILTY SAND (A-2-4)
185	33.5	30	40	60/4									181.5 WR: GRAY AND BLACK, GRANITE
180													177.0 BORING TERMINATED AT ELEV. 177.0' IN WR: GRAY AND BLACK, GRANITE

NCDOT_BORE_VARIABLE_DEPTH_04-063 BR. 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05



2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-063		ID: MA5017B		COUNTY FRANKLIN		GEOLOGIST J. HOWARD							
SITE DESCRIPTION BRIDGE #41 ON SR 1235 (DYKING RD.) OVER TOOLES CREEK						GROUND WATER (ft)							
BORING NO. EB1B		BORING LOCATION 12+89		OFFSET 16.0' RT.		ALIGNMENT -L-							
COLLAR ELEV. 211.1 ft		NORTHING		EASTING		0 HR. 4.0							
TOTAL DEPTH 53.5 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO							
DATE STARTED 3-18-05		COMPLETED 3-18-05		SURFACE WATER DEPTH N/A									
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
211.1													EXISTING GROUND
210	0.0	1	3	3									211.1 ROOTMAT
	3.5	1	1	1									210.9 RDWY EMB: ORANGE, MED. STIFF TO SOFT, SANDY CLAY (A-7-5)
205	6.0	1	2	2									
	8.5	WOH	2	2									
200	13.5	1	2	3									202.1 ALLUV: GRAY, LOOSE, SILTY SAND (A-2-4)
	18.5	3	4	6									198.1 ALLUV: GRAY, MED. STIFF TO STIFF, SANDY CLAY (A-6)
195	23.5	7	9	13									187.6 ALLUV: GRAY, MED. DENSE, SILTY SAND (A-2-4)
190	28.5	15	16	27									182.6 RES: BLACK, WHITE AND GRAY, DENSE TO V. DENSE, SILTY SAND (A-2-4)
185	33.5	34	66/4										177.1 WR: BLACK, WHITE AND GRAY, SCHIST
180	38.5	13	24	41									174.6 RES: BLACK, ORANGE AND GRAY, V. DENSE, SILTY SAND (A-2-4)
175	43.5	60/2											170.6 WR: BLACK, TAN AND GRAY, GRANITE
170	48.5	60/0											
165													
160													157.6 BORING TERMINATED AT ELEV. 157.6' IN WR: BLACK, TAN AND GRAY, GRANITE


NCDOT_BORE_VARIABLE_DEPTH_04-063 BR. 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05



2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1




NCDOT_BORE_VARIABLE_DEPTH 04-088 BR 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05




2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1



NCDOT_BORE_VARIABLE_DEPTH 04-088 BR 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05




2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-063		ID. MA5017B		COUNTY FRANKLIN		GEOLOGIST Y. SALEH							
SITE DESCRIPTION BRIDGE #41 ON SR 1235 (DYKING RD.) OVER TOOLES CREEK						GROUND WATER (ft)							
BORING NO. EB2A		BORING LOCATION 14+09		OFFSET 15.0' LT.		ALIGNMENT -L-							
COLLAR ELEV. 211.0 ft		NORTHING		EASTING		0 HR. 8.0							
TOTAL DEPTH 44.2 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO							
DATE STARTED 3-02-05		COMPLETED 3-03-05		SURFACE WATER DEPTH N/A									
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
211.0													EXISTING GROUND
210.0	0.0	3	2	2									210.9 ROOTMAT RDWY EMB: TAN AND BROWN, LOOSE, SILTY SAND (A-2-4)
	4.0	2	3	2									205.5 RDWY EMB: GRAY, LOOSE, CLAYEY SAND (A-2-6)
205.0	6.0	2	7	2									202.5 ALLUV: BLUE AND GRAY, V. SOFT, SANDY CLAY (A-6)
	9.0	WOH	WOH	WOH									197.5 ALLUV: BLUE AND GRAY, STIFF TO V. STIFF, CLAYEY SILT (A-4)
200.0	14.0	4	4	7									187.5 ALLUV: GRAY, LOOSE, SILTY SAND (A-2-4)
	19.0	9	9	12									186.0 ALLUV: GREEN, MED. STIFF, SILT (A-4)
190.0	24.0	4	2	4									182.5 RES: WHITE, GRAY AND BROWN, MED. DENSE TO V. DENSE, SILTY SAND (A-2-4)
	29.0	7	9	8									176.5 WR: BROWN AND TAN, GRANITE
185.0	34.0	38	62/4										166.8 BORING TERMINATED AT ELEV. 166.7' IN WR: BROWN AND TAN, GRANITE
180.0	39.0	100/4											
175.0	44.0	60/2											

NCDOT_BORE_VARIABLE_DEPTH_04-063 BR 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05



2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803


N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-063		ID. MA5017B		COUNTY FRANKLIN		GEOLOGIST C. BRUINSMA							
SITE DESCRIPTION BRIDGE #41 ON SR 1235 (DYKING RD.) OVER TOOLES CREEK						GROUND WATER (ft)							
BORING NO. EB2B		BORING LOCATION 14+07		OFFSET 14.0' RT.		ALIGNMENT -L-							
COLLAR ELEV. 211.3 ft		NORTHING		EASTING		0 HR. 7.4							
TOTAL DEPTH 54.0 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO							
DATE STARTED 3-22-05		COMPLETED 3-22-05		SURFACE WATER DEPTH N/A									
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
211.3													EXISTING GROUND
210.0	1.0	2	2	2									211.1 ROOTMAT RDWY EMB: BROWN, LOOSE TO V. LOOSE, CLAYEY SAND (A-2-6)
	2.8	1	WOH	1									205.8 RDWY EMB: ORANGE AND BROWN, MED. STIFF, SANDY CLAY (A-6)
205.0	5.8	1	2	5									204.2 RDWY EMB: ORANGE AND BROWN, MED. STIFF, SANDY CLAY (A-6)
	7.8	1	4	4									202.5 ALLUV: GRAY AND BROWN, LOOSE, CLAYEY SILTY SAND (A-2-4)
200.0	12.7	WOH	2	2									200.3 ALLUV: GRAY, LOOSE, SAND (A-1-b)
	17.7	6	5	9									195.3 ALLUV: GRAY, MED. DENSE, CLAYEY SAND (A-2-6)
190.0	22.7	7	7	10									192.3 ALLUV: GRAY, MED. DENSE, SAND (A-1-b)
	27.7	12	11	11									185.8 RES: BROWN AND GRAY, MED. DENSE TO V. DENSE, SILTY SAND (A-2-4) SAPROLITIC
185.0	32.7	11	9	13									171.8 WR: BROWN, WHITE AND BLACK, GRANITE
	37.7	37	24	63									165.3 RES: BROWN AND WHITE, V. DENSE, SILTY SAND (A-2-4) SAPROLITIC
180.0	42.7	100/4											158.1 WR: TAN AND PINK, GRANITE
	47.7	22	17	34									157.3 BORING TERMINATED AT ELEV. 157.3' IN WR: TAN AND PINK, GRANITE
175.0	52.7	30	53	47/3									

NCDOT_BORE_VARIABLE_DEPTH_04-063 BR 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05

8+00 9+00 10+00 11+00 12+00 13+00 14+00 15+00




NOTES:

BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RT., ELEVATION 204.36'

PLANS ADOPTED FROM HYDRAULIC SURVEY FILES
RECEIVED FROM SUNGATE, DATED 9-28-04

STATIONING ON LOCATION PLAN, CROSS-SECTIONS, PROFILE AND
BORING LOGS BASED UPON HYDRO REPORT DATED 9-28-04




BORING LOCATION PLAN

NCDOT PROJECT #: MA5018B
FRANKLIN CO., NC
BRIDGE #42 ON SR 1235 (DYKING RD.)
OVER LYNCH CREEK





TIERRA
GEOTECHNICAL • MATERIALS
ENGINEERING

TIERRA, INC.
2736 ROWLAND RD.
RALEIGH, NC 27615
PHONE (919) 871-0800
FAX (919) 871-0803



BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'




PROFILE 15' LEFT OF -L-

NCDOT PROJECT #: MA5018B
FRANKLIN CO., NC
BRIDGE #42 ON SR 1235 (DYKING RD.)
OVER LYNCH CREEK

TIERRA, INC.
2736 HOWLAND RD.
RALEIGH, NC 27605
PHONE: 919-877-0330
FAX: 919-877-0332


ELEV. (FT.)

ELEV. (FT.)




BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE




HORIZONTAL SCALE



CROSS SECTION END BENT 1


NCDOT PROJECT #: MA5018B
FRANKLIN CO., NC
BRIDGE #42 ON SR 1235 (DYKING RD.)
OVER LYNCH CREEK






BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE



HORIZONTAL SCALE



CROSS SECTION END BENT 2

NCDOT PROJECT #: MA5018B
FRANKLIN CO., NC
BRIDGE #42 ON SR 1235 (DYKING RD.)
OVER LYNCH CREEK






2736 ROWLAND ROAD
 RALEIGH, NORTH CAROLINA 27615
 Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
 BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-064	ID. MA5018B	COUNTY FRANKLIN	GEOLOGIST J. HOWARD
SITE DESCRIPTION BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK			GROUND WATER (ft)
BORING NO. EB1A	BORING LOCATION 9+94	OFFSET 16.0' LT.	ALIGNMENT -L-
COLLAR ELEV. 211.5 ft	NORTHING	EASTING	0 HR. 14.0 24 HR. 10.8
TOTAL DEPTH 26.5 ft	DRILL MACHINE D-50	DRILL METHOD MUD ROTARY	HAMMER TYPE AUTO
DATE STARTED 3-15-05	COMPLETED 3-15-05	SURFACE WATER DEPTH N/A	



CORE BORING REPORT

DATE: 3-15-05

PROJECT: MA5018B I.D. NO.: BORING NO: EB1A GEOLOGIST: J. HOWARD

DESCRIPTION: BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK

COUNTY: FRANKLIN COLLAR ELEV.: 211.5 FT TOTAL DEPTH: 26.5 FT

ELEV. (FT)	DEPTH (FT)	DRILL RATE MIN/FT	RUN (FT)	REC FT %	RQD FT %	SAMP #	FIELD CLASSIFICATION AND REMARKS
191.0	20.5	3:00	1.0	1.0/1.0	1.0/1.0		20.5-26.5 CR: TAN, ORANGE AND GRAY, MOD. WEATHERED TO FRESH, HARD, MOD. CLOSELY FRACTURED, GRANITE
190.0	21.5			100%	100%		
190.0	21.5	3:30	5.0	4.25/5.0	4.25/5.0		STRATA REC = 88% STRATA RQD = 88%
		3:00					
		1:15					
185.0	26.5	2:15		85%	85%		
		3:00					

CORING TERMINATED AT 26.5 FT
 ELEVATION 185.0 FT

DRILLER: F. COX CORE SIZE: HQ EQUIPMENT: D-50

NCDOT_BORE_VARIABLE DEPTH 04-064 BR 42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05




2736 ROWLAND ROAD
 RALEIGH, NORTH CAROLINA 27615
 Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
 BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-064	ID. MA5018B	COUNTY FRANKLIN	GEOLOGIST J. HOWARD
SITE DESCRIPTION BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK			
BORING NO. EB1B	BORING LOCATION 9+88	OFFSET 17.0' RT.	ALIGNMENT -L-
COLLAR ELEV. 211.3 ft	NORTHING	EASTING	GROUND WATER (ft) 0 HR. 12.5 24 HR. 10.1
TOTAL DEPTH 23.8 ft	DRILL MACHINE D-50	DRILL METHOD MUD ROTARY	HAMMER TYPE AUTO
DATE STARTED 3-15-05	COMPLETED 3-15-05	SURFACE WATER DEPTH N/A	



NCDOT_BORE_VARIABLE_DEPTH_04-064_BR_42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05




2736 ROWLAND ROAD
 RALEIGH, NORTH CAROLINA 27615
 Phone (919) 871-0800 Fax (919) 871-0803


BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-064	ID. MA5018B	COUNTY FRANKLIN	GEOLOGIST J. HOWARD
SITE DESCRIPTION BRIDGE #42 ON SR 1235 (DYKING RD.) OVER LYNCH CREEK			GROUND WATER (ft)
BORING NO. B1A	BORING LOCATION 10+26	OFFSET 19.0' LT.	ALIGNMENT -L-
COLLAR ELEV. 204.3 ft	NORTHING	EASTING	0 HR. 0.0 24 HR. 5.0
TOTAL DEPTH 54.1 ft	DRILL MACHINE D-50	DRILL METHOD MUD ROTARY	HAMMER TYPE AUTO
DATE STARTED 3-14-05	COMPLETED 3-14-05	SURFACE WATER DEPTH N/A	




NCDOT_BORE_VARIABLE_DEPTH_04-064_BR_42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05



2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1




NCDOT_BORE_VARIABLE_DEPTH_04-064_BR_42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05



2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1



NCDOT_BORE_VARIABLE_DEPTH_04-064_BR_42 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS

GEOTECHNICAL UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

ID	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
	MA5017B	2	20

SOIL DESCRIPTION				GRADATION				ROCK DESCRIPTION				TERMS AND DEFINITIONS																																																																																																																																																																																																									
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED OR WEATHERED EARTH MATERIALS WHICH CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND WHICH YIELDS LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (ASHTO T208, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM AND BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:</p> <p>VERY STIFF, GRAY SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HARDY PLASTIC, A-7-6</p>				<p>WELL GRADED: INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE UNIFORM: INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (A-5, A-6, A-7) POORLY GRADED: INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS ARE DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>				<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WHEN TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS, IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK.</p> <p>ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>				<p>ALLUVIUM (ALLUV.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER.</p> <p>AQUIFER - A WATER BEARING FORMATION OR STRATA.</p> <p>ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.</p> <p>ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC.</p> <p>ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.</p> <p>CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.</p> <p>COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.</p> <p>CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.</p> <p>DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.</p> <p>DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.</p> <p>FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.</p> <p>FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.</p> <p>FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOOSED FROM PARENT MATERIAL.</p> <p>FLOOD PLAIN (F.P.) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.</p> <p>FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.</p> <p>JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.</p> <p>LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.</p> <p>LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.</p> <p>MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLED IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.</p> <p>PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERWEAVING IMPERVIOUS STRATUM.</p> <p>RESIDUAL SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.</p> <p>ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.</p> <p>SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.</p> <p>SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRODUCED ROCKS.</p> <p>SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.</p> <p>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS IN OR B.P.F. OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS LESS THAN 0.1 FOOT PENETRATION WITH 60 BLOWS.</p> <p>STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.</p> <p>STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.</p> <p>TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																																																									
<p>SOIL LEGEND AND AASHTO CLASSIFICATION</p> <table border="1"> <tr> <th>GENERAL CLASS.</th> <th colspan="7">GRANULAR MATERIALS (>5% PASSING #200)</th> <th colspan="7">SILT-CLAY MATERIALS (>85% PASSING #200)</th> <th colspan="7">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th colspan="2">A-1</th> <th colspan="2">A-3</th> <th colspan="3">A-2</th> <th colspan="2">A-4</th> <th colspan="3">A-5</th> <th colspan="2">A-6</th> <th colspan="2">A-7</th> <th colspan="2">A-1, A-2</th> <th colspan="3">A-4, A-5</th> </tr> <tr> <th>SYMBOL</th> <td colspan="2">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="3">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="3">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="2">[Symbol]</td> <td colspan="3">[Symbol]</td> </tr> <tr> <th>% PASSING</th> <td colspan="2">10</td> <td colspan="2">40</td> <td colspan="3">60</td> <td colspan="2">75</td> <td colspan="3">100</td> <td colspan="2">100</td> <td colspan="2">100</td> <td colspan="2">100</td> <td colspan="3">100</td> </tr> <tr> <th>LIQUID LIMIT</th> <td colspan="2">≤ 5</td> <td colspan="2">≤ 10</td> <td colspan="3">≤ 15</td> <td colspan="2">≤ 20</td> <td colspan="3">≤ 25</td> <td colspan="2">≤ 30</td> <td colspan="2">≤ 40</td> <td colspan="2">≤ 50</td> <td colspan="3">≤ 60</td> </tr> <tr> <th>PLASTIC INDEX</th> <td colspan="2">≤ 4</td> <td colspan="2">≤ 7</td> <td colspan="3">≤ 10</td> <td colspan="2">≤ 12</td> <td colspan="3">≤ 15</td> <td colspan="2">≤ 20</td> <td colspan="2">≤ 25</td> <td colspan="2">≤ 30</td> <td colspan="3">≤ 40</td> </tr> <tr> <th>GROUP INDEX</th> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="3">0</td> <td colspan="2">0</td> <td colspan="3">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="3">0</td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td colspan="2">STONE FRAGS, GRAVEL AND SAND</td> <td colspan="2">FINE SAND</td> <td colspan="3">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SANDS</td> <td colspan="3">CLAYEY SANDS</td> <td colspan="2">CLAYEY SILTS</td> <td colspan="2">CLAYEY SILTS</td> <td colspan="2">CLAYEY SILTS</td> <td colspan="3">MUCK, PEAT</td> </tr> <tr> <th>GENERATING AS A SUBGRADE</th> <td colspan="7">EXCELLENT TO GOOD</td> <td colspan="7">FAIR TO POOR</td> <td colspan="7">POOR</td> </tr> </table> <p>P.I. OF A-7-5 ≤ L.L. - 30 + P.I. OF A-7-6 > L.L. - 30</p>				GENERAL CLASS.	GRANULAR MATERIALS (>5% PASSING #200)							SILT-CLAY MATERIALS (>85% PASSING #200)							ORGANIC MATERIALS							GROUP CLASS.	A-1		A-3		A-2			A-4		A-5			A-6		A-7		A-1, A-2		A-4, A-5			SYMBOL	[Symbol]		[Symbol]		[Symbol]			[Symbol]		[Symbol]			[Symbol]		[Symbol]		[Symbol]		[Symbol]			% PASSING	10		40		60			75		100			100		100		100		100			LIQUID LIMIT	≤ 5		≤ 10		≤ 15			≤ 20		≤ 25			≤ 30		≤ 40		≤ 50		≤ 60			PLASTIC INDEX	≤ 4		≤ 7		≤ 10			≤ 12		≤ 15			≤ 20		≤ 25		≤ 30		≤ 40			GROUP INDEX	0		0		0			0		0			0		0		0		0			USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND			SILTY SANDS		CLAYEY SANDS			CLAYEY SILTS		CLAYEY SILTS		CLAYEY SILTS		MUCK, PEAT			GENERATING AS A SUBGRADE	EXCELLENT TO GOOD							FAIR TO POOR							POOR							<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p>				<p>WEATHERED ROCK (WR)</p> <p>CRYSTALLINE ROCK (CR)</p> <p>NON-CRYSTALLINE ROCK (NCR)</p> <p>COASTAL PLAIN SEDIMENTARY ROCK (CP)</p>				<p>WEATHERING</p> <p>FRESH</p> <p>VERY SLIGHT (V. SLI.)</p> <p>SLIGHT (SLI.)</p> <p>MODERATE (MOD.)</p> <p>MODERATELY SEVERE (MOD. SEV.)</p> <p>SEVERE (SEV.)</p> <p>VERY SEVERE (V. SEV.)</p> <p>COMPLETE</p>			
GENERAL CLASS.	GRANULAR MATERIALS (>5% PASSING #200)							SILT-CLAY MATERIALS (>85% PASSING #200)							ORGANIC MATERIALS																																																																																																																																																																																																						
GROUP CLASS.	A-1		A-3		A-2			A-4		A-5			A-6		A-7		A-1, A-2		A-4, A-5																																																																																																																																																																																																		
SYMBOL	[Symbol]		[Symbol]		[Symbol]			[Symbol]		[Symbol]			[Symbol]		[Symbol]		[Symbol]		[Symbol]																																																																																																																																																																																																		
% PASSING	10		40		60			75		100			100		100		100		100																																																																																																																																																																																																		
LIQUID LIMIT	≤ 5		≤ 10		≤ 15			≤ 20		≤ 25			≤ 30		≤ 40		≤ 50		≤ 60																																																																																																																																																																																																		
PLASTIC INDEX	≤ 4		≤ 7		≤ 10			≤ 12		≤ 15			≤ 20		≤ 25		≤ 30		≤ 40																																																																																																																																																																																																		
GROUP INDEX	0		0		0			0		0			0		0		0		0																																																																																																																																																																																																		
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND			SILTY SANDS		CLAYEY SANDS			CLAYEY SILTS		CLAYEY SILTS		CLAYEY SILTS		MUCK, PEAT																																																																																																																																																																																																		
GENERATING AS A SUBGRADE	EXCELLENT TO GOOD							FAIR TO POOR							POOR																																																																																																																																																																																																						
<p>CONSISTENCY OR DENSENESS</p> <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>4 10 30 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>2 TO 4 4 TO 8 8 TO 15 15 TO 30 ≥ 30</td> <td>0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 ≥ 4</td> </tr> </table>				PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	4 10 30 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	2 TO 4 4 TO 8 8 TO 15 15 TO 30 ≥ 30	0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 ≥ 4	<p>MISCELLANEOUS SYMBOLS</p> <p>ROADWAY EMBANKMENT WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL OTHER THAN ROADWAY EMBANKMENTS</p> <p>INFERRED SOIL BOUNDARIES</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP/DIP DIRECTION OF ROCK STRUCTURES</p> <p>SOUNDING ROD</p> <p>TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>SPT N-VALUE</p> <p>SPT REFUSAL</p>				<p>ROCK HARDNESS</p> <p>VERY HARD</p> <p>HARD</p> <p>MODERATELY HARD</p> <p>MEDIUM HARD</p> <p>SOFT</p> <p>VERY SOFT</p>																																																																																																																																																																																																	
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																																																																		
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	4 10 30 50	N/A																																																																																																																																																																																																																		
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	2 TO 4 4 TO 8 8 TO 15 15 TO 30 ≥ 30	0.25 0.25 TO 0.5 0.5 TO 1 1 TO 2 2 TO 4 ≥ 4																																																																																																																																																																																																																		
<p>TEXTURE OR GRAIN SIZE</p> <table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.0</td> <td>0.425</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>SOIL ORDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CS.SQ.)</th> <th>FINE SAND (F.SQ.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td>GRAIN SIZE</td> <td>305</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> <tr> <td>IN.</td> <td>12"</td> <td>3"</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>				U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.0	0.425	0.25	0.075	0.053	SOIL ORDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS.SQ.)	FINE SAND (F.SQ.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE	305	75	2.0	0.25	0.05	0.005	IN.	12"	3"					<p>ABBREVIATIONS</p> <p>AR - AUGER REFUSAL</p> <p>BT - BORING TERMINATED</p> <p>CL - CLAY</p> <p>CPT - CONE PENETRATION TEST</p> <p>CSE - COARSE</p> <p>DMT - DILATOMETER TEST</p> <p>DPT - DYNAMIC PENETRATION TEST</p> <p>∅ - VOID RATIO</p> <p>F - FINE</p> <p>FOSS. - FOSSILIFEROUS</p> <p>FRAC. - FRACTURED</p> <p>FRAGS. - FRAGMENTS</p> <p>MED. - MEDIUM</p> <p>PMT - PRESSUREMETER TEST</p> <p>SD - SAND, SANDY</p> <p>SL - SILT, SILTY</p> <p>SLL - SLIGHTLY</p> <p>TCR - TRICONE REFUSAL</p> <p>U - UNIT WEIGHT</p> <p>U_d - DRY UNIT WEIGHT</p> <p>W - MOISTURE CONTENT</p> <p>V - VERY</p> <p>VST - VANE SHEAR TEST</p>				<p>EQUIPMENT USED ON SUBJECT PROJECT</p> <p>CRILL UNITS:</p> <p>MOBILE B-</p> <p>BK-51</p> <p>CME-45</p> <p>CME-550</p> <p>PORTABLE HOIST</p> <p>OTHER C-50</p> <p>OTHER</p> <p>ADVANCING TOOLS:</p> <p>CLAY BITS</p> <p>6" CONTINUOUS FLIGHT AUGER</p> <p>8" HOLLOW AUGERS</p> <p>HARD FACED FINGER BITS</p> <p>TUNG-CARBIDE INSERTS</p> <p>CASING</p> <p>TRICONE 3" STEEL TEETH</p> <p>TRICONE TUNG-CARB.</p> <p>CORE BIT</p> <p>OTHER</p> <p>HAMMER TYPE:</p> <p>AUTOMATIC</p> <p>MANUAL</p> <p>CORE SIZE:</p> <p>B</p> <p>N</p> <p>H</p> <p>HAND TOOLS:</p> <p>POST HOLE DIGGER</p> <p>HAND AUGER</p> <p>SCUNDING ROD</p> <p>VANE SHEAR TEST</p> <p>OTHER</p>				<p>FRACTURE SPACING</p> <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 18 FEET</td> <td>VERY THICKLY BEDDED</td> <td>> 4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 18 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table> <p>INDURATION</p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE</p> <p>MODERATELY INDURATED</p> <p>INDURATED</p> <p>EXTREMELY INDURATED</p>				TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 18 FEET	VERY THICKLY BEDDED	> 4 FEET	WIDE	3 TO 18 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET																																																																																																																																							
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																																															
	4.75	2.0	0.425	0.25	0.075	0.053																																																																																																																																																																																																															
SOIL ORDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CS.SQ.)	FINE SAND (F.SQ.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																																															
GRAIN SIZE	305	75	2.0	0.25	0.05	0.005																																																																																																																																																																																																															
IN.	12"	3"																																																																																																																																																																																																																			
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																																																																		
VERY WIDE	MORE THAN 18 FEET	VERY THICKLY BEDDED	> 4 FEET																																																																																																																																																																																																																		
WIDE	3 TO 18 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																																		
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																																		
CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																																		
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																																		
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																																		
<p>PLASTICITY</p> <table border="1"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table> <p>COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YEL-BRN, BLUE-GRAY) MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>				NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p>NOTES:</p> <p>BENCH MARK: 3M #2, -BL- STA. 12+59.47, 52.60' RIGHT</p> <p>ELEVATION: 204.36'</p>																																																																																																																																																																																																		
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																																																			
LOW PLASTICITY	0-5	VERY LOW																																																																																																																																																																																																																			
MED. PLASTICITY	6-15	SLIGHT																																																																																																																																																																																																																			
HIGH PLASTICITY	16-25	MEDIUM																																																																																																																																																																																																																			
	26 OR MORE	HIGH																																																																																																																																																																																																																			

8+00

9+00

10+00


11+00

12+00

13+00

14+00

15+00




NOTES:

BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RT., ELEVATION 204.36'

PLANS ADOPTED FROM HYDRAULIC SURVEY FILES
RECEIVED FROM SUNGATE, DATED 9-28-04

STATIONING ON LOCATION PLAN, CROSS-SECTIONS, PROFILE AND
BORING LOGS BASED UPON HYDRO REPORT DATED 9-28-04




BORING LOCATION PLAN

NCDOT PROJECT #: MA5017B
FRANKLIN CO., NC
BRIDGE #41 ON SR 1235 (DYKING RD.)
OVER TOOLES CREEK



TIERRA
GEOTECHNICAL • MATERIALS
ENGINEERING

TIERRA, INC.
2735 ROWLAND RD.
RALEIGH, NC 27615
PHONE (919) 871-0800
FAX (919) 871-0803



BENCH MARK: BM #2, -BL- STA. 12+59.47,
 52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE

0 10 20



HORIZONTAL SCALE

0 10 20




PROFILE 15' RIGHT OF -L-

NCDOT PROJECT #: MA5017B
 FRANKLIN CO., NC
 BRIDGE #41 ON SR 1235 (DYKING RD.)
 OVER TOOLE'S CREEK




ELEV. (FT.)




ELEV. (FT.)

BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE



HORIZONTAL SCALE




CROSS SECTION END BENT 1

NCDOT PROJECT #: MA5017B
FRANKLIN CO., NC
BRIDGE #41 ON SR 1235 (DYKING RD.)
OVER TOOLES CREEK




ELEV. (FT.)

ELEV. (FT.)




BENCH MARK: BM #2, -BL- STA. 12+59.47,
52.60' RIGHT, ELEVATION OF 204.36'

VERTICAL SCALE



HORIZONTAL SCALE



CROSS SECTION END BENT 2

NCDOT PROJECT #: MA5017B
FRANKLIN CO., NC
BRIDGE #41 ON SR 1235 (DYKING RD.)
OVER TOOLE'S CREEK






2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1




NCDOT_BORE_VARIABLE_DEPTH 04-088 BR 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05




2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1



NCDOT_BORE_VARIABLE_DEPTH 04-088 BR 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05




2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-063		ID. MA5017B		COUNTY FRANKLIN		GEOLOGIST Y. SALEH							
SITE DESCRIPTION BRIDGE #41 ON SR 1235 (DYKING RD.) OVER TOOLES CREEK						GROUND WATER (ft)							
BORING NO. EB2A		BORING LOCATION 14+09		OFFSET 15.0' LT.		ALIGNMENT -L-							
COLLAR ELEV. 211.0 ft		NORTHING		EASTING		0 HR. 8.0							
TOTAL DEPTH 44.2 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO							
DATE STARTED 3-02-05		COMPLETED 3-03-05		SURFACE WATER DEPTH N/A									
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
211.0													EXISTING GROUND
210.0	0.0	3	2	2									210.9 ROOTMAT RDWY EMB: TAN AND BROWN, LOOSE, SILTY SAND (A-2-4)
	4.0	2	3	2									205.5 RDWY EMB: GRAY, LOOSE, CLAYEY SAND (A-2-6)
205.0	6.0	2	7	2									202.5 ALLUV: BLUE AND GRAY, V. SOFT, SANDY CLAY (A-6)
	9.0	WOH	WOH	WOH									197.5 ALLUV: BLUE AND GRAY, STIFF TO V. STIFF, CLAYEY SILT (A-4)
200.0	14.0	4	4	7									187.5 ALLUV: GRAY, LOOSE, SILTY SAND (A-2-4)
	19.0	9	9	12									186.0 ALLUV: GREEN, MED. STIFF, SILT (A-4)
190.0	24.0	4	2	4									182.5 RES: WHITE, GRAY AND BROWN, MED. DENSE TO V. DENSE, SILTY SAND (A-2-4)
	29.0	7	9	8									176.5 WR: BROWN AND TAN, GRANITE
185.0	34.0	38	62/4										166.8 BORING TERMINATED AT ELEV. 166.7' IN WR: BROWN AND TAN, GRANITE
180.0	39.0	100/4											
175.0	44.0	60/2											

NCDOT_BORE_VARIABLE_DEPTH_04-063 BR 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05



2736 ROWLAND ROAD
RALEIGH, NORTH CAROLINA 27615
Phone (919) 871-0800 Fax (919) 871-0803

N.C.D.O.T. GEOTECHNICAL UNIT
BORING LOG

SHEET 1 OF 1

PROJECT NO. 6211-04-063		ID. MA5017B		COUNTY FRANKLIN		GEOLOGIST C. BRUINSMA							
SITE DESCRIPTION BRIDGE #41 ON SR 1235 (DYKING RD.) OVER TOOLES CREEK						GROUND WATER (ft)							
BORING NO. EB2B		BORING LOCATION 14+07		OFFSET 14.0' RT.		ALIGNMENT -L-							
COLLAR ELEV. 211.3 ft		NORTHING		EASTING		0 HR. 7.4							
TOTAL DEPTH 54.0 ft		DRILL MACHINE D-50		DRILL METHOD MUD ROTARY		HAMMER TYPE AUTO							
DATE STARTED 3-22-05		COMPLETED 3-22-05		SURFACE WATER DEPTH N/A									
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
211.3													EXISTING GROUND
210.0	1.0	2	2	2									211.1 ROOTMAT RDWY EMB: BROWN, LOOSE TO V. LOOSE, CLAYEY SAND (A-2-6)
	2.8	1	WOH	1									205.8 RDWY EMB: ORANGE AND BROWN, MED. STIFF, SANDY CLAY (A-6)
205.0	5.8	1	2	5									204.2 RDWY EMB: ORANGE AND BROWN, MED. STIFF, SANDY CLAY (A-6)
	7.8	1	4	4									202.5 ALLUV: GRAY AND BROWN, LOOSE, CLAYEY SILTY SAND (A-2-4)
200.0	12.7	WOH	2	2									200.3 ALLUV: GRAY, LOOSE, SAND (A-1-b)
	17.7	6	5	9									195.3 ALLUV: GRAY, MED. DENSE, CLAYEY SAND (A-2-6)
190.0	22.7	7	7	10									192.3 ALLUV: GRAY, MED. DENSE, SAND (A-1-b)
	27.7	12	11	11									185.8 RES: BROWN AND GRAY, MED. DENSE TO V. DENSE, SILTY SAND (A-2-4) SAPROLITIC
185.0	32.7	11	9	13									171.8 WR: BROWN, WHITE AND BLACK, GRANITE
	37.7	37	24	63									165.3 RES: BROWN AND WHITE, V. DENSE, SILTY SAND (A-2-4) SAPROLITIC
180.0	42.7	100/4											158.1 WR: TAN AND PINK, GRANITE
	47.7	22	17	34									157.3 BORING TERMINATED AT ELEV. 157.3' IN WR: TAN AND PINK, GRANITE
175.0	52.7	30	53	47/3									

NCDOT_BORE_VARIABLE_DEPTH_04-063 BR 41 - FRANKLIN CO.GPJ NCDOT.GDT 5/18/05