D: B-3672

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS
GEOTECHNICAL UNIT

CONTENTS:

<u>Shket</u>	<u>DESCRIPTION</u>
1	TITLE SHEET
2	LEGEND
3	TEST SITE PLAN
4	PROFILE
5	CROSS SECTIONS
6-9	BORING LOGS
10	SOIL SAMPLE RESULT
11	SCOUR REPORT
12	CORE PHOTOGRAPHS

STRUCTURE SUBSURFACE INVESTIGATION

STATE PROJECT <u>8.2312401</u> I.D. NO. <u>B-3672</u>
F.A. PROJECT <u>BRZ-1718(4)</u>
COUNTY <u>JOHNSTON</u>
PROJECT DESCRIPTION <u>BRIDGE NO. 415 ON</u>
SR 1718 OVER BUFFALO CREEK

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WAS MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORNG LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL UNIT @ (1919) 250-4088, NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORNING LOGS, ROCK CORES, OR SOIL TEST DATA IS PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BORCHOLE, THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY 10 THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION, THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.


THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR QUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIOND TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

INVESTIGATED BY O.B. OTT PERSONNEL D.S. TIGNOR


CHECKED BY T.P. MOOREFIELD T.N. BENNEKIN

SUBMITTED BY D. N. ARGENBRIGHT N.P. WALLACE

DATE JANUARY, 2003



NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS
FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE
CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE,



DRAWN BY: __TTW, JLL

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS

GEOTECHNICAL UNIT


SUBSURFACE INVESTIGATION


,					SOIL AND RO	CK LEGEND, TERM	S, SYMB	OLS, AND	 ABBREVI	ATIONS			
	SOIL DESC	CRIPTION			GRADATION			,		DESCRIPTION		TERMS AND DEFINITIONS	
WHICH CAN BE PENETRATED 100 BLOWS PER FOOT ACCOR CLASSIFICATION IS BASED O	THE UNCONSOLIDATED, SEMI- WITH A CONTINUOUS FLIGHT I RDING TO STANDARD PENETRAT ON THE AASHTO SYSTEM AND	CONSOLIDATED OR WEA' POWER AUGER, AND WHI FION TEST (AASHTO T2 BASIC DESCRIPTIONS G	ICH YIELDS LESS THAN 206, ASTM D-1586). SOIL GENERALLY SHALL INCLUDE:	POORLY CRADED	OD REPRESENTATION OF PARTICLE SIZES FF. PARTICLES ARE ALL APPROXIMATELY THE URE OF UNIFORM PARTICLES OF TWO OR MO ANGULARITY OF GRAINS	SAME SIZE. (ALSO	ROCK LINE SPT REFUS IN NON-COA OF WEATHE	INDICATES THE LEVE AL IS PENETRATION ASTAL PLAIN MATERI RED ROCK.	AIN MATERIAL THA EL AT WHICH NON-(BY A SPLIT SPOON AL, THE TRANSITION	IT WHEN TESTED, WOULD YIELD SPT COASTAL PLAIN MATERIAL WOULD Y I SAMPLER EQUAL TO OR LESS THA ON BETWEEN SOIL AND ROCK IS OF	TELD SPT REFUSAL.	ALLUYIUM (ALLUY.) - SOILS WHICH HAVE BEEN TRANSPORTED BY WATER. AOUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.	
AS MINERALOGICAL COMPOSI VERY STA	IRE, MOISTURE, AASHTO CLASSIF ITION, ANGULARITY, STRUCTURE, TIFF, GRAY SULY CLAY, MOIST WITH INTERBEL	PLASTICITY, ETC. EXAM DOED FINE SAND UNERS, HICHU	MPLE: 1 PLASTAC, A-7-6	SUBANGULAR, SUBROUNDED, OR F			WEATHERED ROCK (WR)	RIALS ARE TYPICALL	9	OWS: LAIN MATERIAL THAT YİELDS SPT	N VALUES > 100 BLOWS	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL	
GENERAL GRANUL		HTO CLASSIFI SILT-CLAY MATERIALS >85% PASSING *200)	ICATION ORGANIC MATERIALS		MINERALOGICAL COMPOSITION TO THE LEGISTRAN MICA, TALC, KAOLIN, ETC. ARE LEGIST OF SIGNIFICANCE.		CRYSTALLINE ROCK (CR)		WOULD YIELD SI GNEISS, GABBRO,		E INCLUDES GRANITE,	AT WHICH IS IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS WHICH CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.	
GROUP A-1 A- CLASS. A-1-8 A-1-6	-3 A-2 1 A-2-4 A-2-5 A-2-6 A-2-7	A-4 A-5 A-6 A-7-	7 A-1, A-2 A-4, A-5 6 A-3 A-6, A-7	SLIGHTLY COMPRESSI		LESS THAN 30	NON-CRYSTALL ROCK (NCR)		SEDIMENTARY RO	E GRAIN METAMORPHIC AND NON-CO OCK THAT WOULD YEILD SPT REFUS LITE, SLATE, SANDSTONE, ETC.	GAL IF TESTED. ROCK TYPE	COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE,	
SYMBOL 000000000000000000000000000000000000				MODERATELY COMPRESSIBLE HIGHLY COMPRESSIBLE		GREATER THAN 50	COASTAL PLAI SEDIMENTARY (CP)		SPT REFUSAL. R SHELL BEDS, ETC		BUT MAY NOT YIELD ANDSTONE, CEMENTED	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARRIEL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.	
* 10 50 MX * 40 30 MX 50 MX 51 N			GRANULAR SOILS SILT-CLAY SOILS PEAT	URGANIC MATERIAL	GRANULAR SILT- CLAY SOILS SOILS 2 - 3% 3 - 5% TRG	OTHER MATERIAL	FRESH	ROCK FRESH, CRYSTA	LG BRIGHT. FEW J	ATHERING OINTS MAY SHOW SLIGHT STAINING	ROCK RINGS UNDER	<u>DIKE</u> - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. <u>DIP</u> - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE	
LIQUID LIMIT	MX 35 MX 35 MX 35 MX 35 MX 31 MX 31 MX 31 MX 31 MX 41 MX 40 MX 41	0 MX 41 MN 40 MX 41 M	N SOILS WITH	LITTLE ORGANIC MATTER			VERY SLIGHT	HAMMER IF CRYSTAL ROCK GENERALLY FF CRYSTALS ON A BRO	RESH, JOINTS STAIN	WED, SOME JOINTS MAY SHOW THIN CE SHINE BRIGHTLY. ROCK RINGS U	CLAY COATINGS IF OPEN, NDER HAMMER BLOWS IF	HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.	
GROUP INDEX Ø Ø USUAL TYPES STONE FRAGS.		MX 12 MX 16 MX No N	MX MODERATE ORGANIC SOILS		GROUND WATER EVEL IN BORE HOLE IMMEDIATELY AFTER		(SLI.)	1 INCH, OPEN JOINTS	RESH, JOINTS STAIN MAY CONTAIN CL	NED AND DISCOLORATION EXTENDS AY. IN GRANITOID ROCKS SOME OCC	CASIONAL FELDSPAR	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.	
MATERIALS SAND SAN	AND GRAVEL AND SAND	SOILS SOILS	MATTER FAIR TO BOOD LINGUISTANCE	∀	ATER LEVEL AFTER 24 HOURS.	INC STRATA	CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. MODERATE (MOD.) SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY, ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK. MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL				FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL.		
SUBGRADE	LENT TO GOOD .OF A-7-5 ≤ L.L 30 :	FAIR TO POOR P.I. OF A-7-6 > L.	POOR POUR UNSULTABLE	SPRING OR		no omana					FRENGTH AS COMPARED	THE STREAM. LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.	
		RANGE OF STANDARD		[日] ROADWAY EMBANKM	MISCELLANEOUS SYMBOLS	ANEOUS SYMBOLS MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCK SEVERE MOD. SEV.) SEVERE MOD. SEV.) ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCK SHOWS SEVERE MOD. SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK, ROCK GIVES 'CLUNK IF TESTED, WOULD YIELD SPT REFUSAL FOR THE SEVEN FROM THE SEVEN FRO				ITOID ROCKS, ALL FELDSPARS DULL K SHOWS SEVERE LOSS OF STRENGTH FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED.			
PRIMARY SOIL TYPE GENERALLY	CONSISTENCY VERY LOOSE LOOSE	ETRATION RESISTENCE (N-VALUE) <4 4 TO 10	(TONS/FT ²)	SEVERE ALL ROCKS EXCEPT OL SEVERENCE TO SEVERE ALL ROCKS EXCEPT OL SEVERENCE SEVERENCE TO SEVERENCE SEVER			QUARTZ DISCOLORE	ED OR STAINED.ROCK FABRIC CLEA ANITOID ROCKS ALL FELDSPARS AR	R AND EVIDENT BUT REDUCED E KAOLINIZED TO SOME	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.			
GRANULAR MATERIAL (NON-COHESIVE)	MEDIUM DENSE DENSE VERY DENSE VERY SOFT	10 TO 30 30 TO 50 >50	N/A	ARTIFICIAL FILL O ROADWAY EMBANKM INFERRED SOIL BO	ENTS — CORE BORING DUNDARIES	SS- SPLIT SPOON SAMPLE ST- SHELBY TUBE SAMPLE	IF TESTED, YIELDS SPT. N. VALUES > 100 BPF VERY SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FARRIC FLEMENTS ARE DISCEPTURE F. BUT			<i>00 BPF</i> D OR STAINED. ROCK FABRIC ELEME TO SOIL STATUS, WITH ONLY FRAGM	ENTS OF STRONG ROCK	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS, MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.	
GENERALLY SILT-CLAY	SOFT MEDIUM STIFF	2 TO 4 4 TO 8	<0.25 0.25 TO 0.5 0.5 TO 1	SIJEIJE INFERRED ROCK LI	A PIEZUMETER	RS- ROCK SAMPLE		VESTIGES OF THE O	RIGINAL ROCK FABI	RIC REMAIN. <u>IF TESTED, YIELDS S</u> NOT DISCERNIBLE, OR DISCERNIBLE	SPT N VALUES < 100 BPF	<u>PERCHED WATER</u> - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. <u>RESIDUAL SOIL</u> - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK,	
MATERIAL (COHESIVE)	STIFF VERY STIFF HARD	8 TO 15 15 TO 30 >30	1 TO 2 2 TO 4 >4	25/825 DIP/DIP DIRECTION ROCK STRUCTURES	SLOPE INDICATO	RT- RECOMPACTED TRIAXIAL SAMPLE CBR - CBR SAMPLE		SCATTERED CONCENT ALSO AN EXAMPLE.	RATIONS. QUARTZ I	MAY BE PRESENT AS DIKES OR STI	RINGERS. SAPROLITE IS	ROCK QUALITY DESIGNATION (R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY: TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.	
U.S. STD. SIEVE SIZE	TEXTURE OR	GRAIN SIZE		• - SOUNDING ROD	SPT N-VALUE REF SPT REFUSAL		VERY HARD	CANNOT BE SCRATO SEVERAL HARD BLO	HED BY KNIFE OR	SHARP PICK, BREAKING OF HAND S	PECIMENS REQUIRES	SAPROLITE (SAP.) - RESIDUAL SOIL WHICH RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.	
OPENING (MM) BOULDER COBBL	4.76 2.0 BLE GRAVEL	0.42 0.25 0.0 COARSE FIN	NE STIT CLAY		ABBREVIATIONS	-	HARD		BY KNIFE OR PIC	K ONLY WITH DIFFICULTY, HARD H	AMMER BLOWS REQUIRED	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, WHICH HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS	
(BLDR.) (COB	n.	SAND SAN (CSE, SD.) (F.	ND (SL.) (CL.) 0.05 0.005	AR - AUGER REFUS BT - BORING TERM CL CLAY CPT - CONE PENET	INATED SD SAND, SA SL SILT, SIL	TY	MODERATELY HARD		D BLOW OF A GEO	CK, GOUGES OR GROOVES TO 0.25 I BLOGISTS PICK, HAND SPECIMENS CO		SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.	
SIZE IN. 12" SOIL SOIL MOISTURE SCA	3" L MOISTURE - COR ALE FIELD MOIST	NIDE	TERMS R FIELD MOISTURE DESCRIPTION	CSE COARSE DMT - DILATOMETE DPT - DYNAMIC PE	TCR - TRICON	E REFUSAL EIGHT	MEDIUM HARD	CAN BE EXCAVATED POINT OF A GEOLO	IN SMALL CHIPS GISTS PICK.	ICHES DEEP BY FIRM PRESSURE OF TO PEICES 1 INCH MAXIMUM SIZE	BY HARD BLOWS OF THE	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR B.P.F.) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF LEGOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS LESS THAN 0.1 FOOT PENETRATION WITH 60 BLOWS.	
(ATTERBERG LIMITS)	DESCRIPTIO - SATURATE	IN L	LIQUID; VERY WET, USUALLY	e - VOID RATIO F FINE FOSS FOSSILIFEF FRAC FRACTURED	W - MOISTURE V VERY	CONTENT	SOFT	FROM CHIPS TO SE PIECES CAN BE BR	VERAL INCHES IN OKEN BY FINGER P		ICK POINT. SMALL, THIN	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (S.R.Q.D.) - A MEASURE OF ROCK QUALITY DESCRIBED BY:	
LL LIQUID LI		SEMISOI T	LOW THE GROUND WATER TABLE TO: REQUIRES DRYING TO	FRAGS FRAGMENT MED MEDIUM	rs	-Ka	VERY SOFT	OR MORE IN THICK FINGERNAIL.	NESS CAN BE BROK	EXCAVATED READILY WITH POINT EN BY FINGER PRESSURE, CAN BE	OF PICK, PIECES I INCH SCRATCHED READILY BY	TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 10 CENTIMETERS DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.	
RANGE (PI) PLASTIC I	- WET - 0		OPTIMUM MOISTURE		PMENT USED ON SUBJECT F	PROJECT HAMMER TYPE:	FF TERM	ACTURE SPAC	CING PACING	BEDDI TERM	NG THICKNESS	TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. RENCH MARK: BL-2 REFL- 18+58.14/12.79 FEET RT. REBAR	
OM OPTIMUM M		(M) SOLID; A	AT OR NEAR OPTIMUM MOISTURE	DRILL UNITS: MOBILE B	ADVANCING TOOLS: CLAY BITS	AUTOMATIC MANUAL	VERY WIDE	MORE 3 TO 1	THAN 10 FEET 0 FEET	VERY THICKLY BEDDED THICKLY BEDDED THINLY BEDDED	> 4 FEET 1.5 - 4 FEET 0.16 - 1.5 FEET	WITH CAP ELEVATION: 254.63'	
	- DRY - (C		S ADDITIONAL WATER TO PPTIMUM MOISTURE	⊠ BK-51	6' CONTINUOUS FLIGHT AUGER 8' HOLLOW AUGERS	CORE SIZE:	MODERATELY CLOSE 1 TO 3 FEET CLOSE 0.16 TO 1 FEET VERY CLOSE LESS THAN 0.16 FEET		VERY THINLY BEDDED THICKLY LAMINATED THINLY LAMINATED	0.03 - 0.16 FEET 0.008 - 0.03 FEET < 0.008 FEET	NOTES:		
4	PLAST			CME-45	HARD FACED FINGER BITS	⊠-N WXL	EUD GEDINERA	ADV DOCKS THOUGHT		URATION IING OF THE MATERIAL BY CEMENT	THE HEAT DECOME FTO		
NONPLASTIC	PLASTICITY I 0-5	NDEX (PI)	DRY STRENGTH VERY LOW	CME-550	TUNGCARBIDE INSERTS					JING OF THE MATERIAL BY CEMENT WITH FINGER FREES NUMEROUS G			
LOW PLASTICITY MED. PLASTICITY	6-15 16-25		SLIGHT MEDIUM		CASING W/ ADVANCER	HAND TOOLS:	FR:	ABLE	GENTLE	BLOW BY HAMMER DISINTEGRATES	SAMPLE.		
HIGH PLASTICITY	26 OR		HIGH	PORTABLE HOIST	TRICONE STEEL TEETH	POST HOLE DIGGER	MOD	ERATELY INDURATED		CAN BE SEPARATED FROM SAMPLE EASILY WHEN HIT WITH HAMMER.	WITH STEEL PROBE;		
prospir	COL			OTHER	TRICONE TUNGCARB. CORE BIT	HAND AUGER SOUNDING ROD	IND	URATED		ARE DIFFICULT TO SEPARATE WITH	STEEL PROBE;		
1	NCLUDE COLOR OR COLOR C LIGHT, DARK, STREAKED, ETC			OTHER	OTHER	VANE SHEAR TEST OTHER	ЕХТ	REMELY INDURATED	SHARP I	LT TO BREAK WITH HAMMER. HAMMER BLOWS REQUIRED TO BREA BREAKS ACROSS GRAINS.	K SAMPLE;		
				······································		L	L						

REVISED 09/15/0

 STATE PROJECT NO.
 SHEET NO.
 TOTAL SHEETS

 8.2312401
 2
 12






NORTH CAROLINA DEPARTMENT OF TRANSPORTATION GEOTECHNICAL UNIT BORING LOG

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

GEOTECHNICAL UNIT BORING LOG



SHEET 7 OF 12

PROJECT NO 8.23 240 ID B-3672 COUNTY JOHNSTON GBOLOGIST O.B.OTI	100	ט ט ט ט	u \				echi					BOR			L00	70	. u .		9110
BARDING NO. BI-A	PROJECT 1	NO. 8.	2312	40I		ID.	3-3672	CC	UNTY	MOL	VS T	 ON	GE	OLO	GIST	0.B.0	TI		
COLLAR ELEVATION 244.5' NORTHING 782700.] RASTING 6298/23.2 19 HR. 0.8'	SITE DESC	RIPTION	BF	RIDG	E NO	o. 415	ON SI	R 1718	OVER	BUFF	ALC	CREEK						GROU	ND WATER
TOTAL DEPTH 34.0' DRILL MACHINE BK-5 DRILL METHOD N-CASING/CORE HAMMER TYPE AUTOMATIC STAKT DATE 7/29/02 COMPLETION DATE 7/29/02 SURFACE WATER DEPTH N/A DEPTH TO ROCK SO/O SURFACE WATER DEPTH N/A DEPTH TO ROCK SO/O	BORING N	0. BI-	- A	В	ORIN(G LOC	ATION	17+75.	0	OFF	SET	6.0′LT	AL	JGN	MENT	-L-		0 HR.	N/A
START DATE 7/29/02 COMPLETION DATE 7/29/02 SURPACE WATER DEPTH N/A DEPTH TO ROCK 15,0'	COLLAR E	LEVATIO	ON 2	244.	5′ <u> </u>	N	ORTHING	7827								<u> </u>		24 HR.	0.8′
DEPTH BLOW COUNT PEN. BLOWS PER FOOT SAMPLE MOIL											METH	OD N-CA	SING	/CC	RE	HAMME	R TYP	E AU1	OMATIC
CRAY-FILLING FROM CRAINTE CRAYSTALLING FROM CRAY											SUR	FACE WAT	ER DEP	TH	N/A	DEPT	H TO	ROCK	15.0′
244.5	ELEV.		1			1					ΙΟΟ		MOI.	00					
240.0	244.5 -				1		V						Y				11100		
235.0	240.0	4.0	2	3	3	1.0	XE-					SS-8			TA				SAND
230.0 14.0 100 0.1 100							- 												
230.0	235.0	_ 9.0	4	12	18	1.0		+¥ 30 _ -	 			SS-9	W		D.F.				CAND
225.0	230.0	- _ 14.0	100			0.1				100	+ X				1				
220.0 RS-1 RS-1 RS-1 RS-1 RS-2 RS-2 RAINED TO SOUND, COARSE GRAINED TO SOUND, COARSE GRAINED GRAINED TO SOUND, COARSE GRAINED TO SOUND, COARSE GRAINED GRAINED GRAINED TO SOUND, COARSE GRAINED GRAINED GRAINED TO SOUND, COARSE GRAINED GRAINED TO SOUND, COARSE GRAINED GRAINED TO SOUND, COARSE GRAINED	=	- - -						 											
220.0	225.0	_														CRYSTA	LLINE	ROCK	
215.0 RS-2 FRACTURED TO SOUND, COARSE GRAINED GRANITE 210.0 34.0 CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 205.0 CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE 1. CORING TERMINATED AT THE FRACTURE TO SOUND, COARSE GRAINED GRANITE TO SOUND, COARSE GRANITE TO	220.0	- - -										RS-I							
215.0	220.0											DC_2							
200.0	215.0	 						<u> </u>		-		N3-2			IIVA				OANSL
CORING JERMINATED AT		-										RS-3							
205.0	210.0	34 . 0 -						i	1	1									
200.0	205.0						!	1	1	1									
195.0 — 190.0 — 175.0 — 170.0	1	-						1	1		_								
190.0 — 185.0 — 175.0 — 170.0	200.0	- -						<u> </u>											
190.0 — 185.0 — 175.0 — 170.0		- ·																	
185.0 — 175.0 — 170.0	195.0	- -									- - -								
175.0 — 170.0	190.0	- - 																	
175.0 — 170.0		- -																	
175.0	185 . 0 	 -							 		- 								
175.0	180.0	-									- - -								
170.0		-									- - -								
	175.0	 -									-								
	170 0	-																	
165.0 +		- - -									- - -								
	165.0	<u>-</u> -																	

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

						C	ORE BORING	REPORT									
PRC	JECT:	8.23124	101	ID:	B-3	672	COUNTY:	Johnston	E	BORING NO:	B1-A						
DES	CRIPTI	ON: Bri	dge No	. 415 or	n SR 17	718 over E	Ruffalo Crook		4								
LOC	ATION	OF BORII	NG:	-L- St	a. 17+7	75, Offset	6.0' LT		COMPLE	TION DATE:	7/29/02						
COL	LAR or	GROUND	ELEV	'ATION	: 244	.5 ft	CORE SIZE: NX		EOLOGIST:								
ł							, NXWL core barrel		DRILLER:								
		DRILL		REC	RQD												
ELEV (ft)	DEPTH (ft)	RATE (min/ft)	RUN (ft)	(ft) (%)	(ft) (%)	SAMPLE NUMBER	•	FIELD CLASSIFICATI	ION and REMARKS	3							
229.5	15.0	2:00					Gray-white, very slightly weathe	ered to fresh, sound, coars	se-grained granite								
		2:04 1:94	4.0	3.9	3.9												
225.5	19.0	2:05		(98%)	(98%)												
225.5	19.0	2:26					Gray-white, very slightly weathe	ered to fresh, sound, coars	se-grained granite								
		2:14	5.0	5.0	5.0	RS- 1			o granica granite								
		2:12	3.0	(100%)	(100%)	22.4'-23.0'											
220.5 220.5	24.0	2:18 3:17															
	21.0	3:36		5.0	3.0	RS-2	Gray-white, very slightly weathe fractures at 60 to 65 degrees al	red to fresh, slightly fractu ong foliated bands of mica	ired to sound, coars a	se-grained granite	with						
	ŀ	3:58 4:47	5.0	(100%)		27.4'-28.0'		·									
215.5	29.0	4:16		(100%)	(60%)												
215.5	29.0	2:52 2:59		5.0	5.0		Gray-white, very slightly weathe	red to fresh, sound, coars	ed-grained granite								
		2:39	5.0			RS-3											
210.5	34.0	2:59 2:57		(100%)	(100%)	33.2'-34.0'											
								·									
	-				İ												
	-																
-	ŀ																
	F				ĺ					٠							
	F																
	<u> </u>																
	L		i				BOREHOLE TERMINATED	ATELEMATION OF CO.									

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

PROJECT	NO. 8.	23124	401		ID. E	3-3672	COUNT	Y JOHN	STON	G	EOLO	GIST	0.B. 0	TI	
SITE DESC	RIPTION	BF	RIDGE	E NO	. 415	ON SR 171	8 OVE	R BUFF	ALO CREE						GROUND WATER
BORING N	0. B2	-B	BO	ORING	LOC		22.0		ET 6.0′ R				-L-		HR. N/A
COLLAR E			244.				32694.		EAST			9907.			4 HR. 0.8'
TOTAL DE						INE BK-51			ETHOD N-0					·	AUTOMATIC
START DA						ETION DATE			SURFACE WA		PTH	N/A			OCK 9.0'
ELEV.	DEPTH (FT.)	1			1 1	BLOWS 0 25	50 50		SAMPL 100 NUMBE	R MO	0 I. G		SOIL A	ND R	
244.5	0.0	1	2	2	1.0	 			_ SS-6	W		L0	Al -SE, TAN	LUVIA L GRAY, S	SILTY SAND /
240.0	4.2	1	1	2	1.0	¥-3			SS-7	W		I .			SILTY CLAY, ANIC DEBRIS
235.0	7.5	1	100		0.7			<u> </u>	-X						(GRANITE)
-	 								T_ RS-4				CRYSTA	IIINE	DUCK
230.0	_								 RS-5			GRAY			Y WEATHERED
225.0 -	 						_		_						FRACTURED
- - -	<u> </u>								_ RS-6			TO SC	UND, COAF	RSE-GR.	AINED GRANITE
220.0 -	 - -								-						
215.0	28.5					CORING	TERMIN	IATED_A	<u>- </u>						
-	 -					ELEVAT		I6.0 INT	_						
210.0	<u> </u>					1	RANLT	1							
205.0	_								_						
200.0	_														
	-								_						
195.0	_								_						
190.0	_						_		_						
	_														
185.0	- - -						_		- - -						
180.0	_								_ _ _						
175.0	- -						_		 						
175.0	-														
170.0	-						 		- - -						
165.0	- - -								-				ž.		
103.0	_						_ +		-						

GEOTECHNICAL UNIT BORING LOG

							ODE DODINO DEDO	D. T.	SHEET 8 OF 1							
PRO	NECT	8.23124	104				ORE BORING REPO									
FRC	JJEC1.	8.23124	#U1 	טו	:B-3	672	COUNTY: Johns	ton	BORING NO: B2-B							
DES	CRIPTI	ON: Bri	dge No	. 415 o	n SR 17	718 over E	Buffalo Creek									
		*														
LOC	ATION	OF BORI	NG:	-L- Sta	a. 18+2	2, Offset 6	5.0' RT	COMPL	ETION DATE: 7/25/02							
COL	LAR or	GROUND	ELEV	/ATION	: 244	.5 ft	CORE SIZE: NXWL	GEOLOGIST:	O.B. Oti							
		PMENT:														
	VE EQUI	I WILIYI.			BK 31,	iv-casing	, NXWL core barrel	DRILLER:	D.S. Tignor							
ELEV	DEPTH	DRILL RATE	RUN	REC (ft)	RQD	CAMPLE										
(ft)	(ft)	(min/ft)	(ft)	(%)	(ft) (%)	SAMPLE NUMBER	FIELD C	LASSIFICATION and REMAR	KS							
235.5	9.0	0:45 0:45		3.8	2.2	RS-4	Gray-white, slightly to very slightly weather	ed, slightly to moderately fractu	red, coarse-grained granite							
		0:50	4.5	"	1 2.2	9.7'-10.6'										
231.0	13.5	0:51 0:30/0.5		(84%)	(49%)											
231.0	13.5	1:20					Gray-white, very slightly weathered to fresh	, slightly fractured to sound, co	arse-grained granite with							
		1:30 1:45	5.0	5.0	3.8	RS-5 15.4'-16.0'	fractures at 45 to 65 degree and iron-staini	ng on fracture surfaces								
226.0	18.5	1:42 1:35		(100%)	(76%)											
226.0	18.5	1:25					Gray-white, very slightly weathered to fresh	slightly fractured to sound, coa	arse-grained granite with							
		1:32 1:33	5.0	5.0	5.0	RS-6 21.9'-22.5'	45 to 60 degree fractures	,	gramou gramo wan							
		1:36		(100%)	(100%)											
221.0 221.0	23.5 23.5	1:31 1:04					Gray-white, very slightly weathered to fresh, sound, coarse-grained granite									
	•	1:05	50	5.0	5.0		tame, tery enginery weathered to fresh,	sound, coarse-grained granite								
		1:07 1:10	5.0	(100%)	(100%)											
216.0	28.5	1:11														
	İ															
	ŀ															
	ŀ															
					l											
	ŀ															
	F															
\dashv																
			ĺ													
									*							
							PODELIOI E TONIO									
						.	BOREHOLE TERMINATED AT ELEVAT	TON OF 216.0 FEET, IN GRAP	NITE.							

north carolina department of transportation | North Carolina department of transportation GEOTECHNICAL UNIT BORING LOG

GEOTECHNICAL UNIT BORING LOG

SHEET 9 OF 12 O.B. OTI PROJECT NO. 8.2312401 **ID.** B-3672 COUNTY JOHNSTON GEOLOGIST **ID.** B-3672 PROJECT NO. 8.2312401 COUNTY JOHNSTON GEOLOGIST O.B. OTI SITE DESCRIPTION BRIDGE NO.415 ON SR 1718 OVER BUFFALO CREEK SITE DESCRIPTION BRIDGE NO.415 ON SR 1718 OVER BUFFALO CREEK GROUND WATER GROUND WATER BORING NO. EB2-B BORING LOCATION 18+55.0 OFFSET 15.0' LT ALIGNMENT -L-OHR. DRY BORING NO. EB2-A BORING LOCATION 18+61.0 OFFSET 15.0' RT ALIGNMENT -L-OHR. DRY COLLAR ELEVATION 255.1' **NORTHING** 782720.9 EASTING 1629943.3 24 HR. DRY COLLAR ELEVATION 254.7' **NORTHING** 782690.3 EASTING 1629941.5 24 HR. DRY DRILL MACHINE BK-51 DRILL METHOD H.S. AUGERS HAMMER TYPE AUTOMATIC TOTAL DEPTH 12.4' DRILL MACHINE BK-51 DRILL METHOD H.S. AUGERS TOTAL DEPTH 11.3' HAMMER TYPE AUTOMATIC COMPLETION DATE 7/22/02 SURFACE WATER DEPTH N/A DEPTH TO ROCK 10.5' **START DATE** 7/22/02 **START DATE** 7/22/02 COMPLETION DATE 7/22/02 SURFACE WATER DEPTH N/A DEPTH TO ROCK 12.4' DEPTH BLOW COUNT PEN. DEPTH BLOW COUNT PEN. BLOWS PER FOOT SAMPLE VO LO NUMBER MOI. G SAMPLE V BLOWS PER FOOT SOIL AND ROCK SOIL AND ROCK ELEV. ELEV. (FT.) 0.510.510.5 (FT.) P 100 NUMBER | MOL DESCRIPTION (FT.) 0.510.510.5(FT.) P DESCRIPTION 255.0 254.7 0.0 SS-I М 2 3 | + 0.0 2 4 5 1.0 ROADWAY EMBANKMENT 3.3 2 2 1.0 3.3 | 2 | 3 | 5 l 1.0 ROADWAY EMBANKMENT 250.0 TAN-BROWN. CLAYEY SAND 250.0 TAN-BROWN, CLAYEY SAND 2 2 1.0 М 8.3 | 9 | 10 | 47 | 1.0 RESIDUAL SS-2 RESIDUAL $245.0 \pm 10.5 | 60$ 245.0 -TAN-BROWN, CLAYEY SAND TAN-BROWN, CLAYEY SAND CRYSTALLINE ROCK: (GRANITE) + II.3 -HOLLOW-STEM-AUGER-12.4 WEATHERED ROCK: (GRANITE) HOLLOW_STEM_REFUSAL 240.0 -240.0 + REFUSAL AT ELEVATION AT ELEVATION 242.37 ON 243.8' IN CRYSTALLINE CRYSTALLINE ROCK ROCK GRANITED 235.0 235.0 -CGRANITES 230.0 230.0 225.0 225.0 220.0 220.0 -215.0 215.0 210.0 210.0 205.0 205.0 200.0 200.0 195.0 195.0 190.0 190.0 185.0 185.0 180.0 180.0

PROJ. # - 8.2312401 ID NO. - B-3672 COUNTY - JOHNSTON

EB1-A

			SOIL	TEST	ΓR	ES	<i>UL</i>	TS					
SAMPLE			DEPTH	AASHTO				% BY W	/EIGHT		% PAS	SING (S	IEVES)
NO.	OFFSET	STATION	INTERVAL	CLASS.	L.L.	P.I.	C.SAND	F.SAND	SILT	CLAY	10	40	200
SS-10	11.0' LT	17+40.0	14.8-16.3	A-4(0)	23	3	19.5	47.4	19.0	14.1	100	92	41
SS-11	11.0' LT	17+40.0	19.8-21.3	A-1-b(0)	22	NP	82.3	9.6	3.0	5.0	78	24	7

EB1-B

			SOIL	TES T	^{r}R	ES		TS					
SAMPLE			DEPTH	AASHTO				% BY V	/EIGHT		% PAS	SING (S	SIEVES)
NO.	OFFSET	STATION	INTERVAL	CLASS.	L.L.	P.I.	C.SAND	F.SAND	SILT	CLAY	10	40	200
SS-3	11.5' RT	17+36.0	3.5-5.0	A-7-6(9)	49	27	36.9	16.0	14.7	32.3	98	71	49
SS-4	11.5' RT	17+36.0	8.5-10.0	A-6(1)	30	13	41.3	21.1	16.4	21.2	98	73	39
SS-5	11.5' RT	17+36.0	13.5-15.0	A-1-b(0)	21	NP	88.0	8.4	2.6	1.0	96	25	4

B1-A

			SOIL	TES I	ΓR	ES	UL	TS					
SAMPLE			DEPTH	AASHTO				% BY W	/EIGHT		% PAS	SING (S	IEVES)
NO.	OFFSET	STATION	INTERVAL	CLASS.	L.L.	P.I.	C.SAND	F.SAND	SILT	CLAY	10	40	200
SS-8	6.0' LT	17+75.0	4.0-5.5	A-2-4(0)	20	NP	49.4	34.3	7.2	9.1	100	77	19
SS-9	6.0' LT	17+75.0	9.5-10.5	A-2-4(0)	21	NP	58.5	29.2	9.3	3.0	86	51	14

B2-B

			SOIL	TEST.	ΓR	ES	<i>UL</i>	TS					
SAMPLE			DEPTH	AASHTO				% BY W	/EIGHT		% PAS	SING (S	SIEVES)
NO.	OFFSET	STATION	INTERVAL	CLASS.	L.L.	P.I.	C.SAND	F.SAND	SILT	CLAY	10	40	200
SS-6	6.0' RT	18+22.0	1.0-1.5	A-2-4(0)	27	9	45.6	24.6	12.6	17.2	94	65	31
SS-7	6.0' RT	18+22.0	4.2-5.7	A-6(10)	36	16	2.0	36.1	29.6	32.3	100	99	70

EB2-A

			SOIL	TES T	ΓR	ES	<i>UL</i>	TS					
SAMPLE			DEPTH	AASHTO				% BY W	/EIGHT		% PAS	SING (S	SIEVES)
NO.	OFFSET	STATION	INTERVAL	CLASS.	L.L.	P.I.	C.SAND	F.SAND	SILT	CLAY	10	40	200
SS-1	15.0' LT	18+60.7	1.0-1.5	A-2-6(0)	29	11	48.1	23.2	9.5	19.2	92	61	29
SS-2	15.0' LT	18+60.7	8.3-9.8	A-2-6(0)	31	12	42.5	21.9	15.4	20.2	90	63	35

SHEET 10 OF 12

GEOTECHNICAL UNIT FIELD SCOUR REPORT


PROJECT: 8.2312401 ID: B-3672 COUNTY: Johnston
DESCRIPTION(1): Bridge No. 415 on SR 1718 over Buffalo Creek
INFORMATION ON EXISTING BRIDGE Information obtained from: □ microfilm (Reel:Pos:) □ other: Hydro Report
BR. NO.: 415 BR. LENGTH: 102' NO. BENTS: 7 NO. BENTS IN: CHANNEL: 3 FLOODPLAIN: 4
FOUNDATION TYPE:Timber piles
EVIDENCE OF SCOUR(2):
ABUTMENTS OR END BENT SLOPES: Abutment slope between Bent 5 and End Bent 2 is severely
scoured and eroded.
INTERIOR BENTS: Bent 1 and 5 have washed out areas around piles
CHANNEL BED: Unable to ascertain due to water depth.
CHANNEL BANKS: No evidence of scour along channel banks.
EXISTING SCOUR PROTECTION:
TYPE(3): Rip-rap has been placed on upstream side of embankments.
EXTENT(4): Estimate 3 to 5 feet of rip-rap placed at End Bent 2, minor amount at End Bent 1.
EFFECTIVENESS(5):Appears effective at protecting upstream side of embankment.
OBSTRUCTIONS(6) (DAMS,DEBRIS,ETC.): No obstructions observed.
DESIGN INFORMATION
CHANNEL BED MATERIAL(7) (SAMPLE RESULTS ATTACHED):
Alluvial: Loose, tan-gray, silty sand (A-2-4) (sample SS-6)
CHANNEL BANK MATERIAL(8) (SAMPLE RESULTS ATTACHED):
Alluvial: Loose, tan-gray, silty sand (A-2-4) (sample SS-6)
FOUNDATION BEARING MATERIAL(9): Weathered rock and crystalline rock (granite)
CHANNEL BANK COVER(10): Shrubs and grass.
FLOOD PLAIN WIDTH(11): +/- 200 feet
FLOOD PLAIN COVER(12): Trees, shrubs, and grass

SHEET 11 OF 12

					SHEET IT OF 12
DES	IGN INFORMATION	ON CONT.			
STR	EAMIS: x D	DEGRADING	AGGRADING (13)		
ОТН	ER OBSERVATION	IS AND COMM	MENTS:		
	Abutment slope at	t End Bent 2 is	s also being eroded by runoff fi	from roadway	
			area world orouged by runon in	Tom roudway.	
CHA	NNEL MIGRATION	TENDENCY (14):Toward southeast (Er	nd Bent 2)	
GEO	TECHNICALLY AD.	JUSTED SCO	UR ELEVATIONS(15):		
	Interior bents:	□[#:	·· (f4)		
	_	Elevation	n (feet)		
	Bent	1 236.1			
	Bent	2 236.3			
			cour Elevation (GASE) is uncha d by 5 feet at Bent 2 due to the		
	REPORTED	BY:	T. P. Moorefield	DATE:	7/24/02
		(Field obser	rvations by Onuoha B.Oti and	T. P. Moorefield)	
(1) (2) (3) (4) (5) (6) (7) (8) (9) (10) (11) (12) (13) (14) (15)	NOTE ANY EVIDENCE SLOUGHING, SCOUR NOTE ANY EXISTING DESCRIBE THE EXTE DESCRIBE WHETHER NOTE ANY DAMS, FA DESCRIBE THE CHANDISTRIBUTION, ATTADESCRIBE THE FOUNDESCRIBE THE BANK GIVE THE APPROXIM DESCRIBE THE FLOCCHECK THE APPROXIM GIVE THE GEOTECHI (APPROXIMATELY 10 A BENT BY BENT BAHYDRAULICS THEORGEOTECHNICALLY A EXPLAIN. (RIPRAP A	E OF SCOUR AT R LOCATIONS, DI SCOUR PROTEI ENT OF ANY EXIS R OR NOT THE S LLEN TREES, DI NNEL BED MATE NNEL BANK MAT ACH LAB RESUL NDATION BEARII K COVERING (GF IATE FLOOD PLA DD PLAIN COVER PRIATE SPACE A ENTIAL OF THE E IATELY 100 YEAR NICALLY ADJUS SIS WHERE VAR RETICAL SCOUR ADJUSTED SCOU ARMORING ON S	NG MATERIAL, RASS, TREES, RIP RAP, NONE, ET AIN WIDTH (ESTIMATE). RING (GRASS, TREES, CROPS, ET AS TO WHETHER THE STREAM IS BODY OF WATER TO MIGRATE LA	BUTMENTS (UNDERMIN O BE WORKING. KEN FOR GRAIN SIZE D AKEN FOR GRAIN SIZE TC. TC.) DEGRADING OR AGGRA ATERALLY DURING THE TED OVER THE LIFE OF TON RANGE ACROSS THE RELATIONSHIP BETWEEL JUSTED SCOUR ELEVAT N SCOUR COUNTER ME. CALLY ADJUSTED SCOU	ING, ISTRIBUTION, ADING LIFE OF THE THE BRIDGE E SITE, OR ON N THE TION. IF THE ASURES, R ELEVATION

CORE PHOTOGRAPHS

B1-ABOXES 1 & 2: 15.0 - 34.0 FEET



SHEET 12 OF 12 8.2312401 (B-3672) Bridge No. 415

CORE PHOTOGRAPHS

B2-BBOXES 1 & 2: 9.0 - 28.5 FEET



FEET