

PROJECT: U-3456


STATE	PROJECT NO.	SHEET NO.
N.C.	U-3456	Sig. 1
F.A. PROJ. NO.		
PROJECT ID. NO.		

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS


RICHMOND COUNTY

LOCATION: US 1 FROM SR 1424 (ROBERDEL ROAD) TO SR 1640 (WIREGRASS ROAD)/ SR 1442 (LEDBETTER ROAD) IN ROCKINGHAM

TYPE OF WORK: TRAFFIC SIGNALS



VICINITY MAP



INDEX OF PLANS

SHEET NO.	SIGNAL INVENTORY NO.	LOCATION /DESCRIPTION
SIG. 1	N/A	Title Sheet
SIG. 2-3	08-0849 T1	US 1 at SR 1442 (Ledbetter Rd)/SR 1640 (Wiregrass Rd)
SIG. 4-5	08-0849 T2	US 1 at SR 1442 (Ledbetter Rd)/SR 1640 (Wiregrass Rd)
SIG. 6-7	08-0849 T3	US 1 at SR 1442 (Ledbetter Rd)/SR 1640 (Wiregrass Rd)
SIG. 8-9	08-0849 Final	US 1 at SR 1442 (Ledbetter Rd)/SR 1640 (Wiregrass Rd)
SIG. 10-15		Standard Drawings For Metal Poles


LEGEND

##-#### SIGNAL INVENTORY NUMBER


NCDOT CONTACTS:

TRAFFIC ENGINEERING AND SAFETY SYSTEMS BRANCH
 Timothy J. Williams, PE - S&G Contracts & PEF Support Engineer
 George C. Brown, PE - Signal Equipment Design Engineer

Prepared in the Offices of:



PHASING DIAGRAM



PHASING DIAGRAM DETECTION LEGEND

- ← DETECTED MOVEMENT
- ← UNDETECTED MOVEMENT (OVERLAP)
- UNSIGNALIZED MOVEMENT
- ⇆ PEDESTRIAN MOVEMENT

TABLE OF OPERATION

SIGNAL FACE	PHASE		
	Ø 2+6	Ø 4+8	FLASH
21,22	G	R	Y
41,42	R	G	R
61,62	G	R	Y
81,82	R	G	R

SIGNAL FACE I.D.

- ⊙ Denotes L.E.D.
- Ⓡ 12"
- Ⓢ 12"
- Ⓣ 12"
- 21,22
- 41,42
- 61,62
- 81,82


2070L LOOP & DETECTOR INSTALLATION

LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	DETECTOR PROGRAMMING						
					PHASE	CALLING	EXTENSION	STRETCH	DELAY TIME	SYSTEM LOOP	NEW CARD
2A	6X6	420	6	Y	2	Y	Y	-	-	-	Y
2B	6X40	0	2-4-2	Y	2	Y	Y	-	3	-	Y
4A	6X40	0	2-4-2	Y	4	Y	Y	-	3	-	Y
4B	6X40	0	2-4-2	Y	4	Y	Y	-	15	-	Y
6A	6X6	420	6	Y	6	Y	Y	-	-	-	Y
6B	6X40	0	2-4-2	Y	6	Y	Y	-	3	-	Y
8A	6X40	0	2-4-2	Y	8	Y	Y	-	3	-	Y
8B	6X40	0	2-4-2	Y	8	Y	Y	-	15	-	Y

2-Phase Fully Actuated (Isolated)

NOTES

1. Refer to "Roadway Standard Drawings NCDOT" dated July 2006 and "Standard Specifications for Roads and Structures" dated July 2006.
2. Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
3. Set all detector units to presence mode.
4. Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.



2070L TIMING CHART

FEATURE	PHASE			
	2	4	6	8
Min Green 1*	14	7	14	7
Extension 1*	6.0	2.0	6.0	2.0
Max Green 1*	90	25	90	25
Yellow Clearance	5.3	4.7	5.3	4.5
Red Clearance	1.0	1.0	1.1	1.0
Walk 1*	-	-	-	-
Don't Walk 1	-	-	-	-
Seconds Per Actuation*	2.5	-	2.5	-
Max Variable Initial*	46	-	46	-
Time Before Reduction*	15	-	15	-
Time To Reduce*	45	-	45	-
Minimum Gap	3.0	-	3.0	-
Recall Mode	MIN RECALL	-	MIN RECALL	-
Vehicle Call Memory	YELLOW	-	YELLOW	-
Dual Entry	-	ON	-	ON
Simultaneous Gap	ON	ON	ON	ON

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

LEGEND

PROPOSED		EXISTING
○	Traffic Signal Head	●
○	Modified Signal Head	N/A
○	Sign	○
□	Pedestrian Signal Head With Push Button & Sign	□
○	Signal Pole with Guy	○
○	Signal Pole with Sidewalk Guy	○
⊗	Inductive Loop Detector	⊗
⊗	Controller & Cabinet	⊗
□	Junction Box	□
—	2-in Underground Conduit	—
- - -	Right of Way	- - -
→	Directional Arrow	→
→	Pavement Marking Arrow	→
■	Construction Zone	■
Ⓢ	"YIELD" Sign (R1-2)	Ⓢ

17-JUL-2007 15:36 I:\signal\smw\pgr\pgrus4\1p\project\sheet-3456sig\sig.dgn

Signal Upgrade - Temporary Signal 1- TCP Phase I

122 N. McDowell St., Raleigh, NC 27603

US 1
at
SR 1442 (Ledbetter Road) /
SR 1640 (Wiregrass Road)

Division 8
Richmond County NE of Rockingham

PLAN DATE: May 2007
REVIEWED BY: I.O. Umozurike


PREPARED BY: LHR
REVIEWED BY:

SEAL
NORTH CAROLINA
PROFESSIONAL ENGINEER
TIMOTHY J. WILLIAMS
24393

DATE: 6/28/07

SIG. INVENTORY NO. 08-0849 T1

PHASING DIAGRAM




PHASING DIAGRAM DETECTION LEGEND

- DETECTED MOVEMENT
- UNDETECTED MOVEMENT (OVERLAP)
- UNSIGNALIZED MOVEMENT
- ← PEDESTRIAN MOVEMENT

TABLE OF OPERATION

SIGNAL FACE	PHASE		
	Ø2+6	Ø4+8	F LIGHT
21,22	G	R	Y
41,42	R	G	R
61,62	G	R	Y
81,82	R	G	R

SIGNAL FACE I.D.




2070L LOOP & DETECTOR INSTALLATION

LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	DETECTOR PROGRAMMING					SYSTEM LOOP	NEW CARD
					PHASE	CALLING	EXTENSION	FULL TIME DELAY	STRETCH TIME		
2A	6X6	420	6	Y	2	Y	Y	-	-	-	-
2B	6X40	0	2-4-2	Y	2	Y	Y	Y	-	3	-
4A	6X40	0	2-4-2	Y	4	Y	Y	-	-	3	-
4B	6X40	0	2-4-2	Y	4	Y	Y	-	-	15	-
6B	6X6	420	5	Y	6	Y	Y	-	-	-	-
6C	6X40	0	2-4-2	Y	6	Y	Y	Y	-	3	-
8A	6X40	0	2-4-2	Y	8	Y	Y	-	-	3	-
8B	6X40	0	2-4-2	Y	8	Y	Y	-	-	15	-

2-Phase Fully Actuated (Isolated)

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated July 2006 and "Standard Specifications for Roads and Structures" dated July 2006.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Set all detector units to presence mode.
- Reposition existing signal heads numbered 21, 22, 41, 42, 61, 62, 81 and 82.



2070L TIMING CHART

FEATURE	PHASE			
	2	4	6	8
Min Green 1 *	14	7	14	7
Extension 1 *	6.0	2.0	6.0	2.0
Max Green 1 *	90	25	90	25
Yellow Clearance	5.3	4.7	5.3	4.5
Red Clearance	1.0	1.3	1.3	1.1
Walk 1 *	-	-	-	-
Don't Walk 1	-	-	-	-
Seconds Per Actuation *	2.5	-	2.5	-
Max Variable Initial *	46	-	46	-
Time Before Reduction *	15	-	15	-
Time To Reduce *	45	-	45	-
Minimum Gap	3.0	-	3.0	-
Recall Mode	MIN RECALL	-	MIN RECALL	-
Vehicle Call Memory	YELLOW	-	YELLOW	-
Dual Entry	-	ON	-	ON
Simultaneous Gap	ON	ON	ON	ON

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

LEGEND

PROPOSED	EXISTING
	N/A

Signal Upgrade - Temporary Signal 2- TCP Phase III

Prepared in the Offices of:

 NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 SIGNAL AND GEOMETRICS SECTION

US 1
 at
 SR 1442 (Ledbetter Road) /
 SR 1640 (Wiregrass Road)

Division 8 Richmond County NE of Rockingham
 PLAN DATE: May 2007 REVIEWED BY: I.O. Umozurike
 PREPARED BY: Luhr REVIEWED BY:

122 N. McDowell St., Raleigh, NC 27603

SCALE: 0 40
 1"=40'


REVISIONS: _____ INIT. DATE
 _____ INIT. DATE

J. Williams 6/28/07
 DATE: 6/28/07
 SIG. INVENTORY NO. 08-0849 T2

17-JUL-2007 15:37 s:\s\ts\signal\work\project\3456\sig\0849_t2.dgn

EDI MODEL 2010ECL-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)



- NOTES:
- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
 - Make sure jumpers SEL2-SEL5 are present on the monitor board.

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Ensure that Red Enable is active at all times during normal operation. To prevent Red Failures on unused monitor channels, tie unused red monitor inputs 1,3,5,7,9,10,11,12,13,14,15 & 16 to load switch AC+ per the cabinet manufacturer's instructions.
- Program phases 2 and 6, on the controller unit, for Start Up In Green.
- Enable Simultaneous Gap-Out, on the controller unit, for all phases.
- Program phases 4 and 8, on the controller unit, for Dual Entry.
- Program phases 2 and 6, on the controller unit, for Variable Initial and Gap Reduction.

EQUIPMENT INFORMATION

CONTROLLER.....CONTRACTOR SUPPLIED 2070L
 CABINET.....CONTRACTOR SUPPLIED 332
 SOFTWARE.....ECONOLITE OASIS
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S4,S6,S8
 PHASES USED.....2,4,6,8
 OVERLAPS.....NONE

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S2P	S3	S4	S4P	S5	S6	S6P	S7	S8	S8P
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82	NU
RED		128			101			134			107	
YELLOW		129			102			135			108	
GREEN		130			103			136			109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												
Hand icon												
Person icon												

NU = Not Used

INPUT FILE POSITION LAYOUT


(front view)

FILE	1	2	3	4	5	6	7	8	9	10	11	12	13	14
U	∅ 2	∅ 2	∅ 6	∅ 6	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8
L	2A	2B	6C	6B	8A	8B								
U	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6	∅ 6
L	6B	6B	6B	6B	6B	6B	6B	6B	6B	6B	6B	6B	6B	6B

EX.: 1A, 2A, ETC. = LOOP NO.'S
 FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	INPUT ASSIGNMENT NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND	FULL TIME DELAY	STRETCH TIME	DELAY TIME
2A	TB2-5,6	I2U	39	1	2	2	Y	Y			
2B	TB2-7,8	I2L	43	5	12	2	Y	Y	Y		3
4A	TB4-9,10	I6U	41	3	4	4	Y	Y			3
4B	TB4-11,12	I6L	45	7	14	4	Y	Y			15
6B	TB3-7,8	J2L	44	6	16	6	Y	Y			
6C	TB3-9,10	J3U	64	26	36	6	Y	Y	Y		3
8A	TB5-9,10	J6U	42	4	8	8	Y	Y			3
8B	TB5-11,12	J6L	46	8	18	8	Y	Y			15



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 08-0849T2
 DESIGNED: May 2007
 SEALED: 6-28-07
 REVISED: N/A

Signal Upgrade - Temporary Signal 2

ELECTRICAL AND PROGRAMMING DETAILS FOR:

US 1 at SR 1442 (Ledbetter Road)/ SR 1640 (Wiregrass Road)

Division 8 Richmond County NE of Rockingham

PLAN DATE: 6-26-07 REVIEWED BY: D.T. Joyce

PREPARED BY: D.H. Spaulding REVIEWED BY:

REVISIONS: INIT. DATE

Signature: George C. Brown 6/28/07


Seal: NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 022013 GEORGE C. BROWN

122 N. McDowell St., Raleigh, NC 27603

Sig. Inventory No. 08-0849T2

28-JUN-2007 13:43 s:\ts\sig\work\krc\spaulding\m\spaulding\m\progress\080849T2.sm.e (e_2007).x.dgn

PHASING DIAGRAM



PHASING DIAGRAM DETECTION LEGEND


- ← ● ← DETECTED MOVEMENT
- ← — — ← UNDETECTED MOVEMENT (OVERLAP)
- ← - - - ← UNSIGNALIZED MOVEMENT
- ← - - - ← PEDESTRIAN MOVEMENT

TABLE OF OPERATION

SIGNAL FACE	PHASE		
	02+6	04+8	FLASH
21,22	G	R	Y
41,42	R	G	R
61,62	G	R	Y
81,82	R	G	R

SIGNAL FACE I.D.

⊙ Denotes L.E.D.



21,22
41,42
61,62
81,82


2070L LOOP & DETECTOR INSTALLATION

INDUCTIVE LOOPS				DETECTOR PROGRAMMING								
LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTENSION	FULL TIME DELAY	STRETCH TIME	DELAY TIME	SYSTEM LOOP	NEW CARD
2B	6X6	420	6	Y	2	Y	Y	-	-	-	-	Y
2C	6X40	0	2-4-2	Y	2	Y	Y	Y	-	3	-	Y
4A	6X40	0	2-4-2	Y	4	Y	Y	-	-	3	-	Y
4B	6X40	0	2-4-2	-	4	Y	Y	-	-	-	-	-
4C	6X40	0	2-4-2	-	4	Y	Y	-	-	15	-	-
6B	6X6	420	5	-	6	Y	Y	-	-	-	-	Y
6C	6X40	0	2-4-2	-	6	Y	Y	Y	-	3	-	-
8A	6X40	0	2-4-2	Y	8	Y	Y	-	-	3	-	-
8B	6X40	0	2-4-2	Y	8	Y	Y	-	-	-	-	-
8C	6X40	0	2-4-2	Y	8	Y	Y	-	-	15	-	-

2-Phase Fully Actuated (Isolated)

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated July 2006 and "Standard Specifications for Roads and Structures" dated July 2006.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Reposition existing signal heads numbered 21,22, 41,41, 81 and 82.
- Set all detector units to presence mode.



2070L TIMING CHART

FEATURE	PHASE			
	2	4	6	8
Min Green 1 *	14	7	14	7
Extension 1 *	6.0	2.0	6.0	2.0
Max Green 1 *	90	25	90	25
Yellow Clearance	5.3	4.7	5.3	4.5
Red Clearance	1.4	1.6	1.3	1.6
Walk 1 *	-	-	-	-
Don't Walk 1	-	-	-	-
Seconds Per Actuation *	2.5	-	2.5	-
Max Variable Initial *	46	-	46	-
Time Before Reduction *	15	-	15	-
Time To Reduce *	45	-	45	-
Minimum Gap	3.0	-	3.0	-
Recall Mode	MIN RECALL	-	MIN RECALL	-
Vehicle Call Memory	YELLOW	-	YELLOW	-
Dual Entry	-	ON	-	ON
Simultaneous Gap	ON	ON	ON	ON

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

LEGEND



	PROPOSED Traffic Signal Head		EXISTING Traffic Signal Head
	PROPOSED Modified Signal Head	N/A	EXISTING N/A
	PROPOSED Pedestrian Signal Head With Push Button & Sign		EXISTING Pedestrian Signal Head With Push Button & Sign
	PROPOSED Signal Pole with Guy		EXISTING Signal Pole with Guy
	PROPOSED Signal Pole with Sidewalk Guy		EXISTING Signal Pole with Sidewalk Guy
	PROPOSED Inductive Loop Detector		EXISTING Inductive Loop Detector
	PROPOSED Controller & Cabinet		EXISTING Controller & Cabinet
	PROPOSED Junction Box		EXISTING Junction Box
	PROPOSED 2-in Underground Conduit		EXISTING 2-in Underground Conduit
	PROPOSED Right of Way		EXISTING Right of Way
	PROPOSED Directional Arrow		EXISTING Directional Arrow
	PROPOSED Pavement Marking Arrow		EXISTING Pavement Marking Arrow
	PROPOSED Construction Zone		EXISTING Construction Zone

Signal Upgrade - Temporary signal 3- TCP Phase IV

	Prepared in the Offices of US 1 at SR 1442 (Ledbetter Road) / SR 1640 (Wiregrass Road) Division 8 Richmond County NE of Rockingham		SEAL
	PLAN DATE: May 2007 PREPARED BY: Luhr	REVIEWED BY: I.O. Umozurike REVIEWED BY:	
222 N. McDowell St., Raleigh, NC 27603	SCALE: 1" = 40' 	REVISIONS:	INIT. DATE:
SIG. INVENTORY NO. 08-0849 T3			

**EDI MODEL 2010ECL-NC CONFLICT MONITOR
PROGRAMMING DETAIL**


(remove jumpers and set switches as shown)



REMOVE JUMPERS AS SHOWN

NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Make sure jumpers SEL2-SEL5 are present on the monitor board.



■ = DENOTES POSITION OF SWITCH

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Ensure that Red Enable is active at all times during normal operation. To prevent Red Failures on unused monitor channels, tie unused red monitor inputs 1,3,5,7,9,10,11,12,13,14,15 & 16 to load switch AC+ per the cabinet manufacturer's instructions.
- Program phases 2 and 6, on the controller unit, for Start Up In Green.
- Enable Simultaneous Gap-Out, on the controller unit, for all phases.
- Program phases 4 and 8, on the controller unit, for Dual Entry.
- Program phases 2 and 6, on the controller unit, for Variable Initial and Gap Reduction.

EQUIPMENT INFORMATION

CONTROLLER.....CONTRACTOR SUPPLIED 2070L
 CABINET.....CONTRACTOR SUPPLIED 332
 SOFTWARE.....ECONOLITE OASIS
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S4,S6,S8
 PHASES USED.....2,4,6,8
 OVERLAPS.....NONE

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S2P	S3	S4	S4P	S5	S6	S6P	S7	S8	S8P
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82	NU
RED		128			101			134			107	
YELLOW		129			102			135			108	
GREEN		130			103			136			109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												
Hand icon												
Person icon												

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)

FILE	1	2	3	4	5	6	7	8	9	10	11	12	13	14
U	S	NOT USED	∅ 2	S	S	∅ 4	∅ 4	S	S	S	S	S	S	FS
L	2B	2C	2C	4A	4C	4A	4C	4B	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	DC ISOLATOR
U	S	NOT USED	∅ 6	S	S	∅ 8	∅ 8	S	S	S	S	S	S	ST
L	6B	6C	6C	8A	8C	8A	8C	8B	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	DC ISOLATOR

EX. : 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	INPUT ASSIGNMENT NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND	FULL TIME DELAY	STRETCH TIME	DELAY TIME
2B	TB2-7,8	I2L	43	5	12	2	Y	Y			
2C	TB2-9,10	I3U	63	25	32	2	Y	Y	Y		3
4A	TB4-9,10	I6U	41	3	4	4	Y	Y			3
4B	TB4-11,12	I6L	45	7	14	4	Y	Y			
4C	TB6-1,2	I7U	65	27	34	4	Y	Y			15
6B	TB3-7,8	J2L	44	6	16	6	Y	Y			
6C	TB3-9,10	J3U	64	26	36	6	Y	Y	Y		3
8A	TB5-9,10	J6U	42	4	8	8	Y	Y			3
8B	TB5-11,12	J6L	46	8	18	8	Y	Y			
8C	TB7-1,2	J7U	66	28	38	8	Y	Y			15


INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 08-0849T3
 DESIGNED: May 2007
 SEALED: 6-28-07
 REVISED: N/A

Signal Upgrade - Temporary Signal 3

ELECTRICAL AND PROGRAMMING DETAILS FOR:




122 N. McDowell St., Raleigh, NC 27603

US 1 at SR 1442 (Ledbetter Road)/ SR 1640 (Wiregrass Road)	
Division 8	Richmond County NE of Rockingham
PLAN DATE: 6-26-07	REVIEWED BY: D.T. Joyce
PREPARED BY: D.H. Spaulding	REVIEWED BY:
REVISIONS	INIT. DATE

SEAL
NORTH CAROLINA PROFESSIONAL ENGINEER
SEAL 022013
ENGINEER
GEORGE C. BROWN
Signature: George C. Brown
DATE: 6/28/07
SIG. INVENTORY NO. 08-0849T3

PHASING DIAGRAM



PHASING DIAGRAM DETECTION LEGEND


- DETECTED MOVEMENT
- UNDETECTED MOVEMENT (OVERLAP)
- - - UNSIGNALIZED MOVEMENT
- >— PEDESTRIAN MOVEMENT

TABLE OF OPERATION

SIGNAL FACE	PHASE		
	Ø 2+6	Ø 4+8	F L R
21,22,23	G	R	Y
41,42	R	G	R
61,62,63	G	R	Y
81,82	R	G	R

SIGNAL FACE I.D.

Denotes L.E.D.



- 21,22,23
- 41,42
- 61,62,63
- 81,82


2070L LOOP & DETECTOR INSTALLATION

LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	DETECTOR PROGRAMMING							
					PHASE	CALLING	EXTENSION	FULL TIME DELAY	STRETCH TIME	DELAY TIME	SYSTEM LOOP	NEW CARD
2A	6X6	420	6	Y	2	Y	Y	-	-	-	-	Y
2B	6X6	420	6	-	2	Y	Y	-	-	-	-	-
2C	6X40	0	2-4-2	Y	2	Y	Y	-	-	3	-	Y
4A	6X40	0	2-4-2	-	4	Y	Y	-	-	3	-	-
4B	6X40	0	2-4-2	-	4	Y	Y	-	-	-	-	-
4C	6X40	0	2-4-2	-	4	Y	Y	-	-	15	-	-
6A	6X6	420	5	Y	6	Y	Y	-	-	-	-	Y
6B	6X6	420	5	-	6	Y	Y	-	-	-	-	Y
6C	6X40	0	2-4-2	Y	6	Y	Y	-	-	3	-	Y
8A	6X40	0	2-4-2	-	8	Y	Y	-	-	3	-	-
8B	6X40	0	2-4-2	-	8	Y	Y	-	-	-	-	-
8C	6X40	0	2-4-2	-	8	Y	Y	-	-	15	-	-

2-Phase Fully Actuated (Isolated)

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated July 2006 and "Standard Specifications for Roads and Structures" dated July 2006.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Set all detector units to presence mode.



2070L TIMING CHART

FEATURE	PHASE			
	2	4	6	8
Min Green 1*	14	7	14	7
Extension 1*	6.0	2.0	6.0	2.0
Max Green 1*	90	25	90	25
Yellow Clearance	5.3	4.7	5.3	4.5
Red Clearance	1.5	1.6	1.4	1.6
Walk 1*	-	-	-	-
Don't Walk 1	-	-	-	-
Seconds Per Actuation*	1.5	-	1.5	-
Max Variable Initial*	46	-	46	-
Time Before Reduction*	15	-	15	-
Time To Reduce*	45	-	45	-
Minimum Gap	3.0	-	3.0	-
Recall Mode	MIN RECALL	-	MIN RECALL	-
Vehicle Call Memory	YELLOW	-	YELLOW	-
Dual Entry	-	ON	-	ON
Simultaneous Gap	ON	ON	ON	ON

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

LEGEND

PROPOSED		EXISTING
○	Traffic Signal Head	N/A
○→	Modified Signal Head Sign	N/A
⊥	Pedestrian Signal Head With Push Button & Sign	⊥
⊥	Signal Pole with Guy	⊥
⊥	Signal Pole with Sidewalk Guy	⊥
⊠	Inductive Loop Detector Controller & Cabinet Junction Box	⊠
- - -	2-in Underground Conduit	- - -
- - -	Right of Way	- - -
→	Directional Arrow	→
→	Pavement Marking Arrow	→
○	Metal Strain Pole	○

Signal Upgrade - Final Design

US 1 at SR 1442 (Ledbetter Road) / SR 1640 (Wiregrass Road)

Division 8 Richmond County NE of Rockingham

PLAN DATE: May 2007 REVIEWED BY: I.O. Umozurike

PREPARED BY: Luhr REVIEWED BY:

SCALE: 1"=40'


DATE: 6/28/07

SIG. INVENTORY NO. 08-0849


17-JUL-2007 15:41
 s:\projects\2007\us1\2070L\2070L.dwg
 I:\user\jg\2070L\2070L.dwg

**EDI MODEL 2010ECL-NC CONFLICT MONITOR
PROGRAMMING DETAIL**

(remove jumpers and set switches as shown)




REMOVE DIODE JUMPERS 2-6 AND 4-8.



REMOVE JUMPERS AS SHOWN

NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Make sure jumpers SEL2-SEL5 are present on the monitor board.



■ = DENOTES POSITION OF SWITCH

NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Ensure that Red Enable is active at all times during normal operation. To prevent Red Failures on unused monitor channels, tie unused red monitor inputs 1,3,5,7,9,10,11,12,13,14,15 & 16 to load switch AC+ per the cabinet manufacturer's instructions.
- Program phases 2 and 6, on the controller unit, for Start Up In Green.
- Enable Simultaneous Gap-Out, on the controller unit, for all phases.
- Program phases 4 and 8, on the controller unit, for Dual Entry.
- Program phases 2 and 6, on the controller unit, for Variable Initial and Gap Reduction.

EQUIPMENT INFORMATION

CONTROLLER.....CONTRACTOR SUPPLIED 2070L
 CABINET.....CONTRACTOR SUPPLIED 332
 SOFTWARE.....ECONOLITE OASIS
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...12
 LOAD SWITCHES USED.....S2,S4,S6,S8
 PHASES USED.....2,4,6,8
 OVERLAPS.....NONE

SIGNAL HEAD HOOK-UP CHART

LOAD SWITCH NO.	S1	S2	S2P	S3	S4	S4P	S5	S6	S6P	S7	S8	S8P
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED
SIGNAL HEAD NO.	NU	21,22 23	NU	NU	41,42	NU	NU	61,62 63	NU	NU	81,82	NU
RED		128			101			134			107	
YELLOW		129			102			135			108	
GREEN		130			103			136			109	
RED ARROW												
YELLOW ARROW												
GREEN ARROW												

NU = Not Used

INPUT FILE POSITION LAYOUT

(front view)

FILE	1	2	3	4	5	6	7	8	9	10	11	12	13	14
U	∅ 2	∅ 2	∅ 2	∅ 2	∅ 4	∅ 4	∅ 4	∅ 4	∅ 4	∅ 4	∅ 4	∅ 4	∅ 4	∅ 4
L	2A	2C	NOT USED	NOT USED	4A	4C	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED
U	∅ 6	∅ 6	∅ 6	∅ 6	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8
L	6A	6C	NOT USED	NOT USED	8A	8C	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED
U	∅ 6	∅ 6	∅ 6	∅ 6	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8	∅ 8
L	6B	NOT USED	NOT USED	NOT USED	8B	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED


EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	INPUT ASSIGNMENT NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND	FULL TIME DELAY	STRETCH TIME	DELAY TIME
2A	TB2-5,6	I2U	39	1	2	2	Y	Y			
2B	TB2-7,8	I2L	43	5	12	2	Y	Y			
2C	TB2-9,10	I3U	63	25	32	2	Y	Y	Y		3
4A	TB4-9,10	I6U	41	3	4	4	Y	Y			3
4B	TB4-11,12	I6L	45	7	14	4	Y	Y			
4C	TB6-1,2	I7U	65	27	34	4	Y	Y			15
6A	TB3-5,6	J2U	40	2	6	6	Y	Y			
6B	TB3-7,8	J2L	44	6	16	6	Y	Y			
6C	TB3-9,10	J3U	64	26	36	6	Y	Y	Y		3
8A	TB5-9,10	J6U	42	4	8	8	Y	Y			3
8B	TB5-11,12	J6L	46	8	18	8	Y	Y			
8C	TB7-1,2	J7U	66	28	38	8	Y	Y			15

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 08-0849
 DESIGNED: May 2007
 SEALED: 6-28-07
 REVISED: N/A

Signal Upgrade - Final Design

ELECTRICAL AND PROGRAMMING DETAILS FOR:

US 1
 at
 SR 1442 (Ledbetter Road) /
 SR 1640 (Wiregrass Road)

Division 8 Richmond County NE of Rockingham

PLAN DATE: 6-22-07 REVIEWED BY: D.T. Joyce

PREPARED BY: D.H. Spaulding REVIEWED BY:

REVISIONS INIT. DATE


Signature: George C. Brown 6/28/07
 SEAL: NORTH CAROLINA PROFESSIONAL ENGINEER 022013
 SIG. INVENTORY NO. 08-0849

28-JUN-2007 13:48
 s:\118\sig\workgroups\sig\manispaul\ding\in-progress\0849_sm.eia.2007xx.dgn
 dsouidling

STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

STATE	PROJECT NO.	SHEET NO.
N.C.	U-3456	Sig. 10
F. A. PROJ. NO.	M 1	
PROJECT ID. NO.		

STANDARD DRAWINGS FOR METAL POLES




WIND ZONE LEGEND

WIND ZONE 1 (140 mph) Special Wind Zone	
WIND ZONE 2 (130 mph) Coastal Region	
WIND ZONE 3 (110 mph) Eastern Region	
WIND ZONE 4 (90 mph) Central & Mtn. Region	
WIND ZONE 5 (120 mph) Special Wind Zone	

<http://www.ncdot.org/doh/preconstruct/traffic/tmssu/ws/default.htm>

Prepared in the Offices of:



122 N. McDowell St., Raleigh, NC 27603

Designed in conformance with the 2002 Interim to the 4th Edition 2001

AASHTO

Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals

INDEX OF PLANS

DRAWING NUMBER	DESCRIPTION
M 1	Title Sheet
M 2	Fabrication Details - All Poles
M 3	Fabrication Details - Strain Poles
M 4,5	Fabrication Details - Mast Arm Poles
M 6	Construction Details - Strain Poles
M 7	Construction Details - Foundations
M 8	Standard Strain Poles

NCDOT CONTACTS:


TRAFFIC ENGINEERING AND SAFETY SYSTEMS BRANCH

- G. A. Fuller, P.E. - State ITS and Signals Engineer
- R. E. Mullinax, P.E. - Signals and Geometrics Engineer
- P. L. Alexander, P.E. - Signals and Geometrics Special Projects Engineer
- D. C. Sarkar, P.E. - Signals and Geometrics Structural Engineer
- A. M. Esposito, P.E. - Signals and Geometrics Project Engineer
- C. F. Andrews, Jr. - Signals and Geometrics Project Engineer

SEAL




D. Sarkar 9.2.2005
SIGNATURE DATE



Note: Unless otherwise specified, locate Terminal Compartment 1 foot above the pole base plate at 180 degrees on the pole's radial index.

Terminal Compartment Detail



Construct Templates and Plates from 1/4" min. thick Steel. Galvanizing is not required.
Base Plate Template and Anchor Bolt Lock Plate Details

MFG _____	MFG. DATE: MM/YY _____
SHAFT D/T/L/Y _____	
ARM-A D/T/L/Y _____	
ARM-B D/T/L/Y _____	
A.B. DIA./B.C./L/Y _____	
NCDOT STANDARD _____	


Shaft I.D. Tag
(Provide on Strain Poles and Mast Arm Poles)

- Notes:
- 1) D= Diameter, T= Thickness, L= Length, Y= Yield Strength
 - 2) A.B. = Anchor Bolt
 - 3) B.C. = Bolt Circle of Anchor Bolts
 - 4) If Custom Design, use "NCDOT STANDARD" line for plan pole I.D.
 - 5) See drawing M4 for mounting positions of I.D. tags.


Identification Tag Details

MFG _____	MFG. DATE: MM/YY _____
SECTION D/T/L/Y _____	
NCDOT STANDARD _____	

Arm I.D. Tag
(Provide on each section of a multi-section mast arm)



Anchor Bolt Detail




8 Bolt Base Plate Detail


	Typical Fabrication Details Common To All Metal Poles		
	PLAN DATE: May 2005 PREPARED BY: P.L. Alexander REVISIONS: _____	REVIEWED BY: C.F. Andrews REVIEWED BY: A.M. Esposito INIT. DATE: _____	

Fabrication Details - All Poles

01-SEP-2005 18:22 D:\4004_Metal Pole Standard\dwg2004.mcd 11/10/05 m5.cgn





Cable Entrances at Top of Pole




Section B-B
(See drawing M2)
Pole Base Plate

2 Cable Clamps designed for variable attachment heights from 1'-6" to 10' below the top of the pole.




Section A-A

Radial Orientation for Factory Installed Accessories at Top of Pole




Section C-C

Socket Connection Weld Detail




	<p>Typical Fabrication Details For Strain Poles</p>								
	<p>PLAN DATE: May 2005</p> <p>PREPARED BY: P.L. Alexander</p>	<p>REVIEWED BY: G.F. Andrews</p> <p>REVIEWED BY: A.M. Esposito</p>		<p>SCALE: 0 NA</p> <p>NONE</p>					
<p>222 N. McDowell St., Raleigh, NC 27603</p>		<p>REVISIONS</p> <table border="1"> <tr> <th>NO.</th> <th>DATE</th> <th>DESCRIPTION</th> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table>	NO.	DATE	DESCRIPTION				<p>INIT. DATE</p> <p> </p> <p> </p>
NO.	DATE	DESCRIPTION							
<p>Signature: <i>P.L. Alexander</i> 9.2.2005</p>		<p>DATE: 9.2.2005</p>	<p>SIG. INVENTORY NO.</p>						

01-5P-2005 14:07 C:\Users\palexander\Documents\2004_metro_pole_strainpole.dwg m3.dgn




Note: Strap all signal cables to the side of the pole with 3/4\" stainless steel straps when the distance between the spanwire attachment clamp and the weatherheads exceeds 36\"

Strain Pole Attachments



Attachment of Cable to Intermediate Metal Pole




Metal Pole Grounding Detail

Construction Details - Strain Poles

01-SEP-2005 16:33 w:\p001\ees-011\workgroups\2004\metal pole standard\sig13\004.m6.dgn

	Construction Details Strain Poles		
	PLAN DATE: May 2005 PREPARED BY: C.F. ANDREWS	REVIEWED BY: P.L. ALEXANDER REVIEWED BY: D.C. SARKAR	
SCALE: NA NONE	REVISIONS:	INIT. DATE:	SIG. INVENTORY NO.:


Reinforcing Steel Bars



REINFORCING STEEL TABLE FOR STANDARD DRILL PIER SHAFT (42" & 48" DIAMETER)

Shaft Dia (in.)	Conc. Volume (cu. yds.)	Bar Name	No.	Size	Type	Length
42"	.356 x L	V1	9	#8	STR.	**
		C	*	#4	CIR.	10'-9"
48"	.465 x L	V1	12	#8	STR.	**
		C	*	#4	CIR.	12'-6"

* See Note No. 1
** See Note No. 3



Typical "C" Bars

REINFORCING STEEL TABLE FOR STANDARD 42" and 48" DRILL PIER SHAFT WITH TYPE 1 AND TYPE 2 WING WALLS

Wing Wall Type	Drill Pier Shaft Dia. (in.)	Reinforcing Steel				
		Bar Name	No.	Size	Type	Length
TYPE 1	42"	V1	9	#8	STR.	**
		V2	12	#4	STR.	2'-6"
		H	8	#4	STR.	6'-0"
TYPE 2	42"	C	*	#4	CIR.	10'-9"
		V1	9	#8	STR.	**
		V2	16	#4	STR.	4'-6"
TYPE 2	48"	H	12	#4	STR.	9'-0"
		C	*	#4	CIR.	10'-9"
		V1	12	#8	STR.	**
TYPE 2	48"	V2	16	#4	STR.	4'-6"
		H	12	#4	STR.	9'-6"
		C	*	#4	CIR.	12'-6"

* See Note No. 1
** See Note No. 3


WING WALL DETAILS

Wing Wall Type	Wing Wall Length (Ft.)	Wing Wall Width (Ft.)	Wing Wall Depth (Ft.)	Concrete Volume (Cu. Yds.)
TYPE 1	1'-6"	1'-0"	3'-0"	.4
TYPE 2	3'-0"	1'-0"	5'-0"	1.2


See Note No. 4

Typical Foundation Anchor Bolt Details

(Reinforcing Cage Not Shown for Clarity)



Typical Foundation Conduit Details



2-1" Nonmetallic Conduits for Electrical Service and Grounding Electrode Conductor

Notes

- The number of C-bars is based on foundation depth. For standard foundations, see sheet M 8.
- Circular tie reinforcing rings may be vertically adjusted by +/- 3" at a depth between 2'-0" and 3'-0" to facilitate the installation of electrical conduit entering in the cage.
- The length of V1-bars is based on foundation depth. For standard foundations, see sheet M 8.
- The quantities for steel and concrete shown in the Wing Wall Details Chart reflect the amount of material for 1 pair of wing walls (2 wing walls per drilled pier shaft.)

Construction Details - Foundations

01-SEP-2005 17:48 v:\ee\p\ee-un\11\eev\kgr\cupse\2004_mech1_pole_stand\dsd\2004_m.dgn p:\ee\eev

Prepared in the Office of:

Construction Details Foundations

PLAN DATE: May 2005 REVIEWED BY: P.L. ALEXANDER
 PREPARED BY: G.F. ANDREWS REVIEWED BY: A.M. ESPOSITO

SCALE: NONE

SIGNATURE: *A. Sarker* 9.2.2005
 DATE: 9.2.2005
 SIG. INVENTORY NO.

		STANDARD STRAIN POLES				STANDARD FOUNDATIONS 42" Diameter Drilled Pier Length (L) - Feet						
		Case No.	Pole Height (Ft.)	Base Plate BC (In.)	Moment at the Pole Base (ft-kp)	Clay				Sand		
						Medium N-Value 4-8	Stiff N-Value 9-15	Very Stiff N-Value 16-30	Hard N-Value >30	Loose N-Value 4-10	Medium N-Value 11-30	Dense N-Value >30
WIND ZONE 1	LIGHT	S26L3	26	25	280	20.5	14.0	11.5	9.5	18.0	16.0	14.0
		S30L3	30	25	310	21.0	14.5	11.5	9.5	18.5	16.5	14.5
		S35L3	35	25	350	22.5	15.0	12.0	10.0	19.5	17.5	15.5
	HEAVY	S30H3	30	29	450	25.5	16.5	13.0	11.0	21.0	18.5	16.5
		S35H3	35	29	540	26.0	17.0	13.5	11.5	22.0	19.5	17.0
		S26L2	26	23	250	19.5	13.5	11.0	9.0	18.0	15.5	14.0
WIND ZONE 2	LIGHT	S30L2	30	23	290	20.0	14.0	11.5	9.5	18.5	16.0	14.0
		S35L2	35	23	315	21.0	14.5	11.5	9.5	19.0	16.5	14.5
		S30H2	30	29	415	24.5	16.0	13.0	10.5	21.0	18.5	16.0
	HEAVY	S35H2	35	29	485	25.5	16.5	13.5	11.0	21.5	19.0	16.5
		S26L2	26	23	250	18.5	13.0	10.5	9.0	17.5	15.0	13.5
		S30L2	30	23	290	19.5	13.5	11.0	9.0	18.0	15.5	14.0
WIND ZONE 3	LIGHT	S35L2	35	23	315	20.0	14.0	11.5	9.5	18.5	16.0	14.5
		S30H2	30	29	415	23.0	15.5	12.5	10.0	20.5	17.5	16.0
		S35H2	35	29	485	24.0	16.0	13.0	10.5	21.0	18.0	16.5
	HEAVY	S26L1	26	22	195	18.0	13.0	10.5	9.0	16.5	14.5	13.0
		S30L1	30	22	225	18.5	13.0	10.5	9.0	17.0	15.0	13.5
		S35L1	35	22	255	19.0	13.5	11.0	9.0	17.5	15.5	14.0
WIND ZONE 4	LIGHT	S30H1	30	25	330	22.0	15.0	12.0	9.5	19.5	17.0	15.0
		S35H1	35	25	385	23.0	15.5	12.5	10.0	20.0	17.5	15.5
		S26L2	26	23	250	19.0	13.5	10.5	9.0	17.5	15.5	13.5
	HEAVY	S30L2	30	23	290	20.0	14.0	11.0	9.5	18.0	16.0	14.0
		S35L2	35	23	315	21.0	14.5	11.5	10.0	19.0	16.5	14.5
		S30H2	30	29	415	23.5	15.5	12.5	10.5	21.0	18.0	16.0
WIND ZONE 5	LIGHT	S35H2	35	29	485	25.0	16.5	13.0	11.0	21.5	18.5	16.5
		S26L2	26	23	250	19.0	13.5	10.5	9.0	17.5	15.5	13.5
		S30L2	30	23	290	20.0	14.0	11.0	9.5	18.0	16.0	14.0
	HEAVY	S35L2	35	23	315	21.0	14.5	11.5	10.0	19.0	16.5	14.5
		S30H2	30	29	415	23.5	15.5	12.5	10.5	21.0	18.0	16.0
		S35H2	35	29	485	25.0	16.5	13.0	11.0	21.5	18.5	16.5

Concrete Volume (cubic yards) = .356 X L

Fabrication Design Notes:



1. Values shown in "Moment at the Pole Base" column represents the minimum acceptable capacity allowable for design using a design CSR of 1.
2. Base plate thickness (T) is 2.0 inches.

Foundation Selection:

1. Perform a standard penetration test at each proposed foundation site to determine "N" value.
2. Select the appropriate wind zone from sheet M 1.
3. Select the soil type (Clay or Sand) that best describes the soil characteristics.
4. Get the appropriate pole case load number from the plans or from the Engineer.
5. Select the appropriate column in the chart based on soil type and "N" value. Select the appropriate row based on the pole load case. The foundation depth is the value where the column and the row intersect.

Standard Strain Poles

05-SEP-2005 12:42 c:\p1\hmc\groups\2004\metri pole strndr\std\strn pole.dgn

	Standard Strain Poles and Standard Foundations		
	PLAN DATE: May 2005 PREPARED BY: P.L. Alexander	REVIEWED BY: C.F. Andrews REVIEWED BY: A.W. Esposito	
SCALE: NA None		SIGNATURE: <i>D. Sarkar</i> 9.2.2005 DATE	