

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE GOVERNOR EUGENE A. CONTI, JR. SECRETARY

March 6, 2009

Addendum No. 1

RE:

Contract ID: C201829

WBS # 34948.3.ST1 F.A. # STM-0051(28)

Mecklenburg County (U-3447)

NC 51, Rock Hill-Pineville Road from the SC State line to SR 3645 (Downs Circle)

March 17, 2009 Letting

To Whom It May Concern:

Reference is made to the proposal form recently furnished to you on this project.

The following revisions have been made to the proposal:

On Page No. 28, the project special provision entitled "NOTES TO CONTRACTOR" has been added. Please void Page No. 28 in your proposal and staple the revised Page No. 28 thereto.

Sincerely,

K.A. Garris, RE

Sontract Officer

RAG/jr Attachments

cc:

Mr. J.G. Nance

Mr. Robert Memory

Mr. Ron Hancock, PE Mr. B. S. Moose, PE Mr. R. E. Davenport, Jr., PE

Mr. B. S. Moose, PE Ms. D. M. Barbour, PE Ms. Norma Smith

Mr. Art McMillan, PE

Mr. Ronnie Higgins Mr. Larry Strickland

Mr. J. V. Barbour, PE

Ms. Jaci Kincaid

Mr. Jay A. Bennett, PE

Ms. Lori Strickland

Mr. D. R. Henderson, PE

Ms. Penny Higgins

Ms. Marsha Sample

Project File (2)



noncompensatory and are options that may be needed for protection of rare or unique resources or where special environmental conditions exist at the site which have led to additional requirements being placed in the DWQ's 401 Certifications and approval letters, Isolated Wetland Permits, Riparian Buffer Authorization or a DOT Reclamation Plan's Environmental Assessment for the specific site. Should the Contractor exhaust all Tier I Methods on a site exclusive of rare or unique resources or special environmental conditions, Tier II Methods may be required by regulators on a case by case basis per supplemental agreement.

The Contractor may use cation exchange capacity (CEC) values from proposed site borings to plan and develop the bid for the project. CEC values exceeding 15 milliequivalents per 100 grams of soil may indicate a high potential for turbidity and should be avoided when dewatering into surface water is proposed.

No additional compensation for monitoring borrow pit discharge will be paid.

NOTES TO CONTRACTOR

- 1. 60" Welded Steel Pipe, 60" Welded Steel Pipe in Soil and 60" Welded Steel Pipe Not in Soil shall be 0.875" thick.
- 2. 20" Encasement Pipe shall be 0.250" thick.