CONTENTS

SHEET

I TITLE SHEET

LEGEND
SITE PLAN
PROFILE

5-7 BORE LOGS
SOIL TEST RESULTS
SCOUR REPORT

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

DEAN ARGENBRIGHT GREENVILLE REGIONAL ENGINEERING GEOLOGIST STATE STATE PROJECT REPERENCE NO. SUPER STATE N.C. 33735.1.1 (B-4504) 1 9

STRUCTURE SUBSURFACE INVESTIGATION

PROJ. REFERENCE NO. 33735.1.1 (B-4504)

COUNTY EDGECOMBE

PROJECT DESCRIPTION BRIDGE NO. 52 ON SR 1505

OVER DEEP CREEK AT -L- STATION 20+46.5

-REVISED-

CAUTION NOTICE


THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING, AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES, THE VARIOUS FELD ROPING, LOGS, POCK CORES, AND SOUL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHWICAL ENGINEERING UNIT AT 1999 250-40983. NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOSS, ROCK CORES, OR SOIL TEST DATA ARE PART OF THE CONTRACT.

GENERAL SOL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERRETATION OF ALL AVALABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA TAN WITHIN THE BOREHOLE, THE LABORATORY SAMPLE DATA AND THE IN SITU IN-PLACE! TEST DATA CAN BE RELED ON ONLY TO THE DECREE OF RELIABLITY INHERENT IN THE STANDARD TEST METHOD. THE OSSERVED WATER LEVELS OR SOLL MOSTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOLL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLUMATIC CONDITIONS INCLUDING TEMPERATURES. PRECIPITATION, AND WIND, AS WELL AS OTHER NON-CLUMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MAINY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT, FOR BIDDING AND CONSTRUCTION DURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT, THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR DENION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE EXPOUNTEDED TO THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSART TO SATIST HWESLEF AS TO CONDITIONS TO BE EXPOUNTEDED ON THIS PRODUCT. THE CONTRACTOR SHALL HAVE NO CLAM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

	W.N. CHERRY
	R.E. SMITH
_	
_	
-	
•	
INVESTIGATED B	Y F.M. WESCOTT III
CHECKED BY_	D.N. ARGENBRIGHT
	D.N. ARGENBRIGH
	JUNE, 2008
DATE	JUILE, 2000

PERSONNEL I.R. SWARTLEY



OJECT: 3373.

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS


GEOTECHNICAL ENGINEERING UNIT


SUBSURFACE INVESTIGATION


	SOIL AND RO	CK LEGEND, TERM	S, SYMBOLS, AND ABBREVI	ATIONS	
SOIL DESCRIPTION	GRADATION			DESCRIPTION AND VISION OF THE PROPERTY OF THE	TERMS AND DEFINITIONS
SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS	WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES F UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE	FROM FINE TO COARSE. E SAME SIZE (ALSO	ROCK LINE INDICATES THE LEVEL AT WHICH NON-C	T IF TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL.	ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL	PODRLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR N		SPT REFUSAL IS PENETRATION BY A SPLIT SPOON IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION	SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. ON BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE	ADUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEDUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE:	ANGULARITY OF GRAINS		OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLL		ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS.
CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE	TERMS: ANGULAR,	510772510772	LAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100	OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC.
VERY STAFF, GRAY, SULTY CLAY, WOST WITH WITERBEDDED FINE SAND LAVERS, HIGHLY PLASTIC, A-7-6	SUBANGULAR, SUBROUNDED, OR ROUNDED.		ROCK (WR) BLOWS PER FOO		ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE
SOIL LEGEND AND AASHTO CLASSIFICATION	MINERALOGICAL COMPOSITIO		I UNIDIHLLINE	GRAIN IGNEOUS AND METAMORPHIC ROCK THAT PT REFUSAL IF TESTED, ROCK TYPE INCLUDES GRANITE,	GROUND SURFACE.
GENERAL GRANULAR MATERIALS SILT-CLAY MATERIALS CLASS. (\$35% PASSING *200) CRGANIC MATERIALS (>35% PASSING *200)	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE L WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.	USED IN DESCRIPTIONS	MUCK (CR) GNEISS, GABBRO,	SCHIST, ETC.	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5	COMPRESSIBILITY		NUN-LKYSTALLINE	GRAIN METAMORPHIC AND NON-COASTAL PLAIN OCK THAT WOULD YEILD SPT REFUSAL IF TESTED. ROCK TYPE	COLLUYIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM
CLASS. A-1-a A-1-b A-2-4 A-2-5 A-2-6 A-2-7 A-7-5 A-3 A-6, A-7	SLIGHTLY COMPRESSIBLE LIQUID LIMIT	LESS THAN 31	RUCK INCHI INCLUDES PHYLL	ITE, SLATE, SANDSTONE, ETC. SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD	OF SLOPE.
SYMBOL 000000000000000000000000000000000000		EOUAL TO 31-50 GREATER THAN 50	SEDIMENTARY ROCK SPT REFUSAL. R	OCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
Y PASSAIG	PERCENTAGE OF MATERIA	iL .	(CP) SHELL BEDS, ETC	ATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT
# 10		OTHER MATERIAL			ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE
# 40 30 MX 50 MX 51 MN	TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRA	ACE 1 - 10%	FRESH ROCK FRESH, CRYSTALS BRIGHT. FEW JU HAMMER IF CRYSTALLINE.	DINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER	HORIZONTAL.
LIQUID LIMIT 48 MX 41 MN 48 MX 41 MN 48 MX 41 MN 48 MX 41 MN SOILS WITH	LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LIT MODERATELY ORGANIC 5 - 10% 12 - 20% SON	TTLE 10 - 20% IME 20 - 35%	VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAIN	NED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN.	DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF
PLASTIC INDEX 6 MX NP 10 MX 10 MX 11 MN 11 MN 10 MX 18 MX 11 MN 11 MN LITTLE OR HIGH	PICH A UDCANIC 7/85 7/85 7/85 7/85	GHLY 35% AND ABOVE	(V SLI.) CRYSTALS ON A BROKEN SPECIMEN FAC	CE SHINE BRIGHTLY, ROCK RINGS UNDER HAMMER BLOWS IF	THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
GROUP INDEX 0 0 0 4 MX 8 MX 12 MX 16 MX No MX MODERATE DRG.	INIC GROUND WATER		SLIGHT ROCK GENERALLY FRESH, JOINTS STAIN	NED AND DISCOLORATION EXTENDS INTO ROCK UP TO	FAILT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
USUAL TYPES STONE FRAGS. FINE SILTY OR CLAYEY SILTY CLAYEY ORGANIC	WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER I	DRILLING	(SLI.) 1 INCH. OPEN JOINTS MAY CONTAIN CL	AY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR . CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
OF MAJOR GRAYEL AND SAND GRAVEL AND SAND SOILS SOILS MATTER	STATIC WATER LEVEL AFTER 24 HOURS		i .	DISCOLORATION AND WEATHERING EFFECTS. IN	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM
GEN. RATING AS A EXCELLENT TO GOOD FAIR TO POOR WASA	PERCHED WATER, SATURATED ZONE, OR WATER BEARI	ING STRATA	(MOD.) GRANITOID ROCKS, MOST FELDSPARS AR	RE DULL AND DISCOLORED, SOME SHOW CLAY, ROCK HAS ND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED	PARENT MATERIAL.
AS A EXCELLENT TO GOOD FAIR TO POOR POOR UNSUI	SPRING DR SEEP		WITH FRESH ROCK.	AD SHOWS STORIFICHIN EDSS OF STREETING HS COLUMNICS	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 :PI OF A-7-6 SUBGROUP IS > LL - 30			MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED	D OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL DW KADLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH	FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN
CONSISTENCY OR DENSENESS RANGE OF STANDARD RANGE OF UNCONFINED	MISCELLANEOUS SYMBOLS		(MOD. SEV.) AND CAN BE EXCAVATED WITH A GEOL	OGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK.	THE FIELD.
PRIMARY SOIL TYPE COMPACTNESS OR PENETRATION RESISTENCE COMPRESSIVE STRENGTH	ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION SPT CPT OPT DHT TEST BORIN	ING SAMPLE DESIGNATIONS	IF TESTED, WOULD YIELD SPT REFUSAL		JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
(IV-VALUE) VIBION 1	— 4	S - BULK SAMPLE	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLDREG (SEV.) IN STRENGTH TO STRONG SDIL. IN GRA	D OR STAINED.ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED ANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.
GENERALLY LOOSE 4 TO 10 GRANULAR LOOSE 4 TO 10	SOIL SYMBOL AUGER BORING	SS - SPLIT SPOON	EXTENT. SOME FRAGMENTS OF STRONG	ROCK USUALLY REMAIN.	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
MATERIAL DENSE 10 10 30	ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT - CORE BORING	SAMPLE	IF TESTED, YIELDS SPT N VALUES > 1.	D OR STAINED, ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT	MOTILED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTILING IN
(NON-COHESIVE) VERY DENSE >50	THAT HOADWAY ENDANCHER	ST - SHELBY TUBE SAMPLE	(V SEV.) THE MASS IS EFFECTIVELY REDUCED T	TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK	SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN
VERY SOFT <2 <0.25	INFERRED SOIL BOUNDARY MONITORING WE		REMAINING, SAPROLITE IS AN EXAMPLE	OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR RIC REMAIN. IF TESTED, YIELDS SPT N VALUES < 100 BPF	INTERVENING IMPERVIOUS STRATUM.
GENERALLY SOFT 2 TO 4 0.25 TO 0.50 SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0	INFERRED ROCK LINE PIEZOMETER	RT - RECOMPACTED TRIAXIAL	COMPLETE ROCK REDUCED TO SOIL, BOCK FABRIC	NOT DISCERNIBLE OR DISCERNIBLE ONLY IN SMALL AND	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
MATERIAL STIFF 8 TO 15 1 TO 2	TTTTT ALLUVIAL SOIL BOUNDARY INSTALLATION	SAMPLE	SCATTERED CONCENTRATIONS, QUARTZ	MAY BE PRESENT AS DIKES OR STRINGERS, SAPROLITE IS	ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF
(COHESIVE) VERY STIFF 15 TO 30 2 TO 4 HARD >30 >4	25/025 DIP & DIP DIRECTION OF SLOPE INDICATO	CBR - CALIFORNIA BEARING	ALSO AN EXÁMPLE.	HARDNESS	ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AF EXPRESSED AS A PERCENTAGE.
TEXTURE OR GRAIN SIZE	ROCK STRUCTURES SPT N-VALUE	RATIO SAMPLE .			SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE
U.S. STD. SIEVE SIZE 4 10 40 60 200 270	SOUNDING ROD REF SPT REFUSAL		VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SEVERAL HARD BLOWS OF THE GEOLO	SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES DGIST'S PICK.	PARENT ROCK.
OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	ABBREVIATIONS			CK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL
BOULDER COBBLE GRAVEL COARSE FINE SILT CLA		w - MOISTURE CONTENT	TO DETACH HAND SPECIMEN.		TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
(BLDR.) (COB.) (GR.) (CSE, SD.) (F SD.) (SL.) (CL.)	BT - BORING TERMINATED MED MEDIUM	V - VERY	MODERATELY CAN BE SCRATCHED BY KNIFE OR PIC HARD EXCAVATED BY HARD BLOW OF A GEO	CK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE DLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR
GRAIN MM 305 75 2.0 0.25 0.05 0.005	CL CLAY MICA MICACEOUS CPT - CONE PENETRATION TEST MOD MODERATELY	VST - VANE SHEAR TEST WEA WEATHERED	BY MODERATE BLOWS.	•	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF
SIZE IN. 12 3	CSE COARSE NP - NON PLASTIC	7 - UNIT WEIGHT	MEDIUM CAN BE GROOVED OR GOUGED 0.05 IN HARD CAN BE EXCAVATED IN SMALL CHIPS	NCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE	A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH DUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS PENETRATION EQUAL TO DR LESS
SOIL MOISTURE - CORRELATION OF TERMS	DMT - DILATOMETER TEST ORG ORGANIC DPT - DYNAMIC PENETRATION TEST PMT - PRESSUREMETER TEST	$\gamma_{ m d}$ - DRY UNIT, WEIGHT	POINT OF A GEOLOGIST'S PICK.		THAN 0.1 FOOT PER 60 BLOWS.
SOIL MOISTURE SCALE FIELD MOISTURE GUIDE FOR FIELD MOISTURE DESCRIPTION GUIDE FOR FIELD MOISTURE DESCRIPTION	ION e - VOID RATIO SAP SAPROLITIC		SOFT CAN BE GROVED OR GOUGED READILY	BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL THIN	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH
	F - FINE SD SAND, SANDY FOSS FOSSILIFEROUS SL SILT, SILTY		PIECES CAN BE BROKEN BY FINGER I		OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY
- SATURATED - USUALLY LIQUID, VERY WET, USUALLY (SAT.) FROM BELOW THE GROUND WATER TA	FRAC FRACTURED, FRACTURES SLI SLIGHTLY	•	VERY CAN BE CARVED WITH KNIFE, CAN BE	EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH	TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EDUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE
LL LIOUID LIMIT	FRAGS FRAGMENTS TCR - TRICONE REFUSAL		SOFT OR MORE IN THICKNESS CAN BE BROW	KEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY	TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
PLASTIC SEMISOLID: REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	EQUIPMENT USED ON SUBJECT I	PROJECT	FRACTURE SPACING	BEDDING	TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.
(PI) PL PLASTIC LIMIT		HAMMER TYPE:	TERM SPACING	TERM THICKNESS VERY THICKLY BEDDED > 4 FEET	BENCH MARK: TBM #2 RR SPIKE IN BASE OF 14 GUM 62.3 LT OF
OPTIMUM MOISTURE - MOIST - (M) SOLID: AT OR NEAR OPTIMUM MOIST	105	X AUTOMATIC MANUAL	VERY WIDE MORE THAN 10 FEET	THICKLY BEDDED 1.5 - 4 FEET	STATION 12+73 -BL- ELEVATION: 47,10' FT
OM OPTIMUM MOISTURE - MOIST - (M) SOLIDEAT OR NEAR OPTIMUM MOIST SL SHRINKAGE LIMIT	MOBILE B- CLAY BITS		WIDE 3 TO 10 FEET MODERATELY CLOSE 1 TO 3 FEET	THINLY BEDDED 0.16 - 1.5 FEET VERY THINLY BEDDED 0.03 - 0.16 FEET	ELEVATION: Trate Fi
REQUIRES ADDITIONAL WATER TO	6 CONTINUOUS FLIGHT AUGER	CORE SIZE:	CLOSE . Ø.16 TO 1 FEET	THICKLY LAMINATED 0.008 - 0.03 FEET	NOTES:
- DRY - (D) ATTAIN OPTIMUM MOISTURE	BK-51 8 HOLLOW AUGERS	-В	VERY CLOSE LESS THAN 0.16 FEET	THINLY LAMINATED < 0.008 FEET	
PLASTICITY	CME-458 HARD FACED FINGER BITS			DURATION	
PLASTICITY INDEX (PI) DRY STRENGTH	TUNGCARBIDE INSERTS	1	· ·	NING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	
NONPLASTIC 0-5 VERY LOW PLASTICITY 6-15 SLIGHT	CME-550 X CASING W/ ADVANCER	н	FRIABLE RUBBING GENTLE	G WITH FINGER FREES NUMEROUS GRAINS: : BLOW BY HAMMER DISINTEGRATES SAMPLE.	
MED. PLASTICITY 16-25 MEDIUM	PORTABLE HOIST X TRICONE 215/6 STEEL TEETH	HAND TOOLS:	GRAINS	CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE:	
HIGH PLASTICITY 26 OR MORE HIGH	I —	POST HOLE DIGGER	MODERATELY INDURATED BREAKS	E EASILY WHEN HIT WITH HAMMER.	
COLOR	TRICONE TUNGCARB.	HAND AUGER SOUNDING ROD		ARE DIFFICULT TO SEPARATE WITH STEEL PROBE:	
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY)	CORE BIT	VANE SHEAR TEST	DIFFICE	ULT TO BREAK WITH HAMMER.	
MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		TARKE SHERIN TEST		HAMMER BLOWS REDUIRED TO BREAK SAMPLE: E BREAKS ACROSS GRAINS.	
ł	1		See it to		

PROJECT REFERENCE NO. 33735.I.I(B-4504)

SHEET NO. 2 OF 9







NCDOT GEOTECHNICAL ENGINEERING UNIT BORELOG REPORT

PF	OJEC						3-4504				COUNTY	Edged	ombe			GEOLO	GIST Swa	artley, J. I	₹.	PRO	DJECT	T NO. 3	3735.1.	1	ID. E	3-4504			СО	UNTY	Edgec	ombe		_	GEC	LOGIST	Swartle	y, J. R.	
SI	E DES	CRIP	TION	BRIDG	3E 52	ON S	R 1505	OVER	DEEP C	CREEK								GROUN	D WTR (ft) SITI	E DES	CRIPTIC	N BR	IDGE 52	2 ON S	R 1505	OVER D	EEP CR			***************************************								WTR (ft)
ВС	RING	NO. E	31-B			STA	ATION 2	20+19			OFFSET	7ft RT		AL	IGNME	NT -L-		0 HR	. N/A	ВОР	RING	NO. B1	-B		STA	ATION :	20+19		OF	FSET '	7ft RT			ALIGNM	ENT -L			0 HR.	N/A
CC	LLAR	ELEV.	41.3	ft		TO	TAL DEP	TH 76	6.1 ft		NORTHIN	IG 803	244	E/	STING	2,451,21	2	24 HR	. 0.8	COL	_LAR	ELEV.	41.3 ft		TOT	TAL DEP	TH 76.	1 ft	NO	RTHING	803,	244		EASTING	G 2,45	1,212		24 HR.	0.8
DF	ILL MA	ACHIN	E CM	IE-45B		DRI	LL MET	OD N	/Jud Rot	ary						HAMN	MER TYPE	Automa	tic	DRI	LL MA	ACHINE	CME-4	5B	DRI	LL MET	HOD M	ud Rotar	у :			٠. ٠			HA	AMMER	YPE A	utomatic	
	ART D			07		CO	MP. DAT	E 03/0	01/07		SURFAC	E WATE	R DEPT	H N/A		DEPTI	н то кос	K N/A		STA	RT D	ATE 02	/28/07		CON	MP. DAT	E 03/01	/07	SUI	RFACE	WATE	R DEP	TH N/A	٩	DE	РТН ТО	ROCK	N/A	
ELE (ft	V DRI' ELE (ft	VE DE	PTH_(ft) (BLOW 0.5ft 0.			0	BLO\ 25	WS PER		75 10	11	MOI	0		SOIL AND	ROCK DESC	CRIPTION	DEPTH (I	ELEV (ft)	DRI' ELE (ft	VE EV (ft)	H BLC 0.5ft	0.5ft	NT 0.5ft	0	BLOW 25	S PER FO	OOT 75	100	SAMP NO.	1 /	L 0 I G		SOIL /	AND ROCE	C DESCRI	PTION	
50		<u> </u>								-				-						30	ļ		<u> </u>				Ma	atch Line				<u> </u>			GRAY SA	ANDY SIL	, WET (co	ontinued)	
45		† † †												- - -						-35	ł	74.6	12	14	15		29	.	:: :				-	34.8 E	Boring Te	rminated a	t Elevation	-34.8 ft in	76.1
40		3 7 (0.0 W	OH W	он w	он .		Ţ					V	- 41.3		ROWN SAND	OUND SURFA D, MOIST TO (ALLUVIAL)	SATURAT	0. ED	.040		1													3	very s	tiff silt		
35	35.	9 + 5	5.4	20 2	28 1	7		: : : : , : . ,	45			SS-8		37.3		· . `	(12201112)		4.	0 -45		† †																	
30		7 + 9		5 3	3 2	2	ψ5.	 : : :						33.3	· · · · · · · · · · · · · · · · · · ·	FRAGME	EN SAND W ENTS, SATU OWN FORM	JRATED	. 8.	-50		‡																	
25	_26.	7 + 1	4.6	1 2	2 2	2	4									·		,				T																	
	_21.	7 1 15	9.6	1 2	2 2	2														-55		+																	
	16.	7 + 2	4.6	2 4	4		·\;				• • • •	<u> </u>								-60		+++++++++++++++++++++++++++++++++++++++																	
15		7 + 25	9.6				- • 11 · · · · · · · · · · · · · · · · ·					SS-10								-65		‡ + + +																	
10	6.7	† ; ; ; 34	4.6	4 3	3	3	6			· · ·				<u>-</u> 8.3	GR	RAY SANDY	AND CLAYE	EY SILT, W	33. ET	0 -70		+																	
5	17	† 	0.6	6 7	7 1	1		3				SS-11		<u> </u>		(CAPE F	EAR FURM	ATION)		-75		+ + + +																	
90/08		+		7 1	0 1	4		24						-1.7					43.	-80		† †																	
T.GDT 06/20	-3.3	3 + 44	4.6	8 1:	2 1	7		29				SS-12		N N -6.7		OBAY	AND CONT	DATES	48.	-85	-	† † †																	
GPJ NC DOT	8.3	3 + 49	9.6	6 9) 1	4		23.				SS-13	-			GRAY S	AND, SATUF	KATED		-90		-																	
-15		3 + 54	4.6	6 1:	2 1	1		23										•		-95		‡ ‡ ‡																	
. B4504_GEO_ 02-	18.	3 + 59	9.6	7 1	7 2	1			38											-100		+++++++++++++++++++++++++++++++++++++++															•		
SE DOUBLE		3 + 64		8 1	1 1	1		22	.			SS-14		-21.7		GRAY S	SANDY SILT	, WET	63.	<u>-105</u>		† †																	
CDOT BO	-28.	3 + 69	9.6	7 11	0 1	7		27	.								÷			110		+																	

PROJECT NO. 33735.1.1 ID. B-4504	COUNTY Edgecombe	GEOLOGIST Swartley, J. R.	PROJECT NO. 33735.1.1	ID . B-4504	COUNTY Edgecombe	GEOLOGIST Swartley, J. R.
SITE DESCRIPTION BRIDGE 52 ON SR 1505 OVER DEEP CRE		GROUND WTR (f		52 ON SR 1505 OVER DEEP CRE		GROUND WTR (
BORING NO. EB2-A STATION 20+97	OFFSET 24ft LT	ALIGNMENT -L- 0 HR. N//		STATION 20+97	OFFSET '24ft LT	ALIGNMENT -L- 0 HR. N/
COLLAR ELEV. 43.9 ft TOTAL DEPTH 79.4 ft	NORTHING 803,306	EASTING 2,451,155 24 HR. 3.	COLLAR ELEV. 43.9 ft	TOTAL DEPTH 79.4 ft	NORTHING 803,306	EASTING 2,451,155 24 HR . 3
DRILL MACHINE CME-45B DRILL METHOD Mud Rotary		HAMMER TYPE Automatic	DRILL MACHINE CME-45B	DRILL METHOD Mud Rotary		HAMMER TYPE Automatic
START DATE 02/27/07 COMP. DATE 02/27/07	SURFACE WATER DEPTH N	/A DEPTH TO ROCK N/A	START DATE 02/27/07	COMP. DATE 02/27/07	SURFACE WATER DEPTH	N/A DEPTH TO ROCK N/A
DRIVE DEPTH BLOW COUNT BLOWS PER FOOT BLOWS PER FOOT	75 100 SAMP. V L O NO. MOI G	SOIL AND ROCK DESCRIPTION ELEV. (ft) DEPTH	ELEV DRIVE DEPTH BLOW CO		OT SAMP. L O NO. MOI G	
43.9 0.0			0.0	Match Line	0	35.5 Boring Terminated at Elevation -35.5 ft in
40 39 9 4 0 0 5 7		BROWN GRAY SAND, SATURATED (ALLUVIAL)	-40			hard clay
35 36.0 7.9 4 4 3 2			-45			- - - -
31.0 12.9 7 1 2		32.9 11 GREEN SAND WITH SHELL FRAGMNETS, SATURATED	.50			- - - -
26.0 17.9	-	- (YORKTOWN FORMATION)				- - - - -
2 1 2 • 3		.	_55			 - - - -
	SS-3		-60			
15 16.0 27.9 1 1 2 63		12.9 31	.0 -65			<u>-</u> - -
0 11.0 32.9 3 4 5	SS-4 0000	<u>.</u>	-70			
5 6.0 37.9 6 7 9	SS-5	5.9 38 GRAY CLAYEY SANDY SILT, WET (CAPE FEAR FORMATION)	.0 -75 +			- - - -
0 1.0 42.9 6 10 12	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	 -	-80		,	- - -
5 47.9 8 13 20		· -	-85			
0 -9.0 52.9 5 6 16 -9.2	SS-6	·	-90			- - -
57.9 4 9 12		-	-95			- - - -
20 -19.0 62.9 9 13 17			-100			- - - -
25 7 16 22		-22.1 GRAY SILTY SANDY CLAY, WET	-105			- - - -
-29.0 72.9	: :::: 🕃					- - -
-30			-110			-

B-4504 Bridge No. 52 on SR 1505 over Deep Creek

HOLE #	SAMPLE#	PASS 10	PASS 40	PASS 200	CSESAND	FINESAND	SI	CEALL P	CLASS	DEPTH	MOIST.	ORG.
EB2-A	SS-1	100	82	15	34.4	52.7	11.0	2.0 19 N	P A-2-4(0)	1.0-1.5		
	SS-2	100	87	27	30.4	44.0	17.6	8.0 20 N	P A-2-4(0)	12.9-14.4		
	SS-3	100	87	13	25.7	61.9	12.4	0.0 19 N	P A-2-4(0)	22.9-24.4		
	SS-4	100	36	9	81.7	10.2	8.0	0.0 20 N	P A-1-b(0)	32.9-34.4		
	SS-5	100	97	63	8.8	39.2	42.0	10.0 38 N	P A-4(1)	37.9-39.4		
	SS-6	100	97	54	5.6	53.6	20.7	20.1 33 1) A-4(3)	52.9-54.4		
•	SS-7	100	88	52	21.1	39.4	29.5	10.0 44 1	3 A-7-5(5)	67.9-69.4		
B1-B	SS-8	100	92	9	39.2	54.4	6.4	0.0 17 N	P A-3(0)	5.4-6.9		
	SS-9	100	94	27	21.5	52.4	16.1	10.0 21 N	P A-2-4(0)	9.6-11.1		
	SS-10	100	90	12	47.6	41.6	8.8	2.0 20 N	P A-2-4(0)	24.6-26.1		
	SS-11	100	99	84	2.6	24.9	48.4	24.1 13 N	P A-4(0)	34.6-36.1	•	
	SS-12	100	99	72	3.0	36.5	38.4	22.1 45 N	P A-5(3)	44.6-46.1		
	SS-13	100	100	26	5.0	71.1	11.8	12.0 16 N	P A-2-4(0)	49.6-51.1		
	SS-14	100	86	51	23.7	40.2	26.1	10.0 37 N	P A-4(0)	64.6-66.1		
EB1-A	SS-15	100	93	31	14.9	60.8	16.3	8.0 17 N	P A-2-4(0)	4.0-5.5	٠.	
	SS-16	100	85	32	40.2	39.6	10.2	10.0 25 N	P A-2-4(0)	18.4-19.9		
	SS-17	100	84	13	50.8	37.8	9.4	2.0 22 N	P A-2-4(0)	33.4-34.9		
	SS-18	100	98	63	3.8	42.6	37.5	16.1 36 N	P A-4(0)	43.4-44.9		
	SS-19	100	100	31	8.0	63.3	10.6	18.1 29 4	A-2-4(0)	53.4-54.9		
	SS-20	100	96	66	9.0	35.6	37.3	18.1 28 5	A-4(2)	58.4-59.9		
	SS-21	100	84	. 60	22.6	29.4	38.0	10.0 41 9	A-5(5)	68.4-69.9		



FIELD SCOUR REPORT

WBS:	33735.1.1	_ TIP:	B-4504	COUNTY: E	dgecombe		
DESCRIPTION(1): B	Bridge No. 52 o	n SR 1505	over Deep Cree	ek <u>* 2000</u> .	Q 11 Q 18	Samuel Committee of the	and the state of
			EXISTING	BRIDGE			
Information from:	Field Ir Other	nspection _ (explain) _	X Mic	rofilm (reel	pos: _)	
Bridge No.: <u>5</u> Foundation Type: <u>T</u>		:110.5_	Total Bents:	4 Bents in Chanr	nel: 2 B	ents in Floodplair	n:2
EVIDENCE OF SO Abutments or Er	COUR(2) nd Bent Slopes	None note	ed				
Interior Bents: <u>3</u>	-5 foot scour p	ocket at Be	ent 1				
Channel Bed: <u>N</u>	lone noted						
Channel Bank: 3	-5 feet of scou	r under brid	lge on south bai	nk			
EXISTING SCOUP Type(3): <u>V</u>	R PROTECTIO Vooden wing w		<u>;</u>				.
Extent(4): 1	0'-15' from out	side edge o	of bridge				
Effectiveness(5): A	ppears satisfa	ctory					
Obstructions(6): C	Old concrete bri	dge founda	ation west and u	nderneath bridge			·
		G.					

INSTRUCTIONS

- 1 Describe the specific site's location, including route number and body of water crossed.
- 2 Note scour evidence at existing end bents or abutments (e.g. undermining, sloughing, degradations).
- 3 Note existing scour protection (e.g. rip rap).
- 4 Describe extent of existing scour protection.
- 5 Describe whether or not the scour protection appears to be working.
- 6 Note obstructions such as dams, fallen trees, debris at bents, etc.
- 7 Describe the channel bed material based on observation and/or samples. Include any lab results with report.
- 8 Describe the channel bank material based on observation and/or samples. Include any lab results with report.
- 9 Describe the material covering the banks (e.g. grass, trees, rip rap, none).
- 10 Determine the approximate floodplain width from field observation or a topographic map.
- 11 Describe the material covering the floodplain (e.g. grass, trees, crops).
- 12 Use professional judgement to specify if the stream is degrading, aggrading, or static.
- 13 Describe potential and direction of the stream to migrate laterally during the bridge's life (approx. 100 years).
- 14 Give the design scour elevation (DSE) expected over the life of the bridge (approx. 100 years). This elevation can be given as a range across the site, or for each bent. Discuss the relationship between the Hydraulics Unit theoritical scour and the DSE. If the DSE is dependent on scour counter measures, explain (e.g. rip rap armoring on slopes). The DSE is based on the erodability of materials, giving consideration to the influence of joints, foliation, bedding characteristics, % core recovery, % RQD, differential weathering, shear strength, observations at existing structures, other tests deemed appropriate, and overall geologic conditions at the site.

	DE	SIGN IN	FORM A	TIOI									
<u>DESIGN INFORMATION</u>													
Channel Bed Material(7)	Channel Bed Material(7): Loose to dense sand (SS-8)												
Channel Bank Material(8)): Verv loose to m	edium der	nse sand (SS-1)								
	,				<i></i>								
Channel Bank Cover(9)): <u>Wooded</u>												
Floodplain Width(10): 500+/- feet													
Floodplain Width(10): 500+/- feet													
Floodplain Cover(11): Wooded													
Stream is(12)): Aggradin	g	Degra	ding_	X	Sta	tic						
annel Migration Tendency(13		•											
anner wigration Tendency(13	J. INOU IIKEIY DUU III	ay migrate	Southed	si iUW	ard Lild De	01 L I							
Observations and Other Com	ments: Old roadv	vay emban	nkment pr	esent	near old co	oncrete b	ridge fou	ındation	*				
DESIGN SCOUR ELEVATIO	NS/14)			Fe	et X	Mete	ers						
DESIGN SOCON ELEVANO	110(14)												
BENT	<u>s</u>												
<u>B1</u> _													
23													
· ·													
-													
			L		L	I	I	I	·				
Comparison of DSE to Hydra	ulics Unit theoreti	cal scour:			•								
Design Scour Elevation agree	es with the Hydrau	ulics Unit's	over top	oing tl	neoretical s	cour							
SOIL ANALYSIS RESULTS	FROM CHANNE	I RED AN	D BANK	MATI	ERIAL								
Bed or Bank	T KOM ON ANTE		1										
Sample No.													
Retained #4													
Passed #10		-											
Passed #40		See She	et 9			<u> </u>							
Passed #200		E .	st Results	11									
Coarse Sand		for samp		,		H		ļ					
Fine Sand			nannel bed	d		Ц		 					
Silt		1	nannel bai			4							
Clay						· H							
LL								_					
PI								 					
AASHTO			<u> </u>					 					
Station								 					
Offset								 					
Depth			1		L			1					

Template Revised 02/07/06

ŀ	ported by:		Date:	4/18/2007