


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-0061C		
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
38783.1.1	NHF-74 (80)	P.E.	
38783.2.1	HPPNH-0074(80)	R/W	
38783.3.1	HPPNHS-0074(80)	UTILITY, CONST.	

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**COLUMBUS COUNTY**

**LOCATION: US 74 AT NC211. PROPOSED INTERCHANGE AT INTERSECTION OF US 74 /76 (ANDREW JACKSON HWY.) AND NC 211 (GREEN SWAMP RD.)**

**TYPE OF WORK: INTERSECTION IMPROVEMENTS, GRADING, DRAINAGE, PAVING, STRUCTURE AND SIGNALS.**




TIP PROJECT: R-0061C


OFF SITE DETOUR . . . . .

**BEGIN STATE PROJECT R-0061C**  
-L- Sta. 10+00.00

**END STATE PROJECT R-0061C**  
-L- Sta. 57+50.00



STRUCTURE



**DESIGN DATA**

ADT 2005 =	11,000
ADT 2030 =	20,000
DHV =	10 %
D =	60 %
T =	21 % *
V =	60 MPH
* TTST = 17% DUAL = 4%	

**PROJECT LENGTH**

LENGTH ROADWAY F.A.PROJECT No. NHF-74(80) =	0.900 Miles
TOTAL LENGTH STATE PROJECT No. 38783.1.1 =	0.900 Miles

**FUNC. CLASS FOR PROPOSED**   -L- = INTERSTATE  
PROPOSED                                -Y- = COLLECTOR

Prepared in the Office of:  
**DIVISION OF HIGHWAYS**  
1000 Birch Ridge Dr., Raleigh NC, 27610

2006 STANDARD SPECIFICATIONS

**LETTING DATE:**  
AUGUST 17, 2010

**OMAR R. AZIZI, P.E.**  
PROJECT ENGINEER

**TIMOTHY L. COGGINS, P.E.**  
PROJECT DESIGN ENGINEER




**STRUCTURE DESIGN UNIT**  
1000 Birch Ridge Dr.  
Raleigh NC, 27610

**DIVISION OF HIGHWAYS**  
STATE OF NORTH CAROLINA

THIS IS A CONTROLLED-ACCESS PROJECT  
WITH ACCESS LIMITED TO THE INTERCHANGE


23-JUN-2010 11:45  
\$\$\$\$\$DGN\$\$\$\$\$  
+coggins

(+) 3.2220% (-) 3.6753%  
**GRADE DATA -Y-**  
 P. I. STA. = 27+30.00 -Y-  
 EL. = 95.95'  
 V. C. = 1,068'



DRAWN BY : PEGGY ADKINS DATE : 2-08  
 CHECKED BY : T. AVERETTE DATE : 4-21-10

23-JUN-2010 11:44  
 R:\Structures\Final Plans\R0061c.sd.gdgn  
 tcoggins




PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-  
27+00.00 -Y- BRIDGE NO. 408

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

**GENERAL DRAWING**

FOR BRIDGE ON NC 211  
 OVER US 74/76 BETWEEN  
 SR 1740 AND NC 214

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-1
1			3			TOTAL SHEETS 28
2			4			



**FOUNDATION LAYOUT**


DIMENSIONS LOCATING PILES ARE SHOWN TO PILE CENTERLINE.  
 END BENT BRACE PILES ARE BATTERED AT 3:12.  
 BENT BRACE PILES ARE BATTERED AT 1/2:12.

**NOTES:**

FOR PILES, SEE SPECIAL PROVISIONS.  
 DRIVE PILES AT END BENT NO.1, BENT NO.1 AND END BENT NO.2 TO A REQUIRED BEARING CAPACITY OF 120 TONS PER PILE. THE REQUIRED BEARING CAPACITY IS EQUAL TO THE ALLOWABLE BEARING CAPACITY WITH A MINIMUM FACTOR OF SAFETY OF TWO.  
 THE ALLOWABLE BEARING CAPACITY FOR PILES AT END BENT NO.1, BENT NO.1 AND END BENT NO.2 IS 60 TONS PER PILE.

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-  
27+00.00 -Y-  
 SHEET 2 OF 3

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
**GENERAL DRAWING**  
 FOR BRIDGE ON NC 211  
 OVER US 74/76 BETWEEN  
 SR 1740 AND NC 214




DRAWN BY : PEGGY PARISI DATE : 10-21-09  
 CHECKED BY : T. AVERETTE DATE : 4-21-10

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-2
1			3			TOTAL SHEETS
2			4			28



BM #2: RR SPIKE IN BASE OF 15" PINE AT STA. 33+30.00 -L-, 117' LEFT; ELEV. = 60.67.



LOCATION SKETCH

NOTES:

ASSUMED LIVE LOAD = HS20 OR ALTERNATE LOADING, EXCEPT THAT THE GIRDERS HAVE BEEN DESIGNED FOR HS25.

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.

REMOVABLE FORMS MAY BE USED IN LIEU OF METAL STAY-IN-PLACE FORMS IN ACCORDANCE WITH ARTICLE 420-3 OF THE STANDARD SPECIFICATIONS.

THE CONTRACTOR SHALL PROVIDE INDEPENDENT ASSURANCE SAMPLES OF REINFORCING STEEL AS FOLLOWS: FOR PROJECTS REQUIRING UP TO 400 TONS OF REINFORCING STEEL, ONE 30 INCH SAMPLE OF EACH SIZE BAR USED, AND FOR PROJECTS REQUIRING OVER 400 TONS OF REINFORCING STEEL, TWO 30 INCH SAMPLES OF EACH SIZE BAR USED. THE BARS FROM WHICH THE SAMPLES ARE TAKEN MUST THEN BE SPLICED WITH REPLACEMENT BARS OF THE SIZE AND LENGTH OF THE SAMPLE, PLUS A MINIMUM LAP SPLICE OF THIRTY BAR DIAMETERS.

NEEDLE BEAMS WILL NOT BE ALLOWED UNLESS OTHERWISE CALLED FOR ON THE PLANS OR APPROVED BY THE ENGINEER.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR PRESTRESSED CONCRETE MEMBERS, SEE SPECIAL PROVISIONS.

THIS BRIDGE HAS BEEN DESIGNED BY THE STRENGTH DESIGN METHOD AS SPECIFIED IN AASHTO STANDARD SPECIFICATIONS.

FOR EROSION CONTROL MEASURES, SEE EROSION CONTROL PLANS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR MAINTENANCE AND PROTECTION OF TRAFFIC BENEATH PROPOSED STRUCTURE, SEE SPECIAL PROVISIONS.

FOR CURING CONCRETE, SEE SPECIAL PROVISIONS.

FOR PLACING LOAD ON STRUCTURE MEMBERS, SEE SPECIAL PROVISIONS.

TOTAL BILL OF MATERIAL


	FOUNDATION EXCAVATION FOR BENT	REINFORCED CONCRETE DECK SLAB	GROOVING BRIDGE FLOORS	CLASS A CONCRETE	BRIDGE APPROACH SLABS	REINFORCING STEEL	SPIRAL COLUMN REINFORCING STEEL	54" PRESTRESSED CONCRETE GIRDERS	HP 12 X 53 STEEL PILES	PILE REDRIVES	CONCRETE BARRIER RAIL	4" SLOPE PROTECTION	ELASTOMERIC BEARINGS	EVAZOTE JOINT SEALS
	LUMP SUM	SO.FT.	SO.FT.	CU.YDS.	LUMP SUM	LBS.	LBS.	NO. LIN.FT.	NO. LIN.FT.	EACH	LIN.FT.	SO.YDS.	LUMP SUM	LUMP SUM
SUPERSTRUCTURE		11,086	12,083		LUMP SUM			14 1,385.56			401.29		LUMP SUM	LUMP SUM
END BENT NO.1				46.7		7,296			15 1,200	8		402		
BENT NO.1	LUMP SUM			87.4		15,040	1,602		36 1,980	18				
END BENT NO.2				46.8		7,296			15 1,125	8		402		
TOTAL	LUMP SUM	11,086	12,083	180.9	LUMP SUM	29,632	1,602	14 1,385.56	66 4,305	34	401.29	804	LUMP SUM	LUMP SUM

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-  
27+00.00 -Y-  
 SHEET 3 OF 3

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

GENERAL DRAWING

FOR BRIDGE ON NC 211  
 OVER US 74/76 BETWEEN  
 SR 1740 AND NC 214



DRAWN BY: PEGGY ADKINS DATE: 2-08  
 CHECKED BY: T. AVERETTE DATE: 4-21-10

23-JUN-2010 14:23  
 r:\structures\final plans\r0061c.sd.gdgn  
 tcoggins

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-3
1			3			TOTAL SHEETS
2			4			28



**NOTES**




PROVIDE 1/4" HIGH BEAM BOLSTERS UPPER AT 4'-0" CTS. ATOP THE METAL STAY-IN-PLACE FORMS TO SUPPORT THE BOTTOM MAT OF 'A' BARS. WHEN USING REMOVABLE FORMS, PROVIDE CONTINUOUS HIGH CHAIRS FOR METAL DECK (C.H.C.M.) AT 4'-0" CTS. WITH A HEIGHT TO SUPPORT THE BOTTOM MAT OF 'A' BARS A CLEAR DISTANCE OF 2 1/2" ABOVE THE TOP OF THE REMOVABLE FORM.

LONGITUDINAL STEEL MAY BE SHIFTED SLIGHTLY, AS NECESSARY, TO AVOID INTERFERENCE WITH STIRRUPS IN PRESTRESSED CONCRETE GIRDERS.

PREVIOUSLY CAST CONCRETE IN A CONTINUOUS UNIT SHALL HAVE ATTAINED A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI BEFORE ADDITIONAL CONCRETE IS CAST IN THE UNIT.

BARRIER RAIL IN A CONTINUOUS UNIT SHALL NOT BE CAST UNTIL ALL SLAB CONCRETE IN THE UNIT HAS BEEN CAST AND HAS REACHED A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI.


#5 G1 BAR MAY BE SHIFTED SLIGHTLY, AS NECESSARY, TO CLEAR REINFORCING STEEL AND STIRRUPS.



PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-


SHEET 1 OF 2

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUPERSTRUCTURE TYPICAL SECTION					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					SHEET NO. S-4
					TOTAL SHEETS 28




DRAWN BY : M.D.PISO DATE : 18/05/09  
 CHECKED BY : B.N.BARODAWALA DATE : 16/06/09

23-JUN-2010 11:41  
 R:\Structures\Final Plans\R0061c.sd.ts.dgn  
 rcoogins




SECTION A - A




SECTION B - B

\*\* MEASURED ALONG GIRDER LINE




PLAN



PLAN

BENT DIAPHRAGM BLOCKOUT DETAIL



SECTION

DRAWN BY : M.D.PISO DATE : 18/05/09  
 CHECKED BY : B.N.BARODAWALA DATE : 16/06/09

23-JUN-2010 11:41  
 R:\Structures\Final Plans\R0061c.sd.ts.dgn  
 tcoggins


PROJECT NO. R-0061C  
 COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

SHEET 2 OF 2

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


SUPERSTRUCTURE  
 TYPICAL SECTION

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					TOTAL SHEETS
					28






TOTAL LENGTH OF BRIDGE = 203'-0"  
(FILL FACE TO FILL FACE)




SPAN A

PLAN OF SPANS


SPAN B




TRANSVERSE CONSTRUCTION JOINT DETAIL



REINFORCING STEEL LAYOUT OVER BENT #1



PARTIAL PLAN - END BENT DIAPHRAGM  
(END BENT #1 SHOWN, END BENT #2 SIMILAR)




DETAIL "A"  
(END BENT #2 SHOWN, END BENT #1 SIMILAR)

NOTE: REINFORCING STEEL IN SLAB NOTE SHOWN. LONGITUDINAL REINFORCING STEEL SHALL BE CONTINUOUS THRU JOINT.

DRAWN BY : M.D.PISO DATE : 05/18/09  
CHECKED BY : B.N.BARODAWALA DATE : 09/14/09


23-JUN-2010 11:41  
R:\Structures\Final Plans\R-0061c.sd.s\*.dgn  
tcoggins



PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUPERSTRUCTURE PLAN OF SPANS					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					SHEET NO. S-6
					TOTAL SHEETS 28





FRAMING PLAN

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


SUPERSTRUCTURE  
 FRAMING PLAN

*Imothy 6/23/10*

DRAWN BY : M.D.PISO DATE : 05/18/09  
 CHECKED BY : B.N.BARODAWALA DATE : 06/16/09

23-JUN-2010 11:40  
 R:\Structures\Final Plans\R0061c.sd.fp.dgn  
 tcoggins

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-7
1			3			TOTAL SHEETS
2			4			28




EXTERIOR GDR.
INTERIOR GDR.
EXTERIOR GDR.
INTERIOR GDR.

0.6" Ø L. R. GRADE 270 STRANDS		
AREA (SQ. INCHES)	ULTIMATE STRENGTH (LBS. PER STRAND)	APPLIED PRESTRESS (LBS. PER STRAND)
0.217	58,600	43,950

REINFORCING STEEL FOR ONE GIRDER					
BAR	NUMBER	SIZE	TYPE	LENGTH	WEIGHT
S1	79	#4	1	10'-8"	563
S2	20	#6	1	10'-8"	320
S3	4	#4	2	9'-1"	24
S4	80	#4	3	3'-5"	183
S5	6	#4	2	8'-5"	34
S6	1	#4	2	9'-11"	7
*S7	6	#5	STR	3'-8"	23
S8	4	#4	2	8'-7"	23
S9	1	#3	STR	1'-10"	1
S10	2	#5	2	8'-8"	18
S11	5	#4	STR	7'-0"	23
S12	5	#4	STR	11'-3"	38

\* NOTE: S7 BARS SHALL BE BENT BEFORE SHIPMENT. HEAT BENDING SHALL NOT BE ALLOWED.

**BAR TYPES**



QUANTITIES FOR ONE GIRDER			
	REINFORCING STEEL LB.	7000 PSI CONCRETE C.Y.	0.6" Ø L.R. STRANDS No.
EXTERIOR GIRDER	1219	20.1	36
INTERIOR GIRDER	1252	20.1	36

GIRDERS REQUIRED		
NUMBER	LENGTH	TOTAL LENGTH
14	98'-11 5/8"	1385'-6 3/4"




PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-  
SHEET 1 OF 3

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH

STANDARD  
AASHTO TYPE IV  
PRESTRESSED CONCRETE GIRDER  
CONTINUOUS FOR LIVE LOAD  
SPANS A & B

REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO. S-8  
TOTAL SHEETS 28





SPAN A		
GIRDER	DIM. "A"	DIM. "B"
GDR. A1	47'-4 9/16"	-----
GDR. A2	47'-4 9/16"	51'-7 1/16"
GDR. A3	47'-4 9/16"	51'-7 1/16"
GDR. A4	47'-4 9/16"	51'-7 1/16"
GDR. A5	47'-4 9/16"	51'-7 1/16"
GDR. A6	47'-4 9/16"	51'-7 1/16"
GDR. A7	-----	51'-7 1/16"

SPAN B		
GIRDER	DIM. "A"	DIM. "B"
GDR. B1	-----	51'-7 1/16"
GDR. B2	47'-4 9/16"	51'-7 1/16"
GDR. B3	47'-4 9/16"	51'-7 1/16"
GDR. B4	47'-4 9/16"	51'-7 1/16"
GDR. B5	47'-4 9/16"	51'-7 1/16"
GDR. B6	47'-4 9/16"	51'-7 1/16"
GDR. B7	47'-4 9/16"	-----

NOTE: DIMENSIONS "A" & "B" ARE TAKEN FROM EXPANSION END OF GIRDER.


ASSEMBLED BY: M.D.PISO DATE: 05/18/09  
CHECKED BY: B.N.BARODAWALA DATE: 06/19/09  
DRAWN BY: ELR 8/91 REV. 7/17/98 RWW/LES  
CHECKED BY: GRP 8/91 REV. 10/17/00R RWW/LES  
REV. 5/1/06R TLA/GM






**EMBEDDED PLATE "B-1" DETAILS  
FOR AASHTO TYPE IV GIRDER**

(2 REQ'D PER GIRDER)




**DETAIL "A"**

(FOR AASHTO TYPE IV GIRDERS)



**SECTION "G"**



**SECTION "F"**

(SEE NOTES)

**NOTES**

ALL PRESTRESSING STRANDS SHALL BE 7-WIRE LOW-RELAXATION GRADE 270 STRANDS AND SHALL CONFORM TO AASHTO M203 EXCEPT FOR SAMPLING REQUIREMENTS WHICH SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

ALL REINFORCING STEEL SHALL BE GRADE 60.

APPLY EPOXY PROTECTIVE COATING TO END OF GIRDER SURFACES INDICATED IN ELEVATION VIEW.

EMBEDDED PLATE "B-1" SHALL BE GALVANIZED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS. BEVEL EDGES OF PLATE "B-1" TO GIVE CLOSE FIT BUT NOT TIGHT FIT TO STEEL CASTING FORM.

ANCHOR STUDS SHALL CONFORM TO AASHTO M169 GRADES 1010 THROUGH 1020 OR APPROVED EQUAL, AND SHALL MEET THE TYPE "B" REQUIREMENTS OF SUBSECTION 7.3 OF THE ANSI/AASHTO/AWS D1.5 BRIDGE WELDING CODE.

AT ENDS OF GIRDERS TO BE EMBEDDED IN CONCRETE DIAPHRAGMS OR END WALLS, PRESTRESSING STRANDS MAY EXTEND A MAXIMUM OF 2" BEYOND THE GIRDER ENDS. OTHERWISE, PRESTRESSING STRANDS SHALL BE CUT FLUSH WITH THE GIRDER ENDS.

THE TRANSFER OF LOAD FROM THE ANCHORAGES TO THE GIRDER SHALL BE DONE WHEN CONCRETE HAS REACHED A COMPRESSIVE STRENGTH OF NOT LESS THAN 5600 PSI.

DEPENDING ON THE TYPE OF SYSTEM USED TO SUPPORT THE DECK SLAB FORMS, PRESET ANCHORS MAY BE NECESSARY IN THE PRESTRESSED CONCRETE GIRDER.

THE TOP SURFACE OF THE GIRDER, EXCLUDING THE OUTSIDE 4", SHALL BE RAKED TO A DEPTH OF 1/4".

WHEN DRAPED STRANDS ARE DETAILED, THE LONGITUDINAL LOCATION OF THE HOLD DOWN DEVICES SHALL BE WITHIN 6" OF THE LOCATION SHOWN AND THE CENTER OF GRAVITY OF THE GROUP OF DRAPED STRANDS SHALL BE LOCATED WITHIN 1/2" OF THE THEORETICAL LOCATION SHOWN.

FOR PRESTRESSED CONCRETE MEMBERS, SEE SPECIAL PROVISIONS.

THE UPLIFT FORCE DUE TO DRAPED STRANDS IS 21.04 kips.

DEAD LOAD DEFLECTION TABLE FOR GIRDERS												
0.6" Ø LOW RELAXATION	SPAN A OR SPAN B											
	ALL GIRDERS											
	TENTH POINTS	0	.1	.2	.3	.4	.5	.6	.7	.8	.9	0
CAMBER ( GIRDER ALONE IN PLACE ) ↑	0	0.122	0.231	0.317	0.371	0.390	0.371	0.317	0.231	0.122	0	0
* DEFLECTION DUE TO SUPERIMPOSED D.L. ↓	0	0.053	0.100	0.137	0.160	0.168	0.160	0.137	0.100	0.053	0	0
FINAL CAMBER ↑	0	13/16"	19/16"	23/16"	29/16"	211/16"	29/16"	23/16"	19/16"	13/16"	0	0

\* INCLUDES FUTURE WEARING SURFACE  
ALL VALUES ARE SHOWN IN FEET ( DECIMAL FORM ), EXCEPT " FINAL CAMBER ", WHICH IS GIVEN IN INCHES ( FRACTION FORM ).


PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH


STANDARD  
PRESTRESSED CONCRETE GIRDER  
CONTINUOUS FOR LIVE LOAD  
DETAILS

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-9
1			3			TOTAL SHEETS
2			4			28




ASSEMBLED BY : M.D.PISO DATE :05/18/09  
CHECKED BY : B.N.BARODWALA DATE :09/01/09  
DRAWN BY : ELR 11/91 REV. 10/17/00 RWW/LES  
CHECKED BY : GRP 11/91 REV. 7/10/01RR LES/RDR  
REV. 5/1/06 TLA/GM






EXTERIOR GIRDER INTERIOR GIRDER  
PART SECTION AT INTERMEDIATE DIAPHRAGM




SECTION A-A SECTION B-B  
CONNECTION DETAILS



USE WITH 7/8 H.VY. HEX NUTS & DIRECT TENSION INDICATOR WASHERS AT DIAPHRAGM CHANNEL TO CONNECTOR PLATE CONNECTIONS

USE WITH 1 H.VY. HEX NUTS AT CONNECTOR PLATE TO GIRDER CONNECTIONS

WASHER DETAILS



DIAPHRAGM FACE WEB FACE  
CONNECTOR PLATE DETAILS




PLATE DETAILS

CHANNEL END

STRUCTURAL STEEL NOTES

ALL INTERMEDIATE DIAPHRAGM STEEL, CONNECTOR PLATES AND PLATE WASHERS SHALL BE AASHTO M270 GRADE 50 OR APPROVED EQUAL.

TENSION ON THE AASHTO M164 BOLTS THROUGH THE CHANNEL MEMBER SHALL BE CALIBRATED USING DIRECT TENSION INDICATOR WASHERS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS. FOR DIRECT TENSION INDICATORS, SEE SPECIAL PROVISIONS.

TENSION ON THE AASHTO M164 BOLTS THROUGH THE GIRDER WEB SHALL BE SNUG TIGHTENED FOLLOWED BY AN ADDITIONAL 1/4 TURN.

THE PLATES, BENT PLATES, CHANNELS, ANGLES, AND PLATE WASHERS SHALL BE GALVANIZED OR METALLIZED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS. FOR THERMAL SPRAYED COATINGS (METALLIZATION), SEE SPECIAL PROVISIONS.

FOR METALLIZATION, APPLY AN 8 MIL THICK 99.99 PERCENT ZINC (W-Zn-1) THERMAL SPRAYED COATING WITH A 0.5 MIL THICK SEAL COAT TO ALL STEEL DIAPHRAGM SURFACES IN ACCORDANCE WITH THE THERMAL SPRAYED COATINGS SPECIAL PROVISIONS AND SECTION 442 OF THE STANDARD SPECIFICATIONS.

GALVANIZE THE HIGH STRENGTH BOLTS, NUTS, WASHERS AND DIRECT TENSION INDICATORS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS. FOR HIGH STRENGTH BOLTS, SEE SPECIAL PROVISIONS.

USE A MINIMUM 7/16 THICK PLATE WASHER WITH STANDARD HOLES UNDER EACH BOLT HEAD AND NUT. THE PLATE WASHERS SHALL HAVE SUFFICIENT SIZE TO COVER THE HOLES AFTER INSTALLATION. HARDENED WASHERS AND DIRECT TENSION INDICATORS ARE TO BE USED IN CONJUNCTION WITH THE PLATE WASHERS IN THE CHANNEL MEMBER CONNECTION.

FOR BOLTS THROUGH THE GIRDER WEB, PROVIDE SUFFICIENT LENGTH OF ALL BOLTS TO ACCOMMODATE WASHERS AND THE THICKNESS OF CONNECTING MEMBER PLUS AT LEAST 1/4 PROJECTION BEYOND THE NUT.

INTERMEDIATE DIAPHRAGM ASSEMBLY SHALL COMPLY WITH SECTION 1072 OF THE STANDARD SPECIFICATIONS.


CONTRACTOR SHALL SUBMIT TWO SETS OF WORKING DRAWINGS FOR THE INTERMEDIATE DIAPHRAGM ASSEMBLY FOR REVIEW, COMMENTS AND ACCEPTANCE. AFTER REVIEW, COMMENTS, AND ACCEPTANCE, SUBMIT SEVEN SETS FOR DISTRIBUTION.

IN THE EXTERIOR BAYS, TEMPORARY STRUTS SHALL BE PLACED BETWEEN PRESTRESSED GIRDERS ADJACENT TO THE STEEL DIAPHRAGMS. STRUTS SHALL REMAIN IN PLACE 3 DAYS AFTER CONCRETE IS PLACED. ALL AASHTO M164 H.S. BOLTS SHALL BE FULLY TIGHTENED AFTER THE STRUTS HAVE BEEN REMOVED.

THE COST OF THE STEEL DIAPHRAGMS AND ASSEMBLIES SHALL BE INCLUDED IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE GIRDERS.

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-

SHEET 3 OF 3



STATE OF NORTH CAROLINA					
DEPARTMENT OF TRANSPORTATION					
RALEIGH					
STANDARD					
INTERMEDIATE					
STEEL DIAPHRAGMS					
FOR TYPE IV					
PRESTRESSED CONCRETE					
GIRDERS					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					SHEET NO.
					S-10
					TOTAL SHEETS
					28

ASSEMBLED BY : M.D.PISO DATE :05/18/09  
CHECKED BY : B.N.BARODAWALA DATE :09/14/09  
DRAWN BY : TLA 6/05  
CHECKED BY : VC 6/05

ADDED 10/21/05  
REV. 5/1/06RR KMM/CM

**NOTES**

AT ALL FIXED POINTS OF SUPPORT, NUTS FOR ANCHOR BOLTS ARE TO BE TIGHTENED FINGER TIGHT AND THEN BACKED OFF 1/2 TURN. THE THREAD OF THE NUT AND BOLT SHALL THEN BE BURRED WITH A SHARP POINTED TOOL.

THE 2" Ø PIPE SLEEVE SHALL BE CUT FROM SCHEDULE 40 PVC PLASTIC PIPE. THE PVC PLASTIC PIPE SHALL MEET THE REQUIREMENTS OF ASTM D1785.

STEEL SOLE PLATES, ANCHOR BOLTS, NUTS, AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.



PRIOR TO WELDING, GRIND THE GALVANIZED SURFACE OF THE PORTION OF THE EMBEDDED PLATE AND SOLE PLATE THAT ARE TO BE WELDED. AFTER WELDING, DAMAGED GALVANIZED SURFACES SHALL BE REPAIRED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

WHEN WELDING THE SOLE PLATE TO THE EMBEDDED PLATE IN THE GIRDER, USE TEMPERATURE INDICATING WAX PENS, OR OTHER SUITABLE MEANS, TO ENSURE THAT THE TEMPERATURE OF THE SOLE PLATE DOES NOT EXCEED 300°F. TEMPERATURES ABOVE THIS MAY DAMAGE THE ELASTOMER.

SOLE PLATE "P", BOLTS, NUTS, WASHERS, AND PIPE SLEEVE SHALL BE INCLUDED IN THE PAY ITEM FOR PRESTRESSED CONCRETE GIRDERS.


ANCHOR BOLTS SHALL MEET THE REQUIREMENTS OF ASTM A449. NUTS SHALL MEET THE REQUIREMENTS OF AASHTO M291-DH OR AASHTO M292-2H. WASHERS SHALL MEET THE REQUIREMENTS OF AASHTO M293. NO SHOP DRAWINGS ARE REQUIRED FOR ANCHOR BOLTS, NUTS AND WASHERS. SHOP INSPECTION IS REQUIRED.

ALL SURFACES OF BEARING PLATES SHALL BE SMOOTH AND STRAIGHT.




TYPICAL HALF-PLAN  
(SHOWING CONTINUOUS BENT)

TYPICAL HALF-PLAN  
(SHOWING SIMPLE SPAN BENT)




TYPICAL SECTION OF ELASTOMERIC BEARINGS




E4 (28 REQ'D)

PLAN VIEW OF ELASTOMERIC BEARING

TYPE V



DETAIL "A"




SOLE PLATE DETAILS ("P")

— LOAD RATINGS —	
	MAX.D.L.+ L.L.
TYPE V	180 K

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH  
 STANDARD  
**ELASTOMERIC BEARING**  
**DETAILS**  
 PRESTRESSED CONCRETE GIRDER  
 SUPERSTRUCTURE



ASSEMBLED BY : M.D.PISO	DATE : 05/18/09
CHECKED BY : B.N.BARODAWALA	DATE : 06/16/09
DRAWN BY : EEM 2/97	REV. 8/16/99 RWW/LES
CHECKED BY : VAP 2/97	REV. 10/17/00 RWW/LES
	REV. 5/1/06 TLA/GM

REVISIONS				SHEET NO.
NO.	BY:	DATE:	NO.	DATE:
1			3	
2			4	
				TOTAL SHEETS
				28

NOTES

BARRIER RAIL IN A CONTINUOUS UNIT SHALL NOT BE CAST UNTIL ALL SLAB CONCRETE IN THE UNIT HAS BEEN CAST AND HAS REACHED A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI.


WHEN EVAZOTE JOINT SEAL IS REQUIRED, THE JOINT IN THE DECK SHALL BE SAWED PRIOR TO THE CASTING OF BARRIER RAIL.

ALL REINFORCING STEEL IN BARRIER RAILS SHALL BE EPOXY COATED.

THE #5 S3 AND #5 S4 BARS SHALL BE INSTALLED, USING AN ADHESIVE ANCHORING SYSTEM, AFTER SAWING THE JOINT. THE YIELD LOAD FOR THE #5 S3 AND #5 S4 BARS IS 18.6 KIPS. FIELD TESTING FOR THE ADHESIVE BONDING SYSTEM IS NOT REQUIRED.

VERTICAL GROOVED CONTRACTION JOINTS, 1/2" IN DEPTH, SHALL BE TOOLED IN ALL EXPOSED FACES OF THE BARRIER RAIL AND IN ACCORDANCE WITH ARTICLE 825-10(B) OF THE STANDARD SPECIFICATIONS. THE CONTRACTION JOINT SHALL BE LOCATED AT EACH THIRD POINT BETWEEN BARRIER RAIL EXPANSION JOINTS. ONLY ONE CONTRACTION JOINT IS REQUIRED AT MIDPOINT OF BARRIER RAIL SEGMENTS LESS THAN 20 FEET IN LENGTH AND NO CONTRACTION JOINTS ARE REQUIRED FOR THOSE SEGMENTS LESS THAN 10 FEET IN LENGTH.

BAR TYPES




ALL BAR DIMENSIONS ARE OUT TO OUT

BILL OF MATERIAL


FOR CONCRETE BARRIER RAIL ONLY

BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
* B1	64	#5	STR	14'-7"	973
* B2	96	#5	STR	24'-7"	2461
* S1	390	#5	1	4'-8"	1898
* S2	390	#5	2	5'-2"	2102
* S3	12	#5	3	3'-4"	42
* S4	12	#5	STR	3'-2"	40


* EPOXY COATED REINFORCING STEEL	7516 LBS.
CLASS AA CONCRETE	40.1 CU. YDS.
CONCRETE BARRIER RAIL	401.29 LIN. FT.




PLAN OF BARRIER RAIL




PLAN



END VIEW




SECTION THRU RAIL



SECTION S-S

AT DAM IN OPEN JOINT (THIS IS TO BE USED ONLY WHEN SLIP FORM IS USED)

1/2" EXP. JT. MAT'L HELD IN PLACE WITH GALVANIZED NAILS. (NOTE: OMIT EXP. JT. MAT'L. WHEN SLIP FORM IS USED.)




ELEVATION AT EXPANSION JOINTS BARRIER RAIL DETAILS

END OF RAIL DETAILS

FOR ADHESIVE ANCHORING AT SAWED JOINTS

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH  
STANDARD  
CONCRETE  
BARRIER RAIL



ASSEMBLED BY: M.D.PISO	DATE: 18/05/09
CHECKED BY: B.N.BARODAWALA	DATE: 06/16/09
DRAWN BY: ARB 5/87	REV. 10/17/00 RWW/LES
CHECKED BY: SJD 9/87	REV. 5/7/03R RWW/JTE
	REV. 5/1/06 TLA/GM

REVISIONS				SHEET NO.
NO.	BY:	DATE:	NO.	DATE:
1			3	
2			4	

S-12
TOTAL SHEETS 28



NOTES

THE GUARDRAIL ANCHOR ASSEMBLY SHALL CONSIST OF A 1/4" HOLD DOWN PLATE AND 4 - 7/8" Ø BOLTS WITH NUTS AND WASHERS, RUBRAIL, AND ADHESIVELY ANCHORED BOLTS.

THE HOLD-DOWN PLATE SHALL CONFORM TO AASHTO M270 GRADE 36. AFTER FABRICATION, THE HOLD-DOWN PLATE SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH AASHTO M111.

BOLTS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307 AND NUTS SHALL CONFORM TO THE REQUIREMENTS OF AASHTO M291. BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED. (AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS, NUTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE 7/8" Ø GALVANIZED BOLTS, NUTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.)



THE GUARDRAIL ANCHOR ASSEMBLY IS REQUIRED AT ALL POINTS WHERE APPROACH GUARDRAIL IS TO BE ATTACHED TO THE END OF BARRIER RAIL. FOR POINTS OF ATTACHMENT, SEE SKETCH.

AFTER INSTALLATION, THE EXPOSED THREAD OF THE BOLT SHALL BE BURRED WITH A SHARP POINTED TOOL.


THE COST OF THE GUARDRAIL ANCHOR ASSEMBLY SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR CONCRETE BARRIER RAIL.

THE 1/4" Ø HOLES SHALL BE FORMED OR DRILLED WITH A CORE BIT. IMPACT TOOLS WILL NOT BE PERMITTED. ANY CONCRETE DAMAGED BY THIS WORK SHALL BE REPAIRED TO THE SATISFACTION OF THE ENGINEER.

THE C6 X 8.2 RUBRAIL IS TO BE ADHESIVELY ANCHORED TO THE RAIL USING THREE 3/4" Ø X 6" BOLTS WITH WASHERS. LEVEL ONE FIELD TESTING IS REQUIRED, AND THE YIELD LOAD OF THE 3/4" Ø BOLT IS 12 KIPS. FOR ADHESIVELY ANCHORED ANCHOR BOLTS OR DOWELS, SEE SPECIAL PROVISIONS. SEE ROADWAY STANDARD 862.03 FOR DETAILS AND LOCATION OF THE RUBRAIL.




ELEVATION  
FOR LOCATION OF RUBRAIL, SEE ROADWAY STD. 862.03



SECTION E-E


GUARDRAIL ANCHOR ASSEMBLY DETAILS



PLAN

LOCATION OF ANCHORS FOR GUARDRAIL

END BENT #1 SHOWN, END BENT #2 SIMILAR.




SKETCH SHOWING POINTS OF ATTACHMENTS

\* DENOTES GUARDRAIL ANCHOR ASSEMBLY

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STANDARD GUARDRAIL ANCHORAGE FOR BARRIER RAIL					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					TOTAL SHEETS 28



ASSEMBLED BY : M.D.PISO DATE :06/16/09  
 CHECKED BY : B.N.BARODAWALA DATE :05/18/09  
 DRAWN BY : TLA 5/06  
 CHECKED BY : GM 5/06

ADDED 5/1/06R KMM/GM

SUPERSTRUCTURE REINFORCING STEEL LENGTHS ARE BASED ON THE FOLLOWING MINIMUM SPLICE LENGTHS

BAR SIZE	SUPERSTRUCTURE EXCEPT APPROACH SLABS, PARAPET, AND BARRIER RAIL		APPROACH SLABS		PARAPET AND BARRIER RAIL
	EPOXY COATED	UNCOATED	EPOXY COATED	UNCOATED	
#4	2'-0"	1'-9"	2'-0"	1'-9"	2'-9"
#5	2'-6"	2'-2"	2'-6"	2'-2"	3'-5"
#6	3'-0"	2'-7"	3'-10"	2'-7"	4'-4"
#7	5'-3"	3'-6"			
#8	6'-10"	4'-7"			

GROOVING BRIDGE FLOORS

APPROACH SLABS	2325	SO.FT.
BRIDGE DECK	9758	SO.FT.
TOTAL	12083	SO.FT.


—SUPERSTRUCTURE BILL OF MATERIAL—

	CLASS AA CONCRETE (CU. YDS.)	REINFORCING STEEL (LBS.)	EPOXY COATED REINFORCING STEEL (LBS.)
POUR #1	167.7		
POUR #2	212.4		
TOTALS**	380.1	35315	35945


\*\* QUANTITIES FOR BARRIER RAIL ARE NOT INCLUDED

REINFORCING STEEL BAR SCHEDULE


BAR NO.	NO.	SIZE	TYPE	LENGTH	WEIGHT	BAR NO.	NO.	SIZE	TYPE	LENGTH	WEIGHT
*A1	317	#5	STR.	54'-11"	18157	*B1	222	#4	STR.	23'-6"	3485
A2	317	#5	STR.	54'-11"	18157	*B2	37	#7	STR.	60'-0"	4538
*A101	2	#5	STR.	53'-3"	111	*B3	36	#7	STR.	32'-0"	2355
*A102	4	#5	STR.	51'-2"	213	*B4	37	#7	STR.	17'-3"	1305
*A103	4	#5	STR.	49'-2"	205	B5	248	#5	STR.	51'-11"	13429
*A104	4	#5	STR.	47'-1"	196	*B6	16	#4	STR.	26'-10"	287
*A105	4	#5	STR.	45'-0"	188	*G1	4	#5	STR.	32'-3"	135
*A106	4	#5	STR.	42'-11"	179	*K1	8	#8	1	13'-9"	294
*A107	4	#5	STR.	40'-10"	170	*K2	20	#8	2	19'-10"	1059
*A108	4	#5	STR.	38'-10"	162	K3	12	#4	STR.	5'-6"	44
*A109	4	#5	STR.	36'-9"	153	K4	12	#4	STR.	7'-2"	57
*A110	4	#5	STR.	34'-8"	145	K5	24	#4	STR.	7'-10"	126
*A111	4	#5	STR.	32'-7"	136	K6	12	#4	STR.	6'-9"	54
*A112	4	#5	STR.	30'-7"	128	K7	10	#4	7	5'-10"	39
*A113	4	#5	STR.	28'-6"	119	K8	25	#4	8	11'-4"	189
*A114	4	#5	STR.	26'-5"	110	*K9	36	#6	STR.	6'-7"	356
*A115	4	#5	STR.	24'-4"	102	S1	84	#5	3	5'-9"	504
*A116	4	#5	STR.	22'-4"	93	S2	84	#4	6	4'-8"	262
*A117	4	#5	STR.	20'-3"	84	S3	132	#4	5	2'-9"	242
*A118	4	#5	STR.	18'-2"	76	U1	24	#4	4	14'-10"	238
*A119	4	#5	STR.	16'-1"	67	U2	12	#4	4	12'-10"	103
*A120	4	#5	STR.	14'-1"	59	REINFORCING STEEL 35315 LBS.					
*A121	4	#5	STR.	12'-0"	50	*EPOXY COATED REINFORCING STEEL 35945 LBS.					
*A122	4	#5	STR.	9'-11"	41	A201	4	#5	STR.	53'-3"	222
*A123	4	#5	STR.	7'-11"	33	A202	4	#5	STR.	51'-2"	213
*A124	4	#5	STR.	5'-10"	24	A203	4	#5	STR.	49'-2"	205
*A125	4	#5	STR.	3'-9"	16	A204	4	#5	STR.	47'-1"	196
*A126	4	#5	STR.	1'-8"	7	A205	4	#5	STR.	45'-0"	188



LAYOUT FOR COMPUTING AREA REINFORCED CONCRETE DECK SLAB (SQ. FT. = 11086)




POURING SEQUENCE




OPTIONAL POURING SEQUENCE

POUR ② CAN NOT BE STARTED UNTIL BOTH ADJACENT ① POURS REACH A MINIMUM OF 3000 PSI.



BAR TYPES



ALL BAR DIMENSIONS ARE OUT TO OUT

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-


STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STANDARD SUPERSTRUCTURE BILL OF MATERIAL					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

ASSEMBLED BY : M.D.PISO	DATE : 05/18/09
CHECKED BY : B.N.BARODAWALA	DATE : 09/14/09
DRAWN BY : JMB 5/87	REV. 6/1/94 EEM/GRP
CHECKED BY : SJD 9/87	REV. 8/16/99 RWW/LES
	REV. 5/1/06 TLA/GM












PLAN OF LEFT WING - W1




PLAN OF RIGHT WING - W2




ELEVATION OF LEFT WING - W1



SECTION X-X



SECTION Y-Y




ELEVATION OF RIGHT WING - W2

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


SUBSTRUCTURE  
 END BENT #1



DRAWN BY: J.B. WILSON DATE: 6/30/09  
 CHECKED BY: M.D. PISO DATE: 10/21/09

23-JUN-2010 11:30  
 R:\Structures\Final Plans\R0061c.sd,eb.dgn  
 rcoggins

REVISIONS						SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:	S-16	
1			3			TOTAL SHEETS	
2			4			28	




BAGGED STONE AND PIPE SHALL BE PLACED IMMEDIATELY AFTER COMPLETION OF END BENT EXCAVATION. PIPE MAY BE EITHER CONCRETE, CORRUGATED STEEL, CORRUGATED ALUMINUM ALLOY, OR CORRUGATED PLASTIC. PERFORATED PIPE WILL NOT BE ALLOWED.


BAGGED STONE SHALL REMAIN IN PLACE UNTIL THE ENGINEER DIRECTS THAT IT BE REMOVED. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF SILT ACCUMULATIONS AT BAGGED STONE WHEN SO DIRECTED BY THE ENGINEER. BAGS SHALL BE REMOVED AND REPLACED WHENEVER THE ENGINEER DETERMINES THAT THEY HAVE DETERIORATED AND LOST THEIR EFFECTIVENESS.

NO SEPARATE PAYMENT WILL BE MADE FOR THIS WORK AND THE ENTIRE COST OF THIS WORK SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR THE SEVERAL PAY ITEMS.

### TEMPORARY DRAINAGE AT END BENT




SECTION A-A




PILE SPLICE DETAILS

\*\* POSITION OF PILE DURING WELDING.

### PILE SPLICE DETAILS



SECTION B-B



BAR	SPLICE LENGTH
#10 B1	7'-11"
#10 B2	11'-1"
#5 B3	3'-0"
#4 B5 & #4 K1	2'-5"

### BILL OF MATERIAL

END BENT #1					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	8	#10	1	39'-11"	1374
B2	8	#10	1	41'-6"	1429
B3	4	#5	STR	36'-1"	151
B4	19	#4	STR	3'-5"	43
B5	12	#4	STR	24'-8"	198
B6	4	#4	STR	30'-0"	80
B7	16	#4	STR	3'-2"	34
H1	10	#6	2	7'-10"	118
H2	10	#6	2	8'-2"	123
H3	10	#6	3	8'-8"	130
H4	10	#6	3	8'-4"	125
K1	30	#4	STR	24'-8"	494
K2	8	#4	STR	4'-1"	22
S1	90	#5	4	8'-7"	806
S2	90	#5	5	4'-4"	407
S3	30	#4	6	6'-6"	130
U1	61	#4	7	5'-2"	211
U2	27	#4	7	6'-5"	116
V1	122	#5	STR	6'-8"	848
V2	26	#5	STR	8'-6"	231
V3	26	#5	STR	8'-4"	226

REINFORCING STEEL = 7296 LBS

CLASS "A" CONCRETE BREAKDOWN

POUR #1  
CAP, LOWER PART OF WINGS AND 31.0 C.Y. PILE COLLARS

POUR #2  
BACKWALL AND UPPER PART OF WINGS 15.7 C.Y.

CLASS "A" CONCRETE TOTAL 46.7 C.Y.

HP 12 x 53 STEEL PILES  
No. 15 LIN. FT. 1200


PILE REDRIVES 8 EACH

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-

SHEET 3 OF 3

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH

SUBSTRUCTURE  
END BENT #1




DRAWN BY: J.B. WILSON DATE: 6/25/09  
CHECKED BY: M.D. PISO DATE: 10/21/09

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-17
1			3			TOTAL SHEETS 28
2			4			












SECTION A-A



SECTION B-B



BILL OF MATERIAL					
BENT #1					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	14	#10	1	36'-4"	2189
B2	7	#11	STR	58'-10"	2188
B3	6	#5	STR	58'-10"	368
B4	7	#4	STR	22'-6"	105
M1	48	#10	1	9'-8"	1997
S1	87	#5	2	12'-0"	1089
T1	64	#6	STR	7'-6"	721
T2	60	#6	4	8'-10"	796
T3	56	#7	4	9'-2"	1049
U1	55	#4	3	6'-10"	251
U2	6	#4	3	6'-8"	27
U3	6	#4	3	6'-6"	26
V1	48	#10	1	20'-6"	4234
REINFORCING STEEL				=	15040 LBS
SPIRAL COLUMN REINFORCING STEEL					
SP-1	4	**	5	599'-7"	1602 LBS.
SPIRAL COLUMN REINFORCING STEEL					1602 LBS.
CLASS A CONCRETE BREAKDOWN					
POUR #1 FOOTINGS				CU. YD.	30.8
POUR #2 COLUMNS				CU. YD.	17.9
POUR #3 CAP				CU. YD.	38.7
TOTAL CLASS A CONCRETE				CU. YD.	87.4
HP 12 x 53 STEEL PILES					
No. 36				LIN. FT.	1980
PILE REDRIVES				EA.	18



PLAN OF COLUMNS AND FOOTINGS

FOOTING DIMENSIONS AND REINFORCING STEEL ARE TYPICAL EACH FOOTING. PILE ARRANGEMENT IN FOOTING #4 IS NOT SHOWN, BUT IS IDENTICAL TO PILE ARRANGEMENT IN FOOTING #1.


\*\* THE SP-1 SPIRAL REINFORCING STEEL SHALL BE W20 OR D-20 COLD DRAWN WIRE OR #4 PLAIN OR DEFORMED BAR.

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-

SHEET 2 OF 2

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH

SUBSTRUCTURE  
BENT #1




DRAWN BY: J.B. WILSON DATE: 9/25/09  
CHECKED BY: B.N. BARODAWALA DATE: 10/6/09

23-JUN-2010 11:29  
R:\Structures\Final Plans\R0061c.sd.bl.dgn  
tcogghs


REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS: 28







PLAN OF LEFT WING - W1




PLAN OF RIGHT WING - W2




ELEVATION OF LEFT WING - W1



SECTION X-X



SECTION Y-Y




ELEVATION OF RIGHT WING - W2

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

SUBSTRUCTURE  
 END BENT #2




DRAWN BY: J.B. WILSON DATE: 6/30/09  
 CHECKED BY: M.D. PISO DATE: 10/21/09

23-JUN-2010 11:28  
 R:\Structures\Final Plans\R0061c.sd,eb,dgn  
 tcoggins

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-21
1			3			TOTAL SHEETS
2			4			28






BAGGED STONE AND PIPE SHALL BE PLACED IMMEDIATELY AFTER COMPLETION OF END BENT EXCAVATION. PIPE MAY BE EITHER CONCRETE, CORRUGATED STEEL, CORRUGATED ALUMINUM ALLOY, OR CORRUGATED PLASTIC. PERFORATED PIPE WILL NOT BE ALLOWED.

BAGGED STONE SHALL REMAIN IN PLACE UNTIL THE ENGINEER DIRECTS THAT IT BE REMOVED. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF SILT ACCUMULATIONS AT BAGGED STONE WHEN SO DIRECTED BY THE ENGINEER. BAGS SHALL BE REMOVED AND REPLACED WHENEVER THE ENGINEER DETERMINES THAT THEY HAVE DETERIORATED AND LOST THEIR EFFECTIVENESS.


NO SEPARATE PAYMENT WILL BE MADE FOR THIS WORK AND THE ENTIRE COST OF THIS WORK SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR THE SEVERAL PAY ITEMS.

### TEMPORARY DRAINAGE AT END BENT



\*\* POSITION OF PILE DURING WELDING.



### PILE SPLICE DETAILS



### BILL OF MATERIAL

END BENT #2					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	8	#10	1	39'-11"	1374
B2	8	#10	1	41'-6"	1429
B3	4	#5	STR	36'-1"	151
B4	19	#4	STR	3'-5"	43
B5	12	#4	STR	24'-8"	198
B6	4	#4	STR	30'-0"	80
B7	16	#4	STR	3'-2"	34
H1	10	#6	2	7'-10"	118
H2	10	#6	2	8'-2"	123
H3	10	#6	3	8'-8"	130
H4	10	#6	3	8'-4"	125
K1	30	#4	STR	24'-8"	494
K2	8	#4	STR	4'-1"	22
S1	90	#5	4	8'-7"	806
S2	90	#5	5	4'-4"	407
S3	30	#4	6	6'-6"	130
U1	61	#4	7	5'-2"	211
U2	27	#4	7	6'-5"	116
V1	122	#5	STR	6'-8"	848
V2	26	#5	STR	8'-6"	231
V3	26	#5	STR	8'-4"	226
REINFORCING STEEL					= 7296 LBS
CLASS "A" CONCRETE BREAKDOWN					
POUR #1					
CAP LOWER PART OF WINGS AND 31.1 C.Y. PILE COLLARS					
POUR #2					
BACKWALL AND UPPER PART OF WINGS 15.7 C.Y.					
CLASS "A" CONCRETE TOTAL					46.8 C.Y.
HP 12 x 53 STEEL PILES					
No. 15 LIN. FT. 1125					
PILE REDRIVES					8 EACH

BAR	SPLICE LENGTH
#10 B1	7'-11"
#10 B2	11'-1"
#5 B3	3'-0"
#4 B5 & #4 K1	2'-5"



PROJECT NO. R-0061C

COLUMBUS COUNTY

STATION: 32+50.00 -L-

SHEET 3 OF 3

STATE OF NORTH CAROLINA				
DEPARTMENT OF TRANSPORTATION				
RALEIGH				
SUBSTRUCTURE				
END BENT #2				
REVISIONS				SHEET NO.
NO.	BY:	DATE:	NO.	DATE:
1			3	
2			4	
				S-22
				TOTAL SHEETS 28

DRAWN BY: J.B. WILSON DATE: 6/25/09

CHECKED BY: M.D. PISO DATE: 10/21/09

NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 14045 TWO INCHES COLORED


6/23/10

**GENERAL NOTES**

SLOPE PROTECTION SHALL BE PLACED UNDER THE ENDS OF THE BRIDGE AS SHOWN IN THE DETAILS. STRAIGHT EDGING WILL NOT BE REQUIRED UNLESS, IN THE OPINION OF THE ENGINEER, VISUAL INSPECTION INDICATES A NEED FOR IT. MEASUREMENT AND PAYMENT SHALL BE AS PRESCRIBED IN SECTION 462 OF THE STANDARD SPECIFICATIONS. FOR BERM WIDTH, SEE GENERAL DRAWING.


**ALTERNATE "A"**

ALTERNATE "A" SHALL CONSIST OF 4" POURED-IN-PLACE CONCRETE PAVING AS SHOWN IN THE DETAILS ON THIS SHEET. CONCRETE SHALL BE CLASS "B", THE CONCRETE SURFACE SHALL BE FLOATED WITH A WOODEN FLOAT AND FINISHED. WELDED WIRE FABRIC REINFORCING SHALL BE 6 X 6 - W1.4 X W1.4, 60" WIDE. SLOPE PROTECTION SHALL BE POURED IN 5' STRIPS AS SHOWN IN THE "POURING DETAIL" WITH 2'-0" LONG #4 BARS PLACED ALONG THE SLOPE BETWEEN STRIPS AT 1'-6" MAXIMUM SPACING. SLOPE PROTECTION MAY BE POURED IN ALTERNATE 4' AND 5' STRIPS AS SHOWN IN THE "OPTIONAL POURING DETAIL" WITH ADJACENT RUNS OF WELDED WIRE FABRIC LAPPING AT LEAST 6". THE COST OF THE WELDED WIRE FABRIC AND #4 BARS, IF USED, SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE BID PER SQUARE YARD FOR SLOPE PROTECTION.



POUR A 4'-0" STRIP FIRST. STRIP WIDTHS MAY VARY IN CURVED PORTION.

**OPTIONAL POURING DETAIL**




STRIP WIDTHS MAY VARY IN CURVED PORTION.


**POURING DETAIL**

BRIDGE @ STA. 32+50.00 -L-	4" INCH SLOPE PROTECTION	* WELDED WIRE FABRIC 60 INCHES WIDE
	SQUARE YARDS	APPROX. L.F.
END BENT 1	402	804
END BENT 2	402	804


\* QUANTITY SHOWN IS BASED ON 5' POURS.




**SECTION A-A**




**SECTION B-B**



**PLAN**



**PLAN - END BENT WITH SWEEPED BACK WINGS - SKEWED (1 1/2:1 SLOPE)**



**SECTION ALONG C ROADWAY WHEN FILL CATCHES IN DITCH**

**DETAILS FOR ALTERNATE "A"**


PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

STANDARD  
 SLOPE PROTECTION  
 DETAILS


REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS: 28




ASSEMBLED BY : J.B. WILSON DATE : 7/07/09  
 CHECKED BY : M.D. PISO DATE : 9/10/09  
 DRAWN BY : ELR 5/92 REV. 7/10/01 LES/RDR  
 CHECKED BY : GRP 6/92 REV. 5/7/03 RWW/JTE  
 REV. 5/1/06 TLA/GM






PLAN @ END BENT #1 PLAN @ END BENT #2

DIMENSIONS SHOWN ARE TYPICAL FOR BOTH APPROACH SLABS




SECTION THRU SLAB

SHOWING SECTION WITHOUT CONCRETE WEARING SURFACE



SECTION N-N



END OF CURB WITHOUT SHOULDER BERM GUTTER

NOTES

APPROACH SLAB SHALL NOT BE CONSTRUCTED PRIOR TO COMPLETION OF THE BRIDGE DECK.

FOR REINFORCED BRIDGE APPROACH FILL INCLUDING FABRIC, IMPERMEABLE GEOMEMBRANE, 4" Ø DRAINAGE PIPE, #78M STONE, AND SELECT MATERIAL, SEE ROADWAY PLANS.

AREA BETWEEN THE WINGWALL AND APPROACH SLAB SHALL BE GRADED TO DRAIN THE WATER AWAY FROM THE FILL FACE OF THE BRIDGE AND SHALL BE PAVED. SEE ROADWAY PLANS.

THE 6" COMP. A.B.C. SHALL BE FLUSH WITH THE ROADWAY END OF THE APPROACH SLAB AND SHALL EXTEND 1'-0" OUTSIDE EACH EDGE OF THE APPROACH SLAB.

THE CONTRACTOR MAY USE 4" TYPE B-25.0B ASPHALT CONCRETE BASE COURSE IN LIEU OF 6" COMP. A.B.C. IF THIS OPTION IS USED, THE BASE COURSE SHALL BE FLUSH WITH THE ROADWAY END OF THE APPROACH SLAB, AND THE WIDTH SHALL BE THE SAME AS THAT OF THE APPROACH SLAB.

THE CONTRACTOR MAY USE 5" CLASS "A" CONCRETE BASE IN LIEU OF 6" COMP. A.B.C. IF THIS OPTION IS USED, THE CONCRETE BASE SHALL BE FLUSH WITH THE ROADWAY END OF THE APPROACH SLAB, AND THE WIDTH SHALL BE THE SAME AS THAT OF THE APPROACH SLAB. THE CONCRETE SHALL BE FINISHED TO A SMOOTH SURFACE AND A LAYER OF 30 LB ROOFING FELT SHALL BE PLACED BETWEEN THE CONCRETE BASE AND THE APPROACH SLAB TO PREVENT BOND. THE APPROACH SLAB SHALL NOT BE CAST UNTIL THE CONCRETE BASE HAS REACHED AN AGE OF THREE CURING DAYS.

THE JOINT SHALL BE SAWSAWED PRIOR TO THE CASTING OF THE BARRIER RAIL.

WITH EVAZOTE JOINT SEAL

FOR EVAZOTE JOINT SEALS, SEE SPECIAL PROVISIONS.


THE NOMINAL UNCOMPRESSED SEAL WIDTH OF THE EVAZOTE JOINT SEAL SHALL BE 2 1/2".

FOR ELASTOMERIC CONCRETE, SEE SPECIAL PROVISIONS.

BILL OF MATERIAL					
FOR ONE APPROACH SLAB (2 REQ'D.)					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
*A1	75	#4	STR	21'-4"	1069
A2	78	#4	STR	21'-2"	1103
*B1	106	#5	STR	23'-7"	2607
B2	106	#6	STR	24'-7"	3914
REINFORCING STEEL				LBS.	5017
*EPOXY COATED REINFORCING STEEL				LBS.	3676
CLASS AA CONCRETE				C. Y.	50.3

SPLICE LENGTH CHART	
BAR	MIN. SPLICE
*4 A1	2'-0"
*4 A2	1'-9"






ASSEMBLED BY : J.B. WILSON DATE : 7/01/09  
 CHECKED BY : M.D. PISO DATE : 9/11/09  
 DRAWN BY : EEM 3/95 REV. 7/10/01 LES/RDR  
 CHECKED BY : VAP 3/95 REV. 5/7/03R RWW/JTE  
 REV. 5/1/06R KMM/GM



PROJECT NO. R-0061C  
 COLUMBUS COUNTY  
 STATION: 32+50.00 -L-  
 SHEET 1 OF 2

REVISIONS						SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:	S-24	
1			3			TOTAL SHEETS 28	
2			4				






**SECTION B-B**  
**JOINT SEAL DETAILS @ END BENT**


EVAZOTE JOINT SEAL TO BE CUT, HEAT WELDED AND TURNED UP PARALLEL TO SLOPED FACE OF THE BARRIER RAIL.  
THE JOINT SHALL BE SAWED PRIOR TO THE CASTING OF THE BARRIER RAIL.

ELASTOMERIC CONCRETE	
END BENT NO.	ELASTOMERIC CONCRETE * (CU. FT.)
1	10.1
2	10.1
TOTAL	20.2

\* BASED ON THE MINIMUM BLOCKOUT SHOWN.




NOTE: IMMEDIATELY AFTER THE CONSTRUCTION OF THE APPROACH SLAB, THE CONTRACTOR SHALL PROVIDE TEMPORARY BERM AND SLOPE DRAIN. CONTRACTOR SHALL GRADE TO PIPE INLET AND PROVIDE EROSION RESISTANT MATERIAL AS SHOWN. THE EROSION RESISTANT MATERIAL SHALL BE EITHER 1) ASPHALT PLANT MIX, TYPE 1 OR TYPE 2, MIN. 2\"/>



**TEMPORARY BERM AND SLOPE DRAIN DETAILS**

(TO BE USED WHEN SHOULDER BERM GUTTER IS REQUIRED)




NOTE: IF THE APPROACH SLAB IS NOT CONSTRUCTED IMMEDIATELY AFTER THE BACKFILLING OF THE END BENT EXCAVATION, GRADE TO DRAIN TO THE BOTTOM OF THE SLOPE AND PROVIDE EROSION RESISTANT MATERIAL, SUCH AS FIBERGLASS ROVING OR AS DIRECTED BY THE ENGINEER TO PREVENT SOIL EROSION AND TO PROTECT THE AREA ADJACENT TO THE STRUCTURE. THE CONTRACTOR WILL BE REQUIRED TO REMOVE THESE MATERIALS PRIOR TO CONSTRUCTION OF THE APPROACH SLAB.

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-

SHEET 2 OF 2

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STANDARD					
BRIDGE APPROACH SLAB DETAILS					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					SHEET NO. S-25
					TOTAL SHEETS 28



ASSEMBLED BY : J.B. WILSON	DATE : 7/01/09
CHECKED BY : M.D. PISO	DATE : 9/11/09
DRAWN BY : FCJ	11/88
CHECKED BY : ARB	11/88
REV. 10/17/00	RWW/LES
REV. 5/7/03	RWW/JTE
REV. 5/1/06R	MAA/KMM

OVERHANG BRACKET CALCULATION INSTRUCTIONS

AASHTO SHAPES - TYPES III, IV, V, AND VI

- RECORD KNOWN INFORMATION ON "BRIDGE OVERHANG BRACKET SUMMARY" ON SHEET 2
- CALCULATE THE MAXIMUM SCREED LOAD PER BRACKET (SLPB) WITH AN ESTIMATED  $R = 1.5$ .  $SLPB = R \times W$ . ROUND VALUE UP TO NEAREST SLPB VALUE INDICATED ON APPROPRIATE TABLE 1-1, 1-2, 1-3, OR 1-4.
- WITH THE ESTIMATED SLPB, OVERHANG SLAB THICKNESS, "K" VALUE, AND 45° HANGER SAFE WORKING LOAD (SWL), ENTER THE APPROPRIATE TABLE 1-1, 1-2, 1-3, OR 1-4 (BASED ON OVERHANG DIMENSION) AND DETERMINE THE BRACKET SPACING, S.
- CALCULATE S/D1 AND S/D2, ROUNDING UP TO NEAREST VALUE IN TABLE 2. ENTER TABLE 2 AND DETERMINE R VALUE.
- CALCULATE REVISED SLPB. ROUND VALUE UP TO NEAREST SLPB VALUE INDICATED ON APPROPRIATE TABLE 1-1, 1-2, 1-3, OR 1-4.
- WITH THE REVISED SLPB, OVERHANG SLAB THICKNESS, "K" VALUE AND 45° HANGER SAFE WORKING LOAD (SWL), ENTER THE APPROPRIATE TABLE 1-1, 1-2, 1-3 OR 1-4 (BASED ON OVERHANG DIMENSION) AND DETERMINE REVISED BRACKET SPACING, S.
- CONTINUE ITERATIONS OF STEPS 4-6 UNTIL THE REVISED BRACKET SPACING, S, IS THE SAME AS THE PREVIOUS S VALUE.
- CHECK LUMBER JOIST SPACING: WITH BRACKET SPACING VALUE, S, ROUND THIS VALUE UP TO THE NEAREST VALUE OF ALLOWABLE SPAN LENGTH OF JOIST OF TABLE 3. USING THIS VALUE, ALONG WITH THE AVERAGE OVERHANG SLAB THICKNESS AND THE LUMBER JOIST SIZE, DETERMINE JOIST SPACING FROM TABLE 3. IF NECESSARY, ADJUST LUMBER JOIST SIZE AND/OR JOIST SPACING TO MEET ALLOWABLE SPAN LENGTH OF JOIST.
- CONVERSELY, IF THE DESIRED JOIST SPACING IS KNOWN, USE THIS ALONG WITH THE AVERAGE OVERHANG SLAB THICKNESS AND THE LUMBER JOIST SIZE TO DETERMINE IF ALLOWABLE SPAN LENGTH OF JOIST IS GREATER THAN THE BRACKET SPACING, S. IF NECESSARY, ADJUST LUMBER JOIST SIZE TO MEET REQUIREMENTS OF ALLOWABLE SPAN LENGTH OF JOIST AND JOIST SPACING.
- RECORD REMAINING INFORMATION ON "BRIDGE OVERHANG BRACKET SUMMARY" FORM.
- SUBMIT FORM AND CALCULATIONS FOR REVIEW AND APPROVAL.

TABLE 1-1 (FOR USE ON UP TO 2'-0" OVERHANG & 54" HORIZONTAL LEG LENGTH OF THE OVERHANG BRACKET)

AVG. SLAB THICKNESS (in)	BRACKET DIMENSION (in)	SCREED LOAD PER BRACKET									45° HANGER SWL (lbs)
		2500 lbs.	2250 lbs.	2000 lbs.	1750 lbs.	1500 lbs.	1250 lbs.	1000 lbs.	750 lbs.	0 lbs.	
10	30	3'-6"	4'-0"	4'-5"	2'-1"	2'-7"	3'-2"	3'-8"	4'-2"	5'-9"	4000
	40	3'-6"	4'-0"	4'-5"	2'-1"	2'-7"	3'-2"	3'-8"	4'-2"	5'-9"	6000
	50	3'-6"	4'-0"	4'-5"	2'-1"	2'-7"	3'-2"	3'-8"	4'-2"	5'-9"	6000
12	30	3'-2"	3'-7"	4'-1"	2'-4"	2'-10"	3'-4"	3'-9"	5'-2"	4000	
	40	3'-2"	3'-7"	4'-1"	2'-4"	2'-10"	3'-4"	3'-9"	5'-2"	6000	
	50	3'-2"	3'-7"	4'-1"	2'-4"	2'-10"	3'-4"	3'-9"	5'-2"	6000	
14	30	2'-10"	3'-4"	3'-9"	2'-2"	2'-7"	3'-0"	3'-5"	4'-9"	4000	
	40	2'-10"	3'-4"	3'-9"	2'-2"	2'-7"	3'-0"	3'-5"	4'-9"	6000	
	50	2'-10"	3'-4"	3'-9"	2'-2"	2'-7"	3'-0"	3'-5"	4'-9"	6000	
16	30	2'-8"	3'-0"	3'-5"	2'-0"	2'-4"	2'-9"	3'-2"	4'-4"	4000	
	40	2'-8"	3'-0"	3'-5"	2'-0"	2'-4"	2'-9"	3'-2"	4'-4"	6000	
	50	2'-8"	3'-0"	3'-5"	2'-0"	2'-4"	2'-9"	3'-2"	4'-4"	6000	

TABLE 1-2 (FOR USE ON OVER 2'-0" TO 2'-6" OVERHANG & 54" HORIZONTAL LEG LENGTH OF THE OVERHANG BRACKET)

AVG. SLAB THICKNESS (in)	BRACKET DIMENSION (in)	SCREED LOAD PER BRACKET									45° HANGER SWL (lbs)
		2500 lbs.	2250 lbs.	2000 lbs.	1750 lbs.	1500 lbs.	1250 lbs.	1000 lbs.	750 lbs.	0 lbs.	
10	30	3'-1"	3'-6"	4'-0"	2'-4"	2'-9"	3'-3"	3'-8"	5'-1"	4000	
	40	3'-1"	3'-6"	4'-0"	2'-4"	2'-9"	3'-3"	3'-8"	5'-1"	6000	
	50	3'-1"	3'-6"	4'-0"	2'-4"	2'-9"	3'-3"	3'-8"	5'-1"	6000	
12	30	2'-9"	3'-2"	3'-7"	2'-1"	2'-6"	2'-11"	3'-4"	4'-6"	4000	
	40	2'-9"	3'-2"	3'-7"	2'-1"	2'-6"	2'-11"	3'-4"	4'-6"	6000	
	50	2'-9"	3'-2"	3'-7"	2'-1"	2'-6"	2'-11"	3'-4"	4'-6"	6000	
14	30	2'-6"	2'-10"	3'-3"	2'-3"	2'-7"	3'-0"	4'-1"	4000		
	40	2'-6"	2'-10"	3'-3"	2'-3"	2'-7"	3'-0"	4'-1"	6000		
	50	2'-6"	2'-10"	3'-3"	2'-3"	2'-7"	3'-0"	4'-1"	6000		
16	30	2'-3"	2'-7"	2'-11"	2'-1"	2'-5"	2'-9"	3'-9"	4000		
	40	2'-3"	2'-7"	2'-11"	2'-1"	2'-5"	2'-9"	3'-9"	6000		
	50	2'-3"	2'-7"	2'-11"	2'-1"	2'-5"	2'-9"	3'-9"	6000		

TABLE 1-3 (FOR USE ON OVER 2'-6" TO 3'-0" OVERHANG & 54" HORIZONTAL LEG LENGTH OF THE OVERHANG BRACKET)

AVG. SLAB THICKNESS (in)	BRACKET DIMENSION (in)	SCREED LOAD PER BRACKET									45° HANGER SWL (lbs)
		2500 lbs.	2250 lbs.	2000 lbs.	1750 lbs.	1500 lbs.	1250 lbs.	1000 lbs.	750 lbs.	0 lbs.	
10	30				2'-1"	2'-6"	2'-11"	3'-4"	4'-6"	4000	
	40				2'-1"	2'-6"	2'-11"	3'-4"	4'-6"	6000	
	50	2'-9"	3'-2"	3'-7"	4'-0"	4'-5"	4'-10"	5'-3"	6'-7"	4000	
12	30				3'-11"	4'-3"	4'-8"	5'-0"	6'-1"	4000	
	40				3'-11"	4'-3"	4'-8"	5'-0"	6'-1"	6000	
	50	2'-5"	2'-10"	3'-2"	3'-6"	3'-11"	4'-3"	4'-8"	5'-0"	4000	
14	30				3'-2"	3'-6"	3'-10"	4'-2"	5'-6"	4000	
	40				3'-2"	3'-6"	3'-10"	4'-2"	5'-6"	6000	
	50	2'-2"	2'-6"	2'-10"	3'-2"	3'-6"	3'-10"	4'-2"	5'-6"	4000	
16	30				2'-11"	3'-2"	3'-6"	3'-10"	4'-1"	4000	
	40				2'-11"	3'-2"	3'-6"	3'-10"	4'-1"	6000	
	50	2'-0"	2'-4"	2'-7"	2'-11"	3'-2"	3'-6"	3'-10"	4'-1"	4000	

TABLE 1-4 (FOR USE ON OVER 3'-0" TO 3'-6" OVERHANG & 54" HORIZONTAL LEG LENGTH OF THE OVERHANG BRACKET)

AVG. SLAB THICKNESS (in)	BRACKET DIMENSION (in)	SCREED LOAD PER BRACKET									45° HANGER SWL (lbs)
		2500 lbs.	2250 lbs.	2000 lbs.	1750 lbs.	1500 lbs.	1250 lbs.	1000 lbs.	750 lbs.	0 lbs.	
10	30				2'-3"	2'-11"	3'-7"	4'-3"	5'-9"	4000	
	40				2'-3"	2'-11"	3'-7"	4'-3"	5'-9"	6000	
	50	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	4'-1"	4'-5"	5'-9"	4000	
12	30				2'-1"	2'-8"	3'-4"	3'-11"	5'-2"	4000	
	40				2'-1"	2'-8"	3'-4"	3'-11"	5'-2"	6000	
	50	2'-1"	2'-4"	2'-8"	3'-0"	3'-4"	3'-8"	4'-1"	4'-5"	4000	
14	30				2'-0"	2'-7"	3'-0"	3'-3"	3'-6"	4000	
	40				2'-0"	2'-7"	3'-0"	3'-3"	3'-6"	6000	
	50	2'-2"	2'-5"	2'-8"	3'-0"	3'-4"	3'-8"	4'-1"	4'-5"	4000	
16	30				2'-4"	2'-10"	3'-5"	4'-3"	5'-2"	4000	
	40				2'-4"	2'-10"	3'-5"	4'-3"	5'-2"	6000	
	50	2'-2"	2'-5"	2'-8"	3'-0"	3'-4"	3'-8"	4'-1"	4'-5"	4000	

DEFINITIONS

- SLPB = SCREED LOAD PER BRACKET (R x W)
- R = SCREED LOAD FACTOR, OBTAINED FROM TABLE 2
- W = WHEEL LOAD
- S = BRACKET SPACING
- T = AVERAGE SLAB THICKNESS
- SWL = SAFE WORKING LOAD
- K = DIMENSION DEFINED ON "BRIDGE OVERHANG BRACKET SUMMARY" ON SHEET 2
- L = OVERHANG MEASURED FROM EDGE OF TOP FLANGE TO EDGE OF SUPERSTRUCTURE


PROJECT NO. R-0061C  
COLUMBUS COUNTY  
STATION: 32+50.00 -L-

SHEET 1 OF 3

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
RALEIGH

STANDARD OVERHANG FALSEWORK

AASHTO TYPES  
III, IV, V, AND VI



REVISIONS				SHEET NO.
NO.	BY:	DATE:	NO.	DATE:
1			3	
2			4	

ASSEMBLED BY:	DATE:
CHECKED BY:	DATE:
DRAWN BY: R. WRIGHT 06/04	REV.
CHECKED BY: C. V. CHAO 06/04	




**BRIDGE OVERHANG BRACKET SUMMARY**

TOTAL SCREED WEIGHT = \_\_\_\_\_ LBS.  
 NUMBER OF SCREED WHEELS = \_\_\_\_\_  
 SCREED WHEEL LOAD (W) = \_\_\_\_\_ LBS.  
 SCREED LOAD PER BRACKET = \_\_\_\_\_ LBS.

PROJECT No. : \_\_\_\_\_  
 COUNTY : \_\_\_\_\_  
 STATION : \_\_\_\_\_  
 DESCRIPTION : \_\_\_\_\_

DATE : \_\_\_\_\_  
 DESIGN BY : \_\_\_\_\_  
 CHECK BY : \_\_\_\_\_



**OVERHANG FALSEWORK**

**NOTES**


DESIGN INCLUDES CONSTRUCTION LIVE LOAD 20 PSF ON THE AREA SUPPORTED AND 75 PLF AT THE OUTSIDE DECK OF OVERHANGS.

REQUIRED MINIMUM DIAGONAL LEG CAPACITY: 3600 LB WORKING LOAD


THE CONTRACTOR HAS THE OPTION OF SUBMITTING HIS OWN DESIGN FOR OVERHANG FALSEWORK IN ACCORDANCE WITH THE SPECIAL PROVISIONS.

SUBMITTALS UTILIZING THE INSTRUCTIONS AND PROCEDURES DESCRIBED ON SHEET 1 OF 3 SHALL BE IN ACCORDANCE WITH THE APPLICABLE SECTIONS OF THE SPECIFICATIONS AND SPECIAL PROVISIONS, EXCEPT THAT CALCULATIONS FOR OVERHANG FALSEWORK NEED NOT BE SEALED BY A REGISTERED ENGINEER.

FOR OVERHANG FALSEWORK BRACING DESIGN, SEE SHEET 3 OF 3.



4-WHEEL MACHINE



8-WHEEL MACHINE

TABLE 2: SCREED LOAD FACTOR "R"

4 WHEEL MACHINE	
S/D1	R
<= 1.0	1.00
1.1	1.09
1.2	1.17
1.3	1.23
1.4	1.29
1.5	1.33
1.6	1.38
1.7	1.41
1.8	1.44
1.9	1.47
2.0	1.50
2.2	1.55
2.4	1.58
2.6	1.62
2.8	1.64
3.0	1.67
3.5	1.71
4.0	1.75

		THE SCREED LOAD FACTOR R (FOR 8 WHEEL MACHINE)																	
		S/D <sub>2</sub>																	
		<= 1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.2	2.4	2.6	2.8	3.0	3.5	4.0
S/D <sub>1</sub>	<= 1.0	1.00	1.09	1.17	1.23	1.29	1.33	1.38	1.41	1.44	1.47	1.50	1.55	1.58	1.62	1.64	1.67	1.71	1.75
	1.1	1.09	1.18	1.26	1.32	1.38	1.42	1.47	1.50	1.54	1.56	1.59	1.64	1.67	1.71	1.73	1.76	1.81	1.84
	1.2	1.17	1.26	1.33	1.40	1.45	1.50	1.54	1.58	1.61	1.64	1.67	1.71	1.75	1.78	1.81	1.83	1.88	1.92
	1.3	1.23	1.32	1.40	1.46	1.52	1.56	1.61	1.64	1.68	1.70	1.73	1.78	1.81	1.85	1.87	1.90	1.95	1.98
	1.4	1.29	1.38	1.45	1.52	1.57	1.62	1.66	1.70	1.73	1.76	1.79	1.83	1.87	1.90	1.93	1.95	2.00	2.07
	1.5	1.33	1.42	1.50	1.56	1.62	1.67	1.71	1.75	1.78	1.81	1.83	1.88	1.92	1.95	1.98	2.00	2.10	2.17
	1.6	1.38	1.47	1.54	1.61	1.66	1.71	1.75	1.79	1.82	1.85	1.88	1.92	1.96	1.99	2.04	2.08	2.18	2.25
	1.7	1.41	1.50	1.58	1.64	1.70	1.75	1.79	1.82	1.86	1.89	1.91	1.96	2.00	2.05	2.11	2.16	2.25	2.32
	1.8	1.44	1.54	1.61	1.68	1.73	1.78	1.82	1.86	1.89	1.92	1.94	1.99	2.06	2.12	2.17	2.22	2.32	2.39
	1.9	1.47	1.56	1.64	1.70	1.76	1.81	1.85	1.89	1.92	1.95	1.97	2.04	2.11	2.18	2.23	2.28	2.38	2.45
	2.0	1.50	1.59	1.67	1.73	1.79	1.83	1.88	1.91	1.94	1.97	2.00	2.09	2.17	2.23	2.29	2.33	2.43	2.50
	2.2	1.55	1.64	1.71	1.78	1.83	1.88	1.92	1.96	1.99	2.04	2.09	2.18	2.26	2.32	2.38	2.42	2.52	2.59
2.4	1.58	1.67	1.75	1.81	1.87	1.92	1.96	2.00	2.06	2.11	2.17	2.26	2.33	2.40	2.45	2.50	2.60	2.67	
2.6	1.62	1.71	1.78	1.85	1.90	1.95	1.99	2.05	2.12	2.18	2.23	2.32	2.40	2.46	2.52	2.56	2.66	2.73	
2.8	1.64	1.73	1.81	1.87	1.93	1.98	2.04	2.11	2.17	2.23	2.29	2.38	2.45	2.52	2.57	2.62	2.71	2.79	
3.0	1.67	1.76	1.83	1.90	1.95	2.00	2.08	2.16	2.22	2.28	2.33	2.42	2.50	2.56	2.62	2.67	2.76	2.83	
3.5	1.71	1.81	1.88	1.95	2.00	2.10	2.18	2.25	2.32	2.38	2.43	2.52	2.60	2.66	2.71	2.76	2.86	2.93	
4.0	1.75	1.84	1.92	1.98	2.07	2.17	2.25	2.32	2.39	2.45	2.50	2.59	2.67	2.73	2.79	2.83	2.93	3.00	

TABLE 3: ALLOWABLE SPAN LENGTH OF JOISTS AND JOIST SPACINGS


AVG. SLAB THICKNESS (IN)	LUMBER JOIST SIZE (IN X IN)	JOIST SPACINGS			
		15 IN	12 IN	10 IN	8 IN
10	2 X 4	—	4' - 6"	4' - 9"	5' - 0"
	4 X 4	5' - 9"	6' - 3"	6' - 6"	6' - 7"
12	2 X 4	—	4' - 3"	4' - 9"	5' - 0"
	4 X 4	5' - 3"	6' - 0"	6' - 3"	6' - 5"
14	2 X 4	—	4' - 0"	4' - 6"	5' - 0"
	4 X 4	—	5' - 6"	6' - 0"	6' - 4"
16	2 X 4	—	4' - 0"	4' - 3"	4' - 9"
	4 X 4	—	5' - 3"	5' - 9"	6' - 3"

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH


STANDARD OVERHANG FALSEWORK  
 AASHTO TYPES III, IV, V, AND VI



ASSEMBLED BY:	DATE:
CHECKED BY:	DATE:
DRAWN BY: R. WRIGHT 06/04	REV.
CHECKED BY: C. V. CHAO 06/04	

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			28
2			4			






EXTERIOR GIRDER

INTERIOR GIRDER

DETAIL OF REQUIRED OVERHANG FALSEWORK BRACING SYSTEM



NOTES:

EACH #5 TIE BAR SHALL BE WELDED TO ONE STIRRUP LOOP AS SHOWN IN DETAIL "A". #5 TIE BARS SHALL BE WELDED TO TWO ADJACENT STIRRUPS OF THE EXTERIOR GIRDER AND THE ADJACENT INTERIOR GIRDER BETWEEN PERMANENT DIAPHRAGMS. WELD STEEL PLATES IN BETWEEN THE TIE BARS AND THE STIRRUP LOOP. WELDING TWO TIE BARS TO THE SAME STIRRUP LOOP SHALL NOT BE PERMITTED.

MAXIMUM SPACING BETWEEN THE BRACING (TIE BARS-TIMBER STRUT) IS 9'-0" CTS. #5 TIE BARS SHALL BE LOCATED OVER A TIMBER STRUT.

INSTALL TIE BARS AND TIMBER STRUTS PRIOR TO PLACEMENT OF CONCRETE OR SCREED WEIGHT ONTO THE OVERHANG FALSEWORK.

PROJECT NO. R-0061C  
COLUMBUS COUNTY  
 STATION: 32+50.00 -L-

SHEET 3 OF 3

STATE OF NORTH CAROLINA  
 DEPARTMENT OF TRANSPORTATION  
 RALEIGH

STANDARD OVERHANG FALSEWORK

AASHTO TYPES  
 III, IV, V, AND VI



Chang-Chuan Victor Chao  
 5-9-2010

DRAWN BY: R. WRIGHT 06/04 DATE : \_\_\_\_\_  
 CHECKED BY: C. V. CHAO 06/04 DATE : \_\_\_\_\_

07-MAY-2010 12:07  
 D:\wdir\vector\OverhangFalsework\TIEBAR&STRUT\R-0061C.TYPE.IV\R0061COverHangSheets.dgn  
 vchao

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-28
1			3			TOTAL SHEETS
2			4			28

## STANDARD NOTES

### DESIGN DATA:

SPECIFICATIONS	-----	A.A.S.H.T.O. (CURRENT)
LIVE LOAD	-----	SEE PLANS
IMPACT ALLOWANCE	-----	SEE A.A.S.H.T.O.
STRESS IN EXTREME FIBER OF		
STRUCTURAL STEEL - AASHTO M270 GRADE 36	-	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	-	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	-	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION		
GRADE 60	--	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	-----	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	-----	SEE A.A.S.H.T.O.
STRUCTURAL TIMBER - TREATED OR		
UNTREATED - EXTREME FIBER STRESS	-----	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	-----	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	-----	30 LBS. PER CU. FT. (MINIMUM)

### MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2006 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

### CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

### CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1-1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4" FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

### DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

### ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.  
ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.  
IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.  
DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

### REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.  
WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

### STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8" Ø SHEAR STUDS FOR THE 3/4" Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8" Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4" Ø STUDS BASED ON THE RATIO OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".  
EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.  
WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16 INCH OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

### HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.  
METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINIS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

### SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.

ENGLISH

JANUARY, 1990

STD. NO. SN