

NC Department of Transportation Preliminary Site Assessment State Project: U-3812 WBS Element: 34977.1.1

Talmadge S Shepherd Property
Parcel #7
May 6, 2010

AMEC Earth and Environmental, Inc. of North Carolina AMEC Project: 562113812

Troy / Hoizschuh

Engineering Technician

Helen P. Corley, L.G. Senior Project Manager





NC Department of Transportation Preliminary Site Assessment State Project: U-3812 WBS Element: 34977.1.1

Talmadge S Shepherd Property
Parcel #7
May 6, 2010

AMEC Earth and Environmental, Inc. of North Carolina AMEC Project: 562113812

Troy Holzschuh Engineering Technician Helen P. Corley, L.G. Senior Project Manager



TABLE OF CONTENTS

| 1.0 | INTRODUCTION | 1 |
|-----|----------------------------|---|
| | 1.1 Site Location | 1 |
| | 1.2 Site Description | 2 |
| 2.0 | GEOLOGY | 2 |
| | 2.1 Regional Geology | 2 |
| | 2.2 Site Geology | 2 |
| 3.0 | FIELD ACTIVITIES | 3 |
| | 3.1 Preliminary Activities | 3 |
| | 3.2 Site Reconnaissance | |
| | 3.3 Geophysical Survey | 3 |
| | 3.4 Well Survey | 4 |
| | 3.5 Soil Sampling | 4 |
| 4.0 | SOIL SAMPLING RESULTS | 5 |
| 5.0 | CONCLUSIONS | 5 |
| 6.0 | RECOMMENDATIONS | 6 |



TABLES

Table 1 Soil Sampling Analytical Results, DRO-GRO

FIGURES

Figure 1 Vicinity Map

Figure 2 Site Map with Sample Locations Figure 3 Site Map with Analytical Data

APPENDICES

Appendix A Photo Log

Appendix B Boring and Well Construction Logs

Appendix C Geophysical Report

Appendix D Laboratory Analytical Data



1.0 INTRODUCTION

In accordance with the North Carolina Department of Transportation (NCDOT) email, dated March 30, 2010, AMEC Earth and Environmental, Inc. of North Carolina (AMEC) has performed a Preliminary Site Assessment (PSA) for the Talmadge S. Shepherd Property (the Site) to be affected by a road improvement project along NC Highway (Hwy) 88 and NC Hwy 194. The Site is a residential property with one building that is identified as Parcel #7 within the NCDOT U-3812 design project. The property is located at 1586 NC Hwy 88 in West Jefferson, Ashe County, North Carolina.

NCDOT contracted AMEC to perform a PSA on the Talmadge S Shepherd Property due to the architectural style of the building indicating that it may have once operated as a garage or gas station. The PSA was performed to determine if soils have been impacted by petroleum compounds as a result of past or present uses of the property within the proposed expanded right-of-way (ROW). The investigation was specifically completed to determine the presence or absence of petroleum hydrocarbons along the proposed ROW. The investigation was conducted in accordance with AMEC's Technical and Cost proposal dated March 5, 2010.

The following report describes our field investigations and results of chemical analyses. It includes the evaluation of the analytical data with regards to the presence or absence of soil contamination within the proposed right-of-way and estimates the extent of soil contamination.

1.1 Site Location and History

The Talmadge S. Shepherd Property is located northeast of the intersection of NC Hwy 88 and NC Hwy 194 in West Jefferson, Ashe County, North Carolina. It is located within the Sedimentary and Metamorphic sediments of the Blue Ridge Belt Physiographic Province of western North Carolina. Figure 1 shows the site location and vicinity.

AMEC studied the NCDENR UST Database for Incident Management and Registered Facilities and did not find any incidents reported for this site.



1.2 Site Description

One multi-occupant residential building constructed of masonite siding and brick occupies the Site. The northern half of the building was being used as a residence and the southern half unoccupied as of the date of this PSA field activity. The proposed road widening will traverse the entire western road frontage of Parcel #7. Two Underground Storage Tanks (USTs) exist, on the southwestern portion of the parcel, immediately west of the southern portion of the building. No monitoring wells are located at this parcel; however a residential water well is located near the southern edge of the Parcel. Appendix A includes a photo log for Site 1.

All of the properties surrounding the Parcel are residential.

2.0 GEOLOGY

2.1 Regional Geology

The Talmadge S. Shepherd Property is located within the Ashe Metamorphic Suite and Tallulah Falls Formation group of the Blue Ridge Belt Physiographic Province of western North Carolina. The Ashe Metamorphic Suite and Tallulah Falls Formation group is amphibolite with intrusive pegmatites.

2.2 Site Geology

Site geology was observed through the sampling of six shallow direct push probe soil borings (SB) onsite. Borings extended to a total depth of eight feet below ground surface (bgs) or shallower in two borings due to refusal. Soils intercepted were fill overlying saprolite. The fill was tan to brown clayey silt, well sorted with sand and rock fragments. The saprolitic soil was orange-brown clayey silt with occasional crumbled quartz veins. Boring logs are presented in Appendix B.

Saturated conditions (ground water) were not encountered in any borings and the maximum total depth was eight feet bgs.



3.0 FIELD ACTIVITIES

3.1 Preliminary Activities

Prior to commencing field sampling activities at the site, several tasks were accomplished in preparation for the subsurface investigation. The Health and Safety Plan (HSP) was modified to include the site-specific health and safety information necessary for the field activities. North Carolina-1-Call was contacted to facilitate the location of underground utilities in the vicinity of selected boring locations SAEDACCO (South Atlantic Environmental Drilling and Construction Co.) of Fort Mill, South Carolina was retained by AMEC to perform the direct push sampling for soil borings. AMEC coordinated with Schnabel Engineering South (Schnabel) who performed two geophysical surveys (electromagnetic and ground penetrating radar) onsite during March. The geophysical results were reviewed and discussed at the completion of each survey. Prism Laboratories, Inc. was contacted for acquisition of sample bottles.

3.2 Site Reconnaissance

AMEC personnel completed site reconnaissance on February 26, 2010. The area was visually examined for the presence of any UST or areas/obstructions that could potentially affect the subsurface investigation and boring locations were marked. Boring locations were marked on March 31, 2010.

3.3 Geophysical Survey

Schnabel performed the geophysical surveys on March 15 and 23, 2010. Schnabel utilized a Geonics EM61-MK2 to perform the electromagnetic induction surveys and a Geophysical Survey Systems SIR-3000 to conduct the ground-penetrating radar (GPR) investigations. These instruments are specifically calibrated to detect metal anomalies that are buried deeply and are characteristically large. The data collected by Schnabel indicates two probable underground storage tanks present west of the southern portion of the building and just outside of the proposed expanded ROW on Parcel # 7. The GPR data suggests that the northern UST is buried approximately 1.5-2.5 feet below ground surface and measures 3.5 feet in diameter by approximately eight feet long (560 gallon capacity). The southern UST is buried approximately 0.5-1.5. feet below ground surface and measures 3.5



feet in diameter and approximately eight feet long (560 gallon capacity). The complete geophysical report can be found in Appendix C.

3.4 Well Survey

No well survey was performed as part of this PSA; however a residential water supply well was noted near the southern edge of the Parcel as shown in Figure 2.

3.5 Soil Sampling

Soil boring occurred on April 9, 2010 at Parcel #7. Six direct push soil borings were conducted within the proposed expanded ROW on Parcel #7. Figure 2 presents the Site Map with sample locations and identifications. Soil borings were located within the proposed expanded ROW, using a focused soil boring placement pattern to target potential soil contamination near the probable USTs. Borings SB-1 through SB-5 were placed in close proximity to the probable USTs, while SB-6 was located to the south near the Parcel edge.

No signs of staining, odor or significant Photo Ionization Detector (PID) reading were detected in any of the soil borings. Soil samples were collected in accordance with EPA protocols in laboratory-supplied containers. The soil samples for Total Petroleum Hydrocarbons (TPH) –Gasoline Range Organics (GRO) analysis were collected using the 5030 prep method with methanol preservation. Samples for TPH-Diesel Range Organics (DRO) analysis were collected in 4oz. glass containers. Once placed in the containers, the samples were labeled with the sample number, time of collection, date of collection, name of the collector, and the requested analysis. The samples were packed on ice, and then hand delivered to Prism Laboratories, a North Carolina Certified Laboratory following proper chain-of-custody procedures.



4.0 SOIL SAMPLING RESULTS

AMEC conducted soil sampling at the Site on April 9, 2010. The purpose of the sampling was to determine if releases of petroleum hydrocarbons had occurred, and if so, to estimate the volume of soil that might require special handling during construction activities. The sampling was accomplished using direct push methods accompanied by field screening for organic vapors with a PID. The laboratory results with PID readings are tabulated in Table 1 and shown on Figure 3.

A minimum of one soil sample was collected from each of the 6 completed soil borings from Parcel #7. Typically, when impacted soil is identified, additional soil samples are obtained. PID readings did not warrant any additional samples. Analyses of soil samples for DRO and GRO did not indicate detectable concentrations in any of the 6 samples. Copies of the original laboratory report and chain-of-custody documentation are included as Appendix D.

5.0 CONCLUSIONS

The following conclusions are based upon AMEC's evaluation of field observations and laboratory analyses of samples collected from the Site on April 9, 2010.

- As of the date of the PSA field activities, the northern portion of the building was used as a residence while the southern building portion was unoccupied.
- Two probable USTs were identified just east beyond the proposed expanded ROW.
- Laboratory analyses of soil samples determined that GRO and DRO were not present above the 10 mg/kg reporting limit.



6.0 RECOMMENDATIONS

If NCDOT acquires Parcel #7, the Talmadge S. Shepherd Property, the two USTs must be closed by removal per the UST guidelines, thus requiring additional sampling.

If NCDOT does not acquire Parcel #7, as road improvement activities approach the ROW caution should be exercised so as not to intercept the UST or any previously unknown impacted soil. In the event that NCDOT encounters potential impacted soil , AMEC recommends the following action:

 Segregation during soil excavation then proper disposal of petroleum-impacted soil from the proposed roadway improvement during construction operations.

6



Table 1 Soil Sampling Analytical Results, DRO-GRO Parcel 7 Ashe County PSA Jefferson, North Carolina

| SAMPLE | | SAMPLE DEPTH | PID | EPA Method 8015B | | |
|------------------|----------|--------------|----------------|------------------|-------------|--|
| SAMPLE ID | DATE | (ft bgs) | READINGS (ppm) | DRO (mg/kg) | GRO (mg/kg) | |
| NC Action Levels | | | 10 | 10 | | |
| P7-SB-1 | 4/9/2010 | 5 - 6 | 0.0 | <9.3 | <6.6 | |
| P7-SB-2 | 4/9/2010 | 4 - 5 | 0.0 | <8.1 | <5.8 | |
| P7-SB-3 | 4/9/2010 | 5 - 6 | 0.0 | <9.0 | <6.5 | |
| P7-SB-4 | 4/9/2010 | 5 - 6 | 0.0 | <8.6 | <6.1 | |
| P7-SB-5 | 4/9/2010 | 4 - 5 | 0.0 | <8.9 | <6.4 | |
| P7-SB-6 | 4/9/2010 | 4 - 5 | 0.0 | <9.8 | <7.0 | |

NOTES:


bgs = below ground surface; ppm = parts per million


Bold Concentrations Exceed Action Levels


DRO = Diesel Range Organics


GRO = Gasoline Range Organics

Standards derived from the North Carolina UST Section Guidelines for Assessment and Corrective Action









APPENDIX A

PHOTO LOG



Photo No. 1

Date: 02/26/10

Direction Photo Taken:

Southeast

Description:

View of Parcel 7 Proposed ROW



Photo No. 2

Date:

04/09/10

Direction Photo Taken:

North

Description:

View of one of the two probable UST's



APPENDIX B

BORING LOGS



AMEC Earth & Environmental, Inc. BORING LOG

| Boring/Well No.: P7-SB1 (5-6) | Site Name: Parcel 7 |
|-------------------------------|--|
| Date: 4-9-10 | Location: West Jefferson, Ashe Co., NC |
| Job No.: 562113812 | Sample Method: Direct Push |
| AMEC Rep: Troy Holzschuh | Drilling Method: Direct Push |
| Drilling Company: SAEDACCO | Driller Name/Cert #: Keith Speece - 2856 |

Remarks:

| Depth (ft BLS) | PID/OVA Reading (ppm) | Blow Counts | |
|-------------------|-----------------------------|-------------|---|
| 0-0.5 | | | Asphalt/Aggregate |
| 0.5-5 | 0 | | (Fill) Tan, poorly sorted, clayey silt with sand and rock, damp |
| 5-6 | 0 | | Orange, well sorted, clayey silt, damp |
| 6-6.5 | | | Granite |
| 6.5-8 | 0 | | Orange, well sorted, clayey silt, damp |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | - | | |
| | - | | |
| | | | |
| | | | |
| | - | | |
| | | | |
| | | | |
| | | | |
| | | WELL CONS | TRUCTION DETAILS (If Applicable) |
| Well Type/Dian | neter: | | Outer Casing Interval: |
| Total Depth: | | | Outer Casing Diameter: |
| Screen Interval | : | | Bentonite Interval: |
| Sand Interval: | | | Slot Size: |
| Grout Interval: | | | Static Water Level: |



AMEC Earth & Environmental, Inc.

| amec BORING LOG | | | | | |
|---------------------|-----------------------------|-------------|--|--|--|
| Boring/Well I | No.: P7-SB2 (| 4-5) | Site Name: Parcel 7 | | |
| Date: 4-9-10 | | | Location: West Jefferson, Ashe Co., NC | | |
| Job No.: 562 | 113812 | | Sample Method: Direct Push | | |
| AMEC Rep: | Troy Holzsch | uh | Drilling Method: Direct Push | | |
| Drilling Com | pany: SAEDA | CCO | Driller Name/Cert #: Keith Speece - 2856 | | |
| Remarks: | | | | | |
| Depth (ft BLS) | PID/OVA Reading (ppm) | Blow Counts | Soil/Lithologic Description | | |
| 0-0.5 | | | Asphalt/Aggregate | | |
| 0.5-7 | 0 | | (Fill) Orange, poorly sorted, clayey silt with sand and rock, damp | | |
| | | | Refusal at 7' | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | T | | |

| | WELL CONSTRUCTION DETAILS (If Applicable) | | | | |
|---------------------|---|--|------------------------|--|--|
| Well Type/Diameter: | | | Outer Casing Interval: | | |
| Total Depth: | | | Outer Casing Diameter: | | |
| Screen Interval: | | | Bentonite Interval: | | |
| Sand Interval: | | | Slot Size: | | |
| Grout Interval: | | | Static Water Level: | | |



AMEC Earth & Environmental, Inc. BORING LOG

| Boring/Well No.: P7-SB3 (5-6) | Site Name: Parcel 7 |
|-------------------------------|--|
| Date: 4-9-10 | Location: West Jefferson, Ashe Co., NC |
| Job No.: 562113812 | Sample Method: Direct Push |
| AMEC Rep: Troy Holzschuh | Drilling Method: Direct Push |
| Drilling Company: SAEDACCO | Driller Name/Cert #: Keith Speece - 2856 |

Remarks:

| Depth (ft BLS) | PID/OVA Reading (ppm) | Blow Counts | Soil/Lithologic Description |
|-------------------|-----------------------------|-------------|---|
| 0-0.5 | | | Asphalt/Aggregate |
| 0.5-8 | 0 | | (Fill) Orange, poorly sorted, clayey silt with sand and rock, damp Refusal at 8' |
| | | | Refusal at 8' |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | 1 | |
| | | 1 | |
| | | + | |
| | | | |
| | | | |
| | | + | |
| | | 1 | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | + | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | WELL CONS | TRUCTION DETAILS (If Applicable) |
| Well Type/Diar | meter: | | Outer Casing Interval: |
| Total Depth: | | | Outer Casing Diameter: |
| Screen Interva | l: | | Bentonite Interval: |
| Sand Interval: | | | Slot Size: |
| Grout Interval: | | | Static Water Level: |



AMEC Earth & Environmental, Inc. BORING LOG

| Boring/Well No.: P7-SB4 (5-6) | Site Name: Parcel 93 |
|-------------------------------|--|
| Date: 4-9-10 | Location: West Jefferson, Ashe Co., NC |
| Job No.: 562113812 | Sample Method: Direct Push |
| AMEC Rep: Troy Holzschuh | Drilling Method: Direct Push |
| Drilling Company: SAEDACCO | Driller Name/Cert #: Keith Speece - 2856 |

Remarks:

Grout Interval:

| Depth (ft BLS) | PID/OVA Reading (ppm) | Blow Counts | Soil/Lithologic Description |
|-------------------|-----------------------------|-------------|---|
| 0-0.5 | | | Asphalt/Aggregate |
| | | | (Fill) Tan/Orange, poorly sorted, clayey silt with sand and rock, |
| 0.5-6 | 0 | | damp |
| 6-6.5 | | | Quartz |
| 6.5-8 | 0 | | Saprolite |
| | | | • |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | WELL CONS | TRUCTION DETAILS (If Applicable) |
| Vell Type/Dia | meter: | | Outer Casing Interval: |
| otal Depth: | | | Outer Casing Diameter: |
| Screen Interval: | | | Bentonite Interval: |
| and Interval: | | | Slot Size: |
| <u> </u> | | | 0 |

Static Water Level:



AMEC Earth & Environmental, Inc. BORING LOG

| Boring/Well No.: P7-SB5 (4-5) | Site Name: Parcel 7 |
|-------------------------------|--|
| | Location: West Jefferson, Ashe Co., NC |
| Job No.: 562113812 | Sample Method: Direct Push |
| AMEC Rep: Troy Holzschuh | Drilling Method: Direct Push |
| Drilling Company: SAEDACCO | Driller Name/Cert #: Keith Speece - 2856 |

Remarks:

Grout Interval:

| Depth (ft BLS) | PID/OVA Reading (ppm) | Blow Counts | · · | | | | | | |
|---------------------------|-----------------------------|-------------|---|--|--|--|--|--|--|
| 0-0.5 | | | Asphalt/Aggregate | | | | | | |
| 0.5-1.5 | 0 | | (Fill) Tan, poorly sorted, clayey silt with sand and rock, damp | | | | | | |
| 1.5-2 | | | Quartz | | | | | | |
| 2-8 | 0 | | Orange, poorly sorted, clayey silt, damp | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | WELL CONS | TRUCTION DETAILS (If Applicable) | | | | | | |
| /ell Type/Diar | neter: | | Outer Casing Interval: | | | | | | |
| otal Depth: | | | Outer Casing Diameter: | | | | | | |
| creen Interval | : | | Bentonite Interval: | | | | | | |
| Sand Interval: Slot Size: | | | | | | | | | |

Static Water Level:



AMEC Earth & Environmental, Inc. BORING LOG

| Site Name: Parcel 7 |
|--|
| Location: West Jefferson, Ashe Co., NC |
| Sample Method: Direct Push |
| Drilling Method: Direct Push |
| Driller Name/Cert #: Keith Speece - 2856 |
| |

Remarks:

| Depth | PID/OVA | | | | | | | | | |
|-----------------|---------|-------------|---|--|--|--|--|--|--|--|
| (ft BLS) | Reading | Blow Counts | Soil/Lithologic Description | | | | | | | |
| | (ppm) | | | | | | | | | |
| 0-0.5 | | | Asphalt/Aggregate | | | | | | | |
| 0.5-6 | 0 | | (Fill) Brown, poorly sorted, clayey silt with sand and rock, damp | | | | | | | |
| 6-8 | 0 | | Saprolite | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | + | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | WELL CONS | TRUCTION DETAILS (If Applicable) | | | | | | | |
| Well Type/Dia | meter: | | Outer Casing Interval: | | | | | | | |
| Total Depth: | | | Outer Casing Diameter: | | | | | | | |
| Screen Interva | l: | | Bentonite Interval: | | | | | | | |
| Sand Interval: | | | Slot Size: | | | | | | | |
| Grout Interval: | | | Static Water Level: | | | | | | | |

APPENDIX C GEOPHYSICAL SURVEY REPORT



April 26, 2010

Mr. Ethan Caldwell, LG, EI NCDOT, Geotechnical Engineering Unit 1020 Birch Ridge Drive Raleigh, NC 27610

RE: State Project: U-3812

WBS Element: 34977.1.1 County: Ashe

Description: Jefferson – NC 88 from NC 194 to US 221 Bus

Subject: Report on Geophysical Surveys for Parcel 7, West Jefferson, NC

Schnabel Engineering Project 09210013.17

Dear Mr. Caldwell:

Schnabel Engineering South, P.C. (Schnabel) is pleased to present this report on the geophysical surveys we conducted on the subject property. The report includes two 11x17 color figures and three 8.5x11 color figures.

1.0 INTRODUCTION

The work described in this report was conducted on March 15 and 23, 2010, by Schnabel under our 2009 contract with the NCDOT. The work was conducted within the accessible areas of the proposed right-of-way and/or easement as indicated by the NCDOT to support their environmental assessment of Parcel 7 (Talmadge S. Shepherd Property). Photographs of the parcel are included on Figure 1. The purpose of the geophysical surveys was to locate possible metal underground storage tanks (UST's) and associated metal product lines in the accessible areas of the right-of-way and/or easement.

The geophysical investigation consisted of electromagnetic (EM) induction surveys using a Geonics EM61-MK2 instrument. The EM61 metal detector is used to locate metal objects buried up to about eight feet below ground surface. Ground-penetrating radar (GPR) investigations of selected EM61 anomalies, including areas of reinforced concrete, and of planned boring locations were conducted using a Geophysical Survey Systems SIR-3000 system equipped with a 400 MHz antenna. Photographs of the equipment used are shown on Figure 2.

2.0 FIELD METHODOLOGY

Locations of geophysical data points were obtained using a sub-meter Trimble Pro-XRS DGPS system. References to direction and location in this report are based on the US State Plane 1983 System, North Carolina 3200 Zone, using the NAD 83 datum, with units in US survey feet. The locations of existing site features (building, curbs, signs, etc.) were recorded for later correlation with the geophysical data and for location references to the NCDOT drawings.

The EM61 data were collected along parallel survey lines spaced approximately 2.5 feet apart. The EM61 and DGPS data were recorded digitally using a field computer and later transferred to a desktop computer for data processing. The GPR data were collected along survey lines spaced one to two feet apart in two orthogonal directions over anomalous EM readings not attributed to cultural features. The GPR data were reviewed in the field to evaluate the possible presence of UST's. The GPR data also were recorded digitally and later transferred to a desktop computer for further review.

Preliminary results for Parcel 7 were sent to Ethan Caldwell of the NCDOT on March 30, 2010.

3.0 DISCUSSION OF RESULTS

The contoured EM61 data for Parcel 7 are shown on Figures 3 and 4. The EM61 early time gate results are plotted on Figure 3. The early time gate data provide the more sensitive detection of metal objects. Figure 4 shows the difference between the response of the top and bottom coils of the EM61 instrument (differential response). The difference is taken to remove the effect of surface and very shallowly buried metallic objects. Typically, the differential response emphasizes anomalies from deeper and larger objects such as UST's.

The early time gate and differential results show anomalies apparently caused by buried utilities and/or known site features (Figures 3 and 4). The GPR data collected to the west of the southern building on Parcel 7 indicated the presence of two probable UST's. The two UST's do not appear to be within the planned right-of way and/or easement but are located close to the right-of way line. Example GPR images showing the reflections from the two probable UST's on Parcel 7 are shown on Figures 3 and 4. Figures 3 and 4 also include the locations of the probable UST's as marked in the field. The GPR data indicate that the southern probable UST (UST No.1) on Parcel 7 is buried approximately 0.5 to 1.5 feet below ground surface and is about 3.5 feet in diameter and about 8 feet long, equivalent to a capacity of about 560 gallons. The GPR data indicate that northern probable UST (UST No. 2) on Parcel 7 is buried approximately 1.5 to 2.5 feet below ground surface and is about 3.5 feet in diameter and about 8 feet long, equivalent to a capacity of about 560 gallons. Photographs of the probable UST locations, as marked in the field, are included on Figure 5.

4.0 CONCLUSIONS

Our evaluation of the geophysical data collected on Parcel 7 on Project U-3812 in West Jefferson, NC indicates the following:

The geophysical data indicate the presence of two probable UST's on Parcel 7. The UST's appear to be 4 to 6 feet outside the planned right-of-way and/or easement. The southern probable UST (probable UST No.1) is about 560-gallon capacity and is buried about 0.5 to 1.5 feet below ground surface. The northern probable UST (probable UST No.2) is also about 560-gallon capacity and is buried about 1.5 to 2.5 feet below ground surface.

5.0 LIMITATIONS

These services have been performed and this report prepared for the North Carolina Department of Transportation in accordance with generally accepted guidelines for conducting geophysical surveys. It is generally recognized that the results of geophysical surveys are non-unique and may not represent actual subsurface conditions.

Thank you for the opportunity to serve you on this project. Please call if you need additional information or have any questions.

Sincerely,

SCHNABEL ENGINEERING SOUTH, PC

James W. Whitt Staff Geophysicist

Edward D. Billington, LG Senior Vice President

JW:NB

Attachment: Figures (5)

FILE: G:\2009 PROJECTS\09210013 (NCDOT 2009 GEOTECH UNIT SERVICES)\09210013.17 (U-3812, ASHE COUNTY)\REPORT\PARCEL 7\PARCEL 7 (U-3812).DOC



Parcel 7 – Talmadge S. Shepherd Property, looking northeast



Parcel 7 – Talmadge S. Shepherd Property, looking southeast



STATE PROJECT U-3812 ASHE CO., NORTH CAROLINA NC DEPT. OF TRANSPORTATION PROJECT NO. 09210013.17

PARCEL 7 SITE PHOTOS




Geonics EM61-MK2



GSSI SIR-3000




STATE PROJECT U-3812 ASHE CO., NORTH CAROLINA NC DEPT. OF TRANSPORTATION PROJECT NO. 09210013.17 PHOTOS OF GEOPHYSICAL EQUIPMENT USED



Note: The contour plot shows the earliest and most sensitive time gate of the EM61 bottom coil/channel in millivolts (mV). The EM data were collected on March 15, 2010, using a Geonics EM61-MK2 instrument. Positioning for the EM61 survey was provided using a submeter Trimble ProXRS DGPS system. Coordinates are in the US State Plane 1983 System, North Carolina Zone 3200, using the NAD 1983 datum. GPR data were acquired on March 23, 2010, using a Geophysical Survey Systems SIR 3000 equipped with a 400 MHz antenna.



STATE PROJECT U-3812 ASHE COUNTY, NORTH CAROLINA NC DEPARTMENT OF TRANSPORTATION PROJECT NO. 09210013.17 PARCEL 7 EM61 EARLY TIME GATE RESPONSE



Note: The contour plot shows the difference, in millivolts (mV), between the readings from the top and bottom coils of the EM61. The difference is taken to reduce the effect of shallow metal objects and emphasize anomalies caused by deeper metallic objects, such as drums and tanks. The EM data were collected on March 15, 2010, using a Geonics EM61-MK2 instrument. Positioning for the EM61 survey was provided using a submeter Trimble ProXRS DGPS system. Coordinates are in the US State Plane 1983 System, North Carolina 3200 Zone, using the NAD 1983 datum. GPR data were acquired on March 23, 2010, using a Geophysical Survey Systems SIR 3000 equipped with a 400 MHz antenna.



STATE PROJECT U-3812 ASHE COUNTY, NORTH CAROLINA NC DEPARTMENT OF TRANSPORTATION PROJECT NO. 09210013.17 PARCEL 7 EM61 DIFFERENTIAL RESPONSE



Parcel 7 – Talmadge S. Shepherd Property, looking northeast. Photo shows approximate marked location of the probable UST near the southwest corner of the southern building.



Parcel 7 – Talmadge S. Shepherd Property, looking northeast. Photo shows approximate marked location of the probable UST near the middle of the front side of the southern building.



STATE PROJECT U-3812 ASHE CO., NORTH CAROLINA NC DEPT. OF TRANSPORTATION PROJECT NO. 09210013.17

PHOTOS OF PROBABLE UST LOCATIONS

APPENDIX D LABORATORY ANALYTICAL RESULTS

Case Narrative



Date:

04/21/10

Company: N. C. Department of Transportation

Contact:

Helen Corley

Address: c/o AMEC Earth & Environmental, Inc.

101 W. Friendly Ave. Suite 603

Greensboro, NC 27401

Client Project ID:

NCDOT: Ashe Co. PSA (Parcel 7)

Prism COC Group No: Collection Date(s):

G0410279 04/09/10

Lab Submittal Date(s):

04/09/10

Client Project Name Or No:

WBS #34977.1.1

This data package contains the analytical results for the project identified above and includes a Case Narrative, Laboratory Report and Quality Control Data totaling 9 pages. A chain-of-custody is also attached for the samples submitted to Prism for this project.

Data qualifiers are flagged individually on each sample. A key reference for the data qualifiers appears at the end of this case narrative. Quality control statements and/or sample specific remarks are included in the sample comments section of the laboratory report for each sample affected.

Semi Volatile Analysis

No Anomalies Reported

Volatile Analysis

No Anomalies Reported

Metals Analysis

Wet Lab and Micro Analysis

N/A

Please call if you have any questions relating to this analytical report.

Data Reviewed by:

04/21/10

Project Manager:

Robbia

Signature:

Review Date:

Signature:

Approval Date:

Data Qualifiers Key Reference:

- B: Compound also detected in the method blank.
- #: Result outside of the QC limits.
- DO: Compound diluted out.
 - E: Estimated concentration, calibration range exceeded.
 - J: The analyte was positively identified but the value is estimated below the reporting limit.
- H: Estimated concentration with a high bias.
- L: Estimated concentration with a low bias.
- M: A matrix effect is present.

Notes: This report should not be reproduced, except in its entirety, without the written consent of Prism Laboratories, Inc. The results in this report relate only to the samples submitted for analysis.



Laboratory Report

04/21/10

N. C. Department of Transportation

Attn: Helen Corley

c/o AMEC Earth & Environmental, Inc.

101 W. Friendly Ave. Suite 603

Greensboro, NC 27401

Project ID:

Project No.:

Sample Matrix: Soil

NCDOT: Ashe Co. PSA

Client Sample ID: P7-SB-1 (5-6)

(Parcel 7)

Prism Sample ID: 276347

WBS #34977.1.1 COC Group: Time Collected:

G0410279 04/09/10 11:05

04/09/10 14:50

| Parameter | Result | Units | Report Limit | MDL | Dilution Factor | Method | Analys Date/Ti | | Anal | yst Batch ID |
|---|--------|-------|-----------------|-------|--------------------|----------|-------------------|--------|----------|-----------------|
| Percent Solids Determination Percent Solids | 75.3 | % | | | 1 | SM2540 G | 04/13/10 | 13:00 | jbrayton | • |
| Diesel Range Organics (DRO) by G | C-FID | | | | | | | | | |
| Diesel Range Organics (DRO) | BRL | mg/kg | 9.3 | 1.5 | 1 | 8015B | 04/16/10 | 22:02 | jvogel | Q49472 |
| Sample Preparation: | | | 25 | .04 g | / 1 mL | 3545 | 04/15/10 | 16:00 | athac | P27278 |
| | | | | | Surrogate | <u>.</u> | % Re | covery | , (| Control Limits |
| | | | | | o-Terphen | yl | | 66 | | 49 - 124 |
| Sample Weight Determination | | | | | | | | | | |
| Weight 1 | 6.54 | g | | | 1 | GRO | 04/13/10 | 0:00 | Ibrown | |
| Weight 2 | 6.43 | g | | | 1 | GRO | 04/13/10 | 0:00 | Ibrown | |
| Gasoline Range Organics (GRO) by | GC-FID | | | | | | | | | |
| Gasoline Range Organics (GRO) | BRL | mg/kg | 6.6 | 4.2 | 50 | 8015B | 04/15/10 | 16:29 | heasler | Q49464 |
| | | | | | Surrogate | 9 | % Re | covery | , | Control Limits |
| | | | | | aaa-TFT | | | 114 | | 55 - 129 |

Sample Comment(s):

BRL = Below Reporting Limit

Values are reported down to the reporting limits only. No J-flags applied.

The results in this report relate only to the samples submitted for analysis and meet state certification requirements other than NELAC certification except for those instances indicated in the case narrative and/or test comments.

All results are reported on a dry-weight basis



Laboratory Report

04/21/10

N. C. Department of Transportation

Attn: Helen Corley

c/o AMEC Earth & Environmental, Inc.

101 W. Friendly Ave. Suite 603

Greensboro, NC 27401

Project ID:

NCDOT: Ashe Co. PSA

(Parcel 7)

Project No.:

WBS #34977.1.1

Sample Matrix: Soil

Client Sample ID: P7-SB-2 (4-5)

Prism Sample ID: 276348

COC Group:

G0410279

Time Collected:

04/09/10

11:15

14:50

Time Submitted: 04/09/10

| Parameter | Result | Units | Report Limit | MDL | Dilution Factor | Method | Analysis Date/Time | | llyst Batch ID |
|----------------------------------|----------|-------|-----------------|-------|--------------------|----------|-----------------------|--------------------|-------------------|
| Percent Solids Determination | | | | | | | | | |
| Percent Solids | 85.7 | % | | | 1 | SM2540 G | 04/13/10 13 | 3:00 jbrayto | า |
| Diesel Range Organics (DRO) by G | C-FID | | | | | | | | |
| Diesel Range Organics (DRO) | BRL | mg/kg | 8.1 | 1.3 | 1 | 8015B | 04/16/10 22 | 2:38 jvogel | Q49472 |
| Sample Preparation | : | | 25 | .06 g | / 1 mL | 3545 | 04/15/10 1 | 6:00 atha | o P27278 |
| | | | | | Surrogate | . | % Reco | very | Control Limits |
| | | | | | o-Terphen | ıyl | 8 | 86 | 49 - 124 |
| Sample Weight Determination | | | | | | | | | |
| Weight 1 | 7.24 | g | | | 1 | GRO | 04/13/10 0: | :00 Ibrown | |
| Weight 2 | 9.65 | g | | | 1 | GRO | 04/13/10 0 | :00 lbrown | |
| Gasoline Range Organics (GRO) b | y GC-FID | | | | | | | | |
| Gasoline Range Organics (GRO) | BRL | mg/kg | 5.8 | 3.7 | 50 | 8015B | 04/15/10 1 | 8:03 heasle | r Q49464 |
| | | | | | Surrogate | ə | % Reco | very | Control Limits |
| | | | | | aaa-TFT | | 12 | - 25 | 55 - 129 |

Sample Comment(s):

BRL = Below Reporting Limit

Values are reported down to the reporting limits only. No J-flags applied.

The results in this report relate only to the samples submitted for analysis and meet state certification requirements other than NELAC certification except for those instances indicated in the case narrative and/or test comments.

All results are reported on a dry-weight basis



Laboratory Report

04/21/10

N. C. Department of Transportation

Attn: Helen Corley

c/o AMEC Earth & Environmental, Inc.

101 W. Friendly Ave. Suite 603

Greensboro, NC 27401

Project ID:

NCDOT: Ashe Co. PSA

(Parcel 7)

Project No.:

WBS #34977.1.1

Sample Matrix: Soil

Client Sample ID: P7-SB-3 (5-6)

Prism Sample ID: 276349

COC Group:

G0410279

Time Collected:

04/09/10 11:30

Time Submitted: 04/09/10

14:50

| Parameter | Result | Units | Report Limit | MDL | Dilution Factor | Method | Analysis Date/Time | Anal | yst Batch ID |
|--|--------------|-------|-----------------|-------|--------------------|----------|-----------------------|------------|-----------------|
| Percent Solids Determination Percent Solids | 77.5 | % | | | 1 | SM2540 G | 04/13/10 13:0 | 0 jbrayton | |
| Diesel Range Organics (DRO) by GO Diesel Range Organics (DRO) | C-FID BRL | mg/kg | 9.0 | 1.5 | 1 | 8015B | 04/16/10 23: | 14 jvogel | Q49472 |
| Sample Preparation: | | | 25 | .03 g | / 1 mL | 3545 | 04/15/10 16: | 00 athac | P27278 |
| | | | | | Surrogate | e | % Recove | ery (| Control Limits |
| | | | | | o-Terphen | ıyl | 77 | | 49 - 124 |
| Sample Weight Determination | | | | | | | | | |
| Weight 1 | 6.73 | g | | | 1 | GRO | 04/13/10 0:00 |) Ibrown | |
| Weight 2 | 7.42 | g | | | 1 | GRO | 04/13/10 0:0 |) Ibrown | |
| Gasoline Range Organics (GRO) by | GC-FID | | | | | | | | |
| Gasoline Range Organics (GRO) | BRL | mg/kg | 6.5 | 4.0 | 50 | 8015B | 04/15/10 18: | 35 heasler | Q49464 |
| | | | | | Surrogate | e | % Recove | ery (| Control Limits |
| | | | | | aaa-TFT | | 111 | | 55 - 129 |

Sample Comment(s):

BRL = Below Reporting Limit

Values are reported down to the reporting limits only. No J-flags applied.

The results in this report relate only to the samples submitted for analysis and meet state certification requirements other than NELAC certification except for those instances indicated in the case narrative and/or test comments.

All results are reported on a dry-weight basis



Laboratory Report

04/21/10

N. C. Department of Transportation

Attn: Helen Corley

c/o AMEC Earth & Environmental, Inc.

101 W. Friendly Ave. Suite 603

Greensboro, NC 27401

Project ID:

NCDOT: Ashe Co. PSA

Project No.:

(Parcel 7) WBS #34977.1.1

Sample Matrix: Soil

Client Sample ID: P7-SB-4 (5-6)

Prism Sample ID: 276350 COC Group: G0410279

Time Collected: 04/09/10 11:45 Time Submitted: 04/09/10 14:50

| Parameter | Result | Units | Report Limit | MDL | Dilution Factor | Method | Analysis Date/Time | Analys | t Batch ID |
|--|----------------------|-------|-----------------|------|--------------------|----------|-----------------------|----------|---------------|
| Percent Solids Determination Percent Solids | 81.5 | % | | | 1 | SM2540 G | 04/13/10 13:00 | jbrayton | |
| Diesel Range Organics (DRO) by GO Diesel Range Organics (DRO) | C <u>-FID</u> BRL | mg/kg | 8.6 | 1.4 | 1 | 8015B | 04/17/10 5:41 | jvogel | Q49477 |
| Sample Preparation | on: | | | 25 g | ′ 1 mL | 3545 | 04/16/10 7:30 | athao | P27282 |
| | | | | | Surrogate | • | % Recovery | Co | ntrol Limits |
| | | | | | o-Terphen | yl | 78 | | 49 - 124 |
| Sample Weight Determination | | | | | | | | | |
| Weight 1 | 6.63 | g | | | 1 | GRO | 04/13/10 0:00 | ibrown | |
| Weight 2 | 6.54 | g | | | 1 | GRO | 04/13/10 0:00 | lbrown | |
| Gasoline Range Organics (GRO) by | GC-FID | | | | | | | | |
| Gasoline Range Organics (GRO) | BRL | mg/kg | 6.1 | 3.8 | 50 | 8015B | 04/15/10 19:06 | heasler | Q49464 |

Surrogate recovery was outside the control limits. No target compounds were detected in this sample that were associated with this surrogate. No further action was taken.

| Surrogate | % Recovery | Control Limits | | |
|-----------|------------|----------------|--|--|
| aaa-TFT | 134 # | 55 - 129 | | |
| | | | | |

Sample Comment(s):

BRL = Below Reporting Limit

Values are reported down to the reporting limits only. No J-flags applied.

The results in this report relate only to the samples submitted for analysis and meet state certification requirements other than NELAC certification except for those instances indicated in the case narrative and/or test comments.

All results are reported on a dry-weight basis

Angela D. Overcash, V.P. Laboratory Services

This report should not be reproduced, except in its entirety, without the written consent of Prism Laboratories, Inc.



Laboratory Report

04/21/10

N. C. Department of Transportation

Attn: Helen Corley

c/o AMEC Earth & Environmental, Inc.

101 W. Friendly Ave. Suite 603

Greensboro, NC 27401

Project ID:

NCDOT: Ashe Co. PSA

(Parcel 7)

Project No.:

WBS #34977.1.1

Sample Matrix: Soil

Client Sample ID: P7-SB-5 (4-5)

Prism Sample ID: 276351

COC Group: G0410279
Time Collected: 04/09/10 1

Time Collected: 04/09/10 11:55 Time Submitted: 04/09/10 14:50

| Parameter | Result | Units | Report Limit | MDL | Dilution Factor | Method | Analys Date/Tir | | Anal | yst Batch ID |
|---|----------|-------|-----------------|-------|--------------------|----------|--------------------|--------|----------|-----------------|
| Percent Solids Determination Percent Solids | 78.0 | % | | | 1 | SM2540 G | 04/13/10 | 13:00 | jbrayton | |
| Diesel Range Organics (DRO) by G | C-FID | | | | | | | | | |
| Diesel Range Organics (DRO) | BRL | mg/kg | 8.9 | 1.4 | 1 | 8015B | 04/17/10 | 6:17 | jvogel | Q49477 |
| Sample Preparation: | | | 25. | .07 g | / 1 mL | 3545 | 04/16/10 | 7:30 | athac | P27282 |
| | | | | | Surrogate | 3 | % Red | covery | , (| Control Limits |
| | | | | | o-Terphen | yl | | 72 | | 49 - 124 |
| Sample Weight Determination | | | | | | | | | | |
| Weight 1 | 5.48 | g | | | 1 | GRO | 04/13/10 | 0:00 | lbrown | |
| Weight 2 | 5.48 | g | | | 1 | GRO | 04/13/10 | 0:00 | lbrown | |
| Gasoline Range Organics (GRO) b | y GC-FID | | | | | | | | | |
| Gasoline Range Organics (GRO) | BRL | mg/kg | 6.4 | 4.0 | 50 | 8015B | 04/15/10 | 19:37 | heasler | Q49464 |
| | | | | | Surrogate | • | % Red | covery | , (| Control Limits |
| | | | | | aaa-TFT | | | 97 | | 55 - 129 |

Sample Comment(s):

BRL = Below Reporting Limit

Values are reported down to the reporting limits only. No J-flags applied.

The results in this report relate only to the samples submitted for analysis and meet state certification requirements other than NELAC certification except for those instances indicated in the case narrative and/or test comments.

All results are reported on a dry-weight basis



Laboratory Report

G0410279

04/21/10

N. C. Department of Transportation

Attn: Helen Corley

c/o AMEC Earth & Environmental, Inc.

101 W. Friendly Ave. Suite 603

Greensboro, NC 27401

Project ID:

NCDOT: Ashe Co. PSA

(Parcel 7)

Project No.:

WBS #34977.1.1

Sample Matrix: Soil

Client Sample ID: P7-SB-6 (4-5)

Prism Sample ID: 276352

COC Group:

Time Collected: 04/09/10 12:10

Time Submitted: 04/09/10 14:50

| Parameter | Result | Units | Report Limit | MDL | Dilution Factor | Method | Analysis Date/Time | Analys | t Batch ID |
|-----------------------------------|--------|-------|-----------------|------|--------------------|-----------|-----------------------|----------|---------------|
| Percent Solids Determination | | | | | | 2340540.0 | 0.140140.4000 | · (L - | |
| Percent Solids | 71.8 | % | | | 1 | SM2540 G | 04/13/10 13:00 | jbrayton | |
| Diesel Range Organics (DRO) by GO | C-FID | | | | | | | | |
| Diesel Range Organics (DRO) | BRL | mg/kg | 9.8 | 1.6 | 1 | 8015B | 04/17/10 7:28 | jvogel | Q49477 |
| Sample Preparation: | | | 24. | 97 g | / 1 mL | 3545 | 04/16/10 7:30 | athao | P27282 |
| | | | | | Surrogate | | % Recovery | Co | ntrol Limits |
| | | | | | o-Terphen | yl | 81 | | 49 - 124 |
| Sample Weight Determination | | | | | | | | | |
| Weight 1 | 6.39 | 9 | | | 1 | GRO | 04/13/10 0:00 | lbrown | |
| Weight 2 | 6.32 | g | | | 1 | GRO | 04/13/10 0:00 | Ibrown | |
| Gasoline Range Organics (GRO) by | GC-FID | | | | | | | | |
| Gasoline Range Organics (GRO) | BRL | mg/kg | 7.0 | 4.4 | 50 | 8015B | 04/15/10 20:08 | heasler | Q49464 |

Surrogate recovery was outside the control limits. No target compounds were detected in this sample that were associated with this surrogate. No further action was taken.

| Surrogate | % Recovery | Control Limits | | |
|-----------|------------|----------------|--|--|
| aaa-TFT | 144 # | 55 - 129 | | |
| | | | | |

Sample Comment(s):

BRL = Below Reporting Limit

Values are reported down to the reporting limits only. No J-flags applied.

The results in this report relate only to the samples submitted for analysis and meet state certification requirements other than NELAC certification except for those instances indicated in the case narrative and/or test comments.

All results are reported on a dry-weight basis



Level II QC Report

4/21/2010

N. C. Department of Transportation

101 W. Friendly Ave. Suite 603

Attn: Helen Corley

c/o AMEC Earth & Environmental, Inc.

Greensboro, NC 27401

Project ID: Project No.: NCDOT: Ashe Co. PSA

(Parcel 7)

WBS #34977.1.1

COC Group Number: G0410279

Date/Time Submitted: 4/9/2010 14:50

Gasoline Range Organics (GRO) by GC-FID, method 8015B

| Method Blank | Result | RL | Control Limit | Units | | | | | QC Batch ID |
|---|------------|-------------|---------------|-------|---------------|-------------------------|----------|--------------------|----------------|
| Gasoline Range Organics (GRO) | ND | 5 | <2.5 | mg/kg | | | | | Q49464 |
| Laboratory Control Sample | Result | Spike Amour | nt | Units | Recovery % | Recovery Ranges % | | A-211 V 21 . 11 14 | QC Batch ID |
| Gasoline Range Organics (GRO) | 48.90 | 50 | | mg/kg | 98 | 67-116 | | | Q49464 |
| Matrix Spike Sample ID: | Result | Spike Amour | nt | Units | Recovery % | Recovery Ranges % | | a control of the | QC Batch ID |
| 276347 Gasoline Range Organics (GRO) | 54.35 | 50 | | mg/kg | 109 | 57-113 | | | Q49464 |
| Matrix Spike Duplicate Sample ID: | Result | Spike Amou | nt | Units | Recovery % | Recovery Ranges % | RPD % | RPD Range % | QC Batch ID |
| 276347 Gasoline Range Organics (GRO) | 53.50 | 50 | | mg/kg | 107 | 57-113 | 2 | 0 - 23 | Q49464 |
| Diesel Range Organics (DRO) by GC- | FID, metho | od 8015B | | | | | | | |
| Method Blank | Result | RL | Control Limit | Units | | | | | QC Batcl ID |
| Diesel Range Organics (DRO) | ND | 7 | <3.5 | mg/kg | | | | | Q49472 |
| Laboratory Control Sample | Result | Spike Amou | nt | Units | Recovery % | Recovery Ranges % | | | QC Batc |
| Diesel Range Organics (DRO) | 54.6 | 80 | | mg/kg | 68 | 55-109 | | | Q49472 |
| Matrix Spike Sample ID: | Result | Spike Amou | nt | Units | Recovery % | Recovery Ranges % | | | QC Bato |
| 275759 Diesel Range Organics (DRO) | 69.9 | 80 | | mg/kg | 87 | 50-117 | | | Q49472 |
| Matrix Spike Duplicate Sample ID: | Result | Spike Amou | nt | Units | Recovery % | Recovery Ranges % | RPD % | RPD Range % | QC Bato |
| 275759 Diesel Range Organics (DRO) | 73.4 | 80 | | mg/kg | 92 | 50-117 | 5 | 0 - 24 | Q49472 |



Level II QC Report

4/21/2010

N. C. Department of Transportation

Attn: Helen Corley

c/o AMEC Earth & Environmental, Inc.

101 W. Friendly Ave. Suite 603 Greensboro, NC 27401

Project ID: Project No.: NCDOT: Ashe Co. PSA

(Parcel 7)

WBS #34977.1.1

COC Group Number: G0410279

Date/Time Submitted: 4/9/2010 14:50

Diesel Range Organics (DRO) by GC-FID, method 8015B

| Method Blank | Result | RL | Control Limit | Units | | | | | QC Batch ID |
|------------------------------------|--------|------------|---------------|-------|---------------|-------------------------|---------------|-------------------|----------------|
| Diesel Range Organics (DRO) | ND | 7 | <3.5 | mg/kg | | | . #1 1000 # # | | Q49477 |
| Laboratory Control Sample | Result | Spike Amou | int | Units | Recovery % | Recovery Ranges % | - V | | QC Batch ID |
| Diesel Range Organics (DRO) | 57.7 | 80 | | mg/kg | 72 | 55-109 | | | Q49477 |
| Matrix Spike Sample ID: | Result | Spike Amou | ınt | Units | Recovery % | Recovery Ranges % | | | QC Batch ID |
| 276350 Diesel Range Organics (DRO) | 54.2 | 80 | | mg/kg | 68 | 50-117 | | | Q49477 |
| Matrix Spike Duplicate Sample ID: | Result | Spike Amou | ınt | Units | Recovery % | Recovery Ranges % | RPD % | RPD Range % | QC Batch ID |
| 276350 Diesel Range Organics (DRO) | 53.5 | 80 | | mg/kg | 67 | 50-117 | 1 | 0 - 24 | Q49477 |

#-See Case Narrative

Page 2 of 2

| Full-Service Analytical Environmental Solutio | |
|---|--|
| PS SM | |

S ಳ

Project Name: _

9

PAGE_

449 Springbrook Road • P.O. Box 240543 • Charlotte, NC 28224-0543 Phone: 704/529-6364 • Fax: 704/525-0409

Eriend Report To/Contact Name: 片と | ピル Client Company Name: AME

1. M. CN L

nvoice To:

N. C. Ste 60 Address:

Phone: 336-641-5392 Fax (Yes) (No): Other 250 Site Location Physical Address: Email (Yes) (No) Email Address EDD Type: PDF V Excel Site Location Name: Oftenshoro

| _ | |
|-----------------------|---|
| | |
| Œ | |
| $\overline{}$ | ٠ |
| U | |
| Ö | * |
| Ш | |
| æ | |
| | |
| > | |
| | |
| 2 | |
| \frown | |
| ᆮ | |
| 5 | |
| CUST | |
| | |
| 不 | |
| | |
| L | |
| <u>—</u> | |
| 0 | |
| _ | |
| 7 | |
| | |
| | |
| ۹ | |
| | |
| 4 | |
| $\overline{\alpha}$ | |
| $\mathbf{\mathbf{v}}$ | |

LAB USE ONLY

VOLATILES rec'd W/OUT HEADSPACE? PROPER PRESERVATIVES indicated Received WITHIN HOLDING TIMES? Samples INTACT upon arrival? $\overline{\Sigma}_{11}$ Received ON WET ICE? Temp CUSTODY SEALS INTACT? QUOTIE # TO ENSURE PROPER BILLING: WAS 349774 Short Hold Analysis: (Yes) (No) UST Project: (Yes) (No) *Please ATTACH any project specific reporting (QC LEVEL I II III IV) provisions and/or QC Requirements

ローション コーニュー Bush Work Must Br Turnaround time is based on business days, excluding weekends and holidays (see REVERSE FOR TERMS & CONDITIONS RECARDING SERVICES RENDERED BY PRISM LABORATORIES, INC. TO CLIENT) Requested Due Date ☐1 Day ☐2 Days ☐3 Days ☐4 Days ☐5 Days Purchase Order No./Billing Reference W 85. 3497 7.1. Samples received after 15:00 will be processed next business day

"Working Days"

| 1 | ŧ | i |
|---|---|---|

| | TO BE FILLED IN BY CLIENT/SAMPLING PERSONNEL |
|-----|--|
| | Certification: NELACUSACEFLNC |
| o | SCOTHERN/A |
| ø | Water Chlorinated: YES NO / |
| | Sample Iced Upon Collection: YES 🗸 NO |
| AMA | ANALYSES REQUESTED |

| PRISM | ID NO. | 376347 | 87634g | 376349 | 27675 | ३ न्६७न | 274353- | | | | -3 COPIES | PRISM USE ONLY | i |
|------------------|---------------------|-----------------|---------------|-------------|-------------|----------------|--|---|--|---|------------------------------|---|--|
| | REMARKS | | | | | | | | | | PRESS DOWN FIRMLY - 3 COPIES | PRISM | Additional Comments: |
| 1 00/07 | 20 | × | | | | | | | | | Affiliation AMEC | shanges must be | //Hours |
| PRESERVA- | | Nove/westrand X | | | | | \rightarrow \right | • | | | | pon relinquishing, this Chain of Custody is your authorization for Prism to proceed with the analyses as requested above. Any changes must be the mitted in writing to the Prism Project Manager. There will be charges for any changes after analyses have been initialized. | Date |
| SAMPLE CONTAINER | NO. SIZE | 7 | | | | | \ -> | • | | | Troy I Holoschul | d with the analyse nanges after analy | |
| SAMPLE | *TYPE SEE BELOW | 6/var | _ | | | | -> | | | - | Sampled By (Print Name) | r Prism to procee | Beceived By: (Signature) |
| MATHIX (SOIL. | WATER OR SLUDGE) | 3 | 7 | | | | -> | | | | Sampled E | orization fo | Rec |
| COLLECTED | MILITARY | 11/05 | = 7 7 | Ç = | ニュ | וולב | DIE | | | | ahuh | dy is your auth et Manager. Th | |
| DATE | COLLECTED | 4-9-10 | - | | | | -> | | | | ha 2 Holy | Obain of Custo | , , |
| TNEI | SAMPLE DESCRIPTION | 17-5A-1/5-6 | 17. < A-1/4.5 | 17-51-42-10 | 12-54-4 KCC | 7-501/1-51 | 12-41-67 | | | | Sampler's Signature | Jpon relinquishing, this | The second secon |

Site Arrival Times: Site Departure Time: Field Tech Fee. Mileages

ONC OSC OTHER:

ONC OSC

LANDFILL

CERCLA

RCRA:

SOLID WASTE:

DRINKING WATER:

Other.

Prism Field Service GROUNDWATER:

O Hail

□ Fed Ex □ UPS NPDES:

Relinquished By: (Signature)

G0410279

ORIGINAL

ONC OSC ONTAINER TYPE CODES: A = Amber C = Clear G = Glass P = Plastic; TL = Teflon-Lined Cap VOA = Volatile Organics Analysis (Zero Head Space)

Method of Shipment: NOTE: ALL SAMPLE COOLERS SHOULD BE TAPED \$HUT WITH CUSTOLESEALS FOR TRANSPORTATION TO THE LABORATORY.

SAMPLES ARE NOT ACCEPTED AND VERIFIED AGAINST GOC UNTIL RECEIVED AT THE LABORATORY.

aboratories By

Received By: (Signature)