

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE
GOVERNOR

EUGENE A. CONTI, JR.
SECRETARY

July 11, 2012

Addendum No. 1

RE: Contract ID C203096
WBS # 2CR.10071.3
State Funded
Beaufort County
NC-99 From SR-1722 To The End Of Pantego Creek Bridge

July 17, 2012 Letting

To Whom It May Concern:

Reference is made to the proposal and sketch maps (plans) furnished to you on this project.

The following revision has been made to the sketch maps:

On Sheet No. 3 the below noted quantity changes have been made to the "Summary of Quantities". Please void Sheet No. 3 in your plans and staple the revised Sheet No. 3 thereto.

The following revision has been made to the proposal:

On Page Nos. 26 and 27 the project special provision entitled "Shoulder Reconstruction" has been revised. Please void Page Nos. 26 and 27 in your proposal and staple the revised Page Nos. 26 and 27 thereto.

On the item sheets the following quantity changes have been made:

<u>Item</u>	Description	Old Quantity	New Quantity
2-0106000000-E-230	Borrow Excavation	273 CY	DELETED
3-1220000000-E-545	Incidental Stone Base	6,835 Ton	2,728 Ton
22-0255000000-E-SP	Aggregate Shoulder Borrow	NEW ITEM	4,640 Ton

The Contractor's bid must include these pay item quantity changes. The contract will be prepared accordingly.

TELEPHONE: 919-707-6900 FAX: 919-250-4119 WEBSITE: WWW.NCDOT.ORG LOCATION: CENTURY CENTER COMPLEX ENTRANCE B-2 1020 BIRCH RIDGE DRIVE RALEIGH NC 27610 Contract C203096 Beaufort County

The Expedite File has been updated to reflect these revisions. Please download the Expedite Addendum File and follow the instructions for applying the addendum. Bid Express will not accept your bid unless the addendum has been applied.

Sincerely,

R. A. Garris, PE Contract Officer

RAG/jag Attachments

cc: Mr. Ron Hancock, PE
Mr. C. E. Lassiter, PE
Ms. Marsha Sample
Ms. D. M. Barbour, PE
Mr. Ronnie Higgins
Mr. J. V. Barbour, PE
Mr. Larry Strickland
Mr. R.E. Davenport, PE
Ms. Lori Strickland
Mr. Ray Arnold, PE
Ms. Penny Higgins
Project File (2)
Ms. Jaci Kincaid



PROJECT SPECIAL PROVISIONS

ROADWAY

SHOULDER RECONSTRUCTION PER SHOULDER MILE:

(1-18-00) (Rev. 5-17-11) 560 R1 R07 A

Description

This work consists of reconstructing each shoulder (including median shoulders as applicable) in accordance with Standard Drawing No. 560.01 and 560.02 of the 2012 Roadway Standard Drawings except that the rate of slope and width will be as shown on typical section, or to the existing shoulder point, whichever is nearer, as long as the desired typical is achieved, and when completed, seeding and mulching. This work shall be performed immediately after the resurfacing operations are complete as directed by the Engineer.

Materials

The Contractor shall use Aggregate Shoulder Borrow (ASB) which meets the following gradation on all maps as directed by the Engineer.

<u>Sieve</u>	Percent Passing	
1 1/2"	100	
1/2"	55 - 95	
#4	35 - 74	

Construction Methods

Obtain material from within the project limits or approved borrow source. Material shall be compacted to the satisfaction of the Engineer.

Any excess material generated by the shoulder reconstruction shall be disposed of by the Contractor in an approved disposal site.

Measurement and Payment

Shoulder Reconstruction will be measured and paid as the actual number of miles of shoulders that have been reconstructed. Measurement will be made along the surface of each shoulder to the nearest 0.01 of a mile. Such price will include disposing of any excess material in an approved disposal site, and for all labor, tools, equipment, and incidentals necessary to complete the work.



Aggregate Shoulder Borrow will be measured and paid at the contract unit price per ton.

Incidental Stone Base will be measured and paid as provided in Article 545-6 of the 2012 Standard Specifications. If ASB is used for Incidental Stone Base, payment will be made for **Aggregate Shoulder Borrow** as referenced above.

Seeding and Mulching will be measured and paid as shown elsewhere in the contract documents.

Payment will be made under:

Pay Item
Shoulder Reconstruction
Aggregate Shoulder Borrow

Pay Unit
Shoulder Mile
Ton

INCIDENTAL STONE BASE:

(7-1-95) (Rev.7-18-06)

545

R5 R28

Description

Place incidental stone base on driveways, mailboxes, etc. immediately after paving and do not have the paving operations exceed stone base placement by more than one week without written permission of the Engineer.

Materials and Construction

Provide and place incidental stone base in accordance with Section 545 of the 2012 Standard Specifications.

Measurement and Payment

Incidental Stone Base will be measured and paid in accordance with Article 545-6 of the 2012 Standard Specifications.

ASPHALT PAVEMENTS - SUPERPAVE:

(6-19-12)

R6 R01

Revise the 2012 Standard Specifications as follows:

Page 6-3, Article 605-7 APPLICATION RATES AND TEMPERATURES, replace this article, including Table 601-1, with the following:

Apply tack coat uniformly across the existing surface at target application rates shown in Table 605-1.