

NOTE: SEE SHEET 1A FOR PLAN SHEET LAYOUT AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

CONTENTS

LINE	STATION	PLAN	XSECT
-L-	14+50 to 35+00	4 - 5	6 - 13
SOIL TEST RESULTS		14	

ROADWAY SUBSURFACE INVESTIGATION

PROJ. REFERENCE NO. 38532.1.1(B-4760) F.A. PROJ. BRZ-4053(1)
 COUNTY GUILFORD
 PROJECT DESCRIPTION BRIDGE NO. 77 ON SR 4053 (SURRETT DR.)
OVER US 29/US 70I-85 BUSINESS


INVENTORY

CAUTION NOTICE
 THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING, AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 250-4088. NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOGS, ROCK CORES, OR SOIL TEST DATA ARE PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACED) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION, AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.


CONTRACT: C202846 ID: B-4760



- PERSONNEL
- D.C. ELLIOT
 - C.J. COFFEY
 - L. RIDDLE
 - M. WHALEN

INVESTIGATED BY B.D. WORLEY
 CHECKED BY K.B. MILLER
 SUBMITTED BY K.B. MILLER
 DATE OCTOBER 2010

★ TRAFFIC SIGNAL



Bradley D. Worley

DRAWN BY: T. WALKER, C. YOUNGBLOOD, B. WORLEY

NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IS IT CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THE PROJECT.

NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

PROJECT REFERENCE NO. 38532.1.(B-4760) SHEET NO. 2


SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION		GRADATION	ROCK DESCRIPTION	TERMS AND DEFINITIONS																																																																																																																																																																									
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:</p> <p align="center"><i>VERY STIFF, GRAN. SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGH PLASTIC, A-7-6</i></p>		<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p align="center">ANGULARITY OF GRAINS</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p>	<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT IF TESTED, WOULD YIELD SPT REFUSAL. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>	<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 60 BLOWS PER FOOT. STRATA CORE RECOVERY (SCRC) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																									
<p align="center">SOIL LEGEND AND AASHTO CLASSIFICATION</p> <table border="1"> <thead> <tr> <th rowspan="2">GENERAL CLASS.</th> <th colspan="7">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="7">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="2">ORGANIC MATERIALS</th> </tr> <tr> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>GROUP CLASS.</td> <td>A-1-a</td> <td>A-1-b</td> <td>A-2-4</td> <td>A-2-5</td> <td>A-2-6</td> <td>A-2-7</td> <td>A-4</td> <td>A-5</td> <td>A-6</td> <td>A-7</td> <td>A-1, A-2</td> <td>A-4, A-5</td> <td>A-6, A-7</td> <td></td> <td></td> <td></td> </tr> <tr> <td>SYMBOL</td> <td colspan="14">[SOIL SYMBOL PATTERNS]</td> <td></td> <td></td> </tr> <tr> <td>% PASSING</td> <td>50</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> </tr> <tr> <td>LIQUID LIMIT PLASTIC INDEX</td> <td>6</td> <td>NP</td> <td>40</td> <td>41</td> <td>41</td> <td>41</td> <td>40</td> <td>41</td> <td>41</td> <td>40</td> <td>41</td> <td>41</td> <td>41</td> <td>41</td> <td>41</td> <td>41</td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td colspan="2">STONE FRAGS GRAVEL AND SAND</td> <td colspan="2">FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="2">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="2">HIGHLY ORGANIC SOILS</td> <td colspan="2"></td> </tr> <tr> <td>GEN. RATING AS A SUBGRADE</td> <td colspan="4">EXCELLENT TO GOOD</td> <td colspan="4">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td colspan="2">UNSATURATED</td> <td colspan="4"></td> </tr> <tr> <td colspan="2"></td> <td colspan="15">PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS ≥ LL - 30</td> </tr> </tbody> </table>		GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)							SILT-CLAY MATERIALS (> 35% PASSING #200)							ORGANIC MATERIALS		A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7							GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7				SYMBOL	[SOIL SYMBOL PATTERNS]																% PASSING	50	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	LIQUID LIMIT PLASTIC INDEX	6	NP	40	41	41	41	40	41	41	40	41	41	41	41	41	41	USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS GRAVEL AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS				GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR	POOR	UNSATURATED								PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS ≥ LL - 30															<p align="center">MINERALOGICAL COMPOSITION</p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p>		<p align="center">WEATHERING</p> <table border="1"> <thead> <tr> <th>FRESH</th> <th>VERY SLIGHT (V SL.)</th> <th>SLIGHT (SL.)</th> <th>MODERATE (MOD.)</th> <th>MODERATELY SEVERE (MOD. SEV.)</th> <th>SEVERE (SEV.)</th> <th>VERY SEVERE (V SEV.)</th> <th>COMPLETE</th> </tr> </thead> <tbody> <tr> <td>ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</td> <td>ROCK GENERALLY FRESH, JOINTS STAINED. SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</td> <td>ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</td> <td>SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED. SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</td> <td>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL.</i></td> <td>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, YIELDS SPT N VALUES > 100 BPF.</i></td> <td>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, YIELDS SPT N VALUES < 100 BPF.</i></td> <td>ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</td> </tr> </tbody> </table>		FRESH	VERY SLIGHT (V SL.)	SLIGHT (SL.)	MODERATE (MOD.)	MODERATELY SEVERE (MOD. SEV.)	SEVERE (SEV.)	VERY SEVERE (V SEV.)	COMPLETE	ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.	ROCK GENERALLY FRESH, JOINTS STAINED. SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.	ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED. SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL.</i>	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, YIELDS SPT N VALUES > 100 BPF.</i>	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, YIELDS SPT N VALUES < 100 BPF.</i>	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)							SILT-CLAY MATERIALS (> 35% PASSING #200)							ORGANIC MATERIALS																																																																																																																																																														
	A-1	A-3	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7																																																																																																																																																																			
GROUP CLASS.	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-4, A-5	A-6, A-7																																																																																																																																																																
SYMBOL	[SOIL SYMBOL PATTERNS]																																																																																																																																																																												
% PASSING	50	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10																																																																																																																																																													
LIQUID LIMIT PLASTIC INDEX	6	NP	40	41	41	41	40	41	41	40	41	41	41	41	41	41																																																																																																																																																													
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS GRAVEL AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS																																																																																																																																																																
GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD				FAIR TO POOR				FAIR TO POOR	POOR	UNSATURATED																																																																																																																																																																		
		PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS ≥ LL - 30																																																																																																																																																																											
FRESH	VERY SLIGHT (V SL.)	SLIGHT (SL.)	MODERATE (MOD.)	MODERATELY SEVERE (MOD. SEV.)	SEVERE (SEV.)	VERY SEVERE (V SEV.)	COMPLETE																																																																																																																																																																						
ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.	ROCK GENERALLY FRESH, JOINTS STAINED. SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.	ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED. SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL.</i>	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, YIELDS SPT N VALUES > 100 BPF.</i>	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, YIELDS SPT N VALUES < 100 BPF.</i>	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.																																																																																																																																																																						
<p align="center">COMPRESSIBILITY</p> <table border="1"> <thead> <tr> <th>SLIGHTLY COMPRESSIBLE</th> <th>Moderately Compressible</th> <th>Highly Compressible</th> <th>LIQUID LIMIT LESS THAN 31</th> <th>LIQUID LIMIT EQUAL TO 31-50</th> <th>LIQUID LIMIT GREATER THAN 50</th> </tr> </thead> </table>		SLIGHTLY COMPRESSIBLE	Moderately Compressible	Highly Compressible	LIQUID LIMIT LESS THAN 31	LIQUID LIMIT EQUAL TO 31-50	LIQUID LIMIT GREATER THAN 50	<p align="center">PERCENTAGE OF MATERIAL</p> <table border="1"> <thead> <tr> <th></th> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT-CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> </thead> <tbody> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>12 - 20%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>> 10%</td> <td>> 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>> 35%</td> <td>AND ABOVE</td> </tr> </tbody> </table>			ORGANIC MATERIAL	GRANULAR SOILS	SILT-CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	5 - 12%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	12 - 20%	LITTLE	MODERATELY ORGANIC	5 - 10%	> 10%	> 20%	SOME	HIGHLY ORGANIC	> 10%	> 20%	> 35%	AND ABOVE	<p align="center">GROUND WATER</p> <p>▽ WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING</p> <p>▽ STATIC WATER LEVEL AFTER 24 HOURS</p> <p>▽ PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA</p> <p>○ SPRING OR SEEP</p>																																																																																																																																										
SLIGHTLY COMPRESSIBLE	Moderately Compressible	Highly Compressible	LIQUID LIMIT LESS THAN 31	LIQUID LIMIT EQUAL TO 31-50	LIQUID LIMIT GREATER THAN 50																																																																																																																																																																								
	ORGANIC MATERIAL	GRANULAR SOILS	SILT-CLAY SOILS	OTHER MATERIAL																																																																																																																																																																									
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	5 - 12%	TRACE																																																																																																																																																																									
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	12 - 20%	LITTLE																																																																																																																																																																									
MODERATELY ORGANIC	5 - 10%	> 10%	> 20%	SOME																																																																																																																																																																									
HIGHLY ORGANIC	> 10%	> 20%	> 35%	AND ABOVE																																																																																																																																																																									
<p align="center">CONSISTENCY OR DENSENESS</p> <table border="1"> <thead> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> </thead> <tbody> <tr> <td rowspan="3">GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE</td> <td>< 4</td> <td>< 0.25</td> </tr> <tr> <td>MEDIUM DENSE</td> <td>4 TO 10</td> <td>0.25 TO 1.0</td> </tr> <tr> <td>DENSE</td> <td>10 TO 30</td> <td>1.0 TO 2.0</td> </tr> <tr> <td rowspan="3">GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT</td> <td>< 2</td> <td>< 0.25</td> </tr> <tr> <td>SOFT</td> <td>2 TO 4</td> <td>0.25 TO 0.50</td> </tr> <tr> <td>MEDIUM STIFF</td> <td>4 TO 8</td> <td>0.50 TO 1.0</td> </tr> <tr> <td></td> <td>STIFF</td> <td>8 TO 15</td> <td>1.0 TO 2.0</td> </tr> <tr> <td></td> <td>VERY STIFF</td> <td>15 TO 30</td> <td>2.0 TO 4.0</td> </tr> <tr> <td></td> <td>HARD</td> <td>> 30</td> <td>> 4.0</td> </tr> </tbody> </table>		PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	< 4	< 0.25	MEDIUM DENSE	4 TO 10	0.25 TO 1.0	DENSE	10 TO 30	1.0 TO 2.0	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	< 2	< 0.25	SOFT	2 TO 4	0.25 TO 0.50	MEDIUM STIFF	4 TO 8	0.50 TO 1.0		STIFF	8 TO 15	1.0 TO 2.0		VERY STIFF	15 TO 30	2.0 TO 4.0		HARD	> 30	> 4.0	<p align="center">MISCELLANEOUS SYMBOLS</p> <table border="1"> <tr> <td>[Symbol] ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td> <td>[Symbol] TEST BORING</td> <td>[Symbol] AUGER BORING</td> <td>[Symbol] TEST BORING W/ CORE</td> </tr> <tr> <td>[Symbol] SOIL SYMBOL</td> <td>[Symbol] SPT N-VALUE</td> <td>[Symbol] CORE BORING</td> <td>[Symbol] SPT REFUSAL</td> </tr> <tr> <td>[Symbol] ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td> <td>[Symbol] MONITORING WELL</td> <td>[Symbol] PIEZOMETER INSTALLATION</td> <td></td> </tr> <tr> <td>[Symbol] INFERRED SOIL BOUNDARY</td> <td>[Symbol] SLOPE INDICATOR INSTALLATION</td> <td>[Symbol] CONE PENETROMETER TEST</td> <td></td> </tr> <tr> <td>[Symbol] INFERRED ROCK LINE</td> <td>[Symbol] SOUNDING ROD</td> <td></td> <td></td> </tr> <tr> <td>[Symbol] ALLUVIAL SOIL BOUNDARY</td> <td></td> <td></td> <td></td> </tr> <tr> <td>[Symbol] DIP & DIP DIRECTION OF ROCK STRUCTURES</td> <td></td> <td></td> <td></td> </tr> </table>		[Symbol] ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION	[Symbol] TEST BORING	[Symbol] AUGER BORING	[Symbol] TEST BORING W/ CORE	[Symbol] SOIL SYMBOL	[Symbol] SPT N-VALUE	[Symbol] CORE BORING	[Symbol] SPT REFUSAL	[Symbol] ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT	[Symbol] MONITORING WELL	[Symbol] PIEZOMETER INSTALLATION		[Symbol] INFERRED SOIL BOUNDARY	[Symbol] SLOPE INDICATOR INSTALLATION	[Symbol] CONE PENETROMETER TEST		[Symbol] INFERRED ROCK LINE	[Symbol] SOUNDING ROD			[Symbol] ALLUVIAL SOIL BOUNDARY				[Symbol] DIP & DIP DIRECTION OF ROCK STRUCTURES																																																																																																													
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																										
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE	< 4	< 0.25																																																																																																																																																																										
	MEDIUM DENSE	4 TO 10	0.25 TO 1.0																																																																																																																																																																										
	DENSE	10 TO 30	1.0 TO 2.0																																																																																																																																																																										
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT	< 2	< 0.25																																																																																																																																																																										
	SOFT	2 TO 4	0.25 TO 0.50																																																																																																																																																																										
	MEDIUM STIFF	4 TO 8	0.50 TO 1.0																																																																																																																																																																										
	STIFF	8 TO 15	1.0 TO 2.0																																																																																																																																																																										
	VERY STIFF	15 TO 30	2.0 TO 4.0																																																																																																																																																																										
	HARD	> 30	> 4.0																																																																																																																																																																										
[Symbol] ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION	[Symbol] TEST BORING	[Symbol] AUGER BORING	[Symbol] TEST BORING W/ CORE																																																																																																																																																																										
[Symbol] SOIL SYMBOL	[Symbol] SPT N-VALUE	[Symbol] CORE BORING	[Symbol] SPT REFUSAL																																																																																																																																																																										
[Symbol] ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT	[Symbol] MONITORING WELL	[Symbol] PIEZOMETER INSTALLATION																																																																																																																																																																											
[Symbol] INFERRED SOIL BOUNDARY	[Symbol] SLOPE INDICATOR INSTALLATION	[Symbol] CONE PENETROMETER TEST																																																																																																																																																																											
[Symbol] INFERRED ROCK LINE	[Symbol] SOUNDING ROD																																																																																																																																																																												
[Symbol] ALLUVIAL SOIL BOUNDARY																																																																																																																																																																													
[Symbol] DIP & DIP DIRECTION OF ROCK STRUCTURES																																																																																																																																																																													
<p align="center">TEXTURE OR GRAIN SIZE</p> <table border="1"> <thead> <tr> <th>U.S. STD. SIEVE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> </thead> <tbody> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </tbody> </table>		U.S. STD. SIEVE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	<p align="center">ABBREVIATIONS</p> <table border="1"> <tr> <td>AR - AUGER REFUSAL</td> <td>MED. - MEDIUM</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>MICA. - MICACEOUS</td> <td>WEA. - WEATHERED</td> </tr> <tr> <td>CL - CLAY</td> <td>MOD. - MODERATELY</td> <td>UNIT WEIGHT</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>NP - NON PLASTIC</td> <td>D_r - DRY UNIT WEIGHT</td> </tr> <tr> <td>CSE. - COARSE</td> <td>ORG. - ORGANIC</td> <td>S - BULK</td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>PMT - PRESSUREMETER TEST</td> <td>SS - SPLIT SPOON</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>SAP. - SAPROLITIC</td> <td>ST - SHELBY TUBE</td> </tr> <tr> <td>○ - VOID RATIO</td> <td>SD. - SAND, SANDY</td> <td>RS - ROCK</td> </tr> <tr> <td>F - FINE</td> <td>SL. - SILT, SILTY</td> <td>RT - RECOMPACTED TRIAXIAL</td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td>SLI. - SLIGHTLY</td> <td>RCR - CALIFORNIA BEARING RATIO</td> </tr> <tr> <td>FRAC. - FRACTURED, FRACTURES</td> <td>TCR - TRICONE REFUSAL</td> <td></td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td>W - MOISTURE CONTENT</td> <td></td> </tr> <tr> <td>HL. - HIGHLY</td> <td>V - VERY</td> <td></td> </tr> </table>		AR - AUGER REFUSAL	MED. - MEDIUM	VST - VANE SHEAR TEST	BT - BORING TERMINATED	MICA. - MICACEOUS	WEA. - WEATHERED	CL - CLAY	MOD. - MODERATELY	UNIT WEIGHT	CPT - CONE PENETRATION TEST	NP - NON PLASTIC	D _r - DRY UNIT WEIGHT	CSE. - COARSE	ORG. - ORGANIC	S - BULK	DMT - DILATOMETER TEST	PMT - PRESSUREMETER TEST	SS - SPLIT SPOON	DPT - DYNAMIC PENETRATION TEST	SAP. - SAPROLITIC	ST - SHELBY TUBE	○ - VOID RATIO	SD. - SAND, SANDY	RS - ROCK	F - FINE	SL. - SILT, SILTY	RT - RECOMPACTED TRIAXIAL	FOSS. - FOSSILIFEROUS	SLI. - SLIGHTLY	RCR - CALIFORNIA BEARING RATIO	FRAC. - FRACTURED, FRACTURES	TCR - TRICONE REFUSAL		FRAGS. - FRAGMENTS	W - MOISTURE CONTENT		HL. - HIGHLY	V - VERY																																																																																																																						
U.S. STD. SIEVE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																							
	4.76	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																							
AR - AUGER REFUSAL	MED. - MEDIUM	VST - VANE SHEAR TEST																																																																																																																																																																											
BT - BORING TERMINATED	MICA. - MICACEOUS	WEA. - WEATHERED																																																																																																																																																																											
CL - CLAY	MOD. - MODERATELY	UNIT WEIGHT																																																																																																																																																																											
CPT - CONE PENETRATION TEST	NP - NON PLASTIC	D _r - DRY UNIT WEIGHT																																																																																																																																																																											
CSE. - COARSE	ORG. - ORGANIC	S - BULK																																																																																																																																																																											
DMT - DILATOMETER TEST	PMT - PRESSUREMETER TEST	SS - SPLIT SPOON																																																																																																																																																																											
DPT - DYNAMIC PENETRATION TEST	SAP. - SAPROLITIC	ST - SHELBY TUBE																																																																																																																																																																											
○ - VOID RATIO	SD. - SAND, SANDY	RS - ROCK																																																																																																																																																																											
F - FINE	SL. - SILT, SILTY	RT - RECOMPACTED TRIAXIAL																																																																																																																																																																											
FOSS. - FOSSILIFEROUS	SLI. - SLIGHTLY	RCR - CALIFORNIA BEARING RATIO																																																																																																																																																																											
FRAC. - FRACTURED, FRACTURES	TCR - TRICONE REFUSAL																																																																																																																																																																												
FRAGS. - FRAGMENTS	W - MOISTURE CONTENT																																																																																																																																																																												
HL. - HIGHLY	V - VERY																																																																																																																																																																												
<p align="center">SOIL MOISTURE - CORRELATION OF TERMS</p> <table border="1"> <thead> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td rowspan="2">LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td rowspan="2">OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </tbody> </table>		SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p align="center">EQUIPMENT USED ON SUBJECT PROJECT</p> <table border="1"> <thead> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> MOBILE B-</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td></td> </tr> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> CME-55D</td> <td><input type="checkbox"/> HUNG FACED FINGER BITS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG.-CARBIDE INSERTS</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE * STEEL TEETH</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE * TUNG.-CARB.</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> CORE BIT</td> <td></td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> </tbody> </table>		DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER		<input type="checkbox"/> CME-45C	<input type="checkbox"/> 8" HOLLOW AUGERS		<input type="checkbox"/> CME-55D	<input type="checkbox"/> HUNG FACED FINGER BITS		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG.-CARBIDE INSERTS			<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER			<input type="checkbox"/> TRICONE * STEEL TEETH			<input type="checkbox"/> TRICONE * TUNG.-CARB.			<input type="checkbox"/> CORE BIT				<input type="checkbox"/> POST HOLE DIGGER			<input type="checkbox"/> HAND AUGER			<input type="checkbox"/> SOUNDING ROD			<input type="checkbox"/> VANE SHEAR TEST																																																																																																																			
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																											
LL - LIQUID LIMIT	- SATURATED - (SAT)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																											
	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																											
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																											
	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																											
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																																																																											
<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																											
<input type="checkbox"/> BK-51	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER																																																																																																																																																																												
<input type="checkbox"/> CME-45C	<input type="checkbox"/> 8" HOLLOW AUGERS																																																																																																																																																																												
<input type="checkbox"/> CME-55D	<input type="checkbox"/> HUNG FACED FINGER BITS																																																																																																																																																																												
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG.-CARBIDE INSERTS																																																																																																																																																																												
	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER																																																																																																																																																																												
	<input type="checkbox"/> TRICONE * STEEL TEETH																																																																																																																																																																												
	<input type="checkbox"/> TRICONE * TUNG.-CARB.																																																																																																																																																																												
	<input type="checkbox"/> CORE BIT																																																																																																																																																																												
		<input type="checkbox"/> POST HOLE DIGGER																																																																																																																																																																											
		<input type="checkbox"/> HAND AUGER																																																																																																																																																																											
		<input type="checkbox"/> SOUNDING ROD																																																																																																																																																																											
		<input type="checkbox"/> VANE SHEAR TEST																																																																																																																																																																											
<p align="center">PLASTICITY</p> <table border="1"> <thead> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> </thead> <tbody> <tr> <td>LW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </tbody> </table>		NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	LW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p align="center">FRACTURE SPACING</p> <table border="1"> <thead> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> </thead> <tbody> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>> 4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </tbody> </table>		TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	> 4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET																																																																																																																															
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																											
LW PLASTICITY	0-5	VERY LOW																																																																																																																																																																											
MED. PLASTICITY	6-15	SLIGHT																																																																																																																																																																											
HIGH PLASTICITY	16-25	MEDIUM																																																																																																																																																																											
	26 OR MORE	HIGH																																																																																																																																																																											
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																										
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	> 4 FEET																																																																																																																																																																										
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																										
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																										
CLOSE	0.16 TO 1 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																										
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																										
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																										
<p align="center">COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>		<p align="center">INDURATION</p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <table border="1"> <tr> <td>FRIABLE</td> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>		FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																		
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																																																																												
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																												
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																												
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																												

09/08/09

See Sheet 1-A For Index of Sheets



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS


GUILFORD COUNTY

LOCATION: REPLACEMENT OF BRIDGE NO. 77 ON SR 4053
OVER US 29 /US 70 I-85 BUS

TYPE OF WORK: GRADING, DRAINAGE, PAVING AND STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-4760	2A	14
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
38532.1.1	BRZ-4053(1)	PE	


TIP PROJECT: B-4760



THIS PROJECT IS WITHIN THE MUNICIPAL BOUNDARY OF HIGH POINT

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

CONTRACT:



DESIGN DATA

ADT 2012 =	12,500
ADT 2035 =	17,600
DHV =	12 %
D =	55 %
T =	% *
V =	40 MPH
* TTST =	3% DUAL 5%
FUNC CLASS =	COLLECTOR
STATEWIDE TIER	

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT B-4760 =	0.354 MILES
LENGTH STRUCTURE TIP PROJECT B-4760 =	0.034 MILES
TOTAL LENGTH TIP PROJECT B-4760 =	0.388 MILES

Prepared in the Office of:
DIVISION OF HIGHWAYS
1000 Birch Ridge Dr., Raleigh NC, 27610

2006 STANDARD SPECIFICATIONS	
RIGHT OF WAY DATE: JULY 15, 2011	G.E. BREW, P.E. PROJECT ENGINEER
LETTING DATE: JULY 17, 2012	I.T. YOUNIS PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER

SIGNATURE: _____ P.E.

ROADWAY DESIGN ENGINEER

SIGNATURE: _____ P.E.

**DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA**

STATE HIGHWAY DESIGN ENGINEER P.E.

05-OCT-2010 12:41 S:\Contractors\invest\gaffions\TIP\B4760_GEO_ROWY\CADD_GEO\TECH\PlanProf\B4760_geo_tsh.dgn bdworley AT GEC248231



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE
GOVERNOR

EUGENE A. CONTI, JR.
SECRETARY

October 11, 2010

STATE PROJECT: 38532.1.1 (B-4760)
F.A. PROJECT: BRZ-4053(1)
COUNTY: Guilford
DESCRIPTION: Bridge No. 77 on SR 4053 (Surrett Rd.) over US 29/US 70/I-85 Business
SUBJECT: Geotechnical Report - Inventory

Project Description

The project consists of constructing 0.388 miles of widening and realignment of SR 4053 (Surrett Dr.) between Timber St. and Surrett Court. The new alignment will accommodate the construction of a proposed new bridge over US 29/US 70/I-85 Business.

The geotechnical investigation was conducted August 2010 utilizing NCDOT Geotechnical Engineering Unit personnel. Borings were advanced using a CME-550X drill machine (equipment #AFO0071) equipped with automatic hammer (efficiency rating 72%, 9/3/09). Standard Penetration Test borings were performed at specific locations to provide subsurface information for roadway design and construction. Four preliminary bridge borings were drilled at the time of the roadway investigation to aid in structure foundation design. Rock coring was performed in two of those borings using NW casing and NWD-4 coring equipment. Representative soil samples were collected and submitted to the Materials and Tests Unit for laboratory analysis.

The following alignments were investigated for this project:

<u>Line</u>	<u>Station(±)</u>
-L-	14+50 to 35+00

Physiography, Geology and Surface Water

The project is located in the central portion of the Piedmont Physiographic Province near the city of High Point, N.C. Topography in the area is generally gently rolling. The project area is well-developed urban landscape.

The geology of the project area is dominated by residual saprolitic soils, predominantly sandy silts and silty sands, overlying Paleozoic to Late Proterozoic-age metamorphosed diorite. No in-situ crystalline rock outcrops were located in the project area.

Surface water is drained from the project area by ditches that feed into a small creek that flows north under the project area through a series of culverts.

Soils Properties

Soils encountered at the project site include roadway embankment, alluvial, and residual.

Roadway Embankment soils are present along the proposed alignment and are related to the original alignment of Surrett Drive and US 29/US 70/I-85 Business. These soils consist of red-brown, soft to medium stiff, silty clay (A-7-6).

Recent alluvial deposits, less than 0.5 ft. in depth, were observed in the bed of the creek that drains to the north/northeast across the project area. These deposits consist of a very thin layer of loose, silty sand (A-2-4) and coarse sand (A-1-b). Alluvial soils were not encountered in any of the geotechnical borings performed during the roadway investigation.

Residual soils encountered along the project corridor are derived from weathering of the underlying metamorphosed diorite. Typically, these soils are saprolitic and consist of tan-gray to brown, stiff to very stiff, sandy silt (A-4) and brown, dense to very dense, silty sand (A-2-4). Also encountered in minor amounts was tan-brown, medium stiff, silty clay (A-7-5), tan to red-brown, stiff, saprolitic sandy clay (A-6), and tan-brown, medium stiff, saprolitic clayey silt (A-5).

Rock Properties

Weathered rock was encountered during the roadway investigation. It originates from the underlying metamorphosed diorite. Weathered rock thickness ranges from less than approximately 2 ft. to greater than 15 ft. across the project. The top of weathered rock was encountered below residual soils in borings ranging from elevation 801.3 ft to 837.8 ft.

Crystalline rock was encountered during the roadway investigation and consists of brown to gray, very slightly weathered to fresh, close to wide fractured, moderately hard to very hard, foliated, metamorphosed diorite. The top of crystalline rock was encountered in borings ranging from 797.2 ft. to 837.5 ft.

Ground Water

Ground water data was collected during below average rainfall conditions. Water levels across the project vary due to topographic relief and soil permeability. In the borings performed for this investigation, 24-hour groundwater readings ranged in elevation from 820.9 ft. to 838.0 ft. Groundwater may fluctuate with seasonal precipitation.

Prepared by,

Bradley D. Worley, PG
Project Geological Engineer

MAILING ADDRESS:
NC DEPARTMENT OF TRANSPORTATION
GEOTECHNICAL ENGINEERING UNIT
1589 MAIL SERVICE CENTER
RALEIGH NC 27699-1589

TELEPHONE: 919-250-4088
Fax: 919-250-4237
www.ncdot.gov/doh/preconstruct/highway/geotech

LOCATION:
CENTURY CENTER COMPLEX
ENTRANCE B-2
1020 BIRCH RIDGE DRIVE
RALEIGH NC 27610

PROJECT: B-4760

COUNTY: Guilford

EARTHWORK BALANCE SHEET
DATE: 2/8/2012

COMPILED BY: CJT / JBT/iy


SHEET 1 OF 1 SHEET

STATION	STATION	EXCAVATION (Cubic Yard)					EMBANKMENT (Cubic Yard)				BORROW (Cu. Yd.)	WASTE (Cubic Yard)			
		TOTAL UNCLASS.	ROCK	UNDERCUT	UNSUIT. UNCLASS.	SUITABLE UNCLASS.	TOTAL	ROCK	EARTH	EMBANK. +20%		ROCK	SUITABLE	UNSUIT.	TOTAL
SUMMARY 1 LT SIDE															
-L- 14+50.00 LT	22+55.49	1,206				1,206	7,336	7,336	8,803	7,597					
-L- 24+51.49 LT	34+00.00	213				213	26,329	26,329	31,595	31,382					
SUMMARY 1	SUBTOTAL	1,419				1,419	33,665	33,665	40,398	38,979					
SUMMARY 2 RT SIDE															
-L- 14+50.00	22+55.49	273				273	1,341	1,341	1,609	1,336					
-L- 24+51.49	34+00.00	45				45	1,567	1,567	1,880	1,835					
-LOOPB- 10+50.00	11+50.00	54				54	120	120	144	90					
-LOOPC- 11+00.00	11+50.00	30				30	4	4	5			25		25	
SUMMARY 2	SUBTOTAL	402				402	3,032	3,032	3,638	3,262		25		25	
TOTAL															
		1,821				1,821	36,697	36,697	44,036	42,241		25		25	
SHOULDER MATERIAL							436	436	523	523					
LOSS DUE TO CLEARING & GRUBBING		-100				-100				100					
PROJECT TOTAL															
		1,721				1,721	37,133	37,133	44,560	42,864		25		25	
EST. 5% TO REPLACE TOP SOIL ON BORROW PIT										2,143					
GRAND TOTAL															
		1,721				1,721	37,133	37,133	44,560	45,007		25		25	
SAY		1,800								45,500					
ESTIMATED UNDERCUT = 550 C.Y.															
EST. SELECT GRANULAR MATERIAL = 250 C.Y.															
EST. DRAINAGE DITCH EXCAVATION = 489 C.Y.															


NOTE: EARTHWORK QUANTITIES ARE CALCULATED BY THE ROADWAY DESIGN UNIT. THESE EARTHWORK QUANTITIES ARE BASED IN PART ON SUBSURFACE DATA PROVIDED BY THE GEOTECHNICAL ENGINEERING UNIT.
NOTE: APPROXIMATE QUANTITIES ONLY. UNCLASSIFIED EXCAVATION, FINE GRADING, CLEARING AND GRUBBING, AND REMOVAL OF EXISTING PAVEMENT WILL BE PAID FOR AT THE LUMP SUM PRICE FOR "GRADING".

8/17/99
05-OCT-2010 15:14
S:\Contracts\Investigations\TIP\B4760_GEO_RDN\X\CADD_GEO\TECH\21\B4760_geo_rev005.dwg
REVISED BY: [unclear] DATE: 8/17/99

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION




MATCH LINE -L- STA 21+50 SEE SHEET 4



REVISIONS


8/23/99
S:\Projects\1998\19980823\19980823.dgn
S:\Projects\1998\19980823\19980823.dgn
S:\Projects\1998\19980823\19980823.dgn



18+00.00


-L-

8/23/99
05-OCT-2010 15:16
S:\Contracts\Investigations\TIP\B4760_GEO_ROWY\CADD_GEO\TECH\sec\B4760_Geo_x31.L_2.dgn
Editor:Leu




21+50.00

8/23/99
I:\OCT-2010 15422
S:\CADD\10044\Investigations\TIP\B4760_GEO_RDWY\CADD_GEO\TECH\ssc\B4760_Geo_xsl.L_2.dgn
Bdwor\lei




8/23/99



I:\OCT-2010_15\24
 S:\Con\proj\GIS\Investigations\TIP\B4760\GEO\ROWY\CADD_GEO\TECH\ssc\B4760_Geo_xsl.L_2.dgn
 S:\Con\proj\GIS\Investigations\TIP\B4760\GEO\ROWY\CADD_GEO\TECH\ssc\B4760_Geo_xsl.L_2.dgn
 S:\Con\proj\GIS\Investigations\TIP\B4760\GEO\ROWY\CADD_GEO\TECH\ssc\B4760_Geo_xsl.L_2.dgn


8/23/99



20-OCT-2010 10:19 S:\CONTRACTS\TIP\B4760_GEO_RDWY\CADD_GEO\TECH\SSC\B4760_Geo_xst.L-2.dgn

-L-

8/23/99
I:\CCT-2010 15226
Subcontractors\TIP\B4760.GEO\RDWY\CADD.GEOTECH\XSEC\B4760_Geo_XS1.L_2.dgn



2:1

TEMPORARY SLOPE

3%

6:1

6:1

853.66

B+4

RESIDUAL, RED-TAN, SILTY CLAY (A-7) AND STIFF TO HARD, SAPROLITIC,
MEDIUM STIFF, SAPROLITIC, TAN-BROWN AND GRAYISH WHITE, SILTY FINE SAND (A-2-4)

WEATHERED ROCK, (META-DIORITE)


0070.9

6070.0

27+00.00

-L-

8/23/99
I:\OCT-2010\15428
S:\CADD\14\sec2\AT\GEC2\8231
S:\CADD\14\sec2\AT\GEC2\8231



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C.SAND	F.SAND	SILT	CLAY	10	40	200		
SS-1	40.0 LT	18+00	4.3-5.8	A-4(6)	39	9	10.8	29.8	41.0	18.4	100	96	70	-	-
SS-3	40.0 LT	18+00	9.3-10.8	A-4(0)	29	4	16.5	42.4	16.5	24.5	95	89	51	-	-
SS-6	CL	21+50	9.4-10.9	A-6(8)	38	11	8.0	28.0	45.7	18.4	100	97	74	-	-
SS-8	CL	22+60	9.4-10.9	A-6(5)	35	15	21.4	27.3	26.7	24.5	88	77	51	-	-
SS-9	CL	22+60	14.4-15.9	A-4(0)	24	NP	33.4	33.4	27.1	6.1	100	83	40	-	-
SS-14	30.0 LT	29+50	4.4-5.9	A-7-6(17)	49	22	9.2	22.7	25.3	42.9	100	96	75	-	-
SS-15	30.0 LT	29+50	9.4-10.9	A-6(8)	40	14	11.0	31.6	36.9	20.4	98	94	66	-	-
SS-16	CL	24+44	4.6-6.1	A-7-6(21)	52	27	9.8	16.5	24.7	49.0	99	94	77	-	-
SS-17	CL	24+44	9.6-11.1	A-6(5)	40	12	21.4	32.0	28.2	18.4	99	85	56	-	-
SS-19	19.0 RT	25+56	3.6-5.1	A-7-6(18)	51	22	9.8	19.2	32.2	38.8	100	95	76	-	-
SS-22	19.0 RT	25+56	18.6-20.1	A-2-4(0)	27	3	40.0	30.4	25.5	4.1	90	63	34	-	-
SS-23	19.3 RT	23+47	4.0-5.5	A-7-5(9)	44	11	9.0	29.2	41.4	20.4	100	97	72	-	-
SS-24	19.3 RT	23+47	9.0-10.5	A-5(3)	43	5	13.3	37.6	41.0	8.2	100	95	61	-	-
SS-26	19.3 RT	23+47	19.0-20.5	A-4(0)	27	2	29.4	39.8	26.7	4.1	100	86	41	-	-
SS-28	19.3 RT	23+47	29.0-30.5	A-2-4(0)	28	4	48.6	24.3	19.0	8.2	93	59	31	-	-