

NOTE: SEE SHEET 2A FOR PLAN SHEET LAYOUT AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5178 42549.1.1	1	21
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
		P.E.	
		RW & UTIL.	

CONTENTS

PAGES	TOPIC
1 - 2	TITLE, LEGEND
3, 3A	INV. RPT/EARTHWORK SUM.
4 - 5	PLAN SHEETS
6 - 18	X-SECTS. -L-
19 - 21	X-SECTS. -SR 3431-

ROADWAY
SUBSURFACE INVESTIGATION

PROJ. REFERENCE NO. 42549.1.1 B-5178 F.A. PROJ. BRIMS-0261(80)
COUNTY BUNCOMBE
PROJECT DESCRIPTION REPLACEMENT OF BRIDGES 235 AND 238 ON I-26
OVER SR 3431 (POND ROAD) AND HOMINY CREEK


CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING, AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 250-4088. NEITHER THE SUBSURFACE PLANS AND REPORTS, NOR THE FIELD BORING LOGS, ROCK CORES, OR SOIL TEST DATA ARE PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION, AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THIS PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.


INVENTORY



PERSONNEL

JC KUHNE
MM HAGER
DO CHEEK
DC ELLIOT
C COFFEY
LE RIDDLE
DM MULLEN

INVESTIGATED BY JC KUHNE
CHECKED BY WD FRYE
SUBMITTED BY WD FRYE
DATE 9/6/2011



CONTRACT: C202880 ID: B-5178

DRAWN BY: JC KUHNE JT WILLIAMS

NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IT IS CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THE PROJECT.

NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION				GRADATION				ROCK DESCRIPTION				TERMS AND DEFINITIONS																																															
<p>SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE:</p> <p align="center"><i>VERY STIFF, GRN. SILTY CLAY, MOST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>				<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES.</p> <p align="center">ANGULARITY OF GRAINS</p> <p>THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: <u>ANGULAR</u>, <u>SUBANGULAR</u>, <u>SUBROUNDED</u>, OR <u>ROUNDED</u>.</p>				<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT IF TESTED, WOULD YIELD SPT REFUSAL, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>				<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																															
<p align="center">SOIL LEGEND AND AASHTO CLASSIFICATION</p> <table border="1"> <tr> <th>GENERAL CLASS.</th> <th>GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th>SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th>ORGANIC MATERIALS</th> </tr> <tr> <td>GROUP CLASS.</td> <td>A-1, A-1-b, A-2, A-2-4, A-2-5, A-2-6, A-2-7</td> <td>A-4, A-5, A-6, A-7, A-7-5, A-7-6</td> <td>A-1, A-2, A-3, A-4, A-5</td> </tr> <tr> <td>SYMBOL</td> <td>[Diagrams of soil symbols]</td> <td>[Diagrams of soil symbols]</td> <td>[Diagrams of soil symbols]</td> </tr> <tr> <td>% PASSING</td> <td>50, 30, 15, 10, 5, 2.5, 1.5, 0.75, 0.425, 0.25, 0.15, 0.075, 0.0425, 0.025, 0.015, 0.0075</td> <td>40, 30, 20, 15, 10, 5, 2.5, 1.5, 0.75, 0.425, 0.25, 0.15, 0.075, 0.0425, 0.025, 0.015, 0.0075</td> <td>GRANULAR SOILS, SILT-CLAY SOILS, MUCK, PEAT</td> </tr> <tr> <td>LIQUID LIMIT PLASTIC INDEX</td> <td>6, 10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100</td> <td>10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100</td> <td>SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER, HIGHLY ORGANIC SOILS</td> </tr> <tr> <td>GROUP INDEX</td> <td>0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20</td> <td>0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20</td> <td></td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td>STONE FRAGS, GRAVEL, SAND</td> <td>FINE SAND, SILTY OR CLAYEY GRAVEL AND SAND</td> <td>SILTY SOILS, CLAYEY SOILS</td> </tr> <tr> <td>GEN. RATING AS A SUBGRADE</td> <td>EXCELLENT TO GOOD</td> <td>FAIR TO POOR</td> <td>FAIR TO POOR, POOR, UNSUITABLE</td> </tr> </table> <p align="center">PI OF A-7-5 SUBGROUP IS ≤ LL - 30; PI OF A-7-6 SUBGROUP IS > LL - 30</p>				GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)	SILT-CLAY MATERIALS (> 35% PASSING #200)	ORGANIC MATERIALS	GROUP CLASS.	A-1, A-1-b, A-2, A-2-4, A-2-5, A-2-6, A-2-7	A-4, A-5, A-6, A-7, A-7-5, A-7-6	A-1, A-2, A-3, A-4, A-5	SYMBOL	[Diagrams of soil symbols]	[Diagrams of soil symbols]	[Diagrams of soil symbols]	% PASSING	50, 30, 15, 10, 5, 2.5, 1.5, 0.75, 0.425, 0.25, 0.15, 0.075, 0.0425, 0.025, 0.015, 0.0075	40, 30, 20, 15, 10, 5, 2.5, 1.5, 0.75, 0.425, 0.25, 0.15, 0.075, 0.0425, 0.025, 0.015, 0.0075	GRANULAR SOILS, SILT-CLAY SOILS, MUCK, PEAT	LIQUID LIMIT PLASTIC INDEX	6, 10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100	10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER, HIGHLY ORGANIC SOILS	GROUP INDEX	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20		USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL, SAND	FINE SAND, SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS, CLAYEY SOILS	GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD	FAIR TO POOR	FAIR TO POOR, POOR, UNSUITABLE	<p align="center">MINERALOGICAL COMPOSITION</p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE.</p> <p align="center">COMPRESSIBILITY</p> <p>SLIGHTLY COMPRESSIBLE: LIQUID LIMIT LESS THAN 31 MODERATELY COMPRESSIBLE: LIQUID LIMIT EQUAL TO 31-50 HIGHLY COMPRESSIBLE: LIQUID LIMIT GREATER THAN 50</p> <p align="center">PERCENTAGE OF MATERIAL</p> <table border="1"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT-CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>>10%</td> <td>>20%</td> <td>HIGHLY</td> </tr> </table> <p align="center">GROUND WATER</p> <p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA SPRING OR SEEP</p>				ORGANIC MATERIAL	GRANULAR SOILS	SILT-CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	>10%	>20%	HIGHLY
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)	SILT-CLAY MATERIALS (> 35% PASSING #200)	ORGANIC MATERIALS																																																								
GROUP CLASS.	A-1, A-1-b, A-2, A-2-4, A-2-5, A-2-6, A-2-7	A-4, A-5, A-6, A-7, A-7-5, A-7-6	A-1, A-2, A-3, A-4, A-5																																																								
SYMBOL	[Diagrams of soil symbols]	[Diagrams of soil symbols]	[Diagrams of soil symbols]																																																								
% PASSING	50, 30, 15, 10, 5, 2.5, 1.5, 0.75, 0.425, 0.25, 0.15, 0.075, 0.0425, 0.025, 0.015, 0.0075	40, 30, 20, 15, 10, 5, 2.5, 1.5, 0.75, 0.425, 0.25, 0.15, 0.075, 0.0425, 0.025, 0.015, 0.0075	GRANULAR SOILS, SILT-CLAY SOILS, MUCK, PEAT																																																								
LIQUID LIMIT PLASTIC INDEX	6, 10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100	10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER, HIGHLY ORGANIC SOILS																																																								
GROUP INDEX	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20																																																									
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS, GRAVEL, SAND	FINE SAND, SILTY OR CLAYEY GRAVEL AND SAND	SILTY SOILS, CLAYEY SOILS																																																								
GEN. RATING AS A SUBGRADE	EXCELLENT TO GOOD	FAIR TO POOR	FAIR TO POOR, POOR, UNSUITABLE																																																								
ORGANIC MATERIAL	GRANULAR SOILS	SILT-CLAY SOILS	OTHER MATERIAL																																																								
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																								
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																								
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																								
HIGHLY ORGANIC	>10%	>20%	HIGHLY																																																								
<p align="center">CONSISTENCY OR DENSENESS</p> <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE, LOOSE, MEDIUM DENSE, DENSE, VERY DENSE</td> <td>4, 10, 30, 50, >50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT, SOFT, MEDIUM STIFF, STIFF, VERY STIFF, HARD</td> <td><2, 2 to 4, 4 to 8, 8 to 15, 15 to 30, >30</td> <td><0.25, 0.25 to 0.50, 0.5 to 1.0, 1 to 2, 2 to 4, >4</td> </tr> </table>				PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE, LOOSE, MEDIUM DENSE, DENSE, VERY DENSE	4, 10, 30, 50, >50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT, SOFT, MEDIUM STIFF, STIFF, VERY STIFF, HARD	<2, 2 to 4, 4 to 8, 8 to 15, 15 to 30, >30	<0.25, 0.25 to 0.50, 0.5 to 1.0, 1 to 2, 2 to 4, >4	<p align="center">MISCELLANEOUS SYMBOLS</p> <table border="1"> <tr> <td>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td> <td>SPT TEST BORING</td> <td>SAMPLE DESIGNATIONS</td> </tr> <tr> <td>SOIL SYMBOL</td> <td>AUGER BORING</td> <td>S - BULK SAMPLE</td> </tr> <tr> <td>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td> <td>CORE BORING</td> <td>SS - SPLIT SPOON SAMPLE</td> </tr> <tr> <td>INFERRED SOIL BOUNDARY</td> <td>MONITORING WELL</td> <td>ST - SHELBY TUBE SAMPLE</td> </tr> <tr> <td>INFERRED ROCK LINE</td> <td>PIEZOMETER INSTALLATION</td> <td>RS - ROCK SAMPLE</td> </tr> <tr> <td>ALLUVIAL SOIL BOUNDARY</td> <td>SLOPE INDICATOR INSTALLATION</td> <td>RT - RECOMPACTED TRIAXIAL SAMPLE</td> </tr> <tr> <td>DIP & DIP DIRECTION OF ROCK STRUCTURES</td> <td>SPT N-VALUE</td> <td>CBR - CALIFORNIA BEARING RATIO SAMPLE</td> </tr> <tr> <td>SOUNDING ROD</td> <td>SPT REFUSAL</td> <td></td> </tr> </table>				ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION	SPT TEST BORING	SAMPLE DESIGNATIONS	SOIL SYMBOL	AUGER BORING	S - BULK SAMPLE	ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT	CORE BORING	SS - SPLIT SPOON SAMPLE	INFERRED SOIL BOUNDARY	MONITORING WELL	ST - SHELBY TUBE SAMPLE	INFERRED ROCK LINE	PIEZOMETER INSTALLATION	RS - ROCK SAMPLE	ALLUVIAL SOIL BOUNDARY	SLOPE INDICATOR INSTALLATION	RT - RECOMPACTED TRIAXIAL SAMPLE	DIP & DIP DIRECTION OF ROCK STRUCTURES	SPT N-VALUE	CBR - CALIFORNIA BEARING RATIO SAMPLE	SOUNDING ROD	SPT REFUSAL																	
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																								
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE, LOOSE, MEDIUM DENSE, DENSE, VERY DENSE	4, 10, 30, 50, >50	N/A																																																								
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT, SOFT, MEDIUM STIFF, STIFF, VERY STIFF, HARD	<2, 2 to 4, 4 to 8, 8 to 15, 15 to 30, >30	<0.25, 0.25 to 0.50, 0.5 to 1.0, 1 to 2, 2 to 4, >4																																																								
ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION	SPT TEST BORING	SAMPLE DESIGNATIONS																																																									
SOIL SYMBOL	AUGER BORING	S - BULK SAMPLE																																																									
ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT	CORE BORING	SS - SPLIT SPOON SAMPLE																																																									
INFERRED SOIL BOUNDARY	MONITORING WELL	ST - SHELBY TUBE SAMPLE																																																									
INFERRED ROCK LINE	PIEZOMETER INSTALLATION	RS - ROCK SAMPLE																																																									
ALLUVIAL SOIL BOUNDARY	SLOPE INDICATOR INSTALLATION	RT - RECOMPACTED TRIAXIAL SAMPLE																																																									
DIP & DIP DIRECTION OF ROCK STRUCTURES	SPT N-VALUE	CBR - CALIFORNIA BEARING RATIO SAMPLE																																																									
SOUNDING ROD	SPT REFUSAL																																																										
<p align="center">TEXTURE OR GRAIN SIZE</p> <table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table> <table border="1"> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE, SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td>MM 305</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> <td></td> </tr> <tr> <td>IN. 12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>				U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE, SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)	MM 305	75	2.0	0.25	0.05	0.005		IN. 12	3						<p align="center">ABBREVIATIONS</p> <p>AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HL - HIGHLY MED. - MEDIUM MICA - MICA MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITE SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT v - VERY VST - VANE SHEAR TEST WEA. - WEATHERED γ_d - UNIT WEIGHT γ_s - DRY UNIT WEIGHT</p>																				
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																					
	4.76	2.00	0.42	0.25	0.075	0.053																																																					
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE, SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																					
MM 305	75	2.0	0.25	0.05	0.005																																																						
IN. 12	3																																																										
<p align="center">SOIL MOISTURE - CORRELATION OF TERMS</p> <table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>				SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p align="center">EQUIPMENT USED ON SUBJECT PROJECT</p> <table border="1"> <tr> <td>DRILL UNITS:</td> <td>ADVANCING TOOLS:</td> <td>HAMMER TYPE:</td> </tr> <tr> <td><input type="checkbox"/> MOBILE B-</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> BK-51</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td>CORE SIZE:</td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-45C</td> <td><input checked="" type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> B</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> N</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td><input type="checkbox"/> H</td> </tr> <tr> <td></td> <td><input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> w/ ADVANCER</td> <td>HAND TOOLS:</td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE _____ STEEL TEETH</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE _____ TUNG-CARB.</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td></td> <td><input checked="" type="checkbox"/> CORE BIT</td> <td><input checked="" type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td></td> <td></td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> </table>				DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> BK-51	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:	<input checked="" type="checkbox"/> CME-45C	<input checked="" type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> B	<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> N	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input type="checkbox"/> H		<input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> w/ ADVANCER	HAND TOOLS:		<input type="checkbox"/> TRICONE _____ STEEL TEETH	<input type="checkbox"/> POST HOLE DIGGER		<input type="checkbox"/> TRICONE _____ TUNG-CARB.	<input type="checkbox"/> HAND AUGER		<input checked="" type="checkbox"/> CORE BIT	<input checked="" type="checkbox"/> SOUNDING ROD			<input type="checkbox"/> VANE SHEAR TEST				
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																									
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																									
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																									
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																									
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																									
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																									
<input type="checkbox"/> MOBILE B-	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																									
<input type="checkbox"/> BK-51	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																									
<input checked="" type="checkbox"/> CME-45C	<input checked="" type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> B																																																									
<input type="checkbox"/> CME-550	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> N																																																									
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input type="checkbox"/> H																																																									
	<input checked="" type="checkbox"/> CASING <input checked="" type="checkbox"/> w/ ADVANCER	HAND TOOLS:																																																									
	<input type="checkbox"/> TRICONE _____ STEEL TEETH	<input type="checkbox"/> POST HOLE DIGGER																																																									
	<input type="checkbox"/> TRICONE _____ TUNG-CARB.	<input type="checkbox"/> HAND AUGER																																																									
	<input checked="" type="checkbox"/> CORE BIT	<input checked="" type="checkbox"/> SOUNDING ROD																																																									
		<input type="checkbox"/> VANE SHEAR TEST																																																									
<p align="center">PLASTICITY</p> <table border="1"> <tr> <th>NONPLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>LOW PLASTICITY</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MED. PLASTICITY</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGH PLASTICITY</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>				NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH	LOW PLASTICITY	0-5	VERY LOW	MED. PLASTICITY	6-15	SLIGHT	HIGH PLASTICITY	16-25	MEDIUM		26 OR MORE	HIGH	<p align="center">FRACATURE SPACING</p> <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table> <p align="center">BEDDING</p> <table border="1"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>> 4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>				TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FEET	VERY CLOSE	LESS THAN 0.16 FEET	TERM	THICKNESS	VERY THICKLY BEDDED	> 4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET											
NONPLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																									
LOW PLASTICITY	0-5	VERY LOW																																																									
MED. PLASTICITY	6-15	SLIGHT																																																									
HIGH PLASTICITY	16-25	MEDIUM																																																									
	26 OR MORE	HIGH																																																									
TERM	SPACING																																																										
VERY WIDE	MORE THAN 10 FEET																																																										
WIDE	3 TO 10 FEET																																																										
MODERATELY CLOSE	1 TO 3 FEET																																																										
CLOSE	0.16 TO 1 FEET																																																										
VERY CLOSE	LESS THAN 0.16 FEET																																																										
TERM	THICKNESS																																																										
VERY THICKLY BEDDED	> 4 FEET																																																										
THICKLY BEDDED	1.5 - 4 FEET																																																										
THINLY BEDDED	0.16 - 1.5 FEET																																																										
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																										
THICKLY LAMINATED	0.008 - 0.03 FEET																																																										
THINLY LAMINATED	< 0.008 FEET																																																										
<p align="center">COLOR</p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>				<p align="center">INDURATION</p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <table border="1"> <tr> <td>FRIABLE</td> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>				FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																												
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																										
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																										
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																										
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																										
<p align="center">NOTES:</p> <p align="right">ELEVATION: _____ FT.</p>				<p align="center">BENCH MARK: NA</p>																																																							

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5178	2A	21
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
42549.1.1.	BRIMS-0261(80)	PE	


BUNCOMBE COUNTY

**LOCATION: REPLACEMENT OF BRIDGES NO. 235 AND
238 ON I-26 OVER SR. 3431 (POND RD.) AND
HOMINY CREEK**

**TYPE OF WORK: RESURFACING, PAVING, GRADING, DRAINAGE,
STRUCTURE, STRUCTURE REMOVAL, GUARDRAIL,
RETAINING WALL AND MEDIAN BARRIER**

TIP PROJECT: B-5178

VICINITY MAP




THIS IS A CONTROLLED ACCESS PROJECT

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION

CONTRACT:

GRAPHIC SCALES



DESIGN DATA

ADT 2011 = 81700
ADT 2033 = 103600
DHV = 8 %
D = 55 %
T = 16 % *
V = 70 MPH
* TTST = 10 DUAL 6
FUNC CLASS =
INTERSTATE
STANDARD TIER

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT B-5178 = 0.288 MILE
LENGTH STRUCTURE TIP PROJECT B-5178 = 0.058 MILE
TOTAL LENGTH TIP PROJECT B-5178 = 0.346 MILE

Prepared in the Office of:
DIVISION OF HIGHWAYS
1000 Birch Ridge Dr., Raleigh NC, 27610

2006 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: JIMMY GOODNIGHT, PE
AUGUST 19, 2011
PROJECT ENGINEER

LETTING DATE: TIM GOINS, PE
AUGUST 21, 2012
PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER

SIGNATURE: _____ P.E.
ROADWAY DESIGN ENGINEER

SIGNATURE: _____ P.E.
STATE HIGHWAY DESIGN ENGINEER

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA



STATE HIGHWAY DESIGN ENGINEER

COMPUTED BY: NNA
 CHECKED BY: TDG

DATE
 DATE

PROJECT NO. B-5178
 SHEET NO. 1 OF 1

EARTHWORK BALANCE SHEET IN CUBIC YARDS

LOCATION	UNCLASSIFIED EXCAVATION	UNDERCUT EXCAVATION	UNSUITABLE EARTH EXCAVATION	SUITABLE EARTH EXCAVATION	TOTAL EMB'T	EARTH EMBANKMENT	ROCK EMB'T	EMB'T + % 15	BORROW	SELECT BORROW	SUITABLE WASTE	UNSUITABLE WASTE	TOTAL WASTE
-TEMP_ALN1-12+18.01 TO 15+88.61	942	0	0	942	717	717	0	825	0	0	117	0	117
-TEMP_ALN1-19+19.64 TO 22+93.74	20725	0	0	20725	12	12	0	14	0	0	20711	0	20711
-L- 28+00 TO 30+00 LT	349	0	0	349	236	236	0	271	0	0	78	0	78
-L- 30+50.00 TO 34+20.00 LT	1247	0	0	1247	140	140	0	161	0	0	1086	0	1086
-L- 37+50.50 TO 41+00.00 LT	386	0	0	386	160	160	0	184	0	0	202	0	202
-L- 41+50.00 TO 46+00.00 LT	5345	0	0	5345	352	352	0	405	0	0	4940	0	4940
	0	0	0	0	0	0	0	0	0	0	0	0	0
WASTE IN LIEU OF BORROW	0	0	0	0	0	0	0	0	0	0	0	0	0
SUBTOTALS PHASE 1 -L-	28994	0	0	28994	1617	1617	0	1860	0	0	27134	0	27134
-TEMP_ALN2- 14+05.14 TO 19+57.36	154	0	0	154	794	794	0	913	759	0	0	0	0
-TEMP_ALN2- 23+02.73 TO 28+75.06	15	0	0	15	783	783	0	900	885	0	0	0	0
	0	0	0	0	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0	0	0	0	0
WASTE IN LIEU OF BORROW	0	0	0	0	0	0	0	0	0	0	0	0	0
SUBTOTALS PHASE 2	169	0	0	169	1577	1577	0	1813	1644	0	0	0	0
-L- 28+00 TO 34+00.00 RT	835	0	0	835	1238	1238	0	1424	589	0	0	0	0
-L- 37+50.50 TO 46+00.00 RT	20143	0	0	20143	22	22	0	25	0	0	20118	0	20118
	0	0	0	0	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0	0	0	0	0
WASTE IN LIEU OF BORROW	0	0	0	0	0	0	0	0	-589	0	-589	0	-589
SUBTOTAL PHASE 3 -L-	20978	0	0	20978	1260	1260	0	1449	0	0	19529	0	19529
-Temp_Aln2-14+05.14 TO 19+57.36(REMOVAL)	497	0	0	497	148	148	0	170	0	0	327	0	327
-Temp_Aln2- 23+02.73 TO 28+75.06(REMOVAL)	684	0	0	684	85	85	0	98	0	0	586	0	586
	0	0	0	0	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0	0	0	0	0
SUBTOTAL PHASE 4	1181	0	0	1181	233	233	0	268	0	0	913	0	913
-SR3431- 10+00 TO 22+24.94	15783	0	0	15783	196	196	0	225	0	0	15558	0	15558
	0	0	0	0	0	0	0	0	0	0	0	0	0
SUBTOTAL PHASE 1 -SR3431-	15783	0	0	15783	196	196	0	225	0	0	15558	0	15558
PROJECT SUBTOTALS	67105	0	0	67105	4883	4883	0	5615	1644	0	63134	0	63134
LOSS DUE TO CLEAR. & GRUB	-200	0	0	-200	0	0	0	0	0	0	-200	0	-200
SHOULDER MATERIAL	0	0	0	0	1800	1800	0	2070	2070	0	0	0	0
	0	0	0	0	0	0	0	0	0	0	0	0	0
PROJECT TOTALS	66905	0	0	66905	6683	6683	0	7685	3714	0	62934	0	62934
EST TO REPLACE TOPSOIL ON BORROW PIT	0	0	0	0	0	0	0	0	186	0	0	0	0
GRAND TOTALS	66905	0	0	0	0	0	0	0	3900	0	0	0	0
SAY	67000	0	0	0	0	0	0	0	3900	0	0	0	0

PAVEMENT STRUCTURE VOLUME :	4,630	
DRAINAGE DITCH EXCAVATION :	130	
SHOULDER BORROW:	0	
SHALLOW UNDERCUT	100	(Contingency Item)
CLASS IV SUBGRADE STABILIZATION	100	(Contingency Item)
LESS GRANULAR MAT'L	100	(Contingency Item)

EARTHWORK QUANTITIES ARE CALCULATED BY THE ROADWAY DESIGN UNIT. THESE EARTHWORK QUANTITIES ARE BASED IN PART ON SUBSURFACE DATA PROVIDED BY THE GEOTECHNICAL ENGINEERING UNIT.



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

Michael F. Easley
GOVERNOR

P.O. BOX 25201, RALEIGH, N.C. 27611-5201

Lyndo Tippett
SECRETARY

August 12, 2011

STATE PROJECT: 42549.1.1, B-5178
COUNTY: Buncombe
DESCRIPTION: Roadway and approaches, Br. Nos. 235 and 238 on I-26 over SR 3431 (Pond Road) and Hominy Creek
SUBJECT: Geotechnical Report – Inventory

PROJECT DESCRIPTION

The project consists of .29 miles of existing 4 lane widening along the existing I-26 alignment. A single deck eight lane bridge is proposed to replace the existing bridges. A geotechnical investigation was performed in July, 2011 utilizing a CME 550 ATV mounted drill. Standard Penetration Tests were performed at selected locations along the alignment for cut slopes and a new retaining wall. Representative soil samples were obtained for visual classification in the field.

SR 3431 (Pond Road) will also have the grade lowered to accommodate the new superelevation of the bridge.

The following survey line was investigated, as was the alignment of Pond Road:

<u>Line</u>	<u>Stations</u>
- L -	28+00 – 46+25
-SR 3431-	10+00 – 19+00

AREAS OF SPECIAL GEOTECHNICAL INTEREST

STRUCTURES

The existing bridge is proposed to be replaced with a single 8-lane deck. A Bridge Inventory will be submitted as a separate report.

POTENTIALLY UNSUITABLE SUBSURFACE CONDITIONS

Small areas of soft soils requiring reinforcement may be found in the alluvial soils along Pond Road and are reflected in contingency items for geotextile and select backfill in the Recommendations.

PHYSIOGRAPHY AND GEOLOGY

The Pond Road section of project is contained in the floodplain of Hominy Creek. Interstate 26 and the replacement bridge are approximately 50' above the stream elevation.

Rock is present at the surface as shown on the plansheets, particularly in the vicinity of the proposed retaining wall and around station 17+00 on Pond Road. Fresh rock on this project is quartz rich biotite gneiss of the Ashe Formation and is very durable.

SOIL PROPERTIES

Soils in cut areas of I-26 are generally dense to very dense silty sands with weathered rock seams. Rock will likely be encountered at the base of I-26 cut sections. Cut slopes on Pond Road will be in loose embankment under the existing bridge and a combination of dense silty sand with weathered rock seams to rock going upstation from 15+00 to 18+00.



GROUNDWATER

Groundwater exists essentially in the alluvial deposits at the base flow level of Hominy Creek. Roadway borings along I-26 show relatively shallow water depths that are not expected to affect slope stability or require specialized drainage.

Respectfully submitted,

Jody C. Kunne

PROJECT REFERENCE NO. B-5178	SHEET NO. 2 of 2
RAW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	



SKETCH SHOWING BRIDGE WIDTH IN RELATION TO ROADWAY APPROACH

PIs Sta 24+92.18 $\Theta_s = 4' 45'' 00.0''$ $L_s = 380.00'$ $LT = 253.42'$ $ST = 126.75'$	PI Sta 31+69.17 $\Delta = 27' 00'' 33.9'' (LT)$ $D = 2' 30'' 00.0''$ $t = 1080.38'$ $T = 550.42'$ $R = 2,291.83'$ $SE = \text{SEE PLANS}$	PIs Sta 38+25.88 $\Theta_s = 4' 45'' 00.0''$ $L_s = 380.00'$ $LT = 253.42'$ $ST = 126.75'$
--	---	--


MATCHLINE - STA. 41+00.00 SEE SHEET 5

MATCHLINE -SR3431- STA. 19+00.00 SEE SHEET 6

PROJECT REFERENCE NO. B-5178	SHEET NO. 5 of 21
RAW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR P/W ACQUISITION PRELIMINARY PLANS DO NOT USE FOR CONSTRUCTION	

MATCHLINE -L- STA. 41+00.00 SEE SHEET 4

END TIP PROJECT B-5178
STA. 47+68.00 -LRT-




+84.39
EXIST RW
200.39'

BM#4
BL - STA 66+76.60
96.7' RIGHT
ELEV. = 2054.96'

NAD 83


TOP=2023.17
REV=2008.01


8/23/12
12-AUG-2011 12:33
C:\Projects\CADD\B5178_GED_RDWY\CADD_GEO\TECH\B5178_GEO_xpl.LT.dgn
Kuhne AT: GEAR 55143



32 + 50.00
— L —


8/23/21
I:\AUG-2011\2-31
C:\Users\jkuhn\Documents\Roadways\B5178_GEO_RDWY\CADD_GEO\TECH\ssc\B-5178_Geo_xp1.LT.dgn
kkuhn
08/23/21 11:54





I2-AUG-2011 12:35
 C:\Projects\B-5178\Roadways\B-5178_GED_RDWY\CADD_GEDTECH\XSC\B-5178_GEO.XPL.LT.dgn
 Author: AL_GED_55443

8/23/12
I:\Projects\ADDP\Roadways\B5178_GEO_RDWY\CADD_GEDTECH\ssc\B-5178_Geo_xp1.LT.dgn
12-AUG-2011 12:32
User: jmc
Title: B-5178



WEATHERED ROCK, GRAY WEATHERED BIOTITE GNEISS W/ HARD RK SEAMS

ROD SOUNDING
WEATHERED RK/RK @ 3.0'

S.S. 2068.37

B-II
32+50.00
81 LT

SAPROLITE, YEL.-GRAY TO RED/YEL., SILTY FINE TO COARSE SAND.

60% 0.0

CRYSTALLINE ROCK, BIOTITE GNEISS


0.060

2070.26

32 + 50.00

-L-

8/23/12
I2-AUG-2011 12:32
C:\Program Files\AutoCAD 2011\MapTools\Roadways\B5178_GEO_RDWY\CADD_GEO\TECH\B5178_GEO_RDWY\CADD_GEO\XP1.LT.dgn



WEATHERED ROCK, BRN/GRAY/DK. GRAY, WEATHERED
HORNBLende-BIOTITE GNEISS W/ HARD RK SEAMS

SAPROLITE, BRN. RES. SAPROLITE

PROPOSED RETAINING WALL

ROD SOUNDING
WEATHERED RK/RK @ 2.5'

CRYSTALLINE ROCK, BIOTITE GNEISS

B-10
33+00.00
80+LT
2070.6936


S.S. 2014.89

2068.53

33+00.00


-L-

8/23/12
12-AUG-2011 12:31
C:\Program Files\AutoCAD 2011\Plot\Roadways\B5178_GED_RDWY\CADD_GEDTECH\use\B-5178_Geo_xpl.LT.dgn
Mainline All Geotechnical




-L-


8/23/12
12-AUG-2011 12:49
C:\ProJec\ts\CADD\B\Roadways\B5178_GEO_RDWY\CADD_GEO\TECH\yse\B-5178_Geo_xp1.LT.dgn
Munroe AL 06455313




8/23/14
01-SEP-2011 14:32
C:\Program Files\AutoCAD\acad\acadp_l1\Roadways\B5178_GEO_RDWY\CADD_GEDTECH\B5178_GEO_xpl.LRT.dgn
Autodesk
RI GER239445



01-SEP-2011 14:33
C:\Projects\CAD\Drawings\Roadways\B5178_GEO_RDWY\CADD_GEO\TECH\B5178_GEO_xp1_RT.dgn
ksunne - PL 08/23/11




B-237





12-AUG-2012 12:48
 C:\Projects\ADD\B-5178\Roadways\B5178_GED_RDMY\CADD_GEDTECH\B-5178_Geo_xp1.LT.dgn
 Author: PL-GEN-5543

8/23/11
01-SEP-2011 14:25
C:\Program Files\CADSoft\Roadways\B5178_GEO\RDWY\CADD_GEDITECH\B5178_Geo_xp.L.T.dgn
Mainline All 064555.dwg




12-AUG-2011 12:28
 C:\Program Files\AutoCAD\acad\acadp1\Roadways\B5178_GED_RDWY\CADD_GEDTECH\B5178_Geo_xp1.L.T.dgn
 Author: AL GEORGE






I2-AUG-2011 12:25
 C:\Projects\B5178\Roadways\B5178_GED_RDMYY\CADD_GEDTECH\B5178_Geo_xp1.L1.T.dgn
 Author: AL_GED255473




15 + 40.00
 -SR3431-

8/23/08




PROJ. REFERENCE NO.	SHEET NO.
B-5178	25/31



08-SEP-2011 13:29
 C:\Projects\CADD\Roadways\B5178_GEO_RDWY\CADD_GEO\TECH\B-5178_Geo_xp1_SR3431.dgn
 kshine AT GEN258478

08-SEP-2011 09:28
C:\Program Files\CADD\Geo\Roadways\B5178_GEO\RDWY\CADD_GEO\TECH\B5178_GEO\B5178_Geo_xpl_SR3431_10.dgn
Runne AT GERES49



-SR3431-

17+30.00

B-14
17+34 12.5' LT 1

ROADWAY EMBANKMENT, SILTY SAND W/ COBBLES AND BOULDERS

WEATHERED ROCK, GRAY/DK. GRAY, SEAMY WEATHERED AND CRYSTALLINE ROCK

CRYSTALLINE ROCK, CRYSTALLINE ROCK, BIOTITE GNEISS

60/0.0

100+