problem solved

REVISED PRELIMINARY SITE ASSESSMENT REPORT

651 Country Club Road
Jesse B. Overton, et al Property, Parcel 28
Rocky Mount, North Carolina
State Project U-3331
WBS Element #34927.1.1
Nash County

North Carolina Department of Transportation Geotechnical Engineering Unit 1589 Mail Service Center Raleigh, North Carolina 27699-1589

October 28, 2013

REVISED PRELIMINARY SITE ASSESSMENT REPORT

Parcel 28 651 Country Club Road Rocky Mount, North Carolina State Project U-3331 WBS Element #34927.1.1 Nash County

TABLE OF CONTENTS

Section	Subject	Page
Signatu	re Page	ii
_	ve Summary	
1.0	Introduction	1
2.0	Background	1
3.0	Local Geology and Surroundings	
4.0	Subsurface Investigation	
	4.1 Geophysical Survey	3
	4.1.1 Ground Penetrating Radar Methodology	4
	4.1.2 Time Domain Electromagnetic Methodology	5
	4.1.3 Field Procedures	5
	4.2 Subsurface Soil Investigation	6
5.0	Conclusions and Recommendations	8
Figures 1 2	Site Location Map Site Map Showing Locations of Soil Borings and Existing Groundwate Monitoring Wells Site Map Showing Results of Geophysical Investigation	er
Append	<u>lices</u>	
1	Photographs	
Ш	Soil Boring Lithologic Logs	
III	Certificates of Analysis and Chain of Custody Record for Soil Samples	S

i

GEL Engineering of NC, Inc. an Affiliate of The GEL Group, Inc.

fc: ncdt01013

Signature Page

This document, entitled *Revised Preliminary Site Assessment Report*, has been prepared for the Jesse B. Overton, et al Property, Parcel 28, located at 651 Country Club Road in Rocky Mount, North Carolina (State Project U-3331, WBS Element # 34927.1.1, Nash County). It has been prepared by GEL Engineering of NC, Inc. in accordance with the Notice to Proceed provided by the North Carolina Department of Transportation-GeoEnvironmental Section, Geotechnical Engineering Unit for the exclusive use of the North Carolina Department of Transportation. It has been prepared in accordance with accepted quality control practices and has been reviewed by the undersigned.

Andrew D. Eyer, L.G.
Senior Project Manage

Date

REVISED PRELIMINARY SITE ASSESSMENT REPORT

Parcel 28 651 Country Club Road Rocky Mount, North Carolina State Project U-3331 WBS Element #34927.1.1 Nash County

Executive Summary

The subject site is Parcel 28, located at 651 Country Club Road in Rocky Mount, North Carolina. The primary purpose of this investigation was to evaluate the presence or absence of underground storage tanks (USTs) and constituents of concern in soil within the North Carolina Department of Transportation (NCDOT) Rights-of-Way (ROWs) adjacent to Parcel 28, as a result of previous and/or current operations at the subject site.

Parcel 28 is located on the corner of Country Club Road and Overton Drive and contains a former fire station that is currently used as a search and rescue response facility. Two underground storage tanks (USTs) were reportedly removed in 1989, but there is no known North Carolina Department of Environment and Natural Resources (NCDENR) Groundwater Incident assigned to the site. A single monitoring well is located in the center of the former UST pit. There is no other evidence of USTs, vents, or UST removal.

GEL performed a preliminary site assessment within the NCDOT easterly ROW of Country Club Road adjacent to Parcel 28 that included a geophysical investigation, and the collection and analysis of soil samples. No subsurface anomalies indicative of suspected or known USTs were identified within the investigation area, and it has been concluded that there are no USTs present within the easterly ROW of Country Club Road or the southerly ROW of Overton Drive adjacent to the site.

iii

GEL Engineering of NC, Inc. an Affiliate of The GEL Group, Inc.

fc: ncdt01013

Executive Summary (continued)

Soil samples were collected for analysis from nine borings constructed within the investigation area, and analyzed for DRO and GRO. Neither DRO nor GRO was detected in any of the collected soil samples.

Based on the soil data generated from this investigation, there is no evidence that a release of constituents of concern has occurred within the investigation area at Parcel 28. No additional environmental investigation of the soil or groundwater at the site is recommended at this time.

iν

REVISED PRELIMINARY SITE ASSESSMENT REPORT

Parcel 28
651 Country Club Road
Rocky Mount, North Carolina
State Project U-3331
WBS Element #34927.1.1
Nash County

1.0 Introduction

This document presents the details of a geophysical survey and preliminary site assessment performed within the North Carolina Department of Transportation (NCDOT) Rights-of-Way (ROWs) at Parcel 28 (the Jesse B. Overton, et al Property), located at 651 Country Club Road in Rocky Mount, North Carolina.

Parcel 28 is located on the corner of Country Club Road and Overton Drive and contains a former fire station that is currently used as a search and rescue response facility. Two underground storage tanks (USTs) were reportedly removed in 1989, but there is no known North Carolina Department of Environment and Natural Resources (NCDENR) Groundwater Incident assigned to the site. A single monitoring well is located in the center of the former UST pit. There is no other evidence of USTs, vents, or UST removal.

The site location is shown on Figure 1, an excerpt from the United States Geological Survey (USGS) 7.5-minute quadrangle map of Rocky Mount, North Carolina. The preliminary site assessment was conducted by GEL Engineering of NC, Inc. (GEL) in accordance with the Notice to Proceed issued by NCDOT on August 20, 2013.

The primary purpose of this investigation was to evaluate the presence or absence of USTs and/or constituents of concern in soil within the NCDOT ROWs at the subject site as a result of current and/or former operations.

2.0 Background

NCDOT is planning road improvements to the area in the vicinity of Country Club Road in Rocky Mount, North Carolina. NCDOT wanted to assess the area in the easterly ROW of Country Club Road and the southerly ROW of Overton Drive adjacent to Parcel 28 to evaluate the presence or absence of USTs and soil contamination related to the current

and/or former on-site operations, and the impact (if any) of these operations on the proposed road improvements. Figures 2 and 3 show the general site layout for Parcel 28. One aboveground groundwater monitoring well was observed on the property on September 10, 2013, at the approximate location shown in Figure 2. The monitoring well is also shown in photographs provided in Appendix I. A handheld Magellan 330 map grade global positioning system (GPS) was used to measure the longitude and latitude coordinate for the well, which are listed below. No other monitoring wells were observed on properties adjacent to parcel 28.

Existing Groundwater Monitoring Well Located on Parcel 28

Well ID *	Latitude/Longitude (NAD83)
MW-1	35°58'11.82"N / 77°49'27.72"W

Notes:

- 1) * Assumed ID; corresponds with assumed well ID shown on Figure 2.
- 2) Coordinates are based on North American Datum of 1983 (NAD83)

The NCDENR UST database indicates that two USTs were removed from the site in 1989; however, there are no UST incidents listed for the 651 Country Club Road property in the database. Neither representatives for the search and rescue response operation at the site nor representatives of the NCDENR UST Section could confirm that the monitoring well is currently included in a groundwater monitoring program.

3.0 Local Geology and Surroundings

Parcel 28 is in a developed area of Rocky Mount in Nash County, North Carolina. Surrounding land uses include residential and commercial activities.

The site is located approximately 3.5 miles northwest of the center of Rocky Mount, North Carolina. This area is located on the Fall Line separating the Inner Piedmont and Coastal Plain physiographic provinces of North Carolina. The land surface of the area is characterized by nearly level, and gently sloping, well drained to poorly drained soils. The Eastern Slate Belt of the Inner Piedmont east of the site is typified by mostly metamorphosed volcanic and sedimentary rocks that are Early Paleozoic in age. The Coastal Plain west of the site is comprised of mostly sand and clay sediments, and typifies the geology in the vicinity of the site.

The United States Department of Agriculture's *Web Soil Survey* (2013) (http://websoilsurvey.nrcs.usda.gov/app/WebSoilSurvey.aspx) maps the soil in the investigation area as "Altavista Sandy Loam" (AaA) and "Bibb Loam" (Bb), which are both characterized as sandy and loamy alluvium. The soils encountered at the site during the preliminary site assessment consisted predominantly of tan/grey mottled, sandy, silty clay.

Groundwater was encountered in borings SB-1 through SB-5 during construction of the borings at depths ranging from 6 to 7 feet bgs. Based on the USGS topographic map presented as Figure 1, the site is located approximately 105 feet above mean sea level. The topography in Figure 1 indicates that groundwater in the vicinity of Parcel 28 most likely flows in a southwesterly direction towards Stony Creek.

4.0 Subsurface Investigation

To evaluate the presence or absence of USTs and/or impact to subsurface soil within the NCDOT ROWs of Parcel 28, GEL performed a limited site assessment that consisted of the following tasks:

- Performance of a geophysical investigation to identify the presence or absence of USTs and associated appurtenances within the easterly ROW of Country Club Road and the southerly ROW of Overton Drive at Parcel 28.
- Soil vapor screening of soil samples collected from subsurface soil borings at Parcel 28 within the easterly ROW of Country Club Road and the southerly ROW of Overton Drive to evaluate the potential presence or absence of soil impact from petroleum constituents of concern.
- Collection and laboratory analysis of soil samples from the easterly ROW of Country Club Road and the southerly ROW of Overton Drive.

The details of these tasks are discussed in the following sections.

4.1 Geophysical Survey

The geophysical survey included the deployment of ground penetrating radar (GPR) technology and time domain electromagnetic technology (TDEM) to the site. These technologies were used in concert with one another in order to identify subsurface metallic anomalies and, more specifically, to identify the potential presence of USTs within the investigation area. A brief description of each technology is presented in the

following paragraphs followed by a discussion of the results of the geophysical investigation.

4.1.1 Ground Penetrating Radar Methodology

A RAMAC digital radar control system configured with a 250 Megahertz (MHz) antenna array was used in this investigation. GPR is an electromagnetic geophysical method that detects interfaces between subsurface materials with differing dielectric constants. The GPR system consists of an antenna that houses the transmitter and receiver, a digital control unit that both generates and digitally records the GPR data, and a color video monitor to view data as they are collected in the field.

The transmitter radiates repetitive short-duration electromagnetic waves (at radar frequencies) into the earth from an antenna moving across the ground surface. These radar waves are reflected back to the receiver from the interface of materials with different dielectric constants. The intensity of the reflected signal is a function of the contrast in the dielectric constant between the materials, the conductivity of the material through which the wave is traveling, and the frequency of the signal. Subsurface features that commonly cause such reflections are: 1) natural geologic conditions, such as changes in sediment composition, bedding, and cementation horizons and voids; or 2) unnatural changes to the subsurface, such as disturbed soils, soil backfill, buried debris, tanks, pipelines, and utilities. The digital control unit processes the signal from the receiver and produces a continuous cross-section of the subsurface interface reflection events.

GPR data profiles are collected along transects, which are measured paths along which the GPR antenna is moved. During a survey, marks are placed in the data by the operator at designated points along the GPR transects or with a survey wheel odometer. These marks allow for a correlation between the GPR data and the position of the GPR antenna on the ground.

Depth of investigation of the GPR signal is highly site-specific and is limited by signal attenuation (absorption) in the subsurface materials. Signal attenuation is dependent on the electrical conductivity of the subsurface materials. Signal attenuation is greatest in materials with relatively high electrical conductivities, such as clays, brackish groundwater, or groundwater with a high dissolved solid content from natural or man-

made sources. Signal attenuation is lowest in relatively low-conductivity materials, such as dry sand or rock. Depth of investigation is also dependent on the antenna's transmitting frequency. Depth of investigation generally increases as transmitting frequency decreases; however, the ability to resolve smaller subsurface features is diminished as frequency is decreased.

The GPR antenna used at this site is internally shielded from aboveground interference sources. Accordingly, the GPR response is not affected by overhead power lines, metallic buildings, or nearby objects.

4.1.2 Time Domain Electromagnetic Methodology

The TDEM methods measure the electrical conductivity of subsurface materials. The conductivity is determined by inducing (from a transmitter) a time or frequency-varying magnetic field and measuring (with a receiver) the amplitude and phase shift of an induced secondary magnetic field. The secondary magnetic field is created by subsurface conductive materials behaving as an inductor as the primary magnetic field is passed through them.

The Geonics EM-61 system used in this investigation operates within these principles. However, the EM-61 TDEM system can discriminate between moderately conductive earth materials and very conductive metallic targets. The EM-61 consists of a portable coincident loop time domain transmitter and receiver with a 0.5-meter by 1.0-meter coil system. The EM-61 generates 150 pulses per second and measures the response from the ground after transmission or between pulses. The secondary EM responses from metallic targets are of longer duration than those created by conductive earth materials. By recording the later time EM arrivals, only the response from metallic targets is measured, rather than the field generated by the earth material.

4.1.3 Field Procedures

The GPR and TDEM field investigation was performed on August 26-27, 2013, within the landscaped easterly ROW of Country Club Road and southerly ROW of Overton Drive adjacent to Parcel 28, as shown in Figure 3. A GPR system time range setting of 90 nanoseconds (ns) was used during the entire investigation. This range was determined after a series of test lines were conducted to evaluate the GPR response in the local geologic section. Interpretation of the GPR data was conducted in the field and any

potential anomalies were marked in the field. GPR data processing typically included band pass filtering, background removal, horizontal smoothing, and gain adjustments. TDEM was also used to scan the project site. Any electromagnetic anomalies indicative of buried metallic objects were marked in the field.

It should be noted that "One Call" underground utility locations had been performed within the easterly ROW of Country Club road and the southerly ROW of Overton Drive at Parcel 28 prior to the initiation of the preliminary site assessment field activities at the site. A minimal number of underground utilities were marked by "One Call" within the ROWs.

As shown on Figure 3, a large EM-61 anomaly was identified in the concrete driveway for the site on Country Club Road. The anomaly is interpreted as an EM-61 response to the steel reinforcement rebar used as part of the construction of the driveway. Another, smaller anomaly was identified along the pavement of Overton Drive, as shown in Figure 3. The anomaly location corresponds with the location of an existing reinforced concrete culvert underlying Overton Drive. The anomaly is interpreted as an EM-61 response to the steel reinforcement rebar used as part of the culvert's construction. The TDEM and GPR data did not indicate the presence of "Known USTs," "Probable USTs," or "Possible USTs" in the subsurface of the investigation area. Additionally, there was no visual evidence of USTs in the investigation area.

4.2 Subsurface Soil Investigation

To evaluate the presence or absence of impact to subsurface soil by constituents of concern, GEL collected soil samples from three subsurface soil borings, SB-1 through SB-8, at Parcel 28 on September 10, 2013, for analysis of total petroleum hydrocarbon indicator parameters. The soil borings were constructed within the easterly ROW of Country Club Road, as shown on Figure 2. The longitude and latitude coordinates for the boring locations are listed in the table below, and photographs of the boring locations in presented in Appendix I.

All borings were advanced to a total depth of 8 feet below ground surface (bgs). Soil samples were collected at 3-4 feet and 7-8 feet from each borehole. All soil samples were inspected for indications of impact by constituents of concern, including petroleum hydrocarbons, such as odors, discoloration, or visible sheen. This sampling

was accomplished using direct push technology (DPT) provided by Regional Probing Services of Wake Forest, North Carolina (Regional Probing). Soil boring lithologic logs are attached as Appendix II of this document. Groundwater was encountered in borings SB-1 through SB-5 during construction of the borings at depths ranging from 6 to 7 feet bgs.

The soil samples were screened for the presence of organic vapors using a portable photoionization detector (PID). The PID measures the concentration of organic compounds in the vapor space above a soil sample resulting from volatilization of organic compounds contained in the soil. To screen the soils, each sample was placed in a clean, resealable polyethylene bag. The bag was sealed, and the sample was allowed to equilibrate for approximately 5 minutes, after which time a small opening was made in the bag. The probe of the PID was then inserted into the bag, and the airspace above the soil was screened for organic vapors.

To assess the subsurface soil quality, one soil sample was collected from each soil boring at the sampled depth interval with the highest PID reading and submitted for laboratory analysis. The depth intervals and PID measurements of the collected soil samples submitted to the laboratory for analysis are listed below.

Summary of Location Data and PID Measurements for Soil Samples Collected for Analysis at Parcel 28

Soil Boring	Depth Interval of Soil Sample Collected for Analysis (feet bgs)	PID Reading (ppm)	Latitude/Longitude (NAD83)
SB-1	7-8	4.4	35°58′10.62″N / 77°49′29.52″W
SB-2	7-8	4.9	35°58′11.10″N / 77°49′29.10″W
SB-3	3-4	11.9	35°58′12.12″N / 77°49′28.02″W
SB-4	3-4	5.6	35°58′10.56″N / 77°49′24.78″W
SB-5	7-8	19.2	35°58′11.28″N / 77°49′26.52″W
SB-6	7-8	0.0	35°58′10.86″N / 77°49′25.26″W
SB-7	7-8	0.0	35°58′10.56″N / 77°49′24.60″W
SB-8	7-8	0.0	35°58′10.26″N / 77°49′23.76″W

Notes:

- 1) Coordinates are based on North American Datum of 1983 (NAD83)
- 2) bgs = below ground surface
- 3) PID = photoionization detector
- 4) ppm = parts per million

Following completion of the soil sampling activities, all borings were abandoned by filling the boreholes with soil cuttings and hydrated bentonite. Soil samples were submitted to Pace Analytical Services, Inc. in Huntersville, North Carolina for analysis of diesel range organics (DRO) by EPA Method 8015 with EPA Method 3545 sample preparation, and gasoline range organics (GRO) by EPA Method 8015 with EPA Method 5035A/5030B sample preparation. The analytical results are included on the Certificates of Analysis provided in Appendix III. The results indicate that neither DRO nor GRO were detected in any of the soil samples collected from borings SB-1 through SB-8.


5.0 Conclusions and Recommendations


GEL performed a preliminary site assessment within the NCDOT easterly ROW of Country Club Road adjacent to Parcel 28 that included a geophysical investigation, and the collection and analysis of soil samples. No subsurface anomalies indicative of suspected or known USTs were identified within the investigation area, and it has been concluded that there are no USTs present within the easterly ROW of Country Club Road or the southerly ROW of Overton Drive adjacent to the site.


Soil samples were collected for analysis from eight borings constructed within the investigation area, and analyzed for DRO and GRO. Neither DRO nor GRO was detected in any of the collected soil samples.


Based on the soil data generated from this investigation, there is no evidence that a release of constituents of concern has occurred within the investigation area at Parcel 28. No additional environmental investigation of the soil or groundwater at the site is recommended at this time.











APPENDIX I

PHOTOGRAPHS



<u>Photograph 1</u>: View looking north at soil boring locations, SB-1 and SB-2.



Photograph 2: View looking east at soil boring locations SB-3 and SB-4.



<u>Photograph 3</u>: View looking south at soil boring location SB-5 and monitoring Well MW-1.



Photograph 4: View looking southwest at soil boring locations SB-6, SB-7, and SB-8

APPENDIX II SOIL BORING LITHOLOGIC LOGS

Boring/Well No.: **SB-1**Date Started: 09/10/13
Date Completed: 09/10/13

	Depth	Blow	PID	Soil	
No.	Interval	Counts	(ppm)	Description	Soil Type
1	0.0' - 2.0'			Brown/tan loamy, sandy topsoil/fill; dry to damp; friable; no odor	SM
2	3.0' – 4.0'		1.3	Tan/grey mottled silty clay; firm, dense; dry; no odor	CL
3	4.0' – 6.5'			Same	CL
4	6.5' – 7.0'			Tan/grey medium to coarse-grained sand; poorly graded; wet; no odor	SP
5	7.0' – 8.0'		4.4	Grey/orange mottled clay; firm, dense; damp to wet; no odor	CL
6					
7				Total depth = 8 feet below land surface	
8					
9					
10					
11					
12					

- 1) 4-foot continuous cores using DPT.
- 2) PID readings shown are for discrete samples collected at 3.0' to 4.0' and 7.0' to 8.0'.

Boring/Well No.: **SB-2** Date Started: 09/10/13 Date Completed: 09/10/13

	Depth	Blow	PID	Soil	
No.	Interval	Counts	(ppm)	Description	Soil Type
1	0.0' - 2.0'			Brown/tan loamy, sandy topsoil/fill; dry to damp; friable; no odor	SM
2	3.0' – 4.0'		2.2	Tan/grey mottled silty clay; firm, dense; dry; no odor	CL
3	4.0' - 6.5'			Same	CL
4	6.5' – 7.0'			Tan/grey medium to coarse-grained sand; moderately graded; wet; no odor	SP
5	7.0' – 8.0'		4.9	Grey/orange mottled clay; firm, dense; damp; no odor	CL
6					
7				Total depth = 8 feet below land surface	
8					
9					
10					
11					
12					

- 1) 4-foot continuous cores using DPT.
- 2) PID readings shown are for discrete samples collected at 3.0° to 4.0° and 7.0° to 8.0° .

Boring/Well No.: **SB-3**Date Started: 09/10/13
Date Completed: 09/10/13

	Depth	Blow	PID	Soil	
No.	Interval	Counts	(ppm)	Description	Soil Type
1	0.0' - 2.0'			Brown /tan loamy, sandy topsoil/fill; dry to damp; friable; no odor	SM
2	3.0' – 4.0'		11.9	Tan/grey mottled silty clay; firm, dense; dry; no odor	CL
3	4.0' – 7.0'			Same, with 2" thick stratum of tan/grey medium to coarse-grained sand at 6.0'; dry; no odor	CL/SP
4	7.0' – 8.0'		9.7	Grey/orange mottled clay; firm, dense; wet; no odor	CL
5					
6				Total depth = 8 feet below land surface	
7					
8					
9					
10					
11					
12					

- 1) 4-foot continuous cores using DPT.
- 2) PID readings shown are for discrete samples collected at 3.0° to 4.0° and 7.0° to 8.0° .

Boring/Well No.: **SB-4**Date Started: 09/10/13
Date Completed: 09/10/13

	Depth	Blow	PID	Soil	
No.	Interval	Counts	(ppm)	Description	Soil Type
				Brown sandy, silty topsoil/fill; dry,	
1	0.0' - 3.0'			friable; no odor	SM
2	3.0' – 4.0'		5.6	Grey clay; firm, dense; dry; no odor	CL
3	4.0' - 6.5'			Tan/orange mottled clay; firm, dense; damp; no odor	CL
4	6.5' - 7.5'			Orange fat clay with coarse sand; wet; no odor	СН
				Tan/orange mottled clay; firm, dense;	
5	7.5' – 8.0'		3.4	damp to wet; no odor	CL
6					
7				Total depth = 8 feet below land surface	
8					
9					
10					
11					
12					

- 1) 4-foot continuous cores using DPT.
- 2) PID readings shown are for discrete samples collected at 3.0° to 4.0° and 7.0° to 8.0° .

Boring/Well No.: **SB-5** Date Started: 09/10/13 Date Completed: 09/10/13

	Depth	Blow	PID	Soil	
No.	Interval	Counts	(ppm)	Description	Soil Type
			-		
1	0.0' – 0.5'			Brown topsoil; friable; dry; no odor	SM
2	0.5' - 2.0'			Tan/white fine silt; friable, dry, no odor	ML
3	2.0' – 4.0'		1.8	Tan/orange coarse sand/silt/clay; friable; damp; no odor	SC
4	4.0' – 4.5'			Same, but with more clay	SC/CL
5	4.5' – 6.5'			Tan silty fine-grained sand; wet, friable, no odor	SM
6	6.5' – 8.0'		19.2	Grey clay with coarse sand; very firm/stiff, dense, damp; slight old petroleum odor	CL
7					
8				Total depth = 8 feet below land surface	
9					
10					
11					
12					

- 1) 4-foot continuous cores using DPT.
- 2) PID readings shown are for discrete samples collected at 3.0° to 4.0° and 7.0° to 8.0° .

Boring/Well No.: **SB-6**Date Started: 09/10/13
Date Completed: 09/10/13

	Depth	Blow	PID	Soil	
No.	Interval	Counts	(ppm)	Description	Soil Type
1	0.0' - 3.0'			Tan sandy silt; dry, friable; no odor	SM
2	3.0' – 4.0'		0.0	Brown sandy silt; friable to firm; dry; no odor	SM
3	4.0' – 5.0'			Tan/grey mottled fat clay; dry; no odor	CL
4	5.0' – 8.0'		0.0	Grey sandy, silty clay; stiff/firm, dense, damp; no odor	CL
5					
6				Total depth = 8 feet below land surface	
7					
8					
9					
10					
11					
12					

- 1) 4-foot continuous cores using DPT.
- 2) PID readings shown are for discrete samples collected at 3.0° to 4.0° and 7.0° to 8.0° .

Boring/Well No.: **SB-7** Date Started: 09/10/13 Date Completed: 09/10/13

	Depth	Blow	PID	Soil	
No.	Interval	Counts	(ppm)	Description	Soil Type
			-	★	<u> </u>
1	0.0' - 2.0'			Tan silt; dry, friable; no odor	SM
2	2.0' – 4.0'		0.0	Tan clayey silt; stiff/firm, dense; dry, no odor	SM/ML
3	4.0' - 6.0'			Tan silty fine-grained sand; friable; dry; no odor	SM
4	6.0' – 8.0'		0.0	Orange/brown clayey, coarse sand; friable; wet at 7.5 feet; no odor	SC
5					
6				Total depth = 8 feet below land surface	
7					
8					
9					
10					
11					
12					

- 1) 4-foot continuous cores using DPT.
- 2) PID readings shown are for discrete samples collected at 3.0° to 4.0° and 7.0° to 8.0° .

Boring/Well No.: **SB-8**Date Started: 09/10/13
Date Completed: 09/10/13

	Depth	Blow	PID	Soil	
No.	Interval	Counts	(ppm)	Description	Soil Type

1	0.0' - 3.0'			Tan silt; dry, friable; no odor	SM
2	3.0' – 4.0'		0.0	Tan clayey silt; stiff/firm, dense; dry, no odor	SM/ML
3	4.0' – 6.0'			Tan silty fine-grained sand; friable; dry; no odor	SM
4	6.0' – 8.0'		0.0	Tan/orange mottled clay; firm, dense; dry; no odor	CL
5					
6				Total depth = 8 feet below land surface	
7					
8					
9					
10					
11					
12					

- 1) 4-foot continuous cores using DPT.
- 2) PID readings shown are for discrete samples collected at 3.0° to 4.0° and 7.0° to 8.0° .

APPENDIX III

CERTIFICATES OF ANALYSIS AND CHAIN OF CUSTODY RECORD FOR SOIL SAMPLES



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

September 23, 2013

Andrew Eyer NCDOT North East

,

RE: Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Dear Andrew Eyer:

Enclosed are the analytical results for sample(s) received by the laboratory on September 11, 2013. The results relate only to the samples included in this report. Results reported herein conform to the most current TNI standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

Analyses were performed at the Pace Analytical Services location indicated on the sample analyte page for analysis unless otherwise footnoted.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

angela M. Baioni

Angela Baioni

angela.baioni@pacelabs.com Project Manager

Enclosures

cc: Chemical Testing Engineer, NCDOT





(336)623-8921

Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

CERTIFICATIONS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Charlotte Certification IDs

9800 Kincey Ave. Ste 100, Huntersville, NC 28078 North Carolina Drinking Water Certification #: 37706 North Carolina Field Services Certification #: 5342 North Carolina Wastewater Certification #: 12 South Carolina Certification #: 99006001

Florida/NELAP Certification #: E87627 Kentucky UST Certification #: 84 West Virginia Certification #: 357 Virginia/VELAP Certification #: 460221

REPORT OF LABORATORY ANALYSIS



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

SAMPLE ANALYTE COUNT

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

ab ID	Sample ID	Method	Analysts	Analytes Reported	Laboratory
92171843001	SB-1	EPA 8015 Modified	EJK	2	PASI-C
		EPA 8015 Modified	GAW	2	PASI-C
		ASTM D2974-87	TNM	1	PASI-C
2171843002	SB-2	EPA 8015 Modified	EJK	2	PASI-C
		EPA 8015 Modified	GAW	2	PASI-C
		ASTM D2974-87	TNM	1	PASI-C
2171843003	SB-3	EPA 8015 Modified	EJK	2	PASI-C
		EPA 8015 Modified	GAW	2	PASI-C
		ASTM D2974-87	TNM	1	PASI-C
92171843004 SB-4	SB-4	EPA 8015 Modified	EJK	2	PASI-C
		EPA 8015 Modified	GAW	2	PASI-C
		ASTM D2974-87	TNM	1	PASI-C
2171843005	SB-5	EPA 8015 Modified	EJK	2	PASI-C
		EPA 8015 Modified	GAW	2	PASI-C
		ASTM D2974-87	TNM	1	PASI-C
2171843006	SB-6	EPA 8015 Modified	EJK	2	PASI-C
		EPA 8015 Modified	GAW	2	PASI-C
		ASTM D2974-87	TNM	1	PASI-C
2171843007	SB-7	EPA 8015 Modified	EJK	2	PASI-C
		EPA 8015 Modified	GAW	2	PASI-C
		ASTM D2974-87	TNM	1	PASI-C
2171843008	SB-8	EPA 8015 Modified	EJK	2	PASI-C
		EPA 8015 Modified	GAW	2	PASI-C
		ASTM D2974-87	TNM	1	PASI-C



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

HITS ONLY

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Units	Report Limit	Analyzed	Qualifiers
	0.10	09/13/13 15:29	
	0.10	09/13/13 15:29	
	0.10	09/13/13 15:29	
	0.10	09/13/13 15:30	
	0.10	09/13/13 15:30	
	0.10	09/17/13 16:32	
	0.10	09/17/13 16:32	
	0.10	09/17/13 16:33	
		0.10 0.10 0.10 0.10 0.10 0.10	0.10 09/13/13 15:29 0.10 09/13/13 15:29 0.10 09/13/13 15:30 0.10 09/13/13 15:30 0.10 09/17/13 16:32 0.10 09/17/13 16:32



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

ANALYTICAL RESULTS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Percent Moisture

Date: 09/23/2013 04:04 PM

Lab ID: 92171843001 Sample: SB-1 Collected: 09/10/13 12:13 Received: 09/11/13 15:40 Matrix: Solid Results reported on a "dry-weight" basis **Parameters** Results Units Report Limit DF Prepared Analyzed CAS No. Qual 8015 GCS THC-Diesel Analytical Method: EPA 8015 Modified Preparation Method: EPA 3546 **Diesel Components** ND mg/kg 6.2 09/11/13 17:06 09/12/13 19:47 68334-30-5 Surrogates 87 % 41-119 n-Pentacosane (S) 09/11/13 17:06 09/12/13 19:47 629-99-2 Analytical Method: EPA 8015 Modified Preparation Method: EPA 5035A/5030B **Gasoline Range Organics** ND mg/kg Gasoline Range Organics 5.7 09/18/13 09:25 09/18/13 14:49 8006-61-9 Surrogates 4-Bromofluorobenzene (S) 80 % 70-167 09/18/13 09:25 09/18/13 14:49 460-00-4 **Percent Moisture** Analytical Method: ASTM D2974-87 20.0 % 09/13/13 15:29

0.10

1



Analytical Method: ASTM D2974-87

12.0 %

Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176

09/13/13 15:29

Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

ANALYTICAL RESULTS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Percent Moisture

Percent Moisture

Date: 09/23/2013 04:04 PM

Lab ID: 92171843002 Sample: SB-2 Collected: 09/10/13 12:50 Received: 09/11/13 15:40 Matrix: Solid Results reported on a "dry-weight" basis **Parameters** Results Units Report Limit DF Prepared Analyzed CAS No. Qual 8015 GCS THC-Diesel Analytical Method: EPA 8015 Modified Preparation Method: EPA 3546 **Diesel Components** 5.7 09/11/13 17:06 09/12/13 19:47 68334-30-5 ND mg/kg Surrogates 99 % 41-119 n-Pentacosane (S) 09/11/13 17:06 09/12/13 19:47 629-99-2 Analytical Method: EPA 8015 Modified Preparation Method: EPA 5035A/5030B **Gasoline Range Organics** ND mg/kg Gasoline Range Organics 5.5 09/18/13 09:25 09/18/13 15:12 8006-61-9 Surrogates 4-Bromofluorobenzene (S) 80 % 70-167 09/18/13 09:25 09/18/13 15:12 460-00-4

0.10

1

REPORT OF LABORATORY ANALYSIS



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

ANALYTICAL RESULTS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Percent Moisture

Date: 09/23/2013 04:04 PM

Sample: SB-3 Lab ID: 92171843003 Collected: 09/10/13 13:21 Received: 09/11/13 15:40 Matrix: Solid Results reported on a "dry-weight" basis **Parameters** Results Units Report Limit Prepared Analyzed CAS No. Qual 8015 GCS THC-Diesel Analytical Method: EPA 8015 Modified Preparation Method: EPA 3546 **Diesel Components** ND mg/kg 6.0 09/11/13 17:06 09/12/13 20:10 68334-30-5 Surrogates 112 % 41-119 n-Pentacosane (S) 09/11/13 17:06 09/12/13 20:10 629-99-2 Analytical Method: EPA 8015 Modified Preparation Method: EPA 5035A/5030B **Gasoline Range Organics** ND mg/kg Gasoline Range Organics 6.3 09/18/13 09:25 09/18/13 15:35 8006-61-9 Surrogates 4-Bromofluorobenzene (S) 86 % 70-167 09/18/13 09:25 09/18/13 15:35 460-00-4 **Percent Moisture** Analytical Method: ASTM D2974-87 16.3 % 09/13/13 15:29

0.10

1



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

ANALYTICAL RESULTS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Date: 09/23/2013 04:04 PM

Lab ID: 92171843004 Sample: SB-4 Collected: 09/10/13 13:55 Received: 09/11/13 15:40 Matrix: Solid Results reported on a "dry-weight" basis **Parameters** Results Units Report Limit Prepared Analyzed CAS No. Qual 8015 GCS THC-Diesel Analytical Method: EPA 8015 Modified Preparation Method: EPA 3546 **Diesel Components** 5.6 09/11/13 17:06 09/12/13 20:10 68334-30-5 ND mg/kg Surrogates 100 % 41-119 n-Pentacosane (S) 09/11/13 17:06 09/12/13 20:10 629-99-2 Analytical Method: EPA 8015 Modified Preparation Method: EPA 5035A/5030B **Gasoline Range Organics** ND mg/kg Gasoline Range Organics 5.0 09/18/13 09:25 09/18/13 15:57 8006-61-9 Surrogates 4-Bromofluorobenzene (S) 85 % 70-167 09/18/13 09:25 09/18/13 15:57 460-00-4 **Percent Moisture** Analytical Method: ASTM D2974-87 10.2 % 09/13/13 15:30 Percent Moisture 0.10 1



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

ANALYTICAL RESULTS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Date: 09/23/2013 04:04 PM

Sample: SB-5 Lab ID: 92171843005 Collected: 09/10/13 14:30 Received: 09/11/13 15:40 Matrix: Solid Results reported on a "dry-weight" basis **Parameters** Results Units Report Limit Prepared Analyzed CAS No. Qual 8015 GCS THC-Diesel Analytical Method: EPA 8015 Modified Preparation Method: EPA 3546 **Diesel Components** ND mg/kg 5.7 09/11/13 17:06 09/12/13 20:33 68334-30-5 Surrogates 94 % 41-119 n-Pentacosane (S) 09/11/13 17:06 09/12/13 20:33 629-99-2 Analytical Method: EPA 8015 Modified Preparation Method: EPA 5035A/5030B **Gasoline Range Organics** ND mg/kg Gasoline Range Organics 5.2 09/18/13 09:25 09/18/13 16:20 8006-61-9 Surrogates 4-Bromofluorobenzene (S) 84 % 70-167 09/18/13 09:25 09/18/13 16:20 460-00-4 **Percent Moisture** Analytical Method: ASTM D2974-87 12.9 % 09/13/13 15:30 Percent Moisture 0.10 1



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

ANALYTICAL RESULTS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Date: 09/23/2013 04:04 PM

Lab ID: 92171843006 Sample: SB-6 Collected: 09/10/13 15:05 Received: 09/11/13 15:40 Matrix: Solid Results reported on a "dry-weight" basis **Parameters** Results Units Report Limit Prepared Analyzed CAS No. Qual 8015 GCS THC-Diesel Analytical Method: EPA 8015 Modified Preparation Method: EPA 3546 **Diesel Components** ND mg/kg 5.6 09/11/13 17:06 09/12/13 20:33 68334-30-5 Surrogates 97 % 41-119 n-Pentacosane (S) 09/11/13 17:06 09/12/13 20:33 629-99-2 Analytical Method: EPA 8015 Modified Preparation Method: EPA 5035A/5030B **Gasoline Range Organics** ND mg/kg Gasoline Range Organics 5.0 09/18/13 09:25 09/18/13 16:43 8006-61-9 Surrogates 4-Bromofluorobenzene (S) 88 % 70-167 09/18/13 09:25 09/18/13 16:43 460-00-4 **Percent Moisture** Analytical Method: ASTM D2974-87 10.9 % 09/17/13 16:32 Percent Moisture 0.10 1



Analytical Method: ASTM D2974-87

13.3 %

Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176

09/17/13 16:32

Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

ANALYTICAL RESULTS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Percent Moisture

Percent Moisture

Date: 09/23/2013 04:04 PM

Sample: SB-7 Lab ID: 92171843007 Collected: 09/10/13 15:48 Received: 09/11/13 15:40 Matrix: Solid Results reported on a "dry-weight" basis **Parameters** Results Units Report Limit Prepared Analyzed CAS No. Qual 8015 GCS THC-Diesel Analytical Method: EPA 8015 Modified Preparation Method: EPA 3546 **Diesel Components** ND mg/kg 5.8 09/11/13 17:06 09/12/13 20:56 68334-30-5 Surrogates 82 % 41-119 n-Pentacosane (S) 09/11/13 17:06 09/12/13 20:56 629-99-2 Analytical Method: EPA 8015 Modified Preparation Method: EPA 5035A/5030B **Gasoline Range Organics** ND mg/kg Gasoline Range Organics 5.1 09/18/13 09:25 09/18/13 17:07 8006-61-9 Surrogates 4-Bromofluorobenzene (S) 88 % 70-167 09/18/13 09:25 09/18/13 17:07 460-00-4

0.10

1



21.5 %

Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176

09/17/13 16:33

Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

ANALYTICAL RESULTS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Percent Moisture

Date: 09/23/2013 04:04 PM

Sample: SB-8 Lab ID: 92171843008 Collected: 09/10/13 16:09 Received: 09/11/13 15:40 Matrix: Solid Results reported on a "dry-weight" basis **Parameters** Results Units Report Limit Prepared Analyzed CAS No. Qual 8015 GCS THC-Diesel Analytical Method: EPA 8015 Modified Preparation Method: EPA 3546 **Diesel Components** ND mg/kg 6.4 09/11/13 17:06 09/12/13 20:56 68334-30-5 Surrogates 88 % 41-119 n-Pentacosane (S) 09/11/13 17:06 09/12/13 20:56 629-99-2 Analytical Method: EPA 8015 Modified Preparation Method: EPA 5035A/5030B **Gasoline Range Organics** ND mg/kg Gasoline Range Organics 5.6 09/18/13 09:25 09/18/13 17:30 8006-61-9 Surrogates 4-Bromofluorobenzene (S) 84 % 70-167 09/18/13 09:25 09/18/13 17:30 460-00-4 **Percent Moisture** Analytical Method: ASTM D2974-87

0.10

1



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

QUALITY CONTROL DATA

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Date: 09/23/2013 04:04 PM

QC Batch: GCV/7305 Analysis Method: EPA 8015 Modified

QC Batch Method: EPA 5035A/5030B Analysis Description: Gasoline Range Organics

Associated Lab Samples: 92171843001, 92171843002, 92171843003, 92171843004, 92171843005, 92171843006, 92171843007,

92171843008

METHOD BLANK: 1048949 Matrix: Solid

Associated Lab Samples: 92171843001, 92171843002, 92171843003, 92171843004, 92171843005, 92171843006, 92171843007,

92171843008

		Blank	Reporting		
Parameter	Units	Result	Limit	Analyzed	Qualifiers
Gasoline Range Organics	mg/kg	ND	6.0	09/18/13 11:47	
4-Bromofluorobenzene (S)	%	84	70-167	09/18/13 11:47	

LABORATORY CONTROL SAMPLE: Parameter	1048950 Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Gasoline Range Organics 4-Bromofluorobenzene (S)	mg/kg %	50	55.3	111 83	70-165 70-167	
MATRIX SPIKE & MATRIX SPIKE DU	PLICATE: 1048	951	104895	52		

MATRIX SPIKE & MATRIX SP	IKE DUPLICAT	E: 10489	51		1048952						
			MS	MSD							
	92	171841001	Spike	Spike	MS	MSD	MS	MSD	% Rec		
Parameter	Units	Result	Conc.	Conc.	Result	Result	% Rec	% Rec	Limits	RPD	Qual
Gasoline Range Organics	mg/kg	7.9	42.4	42.4	57.3	61.3	117	126	47-187	7	
4-Bromofluorobenzene (S)	%						87	83	70-167		

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 1048953 1048954											
			MS	MSD							
	921	171841003	Spike	Spike	MS	MSD	MS	MSD	% Rec		
Parameter	Units	Result	Conc.	Conc.	Result	Result	% Rec	% Rec	Limits	RPD	Qual
Gasoline Range Organics	mg/kg	6.2	40.3	40.3	58.1	54.6	129	120	47-187	6	
4-Bromofluorobenzene (S)	%						87	87	70-167		

REPORT OF LABORATORY ANALYSIS



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

QUALITY CONTROL DATA

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

LABORATORY CONTROL SAMPLE:

Date: 09/23/2013 04:04 PM

QC Batch: OEXT/23812 Analysis Method: EPA 8015 Modified QC Batch Method: EPA 3546 Analysis Description: 8015 Solid GCSV

Associated Lab Samples: 92171843001, 92171843002, 92171843003, 92171843004, 92171843005, 92171843006, 92171843007,

92171843008

METHOD BLANK: 1045409 Matrix: Solid

1045410

Associated Lab Samples: 92171843001, 92171843002, 92171843003, 92171843004, 92171843005, 92171843006, 92171843007,

92171843008

Parameter	Units	Blank Result	Reporting Limit	Analyzed	Qualifiers
Diesel Components	mg/kg	ND	5.0	09/12/13 17:27	
n-Pentacosane (S)	%	84	41-119	09/12/13 17:27	

Snike

Parameter	Units	Conc.	Result	% Rec	Limits	Qualifiers
Diesel Components	mg/kg	66.7	53.4	80	49-113	
n-Pentacosane (S)	%			91	41-119	
MATRIX CRIVE & MATRIX CRI	CE DUDUICATE: 4040	. 1 4 4	40454	10		

MATRIX SPIKE & MATRIX SPIK	E DUPLICATI	E: 10454	11		1045412						
			MS	MSD							
	921	71745001	Spike	Spike	MS	MSD	MS	MSD	% Rec		
Parameter	Units	Result	Conc.	Conc.	Result	Result	% Rec	% Rec	Limits	RPD	Qual
Diesel Components n-Pentacosane (S)	mg/kg %	ND	78.5	78.5	70.1	70.2	87 91	88 88	10-146 41-119	0	

LCS

LCS

% Rec



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

QUALITY CONTROL DATA

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

QC Batch: PMST/5831 Analysis Method: ASTM D2974-87

QC Batch Method: ASTM D2974-87 Analysis Description: Dry Weight/Percent Moisture

Associated Lab Samples: 92171843001, 92171843002, 92171843003, 92171843004, 92171843005

SAMPLE DUPLICATE: 1046642

92172053044 Dup

Parameter Units Result Result RPD Qualifiers

Percent Moisture % 11.8 11.8 0

SAMPLE DUPLICATE: 1046643

Date: 09/23/2013 04:04 PM

 Parameter
 Units
 92171843005 Result
 Dup Result
 RPD
 Qualifiers

 Percent Moisture
 %
 12.9
 12.7
 1



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

QUALITY CONTROL DATA

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

QC Batch: PMST/5835 Analysis Method: ASTM D2974-87

QC Batch Method: ASTM D2974-87 Analysis Description: Dry Weight/Percent Moisture

Associated Lab Samples: 92171843006, 92171843007, 92171843008

SAMPLE DUPLICATE: 1048247

92172181007 Dup
Parameter Units Result Result RPD Qualifiers

Percent Moisture % 17.8 16.6 7

SAMPLE DUPLICATE: 1048248

Date: 09/23/2013 04:04 PM

ParameterUnits92172133005 ResultDup ResultRPDQualifiersPercent Moisture%14.815.33



Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

QUALIFIERS

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to changes in sample preparation, dilution of the sample aliquot, or moisture content.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PRL - Pace Reporting Limit.

RL - Reporting Limit.

S - Surrogate

1,2-Diphenylhydrazine (8270 listed analyte) decomposes to Azobenzene.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Acid preservation may not be appropriate for 2-Chloroethylvinyl ether, Styrene, and Vinyl chloride.

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

LABORATORIES

Date: 09/23/2013 04:04 PM

PASI-C Pace Analytical Services - Charlotte



(336)623-8921

Pace Analytical Services, Inc. 2225 Riverside Dr. Asheville, NC 28804 (828)254-7176 Pace Analytical Services, Inc. 9800 Kincey Ave. Suite 100 Huntersville, NC 28078 (704)875-9092

QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project: WBS #34927.1.1 NASH CO.

Pace Project No.: 92171843

Date: 09/23/2013 04:04 PM

Lab ID	Sample ID	QC Batch Method	QC Batch	Analytical Method	Analytical Batch
92171843001	SB-1	EPA 3546	OEXT/23812	EPA 8015 Modified	GCSV/15522
92171843002	SB-2	EPA 3546	OEXT/23812	EPA 8015 Modified	GCSV/15522
92171843003	SB-3	EPA 3546	OEXT/23812	EPA 8015 Modified	GCSV/15522
92171843004	SB-4	EPA 3546	OEXT/23812	EPA 8015 Modified	GCSV/15522
92171843005	SB-5	EPA 3546	OEXT/23812	EPA 8015 Modified	GCSV/15522
92171843006	SB-6	EPA 3546	OEXT/23812	EPA 8015 Modified	GCSV/15522
92171843007	SB-7	EPA 3546	OEXT/23812	EPA 8015 Modified	GCSV/15522
92171843008	SB-8	EPA 3546	OEXT/23812	EPA 8015 Modified	GCSV/15522
92171843001	SB-1	EPA 5035A/5030B	GCV/7305	EPA 8015 Modified	GCV/7315
92171843002	SB-2	EPA 5035A/5030B	GCV/7305	EPA 8015 Modified	GCV/7315
92171843003	SB-3	EPA 5035A/5030B	GCV/7305	EPA 8015 Modified	GCV/7315
92171843004	SB-4	EPA 5035A/5030B	GCV/7305	EPA 8015 Modified	GCV/7315
92171843005	SB-5	EPA 5035A/5030B	GCV/7305	EPA 8015 Modified	GCV/7315
92171843006	SB-6	EPA 5035A/5030B	GCV/7305	EPA 8015 Modified	GCV/7315
92171843007	SB-7	EPA 5035A/5030B	GCV/7305	EPA 8015 Modified	GCV/7315
92171843008	SB-8	EPA 5035A/5030B	GCV/7305	EPA 8015 Modified	GCV/7315
92171843001	SB-1	ASTM D2974-87	PMST/5831		
92171843002	SB-2	ASTM D2974-87	PMST/5831		
92171843003	SB-3	ASTM D2974-87	PMST/5831		
92171843004	SB-4	ASTM D2974-87	PMST/5831		
92171843005	SB-5	ASTM D2974-87	PMST/5831		
92171843006	SB-6	ASTM D2974-87	PMST/5835		
92171843007	SB-7	ASTM D2974-87	PMST/5835		
92171843008	SB-8	ASTM D2974-87	PMST/5835		

<i>y</i>	Sample Condition Upon Receipt (S	CUR) Page 1 of 2
Pace Analytical*	Document Number:	Issuing Authority:
1	F-CHR-CS-03-rev.11	Pace Huntersville Quality Office
Client Name:	FEC	
Where Received:	ersville	Raleigh
Courier: Fed Ex UPS USI	PS Client Commercial Pace	OtherOptional
Custody Seal on Cooler/Box Present		yes no Proj. Due Date: Proj. Name:
Packing Material: Bubble Wrap	☐ Bubble Bags ☐ None ☐ Other_	
Thermometer Used: IR Gun T1102	Type of Ice: Wet Blue N	None Samples on ice, cooling process has begun
Temp Correction Factor T1102	: No Correction T1301: No Correc	STATE OF THE PROPERTY OF THE P
Corrected Cooler Temp.: 2	C Biological Tissue is Frozen:	Yes No N/A Date and Initials of person examining contents:
Temp should be above freezing to 6°C	Commen	
Chain of Custody Present:	EYes □No □N/A 1.	
Chain of Custody Filled Out:	Yes □No □N/A 2.	
Chain of Custody Relinquished:	□Yes □No □N/A 3.	
Sampler Name & Signature on COC:	⊟Yes □No □N/A 4.	
Samples Arrived within Hold Time:	⊟Yes □No □N/A 5.	
Short Hold Time Analysis (<72hr):	□Yes □No □N/A 6.	
Rush Turn Around Time Requested	: □Yes ☑No □N/A 7.	
Sufficient Volume:	□Yes □No □N/A 8.	
Correct Containers Used:	-BYes □No □N/A 9.	
-Pace Containers Used:	☑Yes ☐No ☐N/A	
Containers Intact:	⊟Yes □No □N/A 10.	
Filtered volume received for Dissolved	d tests	
Sample Labels match COC:	⊟Yes □No □N/A 12.	
-Includes date/time/ID/Analysis	Matrix:	
All containers needing preservation have bee	en checked. Yes No N/A 13.	
All containers needing preservation are fou	und to be in ☐Yes ☐No ☐N/A	
compliance with EPA recommendation.		
exceptions: VOA, coliform, TOC, O&G, WI-DRO	□Yes □No □N/A 14.	
Samples checked for dechlorination:		
Headspace in VOA Vials (>6mm):	□Yes □No □N/A 15.	
Trip Blank Present:	□Yes □No □N/A 16.	
Trip Blank Custody Seals Present	□Yes □No □N/A	
Pace Trip Blank Lot # (if purchased):_		
Client Notification/ Resolution:		Field Data Required? Y / N
	Date/Time:	
Comments/ Resolution:		

SCURF Review: AMB Date: 9-11-13
SRF Review: AMB Date: 9-11-13

Note: Whenever there is a discrepancy affecting North Carolina compliance samples, a copy of this form will be sent to the North Carolina DEHNR Certification Office (i.e out of hold, incorrect preservative, out of temp, incorrect containers)

WO#:92171843

(IT no label available)

90			JSTODY / Analytical Request D		
Pace Analytical www.pacelabs.com		The Chain-of-Custody is	a LEGAL DOCUMENT. All relevant fields must be comple		
www.pacelabs.com			- 651 COUNTRY		
section A sequired Client Information:	Section B Required Project Information:		Section C	Page	the Commence of the second
	IDenest Tex	21 40	Invoice Information: Attention:	7 . 107 10 10 10 10	1699422
ddress: P. 0. 130x 14262	Copy To:	el, com	Company Name:	REGULATORY AGENCY	
Ro 110 22709			Company Name: NCDOT Address:		ND WATER TO DRINKING WATER
Rip NC 27769 mail To: ade @gel, com	Purchase Order No.:	±34927.1.1	Race Quote	UST RCRA	OTHER OTHER
hone: 323-8828 Fax: aquested Duo Detector.	Project Name:	5472(.1.1	Reference:	Site Location	J. J. OTHER
equested Due Date/TAT: NORM AC	Project Number: U - 3331	LENTRY CLB. RD	Manager: Pace Profile #: U094 -	STATE: NC	- District State of the Control of t
7 (0)007 42	1 0-3331	NCDT01013		d Analysis Filtered (Y/N)	
Section D Matrix	Codes			Analysis i litered (1/N)	-
Required Client Information MATRIX	/ CODE Se	COLLECTED	Preservatives >		
Drinking Wa Water	WT 8 0	SITE COMPOSITE			
Waste Water Product Soil/Solid	P P START				(X) () (X) (X) (X)
SAMPLE ID OII Wipe	SL (aes) (B) (B) (B) (B) (B) (B) (B) (B) (B) (B		\\ \text{SE} \ \ \ \ \ \ \ \ \ \ \ \ \		Op. 17-1843
(A-Z, 0-9 / ,-) Air Sample IDs MUST BE UNIQUE Tissue		AP A	CONTAINERS Seerved 1 1 1 203 anol Ilysis Test		i- /
Other		TEMP	ONT Sis of Sis		Ö
	MATRIX	TIME DATE TIME	['' 닭이의 [쿠!♡] 뭐 # '''		Pace Project No./ Lab I.D.
	BATE	TIME DATE TIME	# OF Unpre H2SC HNO NaO+ NaO+ Other Other		Pace Project No./ Lab I.D.
5B-	54 G	9/10/13/2/3	42 2 11		001
5,5-2		9/10/13 1250	42 2 1		an
SB-4		3/10/13 1321	A2 2 VV		03
\$13-4		9/10/13 1355	42 2 44		009
SB-5 5B-6	1//	9/10/13 /430	42 2 2		005
38-6		9/10/13/505	42 2 4		11 100
5B-7 SB-8		9/10/13 1548	4 2 2 2		The state of the s
70-0		9/10/13 1609 #	42 2 2		1 008
					+
ADDITIONAL COMMENTS	RELINQUISHED BY / A	FFILIATION DATE	TIME ACCEPTED BY / AFFICIATION	DATE TIME	SAMPLE CONDITIONS
	12	1051 011			CAMILEE CONDITIONS
	and Prance	19EC 9/11/13	1020 By my 1 Be	, ,	
	Janny 1	7/4/13	1540 ((~)	5/11/13 15.422	14 -48
	/		1		
	s	AMPLER NAME AND SIGNATURE			on (1)
ORI	IGINAL	PRINT Name of SAMPLER:	ANDREW EYER		Received on Ice (Y/N) Custody Sealed Cooler (Y/N) Sealed Cooler (Y/N)
		SIGNATURE of SAMPLER:	DATE Signed (MM/DD/YY):	09/11/13	Received on Ice (Y/N) Custody Sealed Cooler (Y/N) (Y/N) Samples Intact (Y/N)
*Important Note: By signing this form you are accepti	ing Pace's NET 30 day payment terms and	agreeing to late charges of 1.5% per month	for any invoices not paid within 30 days.		F-ALL-Q-020rev.07, 15-May-2007