RAL-2UA2440BPJ

COMPUTED BY:	CGM	DATE:	3/06/14
CHECKED BY:	JRR	DATE:	

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

PROJECT NO.	SHEET NO.
U-2579B	3D-5

Note: Invert Elevations indicated are for Bid Purposes only and shall not be used for project construction stakeout. See "Standard Specifications For Roads and Structures, Section 300-5".

LIST OF PIPES, ENDWALLS, ETC. (FOR PIPES 48 INCHES & UNDER)

| LINE & STATION / SIZE / THICKNESS OR GAUGE | OFFSET | STRUCTURE NUMBER FROM | STRUCTURE NUMBER TO | TOP ELEVATION FT. | INVERT ELEVATION FT. | INVERT ELEVATION FT. | MINIMUM REQUIRED SLOPE % | SIDE DRAIN PIPE (STATEWIDE TIER) (RCP, CSP, CAAP, HDPE, or PVC) 15 | 18 | 24 | 30 | 36 | 42 | 48 | DO NOT USE RCP | C. S. PIPE (SE: SHOP ELONGATED) 15 .064 | 18 .064 | 24 .064 | 30 .064 | 36 .079 | 42 .109 | R. C. PIPE CLASS III 15 | 18 | 24 | 30 | 36 | 42 | 48 | R. C. PIPE CLASS IV 15 | 18 | 24 | 30 | 42 | 48 | R. C. PIPE CLASS V 24 | 30 | 36 | 8" DIP (DUCTILE IRON PIPE) | 42" R.C. PIPE CULVERTS, CONTRACTOR DESIGN | 48" R.C. PIPE CULVERTS, CONTRACTOR DESIGN | 36" R.C. PIPE CULVERTS, CONTRACTOR DESIGN | 18" R.C. PIPE CULVERTS, CONTRACTOR DESIGN | 30" WELDED STEEL PIPE, 0.500, TRENCLESS INSTALLATION | 36" WELDED STEEL PIPE, 0.500, TRENCLESS INSTALLATION | 42" WELDED STEEL PIPE, 0.625, TRENCLESS INSTALLATION | 48" WELDED STEEL PIPE, 0.625, TRENCLESS INSTALLATION | ENDWALLS STD. 838.01 OR STD. 838.11 OR 838.80 (UNLESS NOTED OTHERWISE) CY | QUANTITIES FOR DRAINAGE STRUCTURES (NOTE: TOTAL LIN. FT. FOR PAY QUANTITY SHALL BE A + (1.3 X B)) 0' THRU 5' EACH | A 5' THRU 10' LIN. FT. | B 10' AND ABOVE LIN. FT. | C.B. STD. 840.01 OR STD. 840.02 | FRAME, GRATES, AND HOOD STD. 840.03 GRATE TYPE E | F | G | CONCRETE TRANSITIONAL SECTION D.I. STD. 852.04 OR STD. 852.06 | C.B. STD. 852.05 | OPEN THROAT C.B. STD. 840.04 OR STD. 840.05 | D.I. STD. 840.14 OR STD. 840.15 | D.I. FRAME AND GRATES STD. 840.16 | G.D.I. TYPE "A" STD. 840.17 OR STD. 840.26 | G.D.I. TYPE "B" STD. 840.18 OR STD. 840.27 | G.D.I. (W.S. FLAT) FRAME W/ 2 GRATES STD. 840.20 | G.D.I. (W.S. SAG) FRAME W/ GRATE STD. 840.22 | G.D.I. (W.S. SAG) FRAME W/ 2 GRATES STD. 840.22 | G.D.I. (N.S. SAG) FRAME W/ 2 GRATES STD. 840.24 | G.D.I. (N.S. FLAT) FRAME W/ 2 GRATES STD. 840.29 | J.B. STD. 840.31 OR STD. 840.32 | T.B.D.I. STD. 840.36 | STEEL GRATE AND FRAME STD. 840.37 | SPRING BOX STD. 840.41 | M.H. FRAME AND COVER STD. 840.54 | CONVERT EXISTING C.B. TO J.B. | CONVERT EXISTING O.T.C.B. TO 2GI | 15" SIDE DRAIN PIPE ELBOW | 18" SIDE DRAIN PIPE ELBOW | 24" SIDE DRAIN PIPE ELBOW | 30" SIDE DRAIN PIPE ELBOW | 36" SIDE DRAIN PIPE ELBOW | 15" C.S. PIPE ELBOW | 18" C.S. PIPE ELBOW | 24" C.S. PIPE ELBOW | 42" C.S. PIPE ELBOW | BERM DITCH OUTLET STD. 650.10 | MODIFIED CONC. FLUME | PREFORMED SCOUR HOLE (PER EACH) | ENERGY DISSIPATION BASIN | FLOWABLE FILL CY | CONCRETE COLLARS CL. "B" STD. 840.72 CY | CONCRETE AND BRICK PIPE PLUG STD. 840.71 CY | PIPE REMOVAL LIN. FT. | REMARKS |
|---|---|---|---