TIP NO.	SHEET NO.
B-4565	SHEET-2A

APPROVED: DocuSigned by: Ayman Alqudwah F32AC5CAF965472...

DATE: 10/21/2014

SEAL

NORTH CAROLINA PROFESSIONAL SEAL 028387 ENGINEER AYMAN I. ALQUDWAH

SIGN NO.	SIGN TYPE	SIGN SIZE (in.) w x h	ROADWAY STATION	NO. OF SUP.	BEAM SECTION	SUPPORT TYPE BA or S	ATTACH METHOD	MOUNTING METHOD	HORIZ CLR. (ft.)	LENGTH (ft) SNS HT H	MTG HT C	EMBED-MENT	LEFT SUPPORT (ft) S	L	TOTAL LENGTH	CENTER SUPPORT (ft) S	L	TOTAL LENGTH	RIGHT SUPPORT (ft) S	L	TOTAL LENGTH	FOOTING DIAMETER (ft.)	FOOTING DEPTH (ft.)	B/A SUPPORT WEIGHTS (lbs.)	SIMPLE SUPPORT WEIGHTS (lbs.)	REINF. FTGS. (c.y.)	PLAIN FTGS. (c.y.)	FIELD VERIFIED SEE NOTE 2 (mm/dd/yy)
101	B	108 X 54	SEE PLAN	2	W6x9	BA	N/A	N/A	30.00	5.50	7.00	4.5	1.00	13.50	18.00	0.00	0.00	0.00	1.00	13.50	18.00	1.5	5	387.12	0.00	0.65	0.00	
																								TOTAL 388.00	TOTAL 0.00	TOTAL 0.65	TOTAL 0.00	
																							USE:	388.00	0	1		

NOTES

1. DIMENSION "S" REPRESENTS AN INCREASE (+), OR A DECREASE (-) IN POLE LENGTH, RELATIVE TO THE ELEVATION OF THE EDGE OF PAVEMENT.

2. FIELD VERIFICATIONS SHALL BE REQUIRED FOR ALL SUPPORTS, SEE (*) ARTICLE 903-3. FABRICATORS SHALL BE AISC CERTIFIED IN CATEGORY 1, SEE (*) ARTICLE 1072-1. (*) = N.C.D.O.T. STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES

3. PLAN LOCATIONS FOR EXISTING UTILITIES ARE BASED ON THE BEST AVAILABLE INFORMATION AND, THEREFORE MAY NOT BE PRECISELY ACCURATE. THEREFORE, IT IS INCUMBENT UPON THE CONTRACTOR TO DETERMINE THE EXACT LOCATION OF UTILITIES BEFORE BEGINNING WORK IN A LOCATION.



TYPICAL ELEVATION
GROUND MOUNTED SIGNS



TYPE "A"
GROUND MOUNTED SIGNS

10/21/2014
R:\Traffic\Signing\CADD\Signing Layout Plans\B-4565_Engseed 6-11-12.dgn
User:bnowlin