T	IP NO.	SHEET NO.	
R - 2	2915D	SIGN-1A	
APPROVED:	Joseph B. Kopaskie		

DATE: 10/29/2014

SEAL



ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
901.10	TYPE 'A' SIGNS
901.20	TYPE 'B' SIGNS
901.70	SIGN STRINGERS AND SUPPORT SPACING
901.80	SIGN MOUNTING DETAILS - FOR TYPE A AND TYPE B SIGNS
903.10	GROUND MOUNTED SIGN SUPPORTS (WITH THE EXCEPTION
	SHEETS 1 OF 3 AND 2 OF 3 WHICH ARE REPLACED WITH SHEETS SIGN-2A AND 2B IN PLANS)
904.10	ORIENTATION OF GROUND MOUNTED SIGNS
904.50	MOUNTING OF TYPE 'D', 'E' AND 'F' SIGNS ON 'U' CHANNEL POSTS

		SUMMARY OF QUANTITIES		
ITEM NO.		ITEM DESCRIPTION	QUANTITY	UNIT
DESC. NO.	SECT. NO.			
4048000000 4054000000 4060000000 4066000000 4072000000 4096000000 4102000000 4110000000 4116100000 4152000000 4155000000 4192000000 4238000000	902 902 903 903 903 904 904 904 904 904 907 907 907	REINFORCED CONCRETE SIGN FOUNDATION PLAIN CONCRETE SIGN FOUNDATION SUPPORTS, BREAKAWAY STEEL BEAM SUPPORTS, SIMPLE STEEL BEAM SUPPORTS, 3 LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, TYPE E SIGN ERECTION, TYPE F SIGN ERECTION, TYPE A (GROUND MOUNTED) SIGN ERECTION, TYPE B (GROUND MOUNTED) SIGN ERECTION, RELOCATE SIGN TYPE E DISPOSAL OF SIGN SYSTEM, STEEL BEAM DISPOSAL OF SIGN SYSTEM, U-CHANNEL DISPOSAL OF SIGN, D, E OR F	3 1 1853 493 3192 5 102 32 3 2 8 4 61 8 6	C.Y. C.Y. LB. LB. EA. EA. EA. EA. EA. EA. EA. EA. EA.

PROJECT NOTES

- 1. DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 2. DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 3. SIGN ERECTION, RELOCATE SIGN TYPE E
- 4. DISPOSAL OF SUPPORT, U-CHANNEL
- 5. INSTALLED BY STATE FORCES
- 6. DISPOSAL OF SIGN, D, E OR F

GENERAL NOTES

- . SIGNS FURNISHED BY STATE
- . ALL TYPE 'D' SIGNS SHALL BE MOUNTED ON TWO U-CHANNEL POSTS UNLESS OTHERWISE INDICATED ON THE PLANS.
- . IF REMOVAL OR RELOCATION OF SIGNS ON PRIVATE STREET (NON-STATE MAINTAINED) IS REQUIRED DUE TO CONSTRUCTION, THE CONTRACTOR SHALL INFORM THE ENGINEER. THE WORK WILL BE COMPLETED BY OTHERS.
- . WHEN NOT STATIONED OR DIMENSIONED ON PLANS, ALL 'E' AND 'F' SIGNS SHALL BE FIELD LOCATED BY THE ENGINEER
- . ALL EXISTING SIGNS ON "U" CHANNEL POST WITHIN THE PROJECT LIMITS SHALL BE REMOVED AND DISPOSED OF UNLESS OTHERWISE NOTED ON PLANS.
- . WHEN EXISTING SIGNS ARE REMOVED AND INSTALLED ON NEW SUPPORTS, THE RE-ERECTION SHALL IMMEDIATELY FOLLOW THE REMOVAL.
- . THE BACKGROUND FOR TYPE E & F SIGNS SHALL BE GRADE C REFLECTIVE SHEETING.
- . DO NOT BEGIN FABRICATION FOR TYPES A & B SIGNS MOUNTED ON OVERHEAD STRUCTURES OR STEEL SUPPORTS UNTIL "S" DIMENSIONS HAVE BEEN FIELD VERIFIED.
- . SEE ROADWAY PLANS FOR GUARD/GUIDE RAIL DETAILS.