

- 7. FOR THANKSGIVING DAY, BETWEEN THE HOURS OF 6:00 A.M. TUESDAY TO 7:00 P.M. MONDAY.
- 8. FOR CHRISTMAS, BETWEEN THE HOURS OF 6:00 A.M. THE FRIDAY BEFORE THE WEEK OF CHRISTMAS DAY AND 7:00 P.M. THE FOLLOWING TUESDAY AFTER THE WEEK OF CHRISTMAS.

C) DO NOT CONDUCT ANY HAULING OPERATIONS AGAINST THE FLOW OF TRAFFIC OF AN OPEN TRAVELWAY UNLESS THE HAULING OPERATION IS PROTECTED BY BARRIER OR GUARDRAIL OR AS DIRECTED BY THE ENGINEER.

LANE AND SHOULDER CLOSURE REQUIREMENTS

- D) REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED OR AS DIRECTED BY THE ENGINEER.
- E) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN **OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY** STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.
- F) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO A DIVIDED FACILITY AND WITHIN 10 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

- G) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN A LANE OF TRAVEL OF AN UNDIVIDED OR DIVIDED FACILITY, CLOSE THE LANE ACCORDING TO THE TRAFFIC CONTROL PLANS, ROADWAY STANDARD DRAWINGS, OR AS DIRECTED BY THE ENGINEER. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL LANE.
- H) DO NOT WORK SIMULTANEOUSLY WITHIN 15 FT ON BOTH SIDES OF AN OPEN TRAVELWAY, RAMP, OR LOOP WITHIN THE SAME LOCATION UNLESS PROTECTED WITH GUARDRAIL OR BARRIER.

PAVEMENT EDGE DROP OFF REQUIREMENTS

I) BACKFILL AT A 6:1 SLOPE UP TO THE EDGE AND ELEVATION OF EXISTING PAVEMENT IN AREAS ADJACENT TO AN OPENED TRAVEL LANE THAT HAS AN EDGE OF PAVEMENT DROP-OFF AS FOLLOWS:

BACKFILL DROP-OFFS THAT EXCEED 2 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS OF 45 MPH OR GREATER.

BACKFILL DROP-OFFS THAT EXCEED 3 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS LESS THAN 45 MPH.

BACKFILL WITH SUITABLE COMPACTED MATERIAL, AS APPROVED BY THE ENGINEER, AT NO EXPENSE TO THE DEPARTMENT.

J) DO NOT EXCEED A DIFFERENCE OF 2 INCHES IN ELEVATION BETWEEN OPEN LANES OF TRAFFIC FOR NOMINAL LIFTS OF 1.5 INCHES. INSTALL ADVANCE WARNING "UNEVEN LANES" SIGNS (W8-11) IN ADVANCE AND A MINIMUM OF EVERY HALF MILE THROUGHOUT THE UNEVEN AREA.

TRAFFIC PATTERN ALTERATIONS

K) NOTIFY THE ENGINEER TWENTY ONE (21) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

SIGNING

L) INSTALL ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.

- SIGNING (COI
- M) ENSURE TRAFFIC P
- N) INSTALL B (W8-1) 500 ENGINEER.

TRAFFIC CON

- O) WHEN LAI **AREAS NO** 10 FT ON-0 **REFER TO** 1130 (DRU REQUIREM
- P) PLACE TYP ATTACHED
- Q) PLACE AD PERPENDI UNOPENEL

PAVEMENT M

R) INSTALL T ON INTERI

> ROAD NAI ALL


- S) PLACE ON SECOND A APPLICATI
- T) TIE PROPO LINES.
- U) REMOVE/R MARKERS
- V) TRACE THI **PROPER CO** PLACE DR AFTER REN

MISCELLANEC

- W) LAW ENFO AREA AND
- X) IN THE EV TIE-IN ARE THE ENGIN AND BLAC 500 FT RES TO DELINE

	APPROVED:	
DocuSigned by: Matt West AC71A1D0796B425 4/6/2015	SEAL	SEAL 029876 WGINESSION HEW S.

			PROJ. REFERENCE NC	 SHEET NO. TMP - 1B 		
			0 0000			
NTINUED)						
ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY ATTERN.						
BLACK ON ORANGE "DIP" SIGNS (W8-2) AND/OR "BUMP" SIGNS 0 FT IN ADVANCE OF THE UNEVEN AREA, OR AS DIRECTED BY THE 2.						
ITROL DEVICES						
NE CLOSURES ARE NOT IN EFFECT SPACE CHANNELIZING DEVICES IN WORK O GREATER IN FEET THAN TWICE THE POSTED SPEED LIMIT (MPH) EXCEPT, CENTER IN RADII, AND 3 FT OFF THE EDGE OF AN OPEN TRAVELWAY. STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES SECTIONS UMS), 1135 (CONES) AND 1180 (SKINNY DRUMS) FOR ADDITIONAL MENTS.						
PE III BARRICADES, WITH "ROAD CLOSED" SIGN R11-2 D, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY.						
DDITIONAL SETS OF THREE CHANNELIZING DEVICES ICULAR TO THE EDGE OF TRAVELWAY ON 500 FT CENTERS WHEN ED LANES ARE CLOSED TO TRAFFIC.						
MARKINGS AND	MARKERS					
	VEMENT MARKING PAVEMENT AS FOL		ORARY PAVEMENT	MARKERS		
ME	MARKING PAINT	MARK TEI	(ER MPORARY RAISED			
IE APPLICATION OF PAINT FOR TEMPORARY TRAFFIC PATTERNS. PLACE A APPLICATION OF PAINT SIX (6) MONTHS AFTER THE INITIAL TION AND EVERY SIX MONTHS AS DIRECTED BY THE ENGINEER.						
OSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING						
REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND BY THE END OF EACH DAY'S OPERATION.						
IE PROPOSED MONOLITHIC ISLAND LOCATIONS WITH COLOR PAVEMENT MARKINGS PRIOR TO REMOVAL AND INSTALLATION. RUMS TO DELINEATE ANY PROPOSED MONOLITHIC ISLANDS AFTER MOVAL AND BEFORE INSTALLATION.						
ous						
FORCEMENT SHALL BE USED TO MAINTAIN TRAFFIC THROUGH THE WORK D/OR INTERSECTIONS AS DIRECTED BY THE ENGINEER.						
VENT A DRIVEWAY TIE-IN CANNOT BE MADE IN ONE DAY'S TIME, BRING THE EA TO AN APPROPRIATE ROADWAY ELEVATION AS DETERMINED BY NEER. PLACE BLACK ON ORANGE "LOOSE GRAVEL" SIGNS (W8-7) CK ON ORANGE "PAVEMENT ENDS" SIGNS (W8-3) 500 FT AND SPECTIVELY IN ADVANCE OF THE UNEVEN AREAS. USE DRUMS EATE THE EDGE OF ROADWAY ALONG UNPAVED AREAS.						
-						



TRANSPORTATION **OPERATIONS** PLAN