



+

+

uumettien	
Excellence Delivered As F	ro

## NOTES:

LONGITUDINAL STEEL MAY BE SHIFTED SLIGHTLY, AS NECESSARY, TO AVOID INTERFERENCE WITH STIRRUPS IN PRESTRESSED CONCRETE GIRDERS.

PREVIOUSLY CAST CONCRETE IN A CONTINUOUS UNIT SHALL HAVE ATTAINED A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI BEFORE ADDITIONAL CONCRETE IS CAST IN THE UNIT.

BARRIER RAIL IN A CONTINUOUS UNIT SHALL NOT BE CAST UNTIL ALL SLAB CONCRETE IN THE UNIT HAS BEEN CAST AND HAS REACHED A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI.

PROVIDE 11/4" HIGH BEAM BOLSTERS UPPER AT 4'-O"CTS. ATOP THE METAL STAY-IN-PLACE FORMS TO SUPPORT THE BOTTOM MAT OF "A" BARS. WHEN USING REMOVABLE FORMS, PROVIDE CONTINUOUS HIGH CHAIRS FOR METAL DECK (C.H.C.M.) @ 4'-O"CTS. WITH A HEIGHT TO SUPPORT THE BOTTOM MAT OF "A" BARS A CLEAR DISTANCE OF  $2^{1}/_{2}$ " ABOVE THE TOP OF THE REMOVABLE FORM.

\* USE THIS SIZE BAR SUPPORT IN THE AREAS WITH #7 ``B'' BARS. FOR OTHER AREAS WITH #4 ``B'' BARS, USE THE BAR SUPPORT AS SHOWN IN TYPICAL SECTION AT INTERMEDIATE DIAPHRAGM.



