


NOTE: IMMEDIATELY AFTER THE CONSTRUCTION OF THE APPROACH SLAB, THE CONTRACTOR SHALL PROVIDE TEMPORARY BERM AND SLOPE DRAIN. CONTRACTOR SHALL GRADE TO PIPE INLET AND PROVIDE EROSION RESISTANT MATERIAL AS SHOWN. THE EROSION RESISTANT MATERIAL SHALL BE EITHER 1) ASPHALT PLANT MIX, TYPE 1 OR TYPE 2, MIN. 2" DEPTH, 2) EROSION CONTROL MAT, OR 3) CONCRETE, AS DIRECTED BY THE ENGINEER. THE SLOPE DRAIN SHALL CONSIST OF A NON-PERFORATED TEMPORARY DRAINAGE PIPE, 12 INCHES IN DIAMETER.

PLAN VIEW



NOTE: IF THE APPROACH SLAB IS NOT CONSTRUCTED IMMEDIATELY AFTER THE BACKFILLING OF THE END BENT EXCAVATION, GRADE TO DRAIN TO THE BOTTOM OF THE SLOPE AND PROVIDE EROSION RESISTANT MATERIAL, SUCH AS FIBERGLASS ROVING OR AS DIRECTED BY THE ENGINEER TO PREVENT SOIL EROSION AND TO PROTECT THE AREA ADJACENT TO THE STRUCTURE. THE CONTRACTOR WILL BE REQUIRED TO REMOVE THESE MATERIALS PRIOR TO CONSTRUCTION OF THE APPROACH SLAB.

TEMPORARY DRAINAGE DETAIL

TEMPORARY BERM AND SLOPE DRAIN DETAILS

(TO BE USED WHEN SHOULDER BERM GUTTER IS REQUIRED)

PROJECT NO. R-2915B ASHE COUNTY

STATION: 242+67.42 -L-

SHEET 2 OF 2

SEAL F 037180

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

STANDARD

BRIDGE APPROACH SLAB DETIALS

SHEET NO. REVISIONS NO. BY: S04-35 DATE: BY: DATE: TOTAL SHEETS

PLANS PREPARED BY: Gannett Fleming
Raleigh NC 27606-4279
(919) 859-4880 Excellence Delivered **As Promised** NC Lic. No. F-0270

THESE PLANS HAVE BEEN PROPERLY EXAMINED BY THE UNDERSIGNED. I HAVE DETERMINED THAT THEY COMPLY WITH EXISTING NORTH CAROLINA CODES, AND HAVE BEEN PROPERLY ADAPTED FOR USE IN THIS AREA.

ASSEMBLED BY: T.J. KIRSCHBAUM DATE: 10/27/14 CHECKED BY: R.F. WERTMAN DATE: 11/13/14 DRAWN BY : FCJ II/88 REV. IO/I/II CHECKED BY : ARB 11/88 REV. 7/12 REV. 6/13 MAA/GM MAA/GM

STD. NO. BAS4 STR.NO.4