

GENERAL NOTES: EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATION OF BRIDGE DECK. EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FROM BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION SHOWN ON THE PLANS AND NOTIFY THE ENGINEER IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER. ROADWAY MILLING IS INCLUDED TO ENSURE A SMOOTH TRANSITION ONTO THE BRIDGE FLOOR. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL MILL AS REQUIRED TO PROVIDE A SMOOTH TRANSITION TO THE ROADWAY AT BOTH ENDS OF BRIDGE. IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS. FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLANS. LONGITUDINAL CONSTRUCTION JOINTS OF OVERLAYS SHALL BE LOCATED ALONG CENTERLINE OR EDGE OF TRAVEL LANES.

FOR OVERLAY OF BRIDGE WITH EPOXY OVERLAY SYSTEM, SEE SPECIAL PROVISIONS. FOR FOAM JOINT SEALS, SEE SPECIAL PROVISIONS. FOR ELASTOMERIC CONCRETE, SEE SPECIAL PROVISIONS. FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS. FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS. FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS. FOR BRIDGE JOINT DEMOLITION, SEE SPECIAL PROVISIONS. FOR SURFACE PREPARATION, SEE "EPOXY OVERLAY SYSTEM" SPECIAL PROVISION. FOR CONCRETE DECK REPAIR FOR EPOXY OVERLAY, SEE SPECIAL PROVISIONS.

> DocuSigned by William M. (La

6/10/2015

-1EB20097EAAF437..

+

	PROJEC	CT NO.	<u> </u>	<u>P-5</u>	500	FF	
		CRAV				UNTY	
	BRIDGE	E NO		22	2		
	SHEET 2 0	F 2					
	BRIDGE 222 ON						
urke							
SEAL 40257 FENCESSOL	T	THE TRENT RIVER					
40257	REVISIONS SHEET NO.						
HANNA HEW CLANNING	NO. BY:	DATE:	NO. BY	'a	DATE:	S-15	
	1 2		3 4			TOTAL SHEETS 23	