

NOTES

FOR BRIDGE APPROACH FILL INCLUDING GEOTEXTILE, 4" Ø DRAINAGE PIPE, AND #78M STONE BACKFILL, SEE ROADWAY PLANS.

GEOTEXTILE SHALL BE TYPE 1 IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS SECTION 1056.

#78M STONE BACKFILL (CLASS V SELECT MATERIAL) SHALL BE IN ACCORDANCE WITH STANDARD SPECIFICATIONS SECTION 1016.


#78M STONE BACKFILL IS TO BE CONTINUOUS ALONG FILL FACE OF BACKWALL FROM OUTSIDE EDGE TO OUTSIDE EDGE OF APPROACH SLAB.

APPROACH SLAB SHALL NOT BE CONSTRUCTED PRIOR TO COMPLETION OF THE BRIDGE DECK.

AREA BETWEEN THE WINGWALL AND APPROACH SLAB SHALL BE GRADED TO DRAIN THE WATER AWAY FROM THE FILL FACE OF THE BRIDGE AND SHALL BE PAVED. SEE ROADWAY PLANS.

FOR THE 4"Ø DRAINAGE PIPE OUTLET(S), SEE ROADWAY STANDARD DRAWINGS.

FOR EXPANSION JOINT SEALS, SEE SPECIAL PROVISIONS.



CURB DETAILS

Greg Dickey

PROJECT NO. I-3318BB

JOHNSTON COUNTY

STATION: 24+68.00 -L-

SHEET 1 OF 11

DEPARTMENT OF TRANSPORTATION
RALEIGH
STANDARD

BRIDGE APPROACH SLAB FOR RIGID PAVEMENT

REVISIONS						SHEET
١.	BY:	DATE:	NO.	BY:	DATE:	S-68
			3			TOTAL SHEETS
)			4			78

SEAL 21271

COPY W. DISTRIBUTION OF W. DISTRIBUTION OF W. DISTRIBUTION OF THE PROPERTY OF THE

SECTION THRU SLAB