

NOTES

STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR ANCHOR BLOTS.

THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE JOINT BETWEEN THE DECK AND APPROACH SLAB HAS BEEN SAWED AND THE CONCRETE PARAPET IS CAST IF SLIP FORMING IS USED.

BACKWALL SHALL BE PLACED BEFORE APPLYING THE EPOXY PROTECTIVE COATING.

THE TOP SURFACE OF THE END BENT CAP EXCEPT THE BRIDGE SEAT BUILDUPS SHALL BE SLOPED TRANSVERSELY FROM THE FILL FACE TO THE BACK FACE AT THE RATE

THE TOP SURFACE AREAS OF THE END BENT CAPS SHALL BE CURED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS, EXCEPT THE MEMBRANE CURING COMPOUND METHOD SHALL NOT BE USED.

THE COST OF THE FORM LINERS AND SPECIAL SURFACE FINISH ARE INCLUDED IN THE SQ. FT. BID FOR ARCHITECTURAL CONCRETE SURFACE TREATMENT.

FOR ARCHITECTURAL CONCRETE SURFACE TREATMENT, SEE SPECIAL PROVISIONS.

INSTALL THE 4" Ø DRAIN PIPE THROUGH THE WINGWALL AS REQUIRED FOR REINFORCED BRIDGE APPROACH FILLS, SEE THE ROADWAY PLANS, REINFORCING STEEL IN THE WINGWALL MAY BE SHIFTED AS NECESSARY TO CLEAR THE DRAIN PIPE.

"V" BARS AND "K" BARS IN THE BACKWALL SHALL BE FIELD BENT OR CUT IN THE AREA OF THE 22"Ø FORMED HOLE.

TOP OF PILE ELEVATIONS						
1	2,070.93	7	2,069.78			
2	2,070.74	8	2,069.58			
3	2,070.55	9	2,069.37			
4	2,070.37	9	2,069.16			
5	2,070.18	11	2,068.96			
6	2,069.99					

- (A) 2'-5"MIN. SPLICE (TYP. #4 ''B'' AND #4 ''K'' BARS)
- (B) SEE "SHEAR KEY DETAIL" ON SHEET 3 OF 4
- (C) 3-#4 S1 & #4 S2 @ 6"CTS.
- (D) 4-#4 S1 & #4 S2 @ 7"CTS.

B-4159 PROJECT NO._ JACKSON COUNTY 20+16.00 -L-STATION:


SHEET 1 OF 4

BY:

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

SUBSTRUCTURE

END BENT 2



REVI	SHEET NO			
DATE:	NO.	BY:	DATE:	S-53
	3			TOTAL SHEETS
	4			64