PROJECT REFERENCE NO. SHEET NO. B-5404

> ROADWAY DESIGN ENGINEER

Dewberry

2610 WYCLIFF ROAD

EFF. 01-17-2012 REV. 10-30-2012 2012 ROADWAY ENGLISH STANDARD DRAWINGS

TITLE SHEET INDEX OF SHEETS, GENERAL NOTES, AND LIST OF STANDARD DRAWINGS

CONVENTTIONAL SYMBOLS SURVEY CONTROL SHEET and by reference hereby are considered a part of these plans: CENTERLINE COORDINATE LIST

PAVEMENT SCHEDULE, TYPICAL SECTIONS, AND WEDGING DETAILS DETAIL FOR GUARDRAIL ANCHOR UNIT TYPE TEMPORARY W BEAM RETROFIT DIVISION 2 - EARTHWORK DETAIL OF GUARDRAIL ANCHOR UNIT TYPE III 200.02 Method of Clearing - Method II STANDARD TEMPORARY SHORING 225.02 Guide for Grading Subgrade - Secondary and Local GUARDRAIL SUMMARY, SUMMARY OF EARTHWORK, SHOULDER BERM GUTTER SUMMARY,

AND PAVEMENT REMOVAL SUMMARY 3D-1 SUMMARY OF DRAINAGE QUANTITIES 3G-1 SUMMARY OF GEOTECHNICAL QUANTITIES 4 THRU 6 PLAN AND PROFILE SHEETS TMP-1 THRU TMP-5 TRANSPORTATION MANAGEMENT PLANS PMP-1 THRU PMP-2 PAVEMENT MARKING PLAN

EC-1 THRUEC-5 EROSION CONTROL PLANS REFORESTATION PLAN SIGN-1 THRU SIGN-2 SIGNING PLANS UO-1 THRU UO-2 UTILITY BY OTHERS PLANS X-0 CROSS-SECTION SUMMARY X-1 THRU X-10 CROSS-SECTIONS S-1 THRU S-14 STRUCTURE PLANS

INDEX OF SHEETS

SHEET NUMBER

1C-1

1D-1

2A-1

2C-1

2C-2

2G-1

3B-1

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch -N. C. Department of Transportation - Raleigh, N. C., Dated January, 2012 are applicable to this project

STD NO TITLE 225.04 Method of Obtaining Superelevation - Two Lane Pavement DIVISION 3 - PIPE CULVERTS 300.01 Method of Pipe Installation

DIVISION 4 - MAJOR STRUCTURES 422.11 Reinforced Bridge Approach Fills - Sub Regional Tier DIVISION 5 - SUBGRADE, BASES AND SHOULDERS

560.01 Method of Shoulder Construction - High Side of Superelevated Curve - Method I DIVISION 8 - INCIDENTALS 815.02 Subsurface Drain

840.25 Anchorage for Frames - Brick or Concrete or Precast 840.29 Frames and Narrow Slot Flat Grates

840.35 Traffic Bearing Grated Drop Inlet - for Cast Iron Double Frame and Grates

846.01 Concrete Curb, Gutter and Curb & Gutter 846.04 Drop Inlet Installation in Shoulder Berm Gutter

840.00 Concrete Base Pad for Drainage Structures

862.01 Guardrail Placement 862.02 Guardrail Installation 876.01 Rip Rap in Channels

310.10 Driveway Pipe Construction

876.02 Guide for Rip Rap at Pipe Outlets

GENERAL NOTES: 2012 SPECIFICATIONS EFFECTIVE: 01-17-2012

GRADING AND SURFACING OR RESURFACING AND WIDENING:

REVISED: 10-31-2014

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. WHERE NO GRADE LINES ARE SHOWN, THE PROFILES SHOWN DENOTE THE TOP ELEVATION OF THE EXISTING PAVEMENT ALONG THE CENTER LINE OF SURVEY ON WHICH THE PROPOSED RESURFACING WILL BE PLACED. GRADE LINES MAY BE ADJUSTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF

SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

SUBSURFACE DRAINS:

SUBSURFACE DRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 815.02 AT LOCATIONS DIRECTED BY THE ENGINEER.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC NOT SHOWN ON THE PLANS WILL BE PAID FOR AT THE CONTRACT PRICE FOR "TEMPORARY SHORING".

END BENTS:

THE ENGINEER SHALL CHECK THE STRUCTURE END BENT PLANS, DETAILS, AND CROSS-SECTION PRIOR TO SETTING OF THE SLOPE STAKES FOR THE EMBANKMENT OR EXCAVATION APPROACHING A BRIDGE.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE DUKE POWER - POWER (DISTRIBUTION)

FRONTIER - TELEPHONE

ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS.

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY OTHERS.

ROCK

ROCK IS ANTICIPATED BETWEEN -L- STA. 12+10 - 13+80 AND 19+50 - 21+00. BLASTING MAY BE REQUIRED FOR EXCAVATION ON THE PROJECT. SEE SECTION 220 OF THE STANDARD SPECIFICATIONS AND IF APPLICABLE, ROCK BLASTING PROVISION.