

APPROVED: *Ayman Alqudwah*
F30ACSCAF66472
DATE: 1/21/2016



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

SIGN NUMBER: 301 BACKG COLOR: Green DESIGN BY: EEW CHECKED BY: Jan 20, 2016
 TYPE: D COPY COLOR: White PROJECT ID: B-5300 LOCATION: US-264 DIV: 2
 QUANTITY: 1

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 6'-0"
 HEIGHT: 2'-0"
 TOTAL AREA: 12.0 Sq.Ft.

BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 0.75"
 RADII: 3"

MAT'L: 0.125" (3.2 mm) ALUMINUM

NO. Z BARS: LENGTH:

USE NOTES: 1,2

- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade C reflective sheeting.
- Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
D 2000	58.3
D 2000	58.3

FILENAME: b5300_sgn_psh_s02 NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 302 BACKG COLOR: Green DESIGN BY: EEW CHECKED BY: Jan 20, 2016
 TYPE: D COPY COLOR: White PROJECT ID: B-5300 LOCATION: US-264 DIV: 2
 QUANTITY: 1

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 3'-6"
 HEIGHT: 1'-3"
 TOTAL AREA: 4.4 Sq.Ft.

BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 0.5"
 RADII: 1.5"

MAT'L: 0.125" (3.2 mm) ALUMINUM

NO. Z BARS: LENGTH:

USE NOTES: 1,2

- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade C reflective sheeting.
- Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum and demountable.

MOUNT BELOW SIGN 502 ON 1 WOOD POST

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
C 2000	39.3
C 2000	14.2

FILENAME: b5300_sgn_psh_s02 NORTH CAROLINA D.O.T. SIGN DETAIL

1/21/2016
 P:\Projects-B\B5300\Traffic\Signing\CAOD\Signing Layout Plans\B5300_sgn_psh_s02.dgn
 User:rtward

TYPE "D" SIGNS