COMPUTED BY: _	MRL	DATE:_	4/7/2015
CHECKED BY:	AKW	DATF:	4/7/2015

PROJECT REFERENCE NO.	SHEET NO.
U-3308	3G-I

## SUMMARY OF SUBSURFACE DRAINAGE

LINE	STATION	STATION	LOCATION LT/RT/CL	DRAIN TYPE* UD/BD/SD	LF
	CONTINGENCY			UD	1,000
				TOTAL LF	1,000

\*UD = UNDERDRAIN \*BD = BLIND DRAIN \*SD = SUBSURFACE DRAIN

## SUMMARY OF GEOTEXTILE FOR PAVEMENT STABILIZATION

LINE	STATION	STATION	OFFSET	SY	
	CONTIN	NGENCY		5,000	
			TOTAL SY	5,000	

## SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	STATION	STATION	Aggregate Type ASU/AST	Aggregate Thickness INCHES	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Soil Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization
-LALT-	36+40.00	38+15.00	ASU	12"	450	900	1350		
	CONTIN	NGENCY	ASU	12"	1000	1900	3000		
	CONTI	NGENCY	AST					500	
				TOTAL CY/TONS	1450	2800	4350*	500	

AST = AGGREGATE STABILIZATION

\*Total square yards of Geotextile for Soil Stabilization is only the estimated quantity for ASU/AST and may only represent a portion of the geotextile quantity