

NOTES:

1. FOR NOTES SEE SHEET 1 OF 5.


2. FOR DETAILS SEE SHEET 5 OF 5.

CONSTRUCTION SEQUENCE SHORING 2 AND 3:

- 1. WITH SHORING 1 STILL IN PLACE AND PRIOR TO BACKFILLING BEHIND ABUTMENTS, PREDRILL SHAFT HOLE TO THE REQUIRED EMBEDMENT DEPTH SHOWN ON PLANS.
- 2. INSERT W 21×201 INTO PREDRILLED HOLES AND FILL WITH CONCRETE TO THE DEPTH SHOWN.
- 3. INSTALL STEEL LAGGING TO WITHIN 3'-O" OF FINISHED GROUND SURFACE. WELD LAGGING AS SHOWN IN THE STEEL LAGGING DETAIL.
- 4. INSTALL BENT CONNECTION PLATE AS SHOWN IN THE BENT CONNECTION PLATE DETAIL.
- 5. BACKFILL BEHIND SHORING IN 1'-0" MAXIMUM LIFTS. COMPACT SOIL BEHIND WALL PER CONTRACT DOCUMENTS. USE HAND COMPACTION NEAR SHORING. BACKFILL TO WITHIN 3'-0" OF FINISHED GROUND ELEVATION.
- 6. INSTALL TIMBER LAGGING AND PROCEED WITH BACKFILL/COMPACTION UNTIL FINISHED GRADE IS ATTAINED.
- 7. AFTER BACKFILL IS COMPLETED, EXCAVATE IN FRONT OF SHORING AS SHOWN ON SHEET 2 OF 5.

REMOVAL SEQUENCE SHORING 2 AND 3:


- 1. EXCAVATE 3'-0" AND REMOVE/CUT TIMBER LAGGING, UPPER PORTTION OF THE BENT CONNECTOR PLATE, W 21x201 TO 3'-0"BELOW FINISHED GROUND LINE.
- 2. BACKFILL EXCAVATED AREA TO FINISHED GROUND ELEVATION AND HAND COMPACT SOIL IN 1'-0" MAXIMUM LIFTS.





- LAGGING (TYP.)

FILL FACE



PLAN VIEW-SHORING 3 (FOR SHORING LOCATION, SEE SHEET 2 OF 5)

U-3308 PROJECT NO._ DURHAM COUNTY STATION: POT 24+09.63 -LALT-

POT 21+11.43 -NSN-

SHEET 4 OF 5

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

TEMPORARY SHORING

TV/Ralph Whitehead Associates, Inc. 900 W Trade Street, Suite 715 Charlotte, NC 28202 NC License No. F-0991

SEAL 19765

Paul Kelly Jr

REVISIONS SHEET NO. S3-43 DATE: DATE: NO. BY: BY: TOTAL SHEETS

_ DATE : ____6-14 TRL/TJT DRAWN BY : . _ DATE : 6-14 CHECKED BY : PEK

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED