DLB3370

COMPUTED BY: VWB DATE: 9/25/2015

CHECKED BY: JDL DATE: 2/24/2016

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

PROJECT NO.	SHEET NO.
B-5121 / B-5317	3D-6

Note: Invert Elevations indicated are for Bid Purposes only and shall not be used for project construction stakeout.
See "Standard Specifications For Roads and Structures, Section 300-5".

LIST OF PIPES, ENDWALLS, ETC. (FOR PIPES 48 INCHES & UNDER)

| LINE & STATION | OFFSET | STRUCTURE NUMBER FROM | STRUCTURE NUMBER TO | TOP ELEVATION FT. | INVERT ELEVATION FT. | INVERT ELEVATION FT. | MINIMUM REQUIRED SLOPE % | Side Drain Pipe (RCP, CSP, CAAP, HDPE, or PVC) SIZE 8 | 15 | 18 | 24 | 42 | DO NOT USE RCP | DO NOT USE CSP | DO NOT USE CAAP | DO NOT USE HDPE | DO NOT USE PVC | C. S. PIPE THICKNESS OR GAUGE .064 15 | .064 18 | DIP SEALED PIPE SYSTEM SEE SPECIAL PROVISIONS (CLASS 250) 16 | (CLASS 250) 18 | (CLASS 150) 24 | (CLASS 150) 36 | SEALED DRAINAGE STRUCTURE MASONRY CY | QUANTITY FOR SEALED DRAINAGE STRUCTURES NOTE: TOTAL LIN. FT. FOR PAY QUANTITY SHALL BE A + (1.3 X B) A 0' THRU 5' EACH | A 5' THRU 10' LIN. FT. | A 10' AND ABOVE LIN. FT. | B LIN. FT. | BOOTS FOR SEALED STRUCTURES | R. C. PIPE CLASS IV 15 | 18 | 24 | 30 | 36 | 42 | 48 | R. C. PIPE CLASS V 15 | 18 | 24 | 30 | 42" WELDED STEEL PIPE 0.625" THICK, GRADE B IN SOIL | 42" WELDED STEEL PIPE 0.625" THICK, GRADE B NOT IN SOIL | DRAINAGE STRUCTURE MASONRY CY | QUANTITIES FOR DRAINAGE STRUCTURES NOTE: TOTAL LIN. FT. FOR PAY QUANTITY SHALL BE A + (1.3 X B) A 0' THRU 5' EACH | A 5' THRU 10' LIN. FT. | A 10' AND ABOVE LIN. FT. | B LIN. FT. | C.B. STD. 840.01 OR STD. 840.02 | FRAME, GRATES, AND HOOD STD. 840.03 GRATE TYPE E | F | G | CONCRETE TRANSITIONAL SECTION D.I. STD. 852.04 OR STD. 852.06 | C.B. STD. 852.05 | OPEN THROAT C.B. STD. 840.04 OR STD. 840.05 | D.I. STD. 840.14 OR STD. 840.15 | D.I. FRAME AND GRATES STD. 840.16 | G.D.I. TYPE "B" STD. 840.18 OR STD. 840.27 | G.D.I. (W.S. SAG) FRAME W/ 2 GRATES STD. 840.22 | G.D.I. (N.S. SAG) FRAME W/ GRATE STD. 840.24 | G.D.I. (N.S. SAG) FRAME W/ 2 GRATES STD. 840.24 | G.D.I. (N.S. FLAT) FRAME W/ GRATE STD. 840.29 | G.D.I. (N.S. FLAT) FRAME W/ 2 GRATES STD. 840.29 | DRIVEWAY D.I. STD. 840.30 | FRAME W/ GRATE FOR DRIVEWAY STD. 840.30 | J.B. STD. 840.31 OR STD. 840.32 | T.B.J.B. STD. 840.34 | T.B.D.I. STD. 840.35 | M.H. STD. 840.51. STD. 840.52. OR STD. 840.53 | M.H. FRAME AND COVER STD. 840.54 | CONVERT EXIST C.B. TO J.B. W/ MH (SP. DETAIL) | CONVERT EXIST J.B. TO C.B. (SPECIAL DETAIL) | CONVERT EXIST J.B. TO SLAB TOP J.B. | ADJUST C.B. | ADJUST D.I. | ADJUST M.H. | 15" SIDE DRAIN PIPE ELBOW | 15" C.S. ELBOW | 18" C.S. ELBOW | C.B. STD 840D82 (SPECIAL DETAIL) | T.B. PRECAST M.H. STD. 840D52 (SPECIAL DETAIL) | T.B.D.I. STD. 840D35 (SPECIAL DETAIL) | BERM DITCH OUTLET STD. 850.10 (PER EACH) | FLOWABLE FILL CY | CONCRETE COLLARS CL. "B" STD. 840.72 CY | CONCRETE AND BRICK PIPE PLUG STD. 840.71 CY | PIPE REMOVAL LIN. FT. | REMARKS |
|---|---|---