This electronic collection of documents is provided for the convenience of the user and is Not a Certified Document -

The documents contained herein were originally issued and sealed by the individuals whose names and license numbers appear on each page, on the dates appearing with their signature on that page. This file or an individual page shall not be considered a certified document.



| | \bot $ $ \bot $ $ \Box \bigcirc |
|--|---|
| RETAINING WALL NO.SOIL NAIL RETAINING WALLS (SQUARE FEET)SOIL NAIL VERIFICATION TESTS | SOIL NAIL PROOF TESTS |
| 1 1,510 2 | 6 |
| 2 4,305 2 | 15 |
| 4 3,550 2 | 11 |
| TOTAL 9,365 SF 6 | 32 |

| PROJECT REFEREN | ICE NO. | SHEET NO. |
|---|--------------------------|--------------------|
| 34605.1.2(R-40 |)60) | VV-1 |
| GEOTECHNICAL ENGINEER VORTH CAROL SEAL 028893 H. STEAL | | ENGINEER |
| DocuSigned by: Michael Stephens 7/5/2016 | | |
| SIGNATURE DATE | SIGNAT | TURE DATE |
| DOCUMENT NOT UNLESS ALL SIGN | CONSIDEREI ATURES CON |) FINAL IPLETED |















NOTES:

FOR SOIL NAIL RETAINING WALLS, SEE SOIL NAIL RETAINING WALLS PROVISION. FOR SINGLE FACED PRECAST CONCRETE BARRIER, SEE ROADWAY PLANS AND SECTION 857 OF THE

STANDARD SPECIFICATIONS.

BEFORE BEGINNING SOIL NAIL WALL DESIGN FOR RETAINING WALL NOS.1,2,AND 4,SURVEY WALL LOCATION AND SUBMIT A REVISED WALL PROFILE VIEW (WALL ENVELOPE)FOR REVIEW. DO NOT START WALL DESIGN OR CONSTRUCTION UNTIL THE REVISED WALL ENVELOPE IS ACCEPTED.

DESIGN RETAINING WALL NOS. 1, 2, AND 4 FOR THE FOLLOWING: 1) H = DESIGN HEIGHT + EMBEDMENT 2) DESIGN LIFE = 100 YEARS 3) MINIMUM EMBEDMENT ELEVATION = 1 FT 4) IN-SITU ASSUMED MATERIAL PARAMETERS: UNIT WEIGHT, γ = 120 LB/CF FRICTION ANGLE, ϕ = 30 DEGREES COHESION, c = 0 LB/SF

DESIGN RETAINING WALL NO. 4 FOR A LIVE LOAD (TRAFFIC) SURCHARGE.

EXISTING OR FUTURE OBSTRUCTIONS SUCH AS FOUNDATIONS, GUARDRAIL, FENCE OR HANDRAIL POSTS, PAVEMENTS, PIPES, INLETS OR UTILITIES MAY INTERFERE WITH SOIL NAILS FOR RETAINING WALL NOS. 1, 2, AND 4.



| PROJECT REFERENCE | CE NO. | SHEET NO. |
|--|--------|-----------|
| 34605.1.2(R-406 | 50) | VV-4 |
| GEOTECHNICAL ENGINEER | | ENGINEER |
| Docusigned by: Michael H. Stephens C447682092314CC 5/13/2016 | | |
| SIGNATURE DATE | SIGNAT | URE DATE |
| DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED | | |

A FENCE OR HANDRAIL IS REQUIRED ON TOP OF RETAINING WALL NOS.1,2,AND 4. SEE ROADWAY PLANS FOR FENCE OR HANDRAIL ATTACHMENT DETAILS.

AN ASHLAR ARCHITECTURAL FINISH IS REQUIRED FOR THE CAST-IN-PLACE REINFORCED CONCRETE FACE FOR RETAINING WALL NOS. 1, 2, AND 4. SEE SOIL NAIL WALL SPECIAL PROVISION.

| ORTH | CAROLINA |
|-------|------------------|
| ENT O | F TRANSPORTATION |
| SION | OF HIGHWAYS |

GEOTECHNICAL ENGINEERING UNIT

RETAINING WALL NOS. 1, 2, AND 4 SOIL NAIL WALL

| REVISIONS | | | | | |
|-----------|----|------|-----|----|------|
| NO. | BY | DATE | NO. | BY | DATE |
| 1 | _ | _ | 3 | _ | _ |
| 2 | _ | _ | 4 | _ | _ |





| FRONT SLOPE WALL EMBEDMENT | | | |
|----------------------------|--------------------|----------------------------|--|
| SLOPE IN STRU(| FRONT OF CTURES | MINIMUM EMBEDMENT DEPTH | |
| | FOR WALLS | H/20 | |
| HURIZUNIAL | FOR ABUTMENTS | H/10 | |
| 3.0H:1.0V WALLS | | Н∕10 | |
| 2.5H:1.OV WALLS | | H/8.5 | |
| 2.0H:1.0V | WALLS | H/7 | |
| 1.5H:1.OV WALLS | | H/5 | |
| 1.25H:1.0V | WALLS | H/4 | |
| 1.0H:1.0V | WALLS | H/3 | |

NOTE: 1) MAINTAIN A MINIMUM BENCH WIDTH OF 4.0 IN FRONT OF THE WALL FOR ITS ENTIRE LENGTH, EXCEPT AT EXISTING CULVERT (SEE CROSS SECTIONS). 2) MINIMUM EMBEDMENT DEPTH OF 2 FT, UNLESS LARGER DEPTHS DICTATED BY THE ABOVE TABLE. 3) MAXIMUM SLOPE OF 1H:1V WILL BE MAINTAINED ON FRONT SLOPES FOR THE ENTIRE LENGTH OF THE WALL. 4) SUBMITT WITH THE WALL DESIGN INTERNAL, EXTERNAL, AND GLOBAL STABILITY ANALYSISES.

| ESTI | MATED WALL QUANTITY |
|------------------------|---------------------|
| RETAINING WALL NO.3 | ₩ 2,440 SQUARE FEET |

* WALL AREA IS MEASURED USING THE TOTAL HEIGHT "H"



















NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS

GEOTECHNICAL ENGINEERING UNIT

RETAINING WALL NO. 5 MSE RETAINING WALL

| REVISIONS | | | | | |
|-----------|----|------|-----|----|------|
| NO. | BY | DATE | NO. | BY | DATE |
| 1 | _ | _ | 3 | _ | |
| 2 | _ | _ | 4 | _ | |

NOTES: FOR MECHANICALLY STABILIZED EARTH (MSE) RETAINING WALLS, SEE MECHANICALLY STABILIZED EARTH RETAINING WALLS PROVISION. FOR STEEL BEAM GUARDRAIL, SEE ROADWAY PLANS AND SECTION 862 OF THE STANDARD SPECIFICATIONS. FOR SINGLE FACED PRECAST CONCRETE BARRIER, SEE ROADWAY PLANS AND SECTION 857 OF THE STANDARD SPECIFICATIONS. A FENCE OR HANDRAIL IS REQUIRED ON TOP OF RETAINING WALL NO. 3. SEE ROADWAY PLANS FOR FENCE OR HANDRAIL ATTACHMENT DETAILS. AT THE CONTRACTOR'S OPTION, USE AN MSE WALL SYSTEM WITH SEGMENTAL RETAINING WALL (SRW) UNITS THAT MEET ARTICLE 1040-4 OF THE STANDARD SPECIFICATIONS FOR RETAINING WALL NOS. 3 AND 5. USE AN MSE WALL SYSTEM WITH SEGMENTAL RETAINING WALL UNITS (SRW) UNITS THAT MEET ARTICLE 1040-4 OF THE STANDARD SPECIFICATIONS FOR RETAINING WALL NOS. 3 AND 5. WHEN USING AN MSE WALL SYSTEM WITH SRW UNITS FOR RETAINING WALL NOS. 3 AND 5, FREEZE-THAW DURABLE SRW UNITS THAT MEET ARTICLE 1040-4 OF THE STANDARD SPECIFICATIONS ARE REQUIRED. A SEPARATION GEOTEXTILE IS REQUIRED AT THE BACK AND SIDES OF THE REINFORCED ZONE FOR RETAINING WALL NO.3. A SEPARATION GEOTEXTILE IS REQUIRED AT THE BACK OF THE REINFORCED ZONE FOR RETAINING WALL NO.5. A DRAIN IS REQUIRED FOR RETAINING WALL NOS. 3 AND 5. BEFORE BEGINNING MSE WALL DESIGN FOR RETAINING WALL NOS. 3 AND 5, SURVEY WALL LOCATION AND SUBMIT A REVISED WALL PROFILE VIEW (WALL ENVELOPE)FOR REVIEW. DO NOT START WALL DESIGN OR CONSTRUCTION UNTIL THE REVISED WALL ENVELOPE IS ACCEPTED. DESIGN RETAINING WALL NOS. 3 AND 5 FOR THE FOLLOWING: 1) H = DESIGN HEIGHT + EMBEDMENT 2) DESIGN LIFE = 100 YEARS 3) MAXIMUM FACTORED VERTICAL PRESSURE ON FOUNDATION MATERIAL = 4.500 LB/SF 4) MINIMUM REINFORCEMENT LENGTH (L) = WALL NO. 3 = 1.0H OR 6 FT, WHICHEVER IS LONGER WALL NO. 5 = 1.5H OR 6 FT, WHICHEVER IS LONGER 5) MINIMUM EMBEDMENT ELEVATION = SEE EMBEDMENT TABLE AND DRAWINGS 6) REINFORCED ZONE AGGREGATE PARAMETERS: AGGREGATE TYPE* UNIT WEIGHT FRICTION ANGLE COHESION (γ) (() (C) DEGREES LB/SF LB/CF COARSE 110 38 0 *SEE MSE RETAINING WALLS PROVISION FOR COARSE AND FINE AGGREGATE MATERIAL REQUIREMENTS. 7) IN-SITU ASSUMED MATERIAL PARAMETERS: FRICTION ANGLE UNIT WEIGHT COHESION MATERIAL TYPE (γ) LB/CF (φ) (C) DEGREES LB/SF 120 30 BACKFILL 0 120 30 0 FOUNDATION DESIGN RETAINING WALL NOS. 3 AND 5 FOR A LIVE LOAD (TRAFFIC) SURCHARGE. EXISTING OR FUTURE OBSTRUCTIONS SUCH AS FOUNDATIONS, GUARDRAIL, FENCE OR HANDRAIL POSTS, PAVEMENTS, PIPES, INLETS OR UTILITIES MAY INTERFERE WITH REINFORCEMENT FOR RETAINING WALL NOS.3 AND 5. DO NOT PLACE LEVELING PAD CONCRETE, AGGREGATE OR REINFORCEMENT FOR RETAINING WALL NOS. 3 AND 5 UNTIL EXCAVATION DIMENSIONS AND FOUNDATION MATERIAL ARE APPROVED. "TEMPORARY SHORING" IS REQUIRED FOR RETAINING WALL NO. 3 IN ACCORDANCE WITH THE TEMPORARY SHORING PROVISION. SEE ROADWAY, STRUCTURE or TRAFFIC CONTROL PLANS. PREPARED BY: MHS DATE: 5/12/16

DATE: 5/12/16

REVIEWED BY: SCC











DESIGN DATA:

+

+

| SPECIFICATIONS | A.A.S.H.T.O. (CURRENT) |
|---|------------------------|
| LIVE LOAD | SEE PLANS |
| IMPACT ALLOWANCE | SEE A.A.S.H.T.O. |
| STRESS IN EXTREME FIBER OF | |
| STRUCTURAL STEEL - AASHTO M270 GRADE 36 - | 20,000 LBS.PER SQ.IN. |
| - AASHTO M270 GRADE 50W - | 27,000 LBS.PER SQ.IN. |
| - AASHTO M270 GRADE 50 - | 27,000 LBS.PER SO.IN. |
| REINFORCING STEEL IN TENSION | |
| GRADE 60 | 24,000 LBS.PER SQ.IN. |
| CONCRETE IN COMPRESSION | 1,200 LBS.PER SQ.IN. |
| CONCRETE IN SHEAR | SEE A.A.S.H.T.O. |
| STRUCTURAL TIMBER - TREATED OR | |
| UNTREATED - EXTREME FIBER STRESS | 1,800 LBS.PER SQ.IN. |
| COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER | 375 LBS.PER SQ.IN. |
| EQUIVALENT FLUID PRESSURE OF EARTH | 30 LBS.PER CU.FT. |

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2012 ``STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

(MINIMUM)

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1-1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4"FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

STANDARD NOTES

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE. ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.

IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER. DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE

AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.

WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8" Ø SHEAR STUDS FOR THE $\frac{3}{4}$ " Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8" Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4" Ø STUDS BASED ON THE RATIO OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-O".

EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2"OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.

WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES.ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16 INCH OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB. METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.

ENGLISH JANUARY, 1990

STD. NO. SN