HYDRAULIC DATA

DESIGN DISCHARGE = 390 CFS FREQUENCY OF DESIGN FLOOD = 50 YRS. DESIGN HIGH WATER ELEVATION = 771.70 DRAINAGE AREA = 0.38 SQ. MI BASE DISCHARGE (Q100) = 410 CFS

= 771.88

BASE HIGH WATER ELEVATION

TO I-85

50'-0"

25'-0", 32'-0"

PROFILE ALONG & CULVERT #2

60'-0"

45'-0"

65'-0"

WOODS

-RPAY8--

/ ₍₂)

OVERTOPPING FLOOD DATA

OVERTOPPING DISCHARGE = >470+ CFS FREQUENCY OF OVERTOPPING FLOOD = >500+ YRS. OVERTOPPING FLOOD ELEVATION = 777.83

GRADE DATA

GRADE POINT ELEVATION @ STA.1+26.46 -SPBY8-= 778.54' BED ELEVATION @ STA. 1+26.46 -SPBY8-= 765.14' ROADWAY FILL SLOPES = 4:1

TOTAL STRUCTURE QUANTITIES		
CLASS A CONCRETE		
PHASE C2-P1	152.0	C.Y.
PHASE C2-P2	132.6	C.Y.
PHASE C1&2-P2	82.2	C.Y.
TOTAL	366.8	C.Y.
REINFORCING STEEL		
PHASE C2-P1 —	23,748	LBS.
PHASE C2-P2	00 504	
PHASE C1&2-P2	12,283	LBS.
TOTAL -	56,552	LBS.
FOUNDATION COND. MATERIAL		
PHASE C2-P1	174	TONS
PHASE C2-P2	152	TONS
PHASE C1&2-P2	82	TONS
TOTAL	408	TONS
CULVERT EXCAVATION	(TOTAL) L	.UMP SUM

NOTES:

ASSUMED LIVE LOAD ------ HL-93 OR ALTERNATE LOADING.

DESIGN FILL MAXIMUM ----- 6.99 FT.

FOR OTHER DESIGN DATA AND NOTES SEE STANDARD NOTE SHEET.

A 3 FOOT STRIP OF FILTER FABRIC SHALL BE ATTACHED TO THE FILL FACE OF THE WING COVERING THE ENTIRE LENGTH OF THE EXPANSION JOINT.

3"Ø WEEP HOLES INDICATED TO BE IN ACCORDANCE WITH THE SPECIFICATIONS.

CONCRETE IN CULVERTS TO BE POURED IN THE FOLLOWING ORDER:

1. WING FOOTINGS AND FLOOR SLAB INCLUDING 4"OF ALL VERTICAL WALLS.

2. THE REMAINING PORTIONS OF THE WALLS AND WINGS FULL HEIGHT FOLLOWED BY ROOF SLAB AND HEADWALLS.

THE RESIDENT ENGINEER SHALL CHECK THE LENGTH OF CULVERT BEFORE STAKING IT OUT TO MAKE CERTAIN THAT IT WILL PROPERLY TAKE CARE OF THE FILL.

AT THE CONTRACTORS OPTION, HE MAY SPLICE THE VERTICAL REINFORCING STEEL IN THE INTERIOR FACE OF EXTERIOR WALL ABOVE LOWER WALL CONSTRUCTION JOINT. THE SPLICE LENGTH SHALL BE AS PROVIDED IN THE SPLICE LENGTH CHART SHOWN ON THE PLANS. EXTRA WEIGHT OF STEEL DUE TO THE SPLICES SHALL BE PAID FOR BY THE CONTRACTOR.

DIMENSIONS FOR WING LAYOUT AS WELL AS ADDITIONAL REINFORCING STEEL EMBEDDED IN BARREL ARE SHOWN ON WING SHEET.

TRANSVERSE CONSTRUCTION JOINTS SHALL BE USED IN THE BARREL, SPACED TO LIMIT THE POURS TO A MAXIMUM OF 70 FT.LOCATION OF JOINTS SHALL BE SUBJECT TO APPROVAL OF THE ENGINEER.

NO PRECAST REINFORCED BOX CULVERT OPTION WILL BE ALLOWED.

THE CONTRACTOR SHALL PROVIDE INDEPENDENT ASSURANCE SAMPLES OF REINFORCING STEEL AS FOLLOWS: FOR PROJECTS REQUIRING UP TO 400 TONS OF REINFORCING STEEL, ONE 30 INCH SAMPLE OF EACH SIZE BAR USED, AND FOR PROJECTS REQUIRING OVER 400 TONS OF REINFORCING STEEL, TWO 30 INCH SAMPLES OF EACH SIZE BAR USED. THE BARS FROM WHICH THE SAMPLES ARE TAKEN MUST THEN BE SPLICED WITH REPLACEMENT BARS OF THE SIZE AND LENGTH OF THE SAMPLE, PLUS A MINIMUM LAP SPLICE OF THIRTY BAR DIAMETERS. PAYMENT FOR THE SAMPLES OF REINFORCING STEEL SHALL BE CONSIDERED INCIDENTAL TO VARIOUS PAY ITEMS.

ALL PIPES THROUGH THE SIDEWALL OF THE CULVERT SHALL BE LOCATED BY THE ENGINEER. THE REINFORCING STEEL SHALL BE FIELD BENT AS NECESSARY TO CLEAR

FOR CULVERT DIVERSION DETAILS & PAY ITEM, SEE EROSION CONTROL PLANS.

FOR CONSTRUCTION SEQUENCE, SEE EROSION CONTROL PLANS.

FOR GROUT FOR STRUCTURES. SEE SPECIAL PROVISIONS.

FOR MAINTENANCE OF TRAFFIC. SEE TRAFFIC CONTROL PLANS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

PROJECT NO. U-2524D GUILFORD COUNTY STATION: 1+26.46 -SPBY8-

SHEET 1 OF 7

DEPARTMENT OF TRANSPORTATION

CULVERT #2 SINGLE 10' X 7' RCBC C2-P1, C2-P2 & C1&2-P2 40°-31'-08" SKEW

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Ting Fang 8/16/2016

SHEET NO. **REVISIONS** C-7 DATE:

16-AUG-2016 14:49
K:\TIPProjects-U\U2524D\Structures\Plans\culvert\u2524d_sd_cul2.dgn

35'-0"

BM #18: RR SPIKE IN 22"OAK, STA. 10+00.00 -Y8-, N 18° 44' 24.6" W, DIST. 575.94', EL. 808.40'

. ک-8۲<u>"</u>"

LOCATION SKETCH

- PROPOSED SINGLE

-SPAY8-

10' X 7' RCBC

-SPBY8

_STA.1+26.46 -SPBY8-

& & & .

40°-31′-08″

TĂNGĂNT A

RIP RAP CLASS II

(ROADWAY PAY ITEM)

\WOODS {

_{ପ୍ରବର୍ଷ} ବ୍ରବ୍ଦ ବ

TO I-85/40

(2)

WOODS

ପ୍ରପ୍ର 서

क्षे छे

WOODS

FOR UTILITY INFORMATION, SEE UTILITY PLANS AND SPECIAL PROVISIONS.

STA.1+26.46 -SPBY8-

40'-0"

15'-0"

A. SORSENGINH

T. H. FANG DESIGN ENGINEER OF RECORD: ___ A. SORSENGINH DATE : 5/26/16

30'-0"

70'-0"

15'-0"

CUL #2