



PAVEMENT SCHEDULE	
C1	PROP. APPROX. 1½" DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ.YD.
C2	PROP. APPROX. 1½" DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ.YD.
C3	PROP. APPROX. 1¼" DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF9.5A, AT AN AVERAGE RATE OF 137.5 LBS. PER SQ.YD.
C4	PROP. APPROX. 2" DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 224 LBS. PER SQ.YD.
C5	PROP. APPROX. 1½" DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF9.5A, AT AN AVERAGE RATE OF 165 LBS. PER SQ.YD.
C6	PROP. APPROX. ¾" DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S4.75A, AT AN AVERAGE RATE OF 85 LBS. PER SQ.YD.
D1	PROP. APPROX. 4" DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ.YD.
E1	PROP. APPROX. 5½" DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 627 LBS. PER SQ.YD.
E3	PROP. APPROX. 5½" DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 627 LBS. PER SQ.YD.
M	MILLED RUMBLE STRIP (16")
R1	EXISTING CONCRETE BRIDGE RAIL
R2	EXISTING CONCRETE 2'-6" CURB & GUTTER
R3	EXISTING CONCRETE VALLEY CURB
R4	EXISTING ROLLED ASPHALT CURB
T1	AGGREGATE SHOULDER BORROW (ASB)
T2	EARTH MATERIAL (SHOULDER RECONSTRUCTION)
U	EXISTING PAVEMENT
V1	MILLING ASPHALT PAVEMENT, 1½" DEPTH
V2	MILLING ASPHALT PAVEMENT, 1¼" DEPTH
V3	MILLING ASPHALT PAVEMENT, 0" - 1¼" DEPTH
V4	MILLING ASPHALT PAVEMENT, 2" DEPTH
V5	MILLING ASPHALT PAVEMENT, ¾" DEPTH
V6	MILLING ASPHALT PAVEMENT, 0" - ¾" DEPTH

PAVEMENT EDGE SLOPES ARE 1:1, EXCEPT FINAL SURFACE COURSE. SEE SHOULDER WEDGE DETAIL.

REVISIONS

07-OCT-2016 09:20 S:\Contracts\2016\Resurfacing Projects\Division 3\Brunswick (October 2016 Letting)\2017CPT.03.06.10101.Etc\_TYP\_REV\_2.dgn  
 8/17/99