

NOTES

ASSUMED LIVE LOAD = HL 93 OR ALTERNATE LOADING.

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS.

THIS BRIDGE IS LOCATED IN SEISMIC ZONE 1.

FOR OTHER DESIGN DATA AND GENERAL NOTES. SEE SHEET SN.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK & FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

INASMUCH AS THE PAINT SYSTEM ON THE EXISTING STRUCTURAL STEEL CONTAINS LEAD, THE CONTRACTOR'S ATTENTION IS DIRECTED TO ARTICLE 107-1 OF THE STANDARD SPECIFICATIONS. ANY COSTS RESULTING FROM COMPLIANCE WITH APPLICABLE STATE OR FEDERAL REGULATIONS PERTAINING TO HANDLING OF MATERIALS CONTAINING LEAD BASED PAINT SHALL BE INCLUDED IN THE BID PRICE FOR "REMOVAL OF EXISTING STRUCTURE AT STATION 13+56.00-L-".

THE MATERIAL SHOWN IN THE CROSS-HATCHED AREA ON SHEET S-1 SHALL BE EXCAVATED FOR A DISTANCE OF 20 FT. EACH SIDE OF CENTERLINE ROADWAY AS DIRECTED BY THE ENGINEER. THIS WORK WILL BE PAID FOR AT THE CONTRACT LUMP SUM PRICE FOR UNCLASSIFIED STRUCTURE EXCAVATION.

THE EXISTING STRUCTURE CONSISTING OF 1 SPAN @ 44'-6", WITH A TIMBER DECK AND A CLEAR ROADWAY WIDTH OF 19'-1" WITH AN 1" ASPHALT WEARING SURFACE ON STEEL I-BEAMS, ON TIMBER CAPS AND PILES, ONE WHICH IS ENCASED IN CONCRETE AND TIMBER BULKHEADS, LOCATED AT THE PROPOSED STRUCTURE, SHALL BE REMOVED. THE EXISTING BRIDGE IS PRESENTLY POSTED BELOW THE LEGAL LOAD LIMIT.

THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST INFORMATION AVAILABLE. SINCE THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR, THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

REMOVAL OF THE EXISTING BRIDGE SHALL BE PERFORMED SO AS NOT TO ALLOW DEBRIS TO FALL INTO THE WATER. THE CONTRACTOR SHALL REMOVE THE BRIDGE AND SUBMIT PLANS FOR DEMOLITION IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS THE EXISTING END BENTS SHALL BE REMOVED DOWN TO EL.514.30 WITH THE REMAINING PORTION LEFT IN PLACE FOR BANK STABILIZATION.

THIS STRUCTURE HAS BEEN DESIGNED IN ACCORDANCE WITH HEC 18, "EVALUATING SCOUR AT BRIDGES", MAY, 2001.

FOR EROSION CONTROL MEASURES, SEE EROSION CONTROL PLANS.

ASPHALT WEARING SURFACE IS INCLUDED IN ROADWAY QUANTITY ON ROADWAY PLANS.

FOR ASBESTOS ASSESSMENT FOR BRIDGE DEMOLITION AND RENOVATION ACTIVITIES, SEE SPECIAL PROVISIONS.

HYDRAULIC DATA

DESIGN DISCHARGE = 1,900 CFS FREQUENCY OF DESIGN FLOOD = 25 YR.

DESIGN HIGH WATER ELEVATION = 516.80 = 8.1 SQ. MI.

BASE DISCHARGE (Q 100) = 2,801 CFS = 518.15

OVERTOPPING FLOOD DATA

OVERTOPPING DISCHARGE =6,000 CFS FREQUENCY OF OVERTOPPING FLOOD =500+ YR. OVERTOPPING FLOOD ELEVATION =520.90

	TOTAL BILL OF MATERIAL															
	REMOVAL OF EXISTING STRUCTURE	PDA TESTING	UNCLASSIFIED STRUCTURE EXCAVATION	CLASS A CONCRETE	BRIDGE APPROACH SLABS	REINFORCING STEEL	HP 12X53 STEEL PILES		STEEL PILE POINTS	VERTICAL CONCRETE BARRIER RAIL	RIP RAP CLASS II	GEOTEXTILE FOR DRAINAGE	ELASTOMERIC BEARINGS	PRI C	-O"X 2'-9" ESTRESSED :ONCRETE DX BEAMS	ASBESTOS ASSESSMENT
	LUMP SUM	EACH	LUMP SUM	CU. YDS.	LUMP SUM	LBS.	NO.	LIN.FT.	EACH	LIN.FT.	TONS	SQ. YDS.	LUMP SUM	NO.	LIN.FT.	LUMP SUM
SUPERSTRUCTURE										150.00				10	750.00	
END BENT NO.1				23.8		3,342	5	125	5		30	45				
END BENT NO.2				23.8		3,342	5	100	5		30	45				
TOTAL	LUMP SUM	1	LUMP SUM	47.6	LUMP SUM	6,684	10	225	10	150.00	60	90	LUMP SUM	10	750.00	LUMP SUM

PROJECT NO. B-5546

RANDOLPH COUNTY

STATION: 13+56.00-L-

SHEET 3 OF 3

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION

RALEIGH

GENERAL DRAWING

FOR BRIDGE OVER MOUNT PLEASANT CREEK ON SR 2481 BETWEEN SR 2550 AND SR 2442

SHEET NO.

S-25

TOTAL SHEETS 38

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED 2

DRAWN BY: D.A. DAVENPORT DATE: 10/08/14
CHECKED BY: J.K. BOWLES DATE: 4/25/16