

TEMPORARY SHORING NOTES

Shoring Location No. 1

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

TEMPORARY SHORING IS REQUIRED FOR THE CULVERT INSTALLATION FROM STATION 40+04 -L-, 8 FT (LT), TO STATION 40+85.5 -L-, 8 FT (LT).

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION 40+04 -L-, 8 FT (LT), TO STATION 40+85.5 -L-, 8 FT (LT), FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

UNIT WEIGHT (γ) = 120 LB/CF
 FRICTION ANGLE (ϕ) = 29 DEGREES
 COHESION (c) = 0 LB/SF
 GROUNDWATER ELEVATION = 700 FT

LIMITED SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM STATION 40+04 -L-, 8 FT (LT), TO STATION 40+85.5 -L-, 8 FT (LT). THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

IT MAY BE PREFERRED TO USE A TEMPORARY SOIL NAIL WALL FOR TEMPORARY SHORING FROM STATION 40+04 -L-, 8 FT (LT), TO STATION 40+85.5 -L-, 8 FT (LT). FOR TEMPORARY SOIL NAIL WALLS, SEE TEMPORARY SOIL NAIL WALLS PROVISION.

Shoring Location No. 2

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

TEMPORARY SHORING IS REQUIRED FOR THE CULVERT INSTALLATION FROM STATION 40+12 -L-, 9.5 FT (RT), TO STATION 40+85 -L-, 9.5 FT (RT).

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION 40+12 -L-, 9.5 FT (RT), TO STATION 40+85 -L-, 9.5 FT (RT), FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

UNIT WEIGHT (γ) = 120 LB/CF
 FRICTION ANGLE (ϕ) = 29 DEGREES
 COHESION (c) = 0 LB/SF
 GROUNDWATER ELEVATION = 700 FT

LIMITED SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM STATION 40+12 -L-, 9.5 FT (RT), TO STATION 40+85 -L-, 9.5 FT (RT). THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

AT THE CONTRACTOR'S OPTION, USE A STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION 40+12 -L-, 9.5 FT (RT), TO STATION 40+85 -L-, 9.5 FT (RT). SEE STANDARD DETAIL NO. 1801.02 FOR STANDARD TEMPORARY WALLS.

Shoring Location No. 3

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

TEMPORARY SHORING IS REQUIRED FOR THE CULVERT INSTALLATION FROM STATION 116+59 -L-, 19 FT (LT), TO STATION 117+65 -L-, 14 FT (LT).

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION 116+59 -L-, 19 FT (LT), TO STATION 117+65 -L-, 14 FT (LT), FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

UNIT WEIGHT (γ) = 120 LB/CF
 FRICTION ANGLE (ϕ) = 29 DEGREES
 COHESION (c) = 0 LB/SF
 GROUNDWATER ELEVATION = 690 FT

LIMITED SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM STATION 116+59 -L-, 19 FT (LT), TO STATION 117+65 -L-, 14 FT (LT). THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

IT MAY BE PREFERRED TO USE A TEMPORARY SOIL NAIL WALL FOR TEMPORARY SHORING FROM STATION 116+59 -L-, 19 FT (LT), TO STATION 117+65 -L-, 14 FT (LT). FOR TEMPORARY SOIL NAIL WALLS, SEE TEMPORARY SOIL NAIL WALLS PROVISION.

Shoring Location No. 4

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

TEMPORARY SHORING IS REQUIRED FOR THE CULVERT INSTALLATION FROM STATION 116+85 -L-, 10 FT (RT), TO STATION 118+19 -L-, 19 FT (RT).

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.



DESIGN TEMPORARY SHORING FROM STATION 116+85 -L-, 10 FT (RT), TO STATION 118+19 -L-, 19 FT (RT), FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

UNIT WEIGHT (γ) = 120 LB/CF
 FRICTION ANGLE (ϕ) = 29 DEGREES
 COHESION (c) = 0 LB/SF
 GROUNDWATER ELEVATION = 700 FT

LIMITED SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM STATION 116+85 -L-, 10 FT (RT), TO STATION 118+19 -L-, 19 FT (RT). THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

AT THE CONTRACTOR'S OPTION, USE A STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION 116+85 -L-, 10 FT (RT), TO STATION 118+19 -L-, 19 FT (RT). SEE STANDARD DETAIL NO. 1801.02 FOR STANDARD TEMPORARY WALLS.

8/17/2016 P:\TIP\Projects-U\3440\Traffic\TrafficControl\TCP\TMP-2.dgn User:rmgdrrett

| | | | |
|--|---|---|---|
| Documented by: APPROVED: <i>Michael Stephens</i> <small>81963158307046C</small> DATE: 8/17/2016 |  |  | <h2 style="margin: 0;">TEMPORARY SHORING NOTES</h2> |
| DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED | | | |