NC LICENSE #P-0189

B - 5398**ROADWAY DESIGN ENGINEER** 16689 Brian A Wiles 10/24/201

SHEET NO.

DOCUMENT NOT CONSIDERED FINAL **UNLESS ALL SIGNATURES COMPLETED**

PROJECT REFERENCE NO.

EFF. 01-17-2012 REV. 02-29-2016

2012 ROADWAY ENGLISH STANDARD DRAWINGS

862.02 Guardrail Installation 876.01 Rip Rap in Channels

876.02 Guide for Rip Rap at Pipe Outlets

TITLE

STD.NO.

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch -N. C. Department of Transportation - Raleigh, N. C., Dated January, 2012 are applicable to this project and by reference hereby are considered a part of these plans:

DIVISION 2 - EARTHWORK 200.02 Method of Clearing - Method II 225.02 Guide for Grading Subgrade - Secondary and Local 225.04 Method of Obtaining Superelevation - Two Lane Pavement DIVISION 3 - PIPE CULVERTS 300.01 Method of Pipe Installation DIVISION 4 - MAJOR STRUCTURES 422.11 Bridge Approach Fills - Sub Regional Tier DIVISION 5 - SUBGRADE, BASES AND SHOULDERS 560.01 Method of Shoulder Construction - High Side of Superelevated Curve - Method I DIVISION 6 - ASPHALT BASES AND PAVEMENTS 654.01 Pavement Repairs DIVISION 8 - INCIDENTALS 806.01 Concrete Right-of-Way Marker 806.02 Granite Right-of-Way Marker 815.02 Subsurface Drain 838.33 Reinforced Concrete Endwall - for Single 66" Pipe 90 Skew Notes for Reinforced Concrete Endwall - Std. Dwg 838.21 thru 838.40 Reinforced Brick Endwall - for Single 66" Pipe 90 Skew 838.75 Notes for Reinforced Brick Endwall - Std. Dwg 838.51 thru 838.70 Precast Endwalls – 12" thru 72" Pipe 90 Skew Concrete Base Pad for Drainage Structures Concrete Grated Drop Inlet Type 'B' - 12" thru 36" Pipe Frames and Narrow Slot Sag Grates Anchorage for Frames - Brick or Concrete or Precast Brick Grated Drop Inlet Type 'B' - 12" thru 36" Pipe 840.29 Frames and Narrow Slot Flat Grates 840.35 Traffic Bearing Grated Drop Inlet – for Cast Iron Double Frame and Grates 840.45 Precast Drainage Structure 840.46 Traffic Bearing Precast Drainage Structure 840.66 Drainage Structure Steps 846.01 Concrete Curb, Gutter and Curb & Gutter 846.04 Drop Inlet Installation in Shoulder Berm Gutter 862.01 Guardrail Placement

SHEET NUMBER SHEET TITLE SHEET

INDEX OF SHEETS, GENERAL NOTES AND STANDARD DRAWINGS 1 A

CONVENTIONAL SYMBOLS 1C-1 THRU 1C-2 SURVEY CONTROL SHEETS

2A - 1PAVEMENT SCHEDULE, TYPICAL SECTIONS AND WEDGING DETAILS

2C-1 DETAIL OF STRUCTURE ANCHOR UNIT, TYPE III

EROSION CONTROL PLANS

INDEX OF SHEETS

REINFORCED CONCRETE ENDWALL DETAIL 2C-2

3B-1 SUMMARIES OF EARTHWORK, ASPHALT PAVEMENT REMOVAL, SHOULDER BERM GUTTER, EXPRESSWAY GUTTER AND GUARDRAIL

LIST OF PIPES, ENDWALLS, ETC. (for PIPES 48" & UNDER) 3D-1 LIST OF PIPE, ENDWALLS, ETC. (for PIPES 54" & OVER)

GEOTECHNICAL SUMMARIES 3G-1

PLAN SHEET PROFILE SHEET

TMP-1 THRU TMP-4 TRAFFIC MANAGEMENT PLANS PMP-1PAVEMENT MARKING PLANS

SIGN-1 THRU SIGN-2 SIGNING PLANS

EC-1 THRU EC-6

X-1A

UO-1 THRU UO-2 UTILITIES BY OTHERS PLANS CROSS-SECTION SUMMARY SHEET

X-1 THRU X-19 CROSS-SECTIONS S-1 THRU S-34 STRUCTURE PLANS

2012 SPECIFICATIONS GENERAL NOTES:

EFFECTIVE: 01-17-2012 REVISED: 10-31-2014

GRADE LINE: GRADING AND SURFACING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. GRADE LINES MAY BE ADJUSTED AT THEIR BEGINNING AND ENDING AND AT STRUCTURES AS DIRECTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

SUBSURFACE DRAINS:

SUBSURFACE DRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 815.02 AT LOCATIONS DIRECTED BY THE ENGINEER.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC WILL BE PAID FOR AS "EXTRA WORK" IN ACCORDANCE WITH SECTION 104-7.

SUBSURFACE PLANS:

NO SUBSURFACE PLANS ARE AVAILABLE ON THIS PROJECT. THE CONTRACTOR SHOULD MAKE HIS OWN INVESTIGATION AS TO THE SUBSURFACE CONDITIONS.

END BENTS:

THE ENGINEER SHALL CHECK THE STRUCTURE END BENT PLANS, DETAILS, AND CROSS-SECTION PRIOR TO SETTING OF THE SLOPE STAKES FOR THE EMBANKMENT OR EXCAVATION APPROACHING A BRIDGE.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE Rutherford EMC - Power, CenturyLink - Telephone, Charter Communications - CATV, Burke County General Services - Water and Burke County General Services - Sewer

ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS, EXCEPT AS SHOWN ON THE PLANS.

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY CONTRACT.

ROCK:

ROCK MAY BE ENCOUNTERED ON THE PROJECT. BLASTING MAY BE REQUIRED FOR EXCAVATION ON THE PROJECT. SEE SECTION 220 OF THE STANDARD SPECIFICATIONS AND IF APPLICABLE, ROCK BLASTING PROVISION.