


LOGICAL I/O PROCESSOR PROGRAMMING DETAIL FOR INDICATOR LAMP CONTROL

- (program controller as shown below)
- FROM MAIN MENU PRESS '2' (PHASE CONTROL), THEN '1' (PHASE CONTROL FUNCTIONS). SCROLL TO THE BOTTOM OF THE MENU AND ENABLE ACT LOGIC COMMANDS 1 AND 2.
 - FROM MAIN MENU PRESS '6' (OUTPUTS), THEN '3' (LOGICAL I/O PROCESSOR).




OUTPUT REFERENCE SCHEDULE
USE TO INTERPRET LOGIC PROCESSOR

INPUT 14 = Preempt 2
OUTPUT 34 = Phase 6 PED Yellow

EV Preemption Control Box Wiring Detail


(wire as shown below)



NOTES


- Relay K1 is shown in the energized (Preempt not active) normal operation state.
- Relay 'K1' is an enclosed DPDT general purpose relay with a 120VAC coil, 10A contacts, and octal-style plug.
- Relay SSR1 is a SPST (normally open) Solid State Relay with AC input and AC (25 amp) output.
- AC Isolator Card shall activate preemption upon removal of AC+ from the input (as shown above). To accomplish this, set invert dip switch on AC Isolator Card.
- IMPORTANT!!** Terminal TB9-12 (on input panel) shall be connected to AC neutral (jumper may have to be added).

FRONT VIEW



PREEMPT 2 AC ISOLATOR (MODEL 252) OUTPUT PROGRAMMING DETAIL

(set DIP switches as shown below)



NOTE: IF ANOTHER MANUFACTURER TYPE OF AC ISOLATOR IS USED, OUTPUT PROGRAMMING IS LIKELY NOT TO EQUATE TO THAT SHOWN ABOVE.

EMERGENCY VEHICLE PREEMPTION PROGRAMMING DETAIL

(program controller as shown below)

From Main Menu press 'A' (Preemption), then '1' (Standard Preemptions). Press 'NEXT' to advance to Preemption #2.


PREEMPTION #2	INTERVAL/TIMING	SETTINGS (NEXT:1-10)	CLEAR/DWELL PHASES
1	255 0.0 0.0		X
2	0 0.0 0.0		
3	0 0.0 0.0		
4	0 0.0 0.0		
5	1 0.0 0.0	X X	

EXIT CALLS	OPTIONS
PRIORITY (Y/N TO SELECT)MED
DELAY TIMER (0-255 SEC)*
MIN GREEN BEFORE PRE (0= DEFAULT)	...1
PED CLEAR BEFORE PRE (0= DEFAULT)	...12
YELLOW CLEAR BEFORE PRE (0= DEFAULT)	...0.0
RED CLEAR BEFORE PRE (0= DEFAULT)	...0.0
DWELL MIN TIMER (0-255 SEC)*
DWELL MAX TIMER (0=OFF,1-255MIN)	...0
DWELL HOLD-OVER TIMER (0-255)0
LATCH CALL?Y
LINK TO NEXT PREEMPT?N
ENABLE BACKUP PROTECTION?N
HOLD CLEAR 1 PHASES DURING DELAY?	...N
FAST GREEN FLASH DWELL PHASES?N
PED CLEARANCE THROUGH YELLOW?N
INHIBIT OVERLAP GREEN EXTENSION?	...N
SERVICE DURING SOFTWARE FLASH?N
REST IN RED DURING DWELL INTERVAL?	..N
FLASH DWELL INTERVAL?N
ALLOW PEDS IN DWELL INTERVAL?N
RE-TIME DWELL INTERVAL?Y
OVERLAPS:ABCDEFGHIJKLMNPO
DWELL INT FLASH YELLOW	
OMIT OVERLAPS:	

* Denotes timing to be determined in field.

LOAD RESISTOR INSTALLATION DETAIL

(install resistor as shown below)



Electrical Detail - Sheet 2 of 2

Electrical and Programming Details for: **US 25 (Hendersonville Road) at NC 146 (Long Shoals Road) / SR 3181 (Miller Road)**

Division 13 Buncombe County Asheville

PLAN DATE: November 2016 REVIEWED BY:

PREPARED BY: James Peterson REVIEWED BY:

REVISIONS: INIT. DATE

750 N. Greenfield Pkwy, Garner, NC 27529

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 13-0284
DESIGNED: January 2016
SEALED: 11-07-16
REVISED: N/A

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SEAL: KEITH M. MIMS, ENGINEER, 036880

DocuSigned by: Keith M. Mims 11/9/2016 2:07:58 PM

SIG. INVENTORY NO. 13-0284

09-1004-2016 13-25
S:\IT\SS\13-0284\13-0284_Sig\13-0284_Sig.dwg
11/9/2016 2:07:58 PM
J Peterson