


PHASING DIAGRAM




**PHASING DIAGRAM DETECTION LEGEND**

- ←●→ DETECTED MOVEMENT
- ←○→ UNDETECTED MOVEMENT (OVERLAP)
- ←---→ UNSIGNALIZED MOVEMENT
- ←- - -> PEDESTRIAN MOVEMENT

SIGNAL FACE	PHASE		
	02+6	04+8	FLASH
21,22	G	R	Y
41,42	R	G	R
61,62	G	R	Y
81,82	R	G	R
P21,P22	W	DW	DRK
P41,P42	DW	W	DRK
P61,P62	W	DW	DRK
P81,P82	DW	W	DRK

W - Walk  
DW - Don't Walk  
DRK - Dark

SIGNAL FACE I.D.




LOOP	INDUCTIVE LOOPS			DETECTOR PROGRAMMING					SYSTEM LOOP	NEW CARD		
	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTENSION	FULL TIME DELAY			STRETCH TIME	DELAY TIME
S1	6x6	+125	3	-	-	-	-	-	-	-	Y	Y
S2	6x6	+110	3	-	-	-	-	-	-	-	Y	Y

2 Phase Pre-Timed (Asheville Signal System)

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated January 2012 and "Standard Specifications for Roads and Structures" dated January 2012.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Set all detector units to presence mode.
- In the event of loop replacement, refer to the current ITS and Signals Design Manual and submit a Plan of Record to the Signal Design Section.
- Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
- Pavement markings are existing.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.
- Locate new cabinet on existing foundation.
- Program controller to allow an Advance Walk movement before serving the vehicle phase.
- Program pedestrian heads to countdown the flashing "Don't Walk" time only.
- Program Phase 2 and 6 for Rest-in-Walk.
- Yellow clearance intervals for phase 4 and 8 may be decreased by 0.2 seconds per week until the desired value is reached.



FEATURE	PHASE			
	2	4	6	8
Min Green 1 *	10	7	10	7
Extension 1 *	0.0	0.0	0.0	0.0
Max Green 1 *	30	20	30	20
Yellow Clearance	3.0	3.0	3.0	3.0
Red Clearance	2.3	2.3	2.3	2.4
Red Revert	2.0	2.0	2.0	2.0
Walk 1 *	23	11	18	4
Don't Walk 1	7	9	12	16
Walk Advance **	3.0	3.0	3.0	3.0
Seconds Per Actuation *	-	-	-	-
Max Variable Initial *	-	-	-	-
Time Before Reduction *	-	-	-	-
Time To Reduce *	-	-	-	-
Minimum Gap	-	-	-	-
Recall Mode	MAX/PED	MAX/PED	MAX/PED	MAX/PED
Vehicle Call Memory	-	-	-	-
Dual Entry	-	-	-	-
Simultaneous Gap	ON	ON	ON	ON

\* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.  
\*\* See Note 9.

LEGEND

PROPOSED	EXISTING
○→ Traffic Signal Head	●→ N/A
●→ Modified Signal Head	○→ N/A
⊥ Sign	⊥ N/A
⊥ Pedestrian Signal Head With Push Button & Sign	⊥ N/A
○→ Signal Pole with Guy	●→ Signal Pole with Guy
○→ Signal Pole with Sidewalk Guy	●→ Signal Pole with Sidewalk Guy
□ Inductive Loop Detector	□ Inductive Loop Detector
□ Controller & Cabinet	□ Controller & Cabinet
□ Junction Box	□ Junction Box
--- 2-in Underground Conduit	--- 2-in Underground Conduit
N/A Right of Way	--- Right of Way
→ Directional Arrow	→ Directional Arrow
⊥ Metal Pole with Mastarm	⊥ Metal Pole with Mastarm
○ Type II Signal Pedestal	● Type II Signal Pedestal
Ⓐ 'STREET NAME' Sign	Ⓐ 'STREET NAME' Sign
Ⓑ 'NO LEFT TURN' Sign R3-2	Ⓑ 'NO LEFT TURN' Sign R3-2
Ⓒ 'NO RIGHT TURN' Sign R3-1	Ⓒ 'NO RIGHT TURN' Sign R3-1
Ⓓ 'DO NOT ENTER' Sign R5-1	Ⓓ 'DO NOT ENTER' Sign R5-1

Signal Upgrade

**Mattern & Craig**  
CONSULTING ENGINEERS • SURVEYORS  
FIRM LICENSE No. C-1154  
12 BROAD STREET  
ASHEVILLE, NORTH CAROLINA 28801  
(828) 254-2201  
FAX (828) 254-4562

Prepared for the Offices of:  
**CITY OF ASHEVILLE**  
161 S. Charlotte St., Asheville, NC 28802

**College St/Pack Square at Spruce St**

Division 13 Buncombe County Asheville

PLAN DATE: OCTOBER 2016 REVIEWED BY: SMH  
PREPARED BY: BGR REVIEWED BY: JBV

SCALE: 1"=30'

SEAL  
JAMES VOSS  
140FD00378041F  
12/13/2016  
SIG. INVENTORY NO. COA-0103